

DUCT SYMBOLS		
DOUBLE LINE SYMBOL	DESCRIPTION	SINGLE LINE SYMBOL
	DUCT- FIRST NUMBER IS VISIBLE DIMENSION.	
	RADIUS ELBOW W/VANE(S) (1.5=R/D STANDARD)	
	DUCT SECTION, POSITIVE PRESSURE	
	DUCT SECTION, NEGATIVE PRESSURE	
	DUCT & AIRFLOW UP(LEFT) POSITIVE PRESSURE	
	DUCT & AIRFLOW DN(RIGHT) POSITIVE PRESSURE	
	DUCT & AIRFLOW UP(LEFT) NEGATIVE PRESSURE	
	DUCT & AIRFLOW DN(RIGHT) NEGATIVE PRESSURE	
	DUCT & AIRFLOW UP(LEFT) NEG./POS. PRESSURE	
	DUCT & AIRFLOW DN(RIGHT) NEG./POS. PRESSURE	
	CHANGE OF ELEVATION=RISE (R), DROP (D)	
	CEILING EXHAUST FAN WITH LIGHT	
	FD- FIRE DAMPER	
	MANUAL VOLUME DAMPER-SPECIFIC TYPE, NO LABEL-BUTTERFLY, OBD-OPPOSED BLADED DAMPER, PBD-PARALLEL BLADE DAMPER	
	BRANCH TAP-W/45 DEG. ENTRY	
	BRANCH TAP-CONICAL SPIN-IN	
	BRANCH TAP-STRAIGHT SPIN-IN	
	TRANSITION	
	HVAC - EQUIP AS NOTED	
	AIR DEVICE, SUPPLY- CEILING, CLEAR	
	AIR DEVICE TAG SPIN-IN DIMENSION AIRFLOW (CFM)	
	AIR DEVICE, SUPPLY- SIDEWALL.	
	AIR DEVICE, RETURN/EXHAUST- SIDEWALL.	

MECHANICAL DRAWING LIST	
M001	MECHANICAL SYMBOL LIST & GENERAL NOTES
M002	MECHANICAL GENERAL NOTES
M101	MECHANICAL FLOOR PLAN
M102	MECHANICAL ROOF PLAN
M201	MECHANICAL DETAILS (1 OF 3)
M202	MECHANICAL DETAILS (2 OF 3)
M203	MECHANICAL DETAILS (3 OF 3)
M401	MECHANICAL SCHEDULES
M401	HOOD DETAILS (1 OF 3)
M402	HOOD DETAILS (2 OF 3)
M403	HOOD DETAILS (3 OF 3)

CODE COMPLIANCE
ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTHING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:
a. VIRGINIA BUILDING CODE 2018 ADOPTS IBC 2018
b. VIRGINIA MECHANICAL CODE 2018 ADOPTS IMC 2018
c. VIRGINIA PLUMBING CODE 2018 ADOPTS IPC 2018
d. VIRGINIA FUEL GAS CODE 2018 ADOPTS IFGC 2018
e. VIRGINIA ELECTRICAL CODE 2017 ADOPTS NEC 2017

MECHANICAL ABBREVIATIONS	
BD	BACKDRAFT DAMPER
CFM	CUBIC FEET OF AIR PER MINUTE
CD	CONDENSATE DRAIN PIPE
DN	DOWN
EER	ENERGY EFFICIENCY RATIO
FC	FLEXIBLE CONNECTION
	HEATING SEASONAL PERFORMANCE FACTOR
HSPF	
IEER	INTEGRATED ENERGY EFFICIENCY RATIO
LDS	LINEAR DIFFUSER SUPPLY
LDR	LINEAR DIFFUSER RETURN
SEER	SEASONAL ENERGY EFFICIENCY RATIO
VD	VOLUME DAMPER
EF	EXHAUST FAN
KEF	KITCHEN EXHAUST FAN
MD	MOTORIZED DAMPER
RTU	ROOFTOP UNIT
KSF	KITCHEN SUPPLY FAN
FD	FIRE DAMPER
SG	SUPPLY GRILLE
RG	RETURN GRILLE
WMS	WIRE MESH SCREEN
CDS	CEILING DIFFUSER SUPPLY
CDR	CEILING DIFFUSER RETURN
CDE	CEILING DIFFUSER EXHAUST
AHU	AIR HANDLING UNIT
ACCU	AIR COOLED CONDENSING UNIT

NORFOLK, VIRGINIA BUILDING DEPT. NOTES	
ALL WORK SHALL COMPLY WITH APPLICABLE SECTIONS OF THE 2018 INTERNATIONAL BUILDING CODE, AND ALL AMENDMENTS AND RULES AND REGULATIONS OF THE DEPARTMENT OF BUILDINGS TO DATE.	
1. ALL HEATING AND COOLING LOADS CALCULATED PER ASHRAE/ACCA 183.	
2. VENTILATION FOR ALL AREA SHALL COMPLY WITH 2018 INTERNATIONAL MECHANICAL CODE, CHAPTER 4.	
3. TESTS WILL BE CONDUCTED UNDER DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT OR OTHER PERSON HAVING NOT LESS THAN FIVE (5) YEARS EXPERIENCE SUPERVISING THE INSTALLATION OF SUCH MECHANICAL SYSTEMS. THE TESTS WILL SHOW COMPLIANCE WITH 2018 INTERNATIONAL ENERGY CONSERVATION CODE REQUIREMENTS AS OUTLINES IN SECTION.	
4. THE LICENSED PROFESSIONAL ENGINEER, ARCHITECT OR OTHER PERSON HAVING NOT LESS THAN FIVE (5) YEARS EXPERIENCE SUPERVISING THE INSTALLATION OF SUCH MECHANICAL SYSTEMS AND CONDUCTING SUCH TESTS WILL FILE DOCUMENTATION AND REPORTS OF TESTS THAT THE SYSTEM COMPLIES WITH THE CONSTRUCTION DOCUMENTS AND APPLICABLE LAWS.	
5. TESTS OF MECHANICAL SYSTEMS SHALL BE PERFORMED IN ACCORDANCE WITH THE FOLLOWING SECTIONS OF THE INTERNATIONAL 2018 INTERNATIONAL MECHANICAL CODE: A. VENTILATION SYSTEM BALANCING 2018 INTERNATIONAL MECHANICAL CODE - 403.3	
6. THE FOLLOWING WORK ITEMS, COMPONENTS, MATERIALS, CAPACITIES, ETC. SHALL COMPLY WITH THE REFERENCED CODE OR STANDARD: A. STANDARDS OF HEATING 2018 INTERNATIONAL MECHANICAL CODE - 309.1 B. DUCT CONSTRUCTION AND INSTALLATION 2018 INTERNATIONAL MECHANICAL CODE - 603 C. AIR INTAKES, EXHAUSTS AND RELIEF 2018 INTERNATIONAL MECHANICAL CODE - 401.5 D. AIR FILTERS 2018 INTERNATIONAL MECHANICAL CODE - 605 E. MANUAL AND AUTOMATIC FIRE AND SMOKE CONTROLS FOR AIR DISTRIBUTION SYSTEMS - 2018 INTERNATIONAL MECHANICAL CODE - 606 F. GAS FIRED EQUIPMENT - 2018 INTERNATIONAL FUEL AND GAS CODE.	
7. MINIMUM TEMPERATURE TO BE MAINTAINED IN OCCUPIED SPACES DURING HEATING SEASON: 68 DEG. FAHRENHEIT.	
8. SMOKE DETECTOR SHALL MEET UL268A.	
9. SMOKE DETECTION SYSTEMS SHALL BE INSTALLED AND SEQUENCED TO FOLLOW CONTROLS OPERATIONS WITH THE REQUIREMENTS OF SECTION MC 606 TO CLOSE DAMPERS AND AUTOMATICALLY STOP THE FAN.	
10. A STATEMENT SHALL BE FILED BY THE OWNER OR TENANT IN POSSESSION THAT THE VENTILATION SYSTEM WILL BE KEPT IN CONTINUOUS OPERATION AT ALL TIMES DURING THE NORMAL OCCUPANCY OF THE STRUCTURE AS REQUIRED BY 2018 INTERNATIONAL MECHANICAL CODE - 403.3	
11. REFER TO ARCHITECTURAL DRAWINGS FOR REQUIRED FIRE-RATED WALL AND SMOKE WALL CONSTRUCTION AND LOCATION.	
12. THESE PLANS ARE APPROVED ONLY FOR THE WORK INDICATED ON THE APPLICATION SPECIFICATION SHEET. ALL OTHER MATTERS SHOWN ARE NOT TO BE RELIED UPON OR TO BE CONSIDERED AS EITHER BEING APPROVED OR IN ACCORDANCE WITH APPLICABLE CODES.	
13. REFER TO ARCHITECTURAL DRAWINGS FOR REQUIRED FIRE-RATED WALL AND SMOKE WALL CONSTRUCTION AND LOCATION.	
14. VENTILATION SYSTEMS SHALL BE BALANCED TO MAINTAIN THE MINIMUM VENTILATION AIRFLOW RATE AS SHOWN IN VENTILATION REQUIREMENT TABLE. THIS SYSTEM SHALL BE BALANCED BY APPROVED METHOD. CONTRACTOR SHALL SUBMIT THE AIR BALANCE REPORT TO THE INSPECTOR OF RESPECTIVE BUILDING DEPARTMENT PRIOR FINAL INSPECTION.	

GENERAL MECHANICAL NOTES AND SPECIFICATIONS

GENERAL

- COORDINATE WORK AMONG ALL DISCIPLINES. IT IS NOT THE INTENT OF THESE DOCUMENTS TO DICTATE WHO MUST DO THE WORK. ALL WORK SHOWN IS THE RESPONSIBILITY OF THE (PRIME) CONTRACTOR.
- FIELD VERIFY ALL CONDITIONS AND MEASURE DIMENSIONS WITHIN THE BUILDING PRIOR TO ORDERING EQUIPMENT AND/OR PROCEEDING WITH INSTALLATION.
- ALL EQUIPMENT SHALL BE FACTORY TESTED, AND CONTRACTOR SHALL VERIFY THEIR CONDITION PRIOR TO INSTALLATION. CONTRACTOR IS RESPONSIBLE FOR EQUIPMENT DAMAGED DURING MOVING AND INSTALLATION.
- EQUIPMENT FOUND DEFECTIVE PRIOR TO FINAL ACCEPTANCE SHALL BE REPLACED AT NO COST TO OWNER.
- SUBMISSION OF BID PROPOSAL IS CONSIDERED AN ACKNOWLEDGEMENT THAT CONTRACTOR VISITED SITE, AND VERIFIED ALL EXISTING CONDITIONS, AND INCLUDED ANY MODIFICATIONS TO EXISTING AND NEW WORK REQUIRED FOR INSTALLATION OF A COMPLETE AND OPERATIONAL MECHANICAL SYSTEM.
- COORDINATE WITH OWNER AND ENGINEER FOR ANY DISRUPTION IN UTILITY SERVICES, PARTICULARLY THOSE THAT MIGHT AFFECT OTHER BUILDINGS.
- CONTRACTOR SHALL NOT PROCEED WITH ANY WORK INVOLVING A CHANGE IN PROJECT SCOPE OR COST WITHOUT FIRST HAVING OBTAINED ENGINEER'S APPROVAL IN WRITING. UNLESS ENGINEER HAS AGREED TO SUCH CHANGE PRIOR TO IT BEING DONE, AND HAS AGREED THAT AN INCREASE IN COST ASSOCIATED WITH SUCH CHANGE IS WARRANTED; CONTRACTOR WILL NOT BE REIMBURSED FOR SUCH CHANGE.
- TESTING, ADJUSTING AND BALANCING (TAB) CONTRACTOR SHALL BE RETAINED BY THE PRIME CONTRACTOR TAB SHALL NOT BE A PART OF THE MECHANICAL CONTRACT.

CODES AND ORDINANCES

- PERFORM ALL WORK PER LATEST VERSION OF INTERNATIONAL MECHANICAL CODE, AND APPLICABLE LOCAL CODES AND ORDINANCES, UNLESS DRAWINGS OR SPECIFICATIONS HAVE MORE STRINGENT REQUIREMENTS.
- CONTRACTOR IS RESPONSIBLE FOR ALL PERMITS AND FEES ASSOCIATED WITH PROJECT, INCLUDING FEES FOR INSPECTIONS, APPLICATIONS, AND PROVISION OF NEW SERVICES.
- NOTIFY ENGINEER OF ANY ASPECTS OF DESIGN WHICH ARE THOUGHT TO BE IN NONCOMPLIANCE WITH APPLICABLE CODES.

COORDINATION

- REFER TO ARCHITECTURAL AND STRUCTURAL PLANS FOR DETAILS OF CONSTRUCTION, INCLUDING BEAMS, FLOOR AND WALL PENETRATIONS, CHASES, AND REFLECTED CEILING PLANS. VERIFY OPENING SIZES WITH EQUIPMENT FURNISHED.
- COORDINATE ALL WORK WITH OTHER TRADES; COORDINATE SCHEDULE OF WORK WITH ALL SUB-CONTRACTORS TO ACHIEVE SMOOTH FLOW OF CONSTRUCTION.
- CONTRACTOR SHALL REVIEW COMPLETE DOCUMENTS PRIOR TO SUBMITTAL OF PROPOSAL TO GAIN COMPLETE UNDERSTANDING OF PROJECT SCOPE, WORK BY OTHERS, AND MECHANICAL WORK ASSOCIATED WITH OTHER DISCIPLINES.
- ENGINEER/ ARCHITECT MUST BE GIVEN AT LEAST A TEN (10) WORKING DAY NOTICE TO PERFORM ALL TYPES OF INSPECTIONS. COORDINATE WORK SCHEDULE WITH ARCHITECT AND ENGINEER TO PLAN ACCORDINGLY FOR APPROPRIATE INSPECTIONS.
- COORDINATE LIGHT LOCATIONS WITH ELECTRICAL CONTRACTOR PRIOR TO INSTALLATION OF AIR DEVICES. LIGHT LOCATIONS TAKE PRECEDENCE OVER AIR DEVICES.

RETURN AIR SYSTEMS

- MECHANICAL DESIGN ASSUMES A MINIMUM 1" DOOR UNDERCUTS FOR ALL DOORS AND WALL PARTITIONS WITHIN CONDITIONED SPACES.
- CONTRACTOR SHALL IMMEDIATELY NOTIFY THE PROJECT ENGINEER IF ANY DOOR OR PARTITION IS NOT PROVIDED WITH A MINIMUM 1" UNDERCUT OR IF ANY OF THE SPECIFIED SYSTEM RETURN PATHS ARE COMPROMISED DURING CONSTRUCTION IN ANY WAY.
- AT A MINIMUM, THE CONTRACTOR SHALL PROVIDE A FIBERGLASS DUCTED TRANSFER BOOT/GRILL ABOVE CEILING FOR ANY DOOR OR PARTITION THAT IS NOT PROVIDED WITH A MINIMUM 1" UNDERCUT.
- RETURN BOOT SHALL TERMINATE IN NEW RETURN AIR DEVICES. RETURN AIR DEVICES SHALL BE WHITE ALUMINUM PERFORATED LAY-IN TYPE WITH ALL NECESSARY MOUNTING HARDWARE TO MATCH OTHER RETURN DEVICES ON SITE. PROVIDE FRAMED AIR DEVICE IF IN HARD CEILING.

METAL AND FLEXIBLE DUCTS

- DRAWINGS ARE DIAGRAMMATIC IN NATURE. FOR CLARITY SAKE, MOST DUCT OFFSETS/RISES/DROPS ARE NOT SHOWN. RECTANGULAR AND ROUND DUCTWORK SHALL BE GALVANIZED STEEL. SIZES SHOWN ARE INSIDE CLEAR DIMENSION.
- PRIOR TO CONSTRUCTION, CONTRACTOR IS REQUIRED TO COORDINATE HEIGHTS OF DUCTWORK LAYOUT WITH EXISTING STRUCTURE, OTHER TRADES, AND PROPOSED CEILING HEIGHT TO CONFIRM ADEQUATE VERTICAL SPACE FOR STACKING.
- CONSTRUCT AND LEAKAGE TEST ALL DUCTWORK BASED ON SMACNA REQUIREMENTS. COORDINATE PRESSURE CLASSES WITH EQUIPMENT SCHEDULES.
- ALL GALVANIZED SHEET METAL DUCT WORK SHALL COMPLY WITH SMACNA'S "HVAC DUCT CONSTRUCTION STANDARDS--METAL AND FLEXIBLE".
- USE 2" GLASS FIBER-REINFORCED FABRIC JOINT AND SEAM TAPE. USE WATER BASED JOINT AND SEAM SEALER. USE FIRE RESISTANT SEALER FOR FILLING OPENINGS AROUND DUCT PENETRATIONS THROUGH WALLS. ACCEPTABLE PRODUCTS ARE DOW CORNING, FIRE STOP FOAM AND FIRE STOP SEALER OR EQUAL.
- USE SHEET METAL SCREWS OR BLIND RIVETS COMPATIBLE WITH DUCT MATERIALS WHEN SECURING ALL DUCTWORK TO STRUCTURE.
- FLEXIBLE DUCT MAY BE USED TO CONNECT TO SUPPLY DIFFUSERS. MAXIMUM LENGTH OF FLEXIBLE DUCT LIMITED TO 6 FEET. PROVIDE FLEXMASTER TYPE 8M UL 181 CLASS I AIR DUCT OR EQUAL. FLEXIBLE DUCT SHALL HAVE MIN. R-8 INSULATING VALUE.
- FLEXIBLE DUCT CLAMP SHALL BE OF STAINLESS STEEL BANDS WITH CADMIUM PLATED HEX SCREW TO TIGHTEN BAND WITH WORM GEAR ACTION.
- PROVIDE TURNING VANES IN ALL SPLITS, TEES AND SWEPT 90 DEGREE ANGLE DUCT FITTINGS. MANUFACTURED TURNING VANES TO BE 1-1/2" WIDE, DOUBLE VANE, CURVED BLADES OF GALVANIZED SHEET STEEL SET 3/4" O.C. ACCEPTABLE MANUFACTURER'S ARE DUCTMATE INDUSTRIES, METALAIRE, WARD INDUSTRIES OR EQUAL.
- WHERE RECTANGULAR TEE FITTINGS ARE SHOWN, PROVIDE FITTING WITH ADJUSTABLE DIVIDER SHEET AND TURNING VANES.
- WHERE RECTANGULAR MAIN AND BRANCH CONNECTIONS ARE SHOWN, PROVIDE EXTRACTOR VANES.
- PROVIDE MANUAL VOLUME CONTROL DAMPERS WHERE SHOWN ON DRAWINGS. DAMPERS TO HAVE NEOPRENE BLADE SEALS AND GALVANIZED STEEL FRAMES, TIE BARS, DAMPER AND BRACKETS ACCEPTABLE MANUFACTURER'S ARE RUSKIN CO., NAILOR INDUSTRIES, FLEXMASTER OR EQUAL.
- ABOVE INACCESSIBLE CEILINGS AND WHERE DUCT CONFIGURATION DOES NOT ALLOW FOR INSTALLATION OF DAMPER IN DUCTWORK OR DIFFUSER, PROVIDE REMOTE MANUAL DAMPER BY YOUNG REGULATOR, (BOWDEN CABLE CONTROL SYSTEM) CONTRACTOR MAY PROVIDE OPPOSED BLADE DAMPER THAT IS INTEGRAL TO GPD WITH ENGINEER'S APPROVAL.

NY ENGINEERS  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25	4
4. Revision 3 : 06.07.24	
3. Revision 2 : 04.24.24	
2. Revision 1 : 03.05.24	
1. Permit set : 01.31.24	
PREPARED BY : NYE	
REVIEWED BY : NYE	
PROJECT NUMBER OS230050.00	
DRAWING TITLE MECHANICAL SYMBOL LIST & GENERAL NOTES	
DRAWING NUMBER M001	
SHEET 1 OF 11	



SECTION 230713 – DUCT INSULATION

1.1 QUALITY ASSURANCE

SURFACE–BURNING CHARACTERISTICS: ALL INSULATION SHALL HAVE COMPOSITE (INSULATION JACKET OR FACING AND ADHESIVE USED TO ADHERE THE FACING OR JACKET TO THE INSULATION) A FLAME–SPREAD INDEX OF 25, AND SMOKE–DEVELOPED INDEX OF 50 FOR INSULATION INSTALLED INDOOR, 75, AND SMOKE–DEVELOPED INDEX OF 150 FOR INSULATION INSTALLED OUTDOORS; ACCORDING TO ASTM E 84.

1.2 FIELD QUALITY CONTROL

A. FIELD INSPECTIONS: BY OWNER–ENGAGED AGENCY.

1.3 INDOOR DUCT AND PLENUM INSULATION SCHEDULE:

- A. CONCEALED, RECTANGULAR, ROUND AND FLAT–OVAL, SUPPLY–RETURN, OUTDOOR–AND EXHAUST–AIR DUCT AND AIR PLENUM INSULATION:
- B. FLEXIBLE ELASTOMERIC, MINERAL–FIBER BLANKET, MINERAL–FIBER BOARD OR POLYOLEFIN WITH MINIMUM INSTALLED THERMAL RESISTANCE AS FOLLOWS:

UNCONDITIONED SPACES: R–6  
WITHIN BUILDING ENVELOPE ASSEMBLY: R–8  
EXTERIOR OF BUILDING: R–8

1.4 ITEMS NOT INSULATED:

1. FIBROUS–GLASS DUCTS.
2. METAL DUCTS WITH DUCT LINER OR SUFFICIENT THICKNESS TO COMPLY WITH ENERGY CODE AND ASHRAE/IESNA 90.1.
3. FACTORY–INSULATED FLEXIBLE DUCTS.
4. FACTORY–INSULATED PLENUMS AND CASINGS.
5. FLEXIBLE CONNECTORS.
6. VIBRATION–CONTROL DEVICES.
7. FACTORY–INSULATED ACCESS PANELS AND DOORS.
8. DUCTS THAT HAVE INTERNAL ACOUSTICAL LINING.

1.5 PRODUCTS

A. THE FOLLOWING INSULATION MANUFACTURERS WILL BE ACCEPTABLE:

1. JOHNS–MANVILLE
2. OWENS–CORNING

1.6 ACOUSTICAL TREATMENT

1. WHERE SHOWN ON THE DRAWINGS, LOW PRESSURE DUCTWORK SHALL BE LINED WITH 1.5" THICK R–6 AS MANUFACTURED BY DUCTMATE 1–1/2 POUND MINIMUM DENSITY, NEOPRENE COATED, FLEXIBLE FIBERGLASS DUCT LINER. LINING SHALL COMPLY WITH NFPA 90A AND SHALL HAVE A FLAME SPREAD CLASSIFICATION OF NOT MORE THAN 25 AND A SMOKE DEVELOPED RATING NOT MORE THAN 50. DUCT SIZES WHERE LINING IS INDICATED ON PLANS ARE MINIMUM INSIDE CLEAR DIMENSIONS REQUIRED,

END OF SECTION 230713

SECTION 233713 – DIFFUSERS, REGISTERS, AND GRILLES

1.1 PRODUCTS

- A. DIFFUSERS, REGISTERS AND GRILLES SHALL BE FURNISHED AND INSTALLED FOR CAPACITIES AND IN LOCATIONS INDICATED ON DRAWINGS. ALL REGISTERS AND DIFFUSERS SHALL BE PRIME COATED STEEL OR EXTRUDED ALUMINUM FINISHED UNLESS OTHERWISE NOTED IN BAKED WHITE ENAMEL.
- B. MANUFACTURERS: TITUS
1. SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCT BY ONE OF THE FOLLOWING:
    - a. CARNES.
    - b. HART & COOLEY INC.
    - c. KRUEGER.
    - d. METALAIR, INC.
    - e. NAILOR INDUSTRIES INC.
    - f. RUSKIN

- C. ALL DIFFUSERS SHALL HAVE CONTROLLING/EQUALIZING GRID AND OPPOSED BLADE DAMPER UNLESS OTHERWISE NOTED.
- D. ALL DUCTED RETURN REGISTERS SHALL HAVE AN OPPOSED BLADE DAMPER UNLESS OTHERWISE NOTED.

END OF SECTION 233713

THERMOSTATIC CONTROL NOTES:

EACH HEATING AND COOLING SYSTEM SHALL BE PROVIDED WITH CONTROLS IN ACCORDANCE WITH SECTIONS C403.4.1 THROUGH C403.4.5.

C403.4.1 THERMOSTATIC CONTROLS (MANDATORY)

THE SUPPLY OF HEATING AND COOLING ENERGY TO EACH ZONE SHALL BE CONTROLLED BY INDIVIDUAL THERMOSTATIC CONTROLS CAPABLE OF RESPONDING TO TEMPERATURE WITHIN THE ZONE. WHERE HUMIDIFICATION OR DEHUMIDIFICATION OR BOTH IS PROVIDED, NOT FEWER THAN ONE HUMIDITY CONTROL DEVICE SHALL BE PROVIDED FOR EACH HUMIDITY CONTROL SYSTEM.

EXCEPTION: INDEPENDENT PERIMETER SYSTEMS THAT ARE DESIGNED TO OFFSET ONLY BUILDING ENVELOPE HEAT LOSSES, GAINS OR BOTH SERVING ONE OR MORE PERIMETER ZONES ALSO SERVED BY AN INTERIOR SYSTEM PROVIDED THAT BOTH OF THE FOLLOWING CONDITIONS ARE MET:  
1.THE PERIMETER SYSTEM INCLUDES NOT FEWER THAN ONE THERMOSTATIC CONTROL ZONE FOR EACH BUILDING EXPOSURE HAVING EXTERIOR WALLS FACING ONLY ONE ORIENTATION (WITHIN ± 45 DEGREES) (0.8 RAD) FOR MORE THAN 50 CONTIGUOUS FEET (15 240 MM).  
2.THE PERIMETER SYSTEM HEATING AND COOLING SUPPLY IS CONTROLLED BY THERMOSTATS LOCATED WITHIN THE ZONES SERVED BY THE SYSTEM.

C403.4.1.2 DEADBAND (MANDATORY).

WHERE USED TO CONTROL BOTH HEATING AND COOLING, ZONE THERMOSTATIC CONTROLS SHALL BE CONFIGURED TO PROVIDE A TEMPERATURE RANGE OR DEADBAND OF NOT LESS THAN 5°F (2.8°C) WITHIN WHICH THE SUPPLY OF HEATING AND COOLING ENERGY TO THE ZONE IS SHUT OFF OR REDUCED TO A MINIMUM.

EXCEPTIONS:

- 1.THERMOSTATS REQUIRING MANUAL CHANGEOVER BETWEEN HEATING AND COOLING MODES.
- 2.OCCUPANCIES OR APPLICATIONS REQUIRING PRECISION IN INDOOR TEMPERATURE CONTROL AS APPROVED BY THE CODE OFFICIAL.

C403.4.1.3 SETPOINT OVERLAP RESTRICTION (MANDATORY).

WHERE A ZONE HAS A SEPARATE HEATING AND A SEPARATE COOLING THERMOSTATIC CONTROL LOCATED WITHIN THE ZONE, A LIMIT SWITCH, MECHANICAL STOP OR DIRECT DIGITAL CONTROL SYSTEM WITH SOFTWARE PROGRAMMING SHALL BE CONFIGURED TO PREVENT THE HEATING SETPOINT FROM EXCEEDING THE COOLING SETPOINT AND TO MAINTAIN A DEADBAND IN ACCORDANCE WITH SECTION C403.4.1.2.

C403.4.2 OFF–HOUR CONTROLS (MANDATORY).

EACH ZONE SHALL BE PROVIDED WITH THERMOSTATIC SETBACK CONTROLS THAT ARE CONTROLLED BY EITHER AN AUTOMATIC TIME CLOCK OR PROGRAMMABLE CONTROL SYSTEM.

EXCEPTIONS:

- 1.ZONES THAT WILL BE OPERATED CONTINUOUSLY.
- 2.ZONES WITH A FULL HVAC LOAD DEMAND NOT EXCEEDING 6,800 BTU/H (2 KW) AND HAVING A MANUAL SHUTOFF SWITCH LOCATED WITH READY ACCESS.

C403.4.2.1 THERMOSTATIC SETBACK (MANDATORY).

THERMOSTATIC SETBACK CONTROLS SHALL BE CONFIGURED TO SET BACK OR TEMPORARILY OPERATE THE SYSTEM TO MAINTAIN ZONE TEMPERATURES DOWN TO 55°F (13°C) OR UP TO 85°F (29°C).

C403.4.2.2 AUTOMATIC SETBACK AND SHUTDOWN (MANDATORY).

AUTOMATIC TIME CLOCK OR PROGRAMMABLE CONTROLS SHALL BE CAPABLE OF STARTING AND STOPPING THE SYSTEM FOR SEVEN DIFFERENT DAILY SCHEDULES PER WEEK AND RETAINING THEIR PROGRAMMING AND TIME SETTING DURING A LOSS OF POWER FOR NOT FEWER THAN 10 HOURS. ADDITIONALLY, THE CONTROLS SHALL HAVE A MANUAL OVERRIDE THAT ALLOWS TEMPORARY OPERATION OF THE SYSTEM FOR UP TO 2 HOURS; A MANUALLY OPERATED TIMER CONFIGURED TO OPERATE THE SYSTEM FOR UP TO 2 HOURS; OR AN OCCUPANCY SENSOR.

C403.4.2.3 AUTOMATIC START (MANDATORY).

AUTOMATIC START CONTROLS SHALL BE PROVIDED FOR EACH HVAC SYSTEM. THE CONTROLS SHALL BE CONFIGURED TO AUTOMATICALLY ADJUST THE DAILY START TIME OF THE HVAC SYSTEM IN ORDER TO BRING EACH SPACE TO THE DESIRED OCCUPIED TEMPERATURE IMMEDIATELY PRIOR TO SCHEDULED OCCUPANCY.

NY ENGINEERS

NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25

4. Revision 3 : 06.07.24

3. Revision 2 : 04.24.24

2. Revision 1 : 03.05.24

1. Permit set : 01.31.24

PREPARED BY : NYE

REVIEWED BY : NYE

PROJECT NUMBER  
OS230050.00

DRAWING TITLE

MECHANICAL  
GENERAL  
NOTES

DRAWING NUMBER

M002

SHEET 2 OF 11



GREASE DUCT SPECIFICATIONS


1. PROVIDE CLEAN OUT AT ALL ELBOWS AND BOTTOM OF RISER AND EVERY 20 FEET HORIZONTAL KITCHEN EXHAUST DUCT.
2. COMMERCIAL KITCHEN GREASE DUCTS SHALL BE DESIGNED FOR THE TYPE OF COOKING APPLIANCE AND HOOD SERVED. COMMERCIAL KITCHEN GREASE DUCTS SHALL BE OF 16 GAUGE MINIMUM BLACK IRON OR PREFABRICATED SINGLE WALL GREASE DUCT WITH UL 1978 AND UL 2221 LISTING.
3. JOINTS, SEAMS AND PENETRATIONS OF GREASE DUCTS SHALL BE MADE WITH A CONTINUOUS LIQUID TIGHT WELD OR BRAZE MADE IN THE EXTERNAL SURFACE IF THE DUCT SYSTEMS.
4. DUCT TO EXHAUST FAN CONNECTIONS SHALL BE FLANGED, GASKETED AND BOLTED TO THE INLET AND OUTLET OF THE FAN FOR INLINE FANS. APPROVED FLEXIBLE CONNECTIONS MAY BE PROVIDED.
5. A VIBRATION ISOLATION CONNECTOR FOR CONNECTING A DUCT TO A FAN SHALL CONSIST OF NON-COMBUSTIBLE PACKING IN A METAL SLEEVE JOINT OF APPROVED DESIGN OR SHALL BE A COATED-FABRIC FLEXIBLE DUCT CONNECTOR LISTED AND LABELED FOR THE APPLICATION. VIBRATION ISOLATION CONNECTORS SHALL BE INSTALLED ONLY AT THE CONNECTION OF A DUCT TO A FAN INLET OR OUTLET.
6. PRIOR TO THE USE OR CONCEALMENT OF ANY PORTION OF A GREASE DUCT SYSTEM, A LEAKAGE TEST SHALL BE PERFORMED AS PER 2018 VIRGINIA MECHANICAL CODE (2018 IMC) SECTION 506.3.2.5. DUCT SHALL BE CONSIDERED TO BE CONCEALED WHERE INSTALLED IN SHAFTS OR COVERED BY COATINGS OR WRAPS THAT PREVENT THE DUCTWORK FROM VISUALLY INSPECTED ON ALL SIDE. THE DUCT INSTALLER SHALL BE RESPONSIBLE FOR PROVIDING THE NECESSARY EQUIPMENT AND PERFORMING THE GREASE DUCT LEAKAGE TEST. THE DUCT LEAKAGE TEST SHALL BE PERFORMED FOR ALL THE DUCT SYSTEMS, INCLUDING THE DUCT-TO-DUCT CONNECTION. THE DUCTWORK SHALL BE PERMITTED TO BE TESTED IN SECTIONS, PROVIDED THAT EVERY JOINT IS TESTED (IF TEST IS FAILED, CONTRACTOR TO PROVIDE NEW KITCHEN EXHAUST DUCT).
7. PROVIDE SMOKE TEST TO PROOF TIGHTNESS OF THE GREASE DUCT.
8. GREASE DUCT BRACING AND SUPPORTS SHALL BE OF NON-COMBUSTIBLE MATERIAL SECURELY ATTACHED TO THE STRUCTURE AND DESIGNED TO CARRY GRAVITY AND SEISMIC LADS WITHIN THE STREET LIMITATIONS OF THE 2018 INTERNATIONAL BUILDING CODE(2018 IBC). BOLTS, SCREWS, RIVETS AND OTHER MECHANICAL FASTENERS SHALL NOT PENETRATE DUCT WALLS.
9. A RESIDUE TRAP SHALL BE PROVIDED AT THE BASE OF EACH VERTICAL RISER WITH PROVISION FOR CLEANOUT IN ACCORDANCE WITH NFPA 96.
10. CLEANOUT OPENINGS SHALL BE PROVIDED AT EVERY CHANGE IN DIRECTION, WITHIN 3 FEET OF THE EXHAUST FAN.
11. CLEANOUT OPENINGS SHALL BE EQUIPPED WITH TIGHT-FITTING DOORS CONSTRUCTED OF STEEL HAVING A THICKNESS NOT LESS THAN THAT REQUIRED FOR THE DUCT. DOORS SHALL BE EQUIPPED WITH A SUBSTANTIAL METHOD OF LATCHING, SUFFICIENT TO HOLD THE DOOR TIGHTLY CLOSED. DOOR ASSEMBLIES SHALL HAVE A GASKET OR SEALANT THAT IS NONCOMBUSTIBLE AND LIQUID TIGHT AND SHALL NOT HAVE FASTENERS THAT PENETRATED THE DUCT
12. A GREASE DUCT SERVING THE TYPE-1 HOOD THAT PENETRATED A CEILING, WALL OR FLOOR SHALL BE ENCLOSED FROM THE FIRE POINT OF PENETRATION TO THE OUTLET TERMINAL. DUCT ENCLOSURES SHALL HAVE A FIRE-RESISTANCE RATING NOT LESS THAN THAT OF THE FIRE-RESISTANCE RATED ASSEMBLY PENETRATED BUT NEED NOT EXCEED 2 HOURS.
13. PROVIDE PROVIDE MINIMUM 2HR INSULATION COVERING OF 2 INCHES AND SUCH MATERIAL SHALL BE IN ACCORDANCE WITH ASTM E2336. FIELD APPLIED GREASE DUCT ENCLOSURE SHALL COMPLY ALL REQUIREMENTS PER 2018 INTERNATIONAL MECHANICAL CODE SECTION 506.3.11.2.

MECHANICAL GENERAL NOTES

- A. CONTRACTOR TO VISIT SITE TO VERIFY ON FIELD CONDITION ALONG WITH THE DRAWINGS & INFORM THE ENGINEER FOR ANY DISCREPANCIES FOUND BEFORE COMMENCING BIDS.
- B. CONTRACTOR SHALL BALANCE EACH AIR DIFFUSER WITH THE CFM SHOWN PLAN.
- C. DUCTWORK SHOWN ON PLAN ARE SCHEMATIC ONLY. CONTRACTOR SHALL COORDINATE WITH OTHER TRADES FOR DUCTWORK ROUTING, OFFSET AND RUN DUCTWORK INSIDE THE STRUCTURE IF REQUIRED. PROVIDE ANY EXTRA DUCTWORK, FITTINGS, INSULATIONS AND OTHER ACCESSORIES IN ORDER TO COMPLETE THE INSTALLATION.
- D. COORDINATE LOCATIONS AND SIZES OF ROOF OPENINGS WITH OWNER AND STRUCTURE ENGINEERS.
- E. EQUIPMENT SIZES, DIMENSIONS AND REQUIRED CONNECTIONS SHALL BE VERIFIED WITH THE ACTUAL EQUIPMENT SELECTED VENDOR DRAWINGS BEFORE FABRICATION OF DUCTWORK, PIPING ETC.
- F. DUCT SIZES SHOWN ON PLANS ARE CLEAR INSIDE AIR STREAM DIMENSIONS.
- G. CONTRACTOR SHALL COORDINATE ALL ELECTRICAL REQUIREMENTS FOR ALL HVAC BASED ON ACTUAL EQUIPMENT SELECTED PRIOR TO INSTALLATION.
- H. CONTRACTOR SHALL COORDINATE EQUIPMENT WEIGHTS AND SUPPORTS BASED ON ACTUAL EQUIPMENT SELECTED.
- I. ALL EXPOSED ROUND DUCTWORK SHALL BE INTERNALLY INSULATED. ALL INTERNAL DUCTWORK SHALL BE EXTERNALLY INSULATED.
- J. COORDINATE WITH ALL TRADES FOR MATERIALS IN RATED AND PLENUM SPACES.
- K. ALL SOURCE OF MECHANICAL INTAKE SHALL MAINTAIN 10 LINEAR FEET SEPARATION BETWEEN ANY SOURCE OF EXHAUST. CONTRACTOR IS RESPONSIBLE TO ADJUST DUCT LENGTH AS NEEDED.
- L. COORDINATE FINAL LOCATION OF EQUIPMENT WITH STRUCTURAL DRAWINGS.
- M. TAKE NECESSARY PRECAUTIONS TO PREVENT DUST AND DIRT MIGRATING TO OCCUPIED AREAS OF THE BUILDING. THIS INCLUDES BLANKING OFF ANY RETURN AIR GRILLES/ DUCTS IN THE WORK AREA. PROVIDE TEMPORARY EXHAUST FANS, DUCTED DIRECTLY TO OUTDOORS, TO MAINTAIN NEGATIVE PRESSURE WITHIN THE WORK AREA.
- N. KEEP ALL ADJOINING AREAS ADJACENT TO THE WORK AREAS CLEAN AND FREE OF DEBRIS.
- O. MECHANICAL CONTRACTOR TO COORDINATE ALL DUCT WORK, CROSSINGS, OVERLAPPING AND PENETRATIONS WITH SITE CONDITIONS AND AS PER EXISTING JOIST LAYOUT, SKYLIGHT AND BEAM IN FIELD. MODIFY DUCT WORK WHEREVER REQUIRED.
- P. CONTRACTOR TO VERIFY ON SITE ALL OUTSIDE AIR & EXHAUST AIR WALL PENETRATION/TERMINATION. INFORM ENGINEER IF ANY DISCREPANCY FOUND.
- Q. PROVIDE FIRE OR FIRE+SMOKE DAMPER WHEREVER DUCTS ARE CROSSING FIRE/SMOKE RATED WALLS/BARRIERS/SLABS. COORDINATE WITH ARCHITECTURAL DRAWING FOR FIRE RATING OF THE WALLS.
- R. CONTRACTOR TO RUN DUCTWORK AS HIGH AS POSSIBLE TO ENSURE THE MAXIMUM CEILING HEIGHT.

FLOOR PLAN KEY NOTES:-

- 1 LOCATION OF DIGITAL THERMOSTAT CONTROL. REUSE EXISTING THERMOSTAT FOR RTU-1(E) IF IN GOOD OPERATING CONDITION. IF NOT, REPLACE WITH SAME KIND. COORDINATE FINAL LOCATION WITH ARCHITECT AND OWNER PRIOR TO ROUGH-IN. PROVIDE LOCKABLE COVER.
- 2 SMOKE DETECTOR SHALL BE FURNISHED/INSTALLED BY MECHANICAL CONTRACTOR AND WIRE BY ELECTRICAL CONTRACTOR TO SHUT DOWN CORRESPONDING RTU UNDER ALARM CONDITIONS. ALL WIRING SHALL BE IN CONDUIT PER N E C SMOKE DETECTOR SHALL BE SYSTEM SENSOR MODEL DH100ACDCLP OR EQUAL.
- 3 EXTEND FULL SIZE SUPPLY & RETURN DUCTWORK FROM EXISTING ROOFTOP UNITS PENETRATIONS TO SPACE. EXTEND AS SHOWN. ACOUSTICALLY LINE THE FIRST 10'-0" OF BOTH SUPPLY AND RETURN MAIN DUCTS.
- 4 PROVIDE REMOTE TEMP AND HUMIDITY SENSOR MOUNTED IN THE SPACE AND WIRE BACK TO T-STAT & H-STAT OF RTU-1(E). CONTRACTOR TO CONFIRM FINAL LOCATION/REQUIREMENT WITH OWNER/ARCHITECT PRIOR INSTALLING.
- 5 INSTALL TYPE 1 GREASE EXHAUST HOOD. SUPPORT HOOD PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. PROVIDE TRAPEZE HANGERS FOR ALL THRU SUPPORT UNDER DUCTWORK AS REQUIRED. TRANSITION FROM HOOD CONNECTION TO WELDED KITCHEN EXHAUST DUCT SIZES SHOWN.
- 6 GREASE DUCT TO BE PROVIDED WITH KITCHEN EQUIPMENT AND INSTALLED BY MECHANICAL CONTRACTOR. INSTALL PER MANUFACTURER'S INSTRUCTIONS.
- 7 16"Ø GREASE EXHAUST DUCT FROM HOOD UP THRU ROOF TO KEF ON MAIN ROOF.
- 8 LOCATION OF DIGITAL THERMOSTAT CONTROL. INSTALL AND WIRE NEW 7-DAY PROGRAMMABLE THERMOSTAT FOR AHU-2(N). COORDINATE EXACT LOCATION WITH ARCHITECT AND OWNER PRIOR TO ROUGH-IN. PROVIDE LOCKABLE COVER. VERIFY WORKING CONDITION OF EXISTING T-SATS. REPLACE IF REQUIRED/NOT WORKING.
- 9 MAKEUP DUCT UP THRU ROOF TO KSF-1(N).
- 10 3"/5" CONCENTRIC VENT FOR WATER HEATER(PROVIDED BY OTHERS) UP TO ROOF. CONTRACTOR TO INSTALL THE VENT AS PER MANUFACTURER'S INSTRUCTION.
- 11 CEILING MOUNTED EXHAUST FAN. INTERCONNECT EXHAUST FAN WITH RESPECTIVE UNIT SERVING THIS ROOM. REFER TO TROUWEN SCHEDULE. FAN SHALL BE SUSPENDED FROM STRUCTURE ABOVE. VERIFY EXACT LOCATION OF STRUCTURAL MEMBERS PRIOR TO INSTALLATION.
- 12 8"Ø TOILET EXHAUST DUCT UP THROUGH THE ROOF AND TERMINATE WITH GOOSENECK AND BIRD SCREEN.
- 13 18"Ø GREASE EXHAUST DUCT FROM HOOD UP THRU ROOF TO KEF ON MAIN ROOF.
- 14 MD TO BE INTERLOCKED WITH RESPECTIVE AHU.
- 15 Ø8" OUTSIDE AIR INTAKE DUCT UP THROUGH ROOF WITH GOOSENECK, WEATHER SKIRT AND BIRD SCREEN.
- 16 CONTRACTOR TO PROVIDE NEW DRAIN LINE FOR THE AHU-1(N). TERMINATE TO THE APPROVED PLACE OF DISPOSAL AS PER LOCAL CODE. PROVIDE SECONDARY DRIP PAN UNDER AC UNIT WITH WATER LEAKAGE SENSOR AND ALARM TO SHUT THE UNIT. IF REQUIRED, PROVIDE CONDENSATE PUMP. CONNECT 1" CD FROM AHU TO APPROVED PLACE OF DISPOSAL.
- 17 PROVIDE REMOTE TEMP SENSOR MOUNTED IN THE SPACE AND WIRE BACK TO T-STAT OF AHU-1(N). CONTRACTOR TO CONFIRM FINAL LOCATION/ REQUIREMENT WITH OWNER/ARCHITECT PRIOR INSTALLING.
- 18 COORDINATE FINAL LOCATION OF EQUIPMENT WITH STRUCTURAL DRAWINGS AND CONFIRM THE SAME WITH ARCHITECT/OWNER.




1 MECHANICAL FLOOR PLAN  
M101 SCALE : 1/4" = 1'-0"

NY ENGINEERS  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25	4
4. Revision 3 : 06.07.24	3
3. Revision 2 : 04.24.24	2
2. Revision 1 : 03.05.24	1
1. Permit set : 01.31.24	
PREPARED BY : NYE	
REVIEWED BY : NYE	
PROJECT NUMBER OS230050.00	
DRAWING TITLE MECHANICAL FLOOR PLAN	
DRAWING NUMBER	
M101	
SHEET	3 OF 11






MECHANICAL GENERAL NOTES

- COORDINATE LOCATIONS AND SIZES OF ROOF OPENINGS WITH OWNER AND STRUCTURAL ENGINEERS.
- EQUIPMENT SIZES, DIMENSIONS AND REQUIRED CONNECTIONS SHALL BE VERIFIED WITH THE ACTUAL EQUIPMENT AT FIELD BEFORE FABRICATION OF DUCTWORK.
- CONTRACTOR SHALL COORDINATE ALL ELECTRICAL REQUIREMENTS FOR ALL HVAC BASED ON ACTUAL EQUIPMENT SELECTED PRIOR TO INSTALLATION.
- ALL SOURCE OF MECHANICAL INTAKE SHALL MAINTAIN 10 LINEAR FEET SEPARATION BETWEEN ANY SOURCE OF EXHAUST. CONTRACTOR IS RESPONSIBLE TO ADJUST DUCT LENGTH AS NEEDED.
- CONTRACTOR TO COORDINATE WITH OWNER / ARCHITECT AND PROVIDE SCREENS AROUND THE UNITS.
- GUARDS SHALL BE PROVIDED WHERE VARIOUS COMPONENTS THAT REQUIRE SERVICE AND ROOF HATCH OPENINGS ARE LOCATED WITHIN 10 FEET OF A ROOF EDGE OR OPEN SIDE OF A WALKING SURFACE AND SUCH EDGE OR OPEN SIDE IS LOCATED MORE THAN 30 INCHES ABOVE THE FLOOR, ROOF, OR GRADE BELOW. THE GUARD SHALL EXTEND NOT LESS THAN 30 INCHES BEYOND EACH END OF COMPONENTS THAT REQUIRE SERVICE. THE TOP OF THE GUARD SHALL BE LOCATED NOT LESS THAN 42 INCHES ABOVE THE ELEVATED SURFACE ADJACENT TO THE GUARD. THE GUARD SHALL BE CONSTRUCTED SO AS TO PREVENT THE PASSAGE OF A 21-INCH-DIAMETER SPHERE AND SHALL COMPLY WITH THE LOADING REQUIREMENTS FOR GUARDS SPECIFIED IN THE INTERNATIONAL BUILDING CODE.

ROOF PLAN KEY NOTES:-


- EXISTING ROOF TOP UNITS TO REMAIN AND TO BE REUSED. CONTRACTOR TO FIELD VERIFY EXACT LOCATION IN THE FIELD. PROVIDE DUCT MODIFICATIONS IF REQUIRED. SET OUTSIDE AIR AS INDICATED ON ROOFTOP UNIT SCHEDULES. MECHANICAL CONTRACTOR SHALL SCRIBE INTO UNIT POSITION OF OUTSIDE AIR DAMPER AND LABEL OUTSIDE AIR VOLUME AND PERCENT OF OUTSIDE AIR. TRANSITION AND CONNECT SUPPLY AND RETURN DUCTWORK FROM BELOW. COORDINATE ROUTING THROUGH STRUCTURAL TRUSSES AND OFFSET AS REQUIRED IN CURB SPACE.
- ROUTE CONDENSATE DRAIN FROM RTU ON THE ROOF TO THE APPROVED PLACE OF DISPOSAL.
- INSTALL EXHAUST AIR FAN ON THE ROOF AS PER MANUFACTURERS RECOMMENDATIONS.
- ALL OUTSIDE AIR INTAKE ON THE ROOF SHALL BE MINIMUM 10 FEET AWAY FROM ANY EXHAUST SOURCE.
- 3"/5" CONCENTRIC VENT FROM WATER HEATER(PROVIDED BY OTHERS). CONTRACTOR TO INSTALL THE VENT AS PER MANUFACTURER'S INSTRUCTION.
- TERMINATE 8"Ø TOILET EXHAUST DUCT 36" ABOVE ROOF WITH GOOSENECK AND BIRD SCREEN.
- CONTRACTOR TO FIELD VERIFY THE FINAL LOCATION OF MAKEUP AIR UNIT, EXHAUST FAN PRIOR BASE BID COMMENCING CONSTRUCTION.
- INSTALL OUTDOOR CONDENSING UNITS ON ROOF WITH ALL REQUIRED ACCESSORIES. CONTRACTOR SHALL CONFIRM THE FINAL LOCATION WITH CLIENT/ OWNER OR ARCHITECT PRIOR CONSTRUCTION/ BASE BID. PROVIDE CONCRETE PADS/STEEL RAILINGS AS REQUIRED. INSTALL OUTDOOR UNITS WITH THE HELP OF VIBRATION ISOLATORS.
- COORDINATE FINAL LOCATION OF EQUIPMENT WITH STRUCTURAL DRAWINGS AND CONFIRM THE SAME WITH ARCHITECT/OWNER.
- CONTRACTOR SHALL COORDINATE REFRIGERANT PIPE ROUTING BETWEEN CONDENSING UNITS AND AC UNITS IN FIELD. MAXIMUM REFRIGERANT PIPING LENGTH SHALL NOT EXCEED THE MANUFACTURER RECOMMENDATION.
- 8"Ø OUTSIDE AIR DUCT. TERMINATE WITH GOOSENECK AND BIRD SCREEN.






NOTE: 1. FOR DUCTS OVER 29" WIDE AND/OR OVER 12" HIGH.


1 LOW PRESSURE BALANCING DAMPER  
M201 N.T.S




2 DIFFUSER CONNECTION DETAIL-FLEX DUCT  
M201 N.T.S



3 UP BLAST EXHAUST FAN DETAIL  
M201 N.T.S



4 SUPPLY AIR DUCTWORK SUB-MAIN/BRANCH DUCT CONNECTION  
M201 N.T.S




5 DUCT HANGING DETAILS  
M201 N.T.S

**NY ENGINEERS**  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM


ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25  
4. Revision 3 : 06.07.24  
3. Revision 2 : 04.24.24  
2. Revision 1 : 03.05.24  
1. Permit set : 01.31.24  
PREPARED BY : NYE  
REVIEWED BY : NYE  
PROJECT NUMBER  
OS230050.00  
DRAWING TITLE  
MECHANICAL  
DETAILS  
(1 OF 3)  
DRAWING NUMBER  
M201  
SHEET 5 OF 11







1 CEILING FAN HANGING SUPPORT DETAIL  
M202 N.T.S




2 TYPICAL DETAIL OF ROOF GOOSENECK  
M202 N.T.S



3 DUCT DETECTOR DETAIL  
M202 N.T.S




4 TYPICAL GREASE DUCT WRAP DETAIL  
M202 N.T.S



NOTES:  
ACCESS DOOR IS TO BE DUCTMATE ULTIMATE DOOR II OR EQUAL.  
ACCESS DOOR IS TO BE U.L. LISTED # 65X3.  
ACCESS DOOR IS TO MEET OR EXCEED THE REQUIREMENTS OF NFPA 96, 2008 EDITION AT ALL LOCATIONS REQUIRED BY LOCAL CODE.


5 TYPICAL GREASE DUCT ACCESS DOOR DETAIL  
M202 N.T.S



NOTES:  
1. ACCESS DOORS (AD) IN GREASE DUCT SHALL BE PLACED AT EVERY CHANGE IN DIRECTION AND SHALL BE DUCTMATE HIGH TEMP (FOR GREASE DUCT) OR EQUAL AND MEET NFPA-96 STANDARDS.  
2. ALL RADIUS ELBOWS ARE TO BE 1.5 CENTERLINE RADIUS. NO MITERED ELBOWS WILL BE ALLOWED.  
3. ALL DUCT IS TO BE 16 GA MINIMUM STEEL OR 18 GA STAINLESS STEEL. FACTORY FABRICATED GREASE DUCT SHALL BE UL 1978 LISTED. ALL DUCTWORK SHALL BE CONTINUOUS LIQUID TIGHT WELD.  
4. DUCT IS TO SLOPE TOWARDS HOOD AT 1/4\"/>


6 TYPICAL GREASE DUCT DETAIL  
M202 N.T.S






1  
M203  
N.T.S

TYPICAL HORIZONTAL AIR HANDLER DETAIL




2  
M203  
N.T.S

FLOOR MOUNTED CONDENSING UNIT SUPPORT DETAIL



3  
M203  
N.T.S

DAMPER LOW PRESSURE SYSTEM  
DETAIL OF SHUTTER TYPE FIRE DETAIL



4  
M203  
N.T.S

MOTORIZED DAMPER DETAIL

**NY ENGINEERS**  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25  
4. Revision 3 : 06.07.24  
3. Revision 2 : 04.24.24  
2. Revision 1 : 03.05.24  
1. Permit set : 01.31.24  
PREPARED BY : NYE  
REVIEWED BY : NYE  
PROJECT NUMBER  
OS230050.00  
DRAWING TITLE  
MECHANICAL  
DETAILS  
(3 OF 3)  
DRAWING NUMBER  
M203  
SHEET 7 OF 11










**PLAN VIEW - ROOM #1**  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)

**SECTION 1 - ROOM #1**  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)

**SECTION 2 - ROOM #2**  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)  
 12" DIA. FAN (12" DIA.)

[illegible]






econ·air



Aloha Hala at Rallyard\_R3

DATE: 1/3/2025
DWG. #: 7254371
DRAWN BY: Johnson
SCALE: 3/4" = 1'-0"
MASTER DRAWING
SHEET NO.




Aloha Hala at Rallyard\_R3

DATE: 1/3/2025
DWG.#: 7254371
DRAWN BY: johnson
SCALE: 3/4" = 1'-0"
MASTER DRAWING
SHEET NO.



Aloha Holo at Rallyard\_R3

DATE: 1/3/2026
DWG. NO: 7254271
DRAWN BY: john.c...
SCALE: 3/4" = 1'-0"
MASTER DRAWING
SHEET NO.



econ·air

Alaha Hala at Rallyard\_R3

DATE: 1/3/2025
DWGL: 7254371
DRAWN BY: JOHN.SA
SCALE: 3/4" = 1'-0"
MASTER DRAWN
SHEET NO.

**NY ENGINEERS**  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.257.3455  
[WWW.NY-ENGINEERS.COM](http://WWW.NY-ENGINEERS.COM)

# ALOHA HOLA AT RAIL YARD

5. Revision 4 : 01.08.25

2. Revision 3 : 04/34/34

2. Revision 1 : 03.05.24

PREPARED BY : NYE

[illegible]

DRAWING TITLE

(2 OF 3)


DRAWING NUMBER

100

---



- DEMAND CONTROL VENTILATION HOOD CONTROL PANEL SPECIFICATIONS:
- THE CONTROL PANEL SHALL BE LISTED BY ETL, UL, ICC-ES AND SHALL COMPLY WITH DEMAND VENTILATION SYSTEM FUNCTION REQUIREMENTS OUTLINED IN EICC 403.5 (2005).
  - THE CONTROL ENCLOSURE SHALL BE NON-FLAMMABLE AND LISTED FOR INSTALLATION INSIDE OF THE SUPPLY/DUCT/EXHAUST CHASSEL. THE CONTROL ENCLOSURE MAY BE CONSTRUCTED OF STAINLESS STEEL OR PAINTED STEEL.
  - TEMPERATURE PROBES LOCATED IN THE EXHAUST DUCT RESERVOIR SHALL BE CONSTRUCTED OF FLAMELESS STEEL.
  - A DIGITAL CONTROLLER SHALL BE PROVIDED TO ACTIVATE THE HOOD EXHAUST FANS DYNAMICALLY BASED ON A USER DEFINED RANGE OF SUPPLY AND DUCT TEMPERATURE SENSORS THIS FUNCTION SHALL MEET THE REQUIREMENTS OF ICC 507.1.
  - A DIGITAL CONTROLLER SHALL PROVIDE ADJUSTABLE Hysteresis SETTINGS TO PREVENT CYCLING OF THE FANS OF THE COOKING APPLIANCE FANS WHEN TANCES OFF AND/OR ON THE HEAT IN THE EXHAUST DUCT.
  - A DIGITAL CONTROLLER SHALL PROVIDE AN ADJUSTABLE MINIMUM FAN RUN-TIME SETTINGS TO PREVENT FAN CYCLING.
  - VARIABLE FREQUENCY DRIVES (VFD) SHALL BE PROVIDED FOR FANS AS REQUIRED. THE DIGITAL CONTROLLER SHALL MODULATE THE VFD'S BASED ON A MINIMUM SETPOINT AND A MAXIMUM SETPOINT OR DEMAND. THE DUCT TEMPERATURE SENSOR INPUTS TO THE DIGITAL CONTROLLER SHALL BE USED TO CALCULATE THE SPEED REFERENCE SIGNAL.
  - AN INTERNAL ALGORITHM TO THE DIGITAL CONTROLLER SHALL MODULATE SUPPLY FAN VFD SPEED PROPORTIONAL TO ALL EXHAUST FANS THAT ARE LOCATED IN THE SAME FAN GROUP AS THE SUPPLY FAN.
  - THE SYSTEM SHALL OPERATE IN FREE MODE DURING LIGHT COOKING LOAD OR COOL DOWN MODE WHEN SUFFICIENT HEAT REMAINS UNDERNEATH THE HOOD SYSTEM AFTER COOKING OPERATION AND/IMPULSES OPERATING DURING OFFICE OF THESE PROCEEDS WILL STANDBY THE SUPPLY FANS AND PROVIDE AN EXHAUST FAN SPEED THAT IS EQUAL TO THE MINIMUM VENTILATION REQUIREMENTS.
  - A DIGITAL CONTROLLER SHALL STANDBY THE SUPPLY FANS/ACTIVATE THE EXHAUST FANS/ACTIVATE THE EXHAUST FANS/STANDBY AND STANDBY AN EXHAUST GAS VALVE INDICATOR/ALARM FOR COOKING TIME.
  - A DIGITAL CONTROLLER SHALL ALLOW FOR EXTERNAL BMS FAN CONTROL VIA DRY CONTACT (EXTERNAL DRIVES SHALL NOT OPERATE FAN OPERATION COOL AS REQUIRED BY CODE).
  - AN I/O INTERFACE SHALL BE PROVIDED WITH THE FOLLOWING FEATURES:
    - A. INTEGRATED GAS VALVE RESET FOR ELECTRONIC GAS VALVES AND RESET RELAY REQUIRED.
    - B. VFD SHALL OPERATE WITH A USER-ALARM NOTIFICATION.
    - C. DUCT TEMPERATURE SENSORS FAILURE DETECTION WITH ALARMS & VISUAL ALARM NOTIFICATION.
    - D. RES-RESIST DUCT TEMPERATURE SENSORS DETECTION WITH ALARMS & VISUAL ALARM NOTIFICATION.
    - E. A SINGLE-TO-VOLTAGE CONTACT PLANT WIRING CONNECTION.
    - F. AN ENERGY SAVING INDICATOR THAT UTILIZES MEASURED KW/H FROM THE VFD'S.



- SEQUENCE OF OPERATIONS:
- THE HOOD CONTROL PANEL IS CAPABLE OF OPERATING IN ONE OR MORE OF THE FOLLOWING STATES AT ANY GIVEN TIME:
    - STANDBY: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).
    - FREE MODE: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).
    - COOL DOWN MODE: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).
    - STANDBY: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).
  - STANDBY: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).
  - FREE MODE: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).
  - COOL DOWN MODE: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).
  - STANDBY: THE SYSTEM OPERATES BASED ON THE DIFFERENTIAL BETWEEN ROOM TEMPERATURE AND THE TEMPERATURE OF THE HOOD EXHAUST OR EXHAUST DUCT (CALL AS FAN ACTIVITY AT ANY GIVEN TIME).

secon·air

Aloma\_Hola at Railyard\_23

DATE: 1/12/2025

DESIGN: [REDACTED]

BY: [REDACTED]

SCALE: 1/8" = 1'-0"

MASTER DRAWING

SHEET NO. 1































NY ENGINEERS

NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25	4
4. Revision 3 : 06.07.24	
3. Revision 2 : 04.24.24	
2. Revision 1 : 03.05.24	
1. Permit set : 01.31.24	
PREPARED BY : NYE	
REVIEWED BY : NYE	
PROJECT NUMBER OS230050.00	
DRAWING TITLE HOOD DETAILS (3 OF 3)	
DRAWING NUMBER M403	
SHEET 11 OF 11	



ELECTRICAL SYMBOLS LIST							GENERAL NOTES ( APPLY TO ALL "E" DRAWINGS)			
LIGHTING		POWER AND TELECOMMUNICATION		ABBREVIATIONS			<div>1. ALL WORK SHALL BE PERFORMED IN STRICT ACCORDANCE WITH THE CURRENT VERSION OF THE NEC 2017, LOCAL JURISDICTION REQUIREMENTS, AND ALL GOVERNING LOCAL CODES, LAWS, AND REGULATIONS.</div> <div>2. CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH ALL EXISTING CONDITIONS THAT MAY AFFECT THE WORK. NO ADDITIONAL COMPENSATION WILL BE CONSIDERED FOR FAILURE TO DO SO.</div> <div>3. CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS, TEST REPORTS, AND CERTIFICATIONS FOR TEMPORARY AND FINAL CERTIFICATE OF OCCUPANCY.</div> <div>4. FIRE STOP ALL PENETRATIONS OF FIRE RATED CONSTRUCTION IN A CODE APPROVED MANNER IN ORDER TO MAINTAIN FIRE RATING. ALL PENETRATIONS SHALL BE SLEEVED AND SEALED WATERTIGHT.</div> <div>5. SECURE ALL SUPPORTS TO BUILDING STRUCTURE UTILIZING TOGGLE BOLTS (HOLLOW MASONRY) EXPANSION SHIELDS OR INSERTS (CONCRETE AND BRICK), MACHINE SCREWS (METAL), BEAM CLAMPS (FRAMEWORK), WOOD SCREWS (WOOD) OR PAN THRU STRAPS (METAL DECK). NAILS, RAWL PLUGS AND WOOD PLUGS ARE NOT PERMITTED. WHERE REQUIRED BY STRUCTURE, PROVIDE THRU BOLTS AND FISH PLATES. SUPPORT HORIZONTAL RUNS OF METALLIC RACEWAYS NOT MORE THAN 10 FT APART. SUPPORT RACEWAY RISERS AT EACH FLOOR LEVEL. RUN EXPOSED RACEWAYS PARALLEL WITH OR AT RIGHT ANGLES TO WALLS.</div> <div>6. LEAVE WIRES WITH SUFFICIENT SLACK TO PERMIT MAKING FINAL CONNECTIONS. RACEWAYS OVER 10 FT LONG IN WHICH WIRING IS NOT INSTALLED: FURNISH FISH WIRE.</div> <div>7. VERIFY LOCATIONS OF OUTLETS AND SWITCHES IN FINISHED ROOMS WITH ARCHITECTURAL DRAWINGS OF INTERIOR DETAILS AND FINISH. IN CENTERING OUTLETS AND LOCATING BOXES AND OUTLETS, ALLOW FOR OVERHEAD PIPES, DUCTS AND MECHANICAL EQUIPMENT, EQUIPMENT, VARIATIONS IN FIREPROOFING AND PLASTERING, WINDOW AND DOOR TRIM, PANELING, HUNG CEILINGS AND THE LIKE. CORRECT ANY INACCURACY RESULTING FROM FAILURE TO DO SO WITHOUT EXPENSE TO OWNER.</div> <div>8. CONTRACTOR SHALL PROVIDE A WARRANTY ON ALL MATERIALS, EQUIPMENT, AND WORKMANSHIP FOR A PERIOD OF ONE YEAR FROM THE DATE OF FINAL ACCEPTANCE.</div> <div>9. ALL UNUSED MATERIALS AND DEBRIS SHALL BE LEGALLY REMOVED AND DISPOSED OF AWAY FROM THE PREMISES ON A DAILY BASIS.</div> <div>10. CONTRACTOR SHALL PATCH, PAINT, AND RESTORE EXISTING SURFACES DAMAGED DURING THE COURSE OF THIS CONSTRUCTION TO PRE-EXISTING CONDITIONS OR BETTER.</div> <div>11. MINIMUM SIZE OF CONDUIT SHALL BE ¾", AND TYPE SHALL BE ELECTRICAL METALLIC TUBING (EMT), UNLESS OTHERWISE NOTED. PROVIDE NYLON DRAG LINE AND CONDUIT CAP FOR ALL EMPTY CONDUITS.</div> <div>12. CONNECT CONDUIT TO MOTOR CONDUIT TERMINAL BOXES WITH FLEXIBLE CONDUIT (MINIMUM 18 IN. LENGTH AND 50% SLACK). DO NOT TERMINATE IN OR FASTEN RACEWAYS TO MOTOR FOUNDATION.</div> <div>13. PULL AND JUNCTION BOXES WHERE INDICATED ON THE DRAWINGS, SHALL BE CONSIDERED SHOWN AT THEIR APPROXIMATE LOCATION. THE CONTRACTOR SHALL LOCATE THEM AS FIELD CONDITIONS DICTATE. ADDITIONAL PULL AND JUNCTION BOXES NOT SHOWN ON DRAWINGS SHALL BE PROVIDED WHERE REQUIRED BY APPLICABLE CODE PROVISIONS OR WHERE CALLED FOR BY FIELD CONDITIONS. PULL AND JUNCTION BOXES SHALL BE SURFACE TYPE IN UNFINISHED AREAS AND INSTALLED CONCEALED IN FINISHED AREAS, AND ALL COVERS TO PULL &amp; JUNCTION BOXES SHALL BE READILY ACCESSIBLE.</div> <div>14. SUPPORT PANEL, JUNCTION AND PULLBOXES INDEPENDENTLY TO BUILDING STRUCTURE WITH NO WEIGHT BEARING ON RACEWAYS.</div> <div>15. FOR EXACT LOCATION AND MOUNTING HEIGHT OF LIGHTING FIXTURES AND SWITCH/RECEPTACLE OUTLETS, REFER TO ARCHITECTURAL REFLECTED CEILING AND POWER PLANS.</div> <div>16. ALL ELECTRICAL ACCESSORIES AND EQUIPMENT INSTALLED OUTSIDE OR EXPOSED TO WEATHER SHALL HAVE NEMA 3R ENCLOSURES AND SHALL BE TIGHTLY GASKETED FOR A COMPLETE RAIN/TIGHT INSTALLATION. ALL BUILDING EXTERIOR MOUNTED RECEPTACLES SHALL BE GFCI RATED AND MOUNTED IN WEATHERPROOF ENCLOSURE.</div> <div>17. ALL ACCESS PANEL LOCATIONS SHALL BE REVIEWED BY ARCHITECT PRIOR TO INSTALLATION.</div> <div>18. ELECTRICAL CONTRACTOR SHALL COORDINATE THE LOCATION AND INSTALLATION OF NEW WORK WITH THE GENERAL CONTRACTOR AND OTHER ASSOCIATED TRADES IN A TIMELY MANNER. THE CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL DIMENSIONS AND CONDITIONS PRIOR TO CONSTRUCTION. REFER TO ALL GENERAL, MECHANICAL, AND ELECTRICAL, DRAWINGS AND SPECIFICATIONS FOR THIS PROJECT.</div> <div>19. ALL CONDUITS AND EQUIPMENT TO BE CONCEALED IN FINISHED SPACES UNLESS OTHERWISE NOTED. CONDUITS SHALL BE ENCASED IN THE CONCRETE FLOOR SLAB.</div> <div>20. ALL EQUIPMENT AND MATERIALS INSTALLED IN PLENUM CEILINGS SHALL BE APPROVED FOR THAT APPLICATION.</div> <div>21. OUTLET BOXES AND JUNCTION BOXES ON OPPOSITE SIDES OF FIRE-RATED WALLS SHALL BE SEPARATED BY A HORIZONTAL DISTANCE OF NOT LESS THAN 24 INCHES, UNLESS FIRE-RATED BOXES OR PUTTY PADS ARE UTILIZED.</div> <div>22. COORDINATE ALL FLOOR PENETRATIONS WITH THE STRUCTURAL AND ARCHITECTURAL DRAWINGS. CONFIRM PENETRATION LOCATIONS WITH THE ENGINEER AND OWNER BEFORE INSTALLATION.</div> <div>23. COORDINATE THE MOUNTING HEIGHT AND LOCATION OF RACEWAYS, COMMUNICATIONS OUTLETS, AND RECEPTACLES WITH THE ARCHITECTURAL CASEWORK DRAWINGS AND DETAILS. COORDINATE LOCATIONS OF LIGHT FIXTURES, SWITCHES, AND RELATED DEVICES WITH THE ARCHITECTURAL DRAWINGS AND DETAILS.</div> <div>24. REFER TO ARCHITECTURAL PLANS FOR FINAL LOCATIONS OF ALL LUMINARIES AND SWITCHES, AND FOR ALL FINISHED CEILING HEIGHTS.</div> <div>25. REFER TO ARCHITECTURAL PLANS FOR FINAL LOCATIONS OF ALL ELECTRICAL DEVICES, AND FOR FINAL CEILING AND WALL HEIGHTS AND LAYOUTS.</div> <div>26. LIGHTING FIXTURES PROVIDED WITH EMERGENCY BATTERY PACKS AND INDICATED WITH SWITCH CONTROL SHALL BE WIRED WITH BATTERY CHARGING/SENSING CIRCUIT WIRED AHEAD OF SWITCH CONTROL.</div> <div>27. NUMBER(S) SHOWN AT RECEPTACLES, JUNCTION BOXES AND EQUIPMENT INDICATES CIRCUIT NUMBERS IN PANELBOARD. PROVIDE WIRE AND CONDUIT TO INTERCONNECT EQUIPMENT AND DEVICES WITH SAME CIRCUIT NUMBERS AND RUN TO PANELBOARD.</div>			
	LIGHTING FIXTURE AND OUTLET BOX. HALF SHADED FIXTURE OR "EM" INDICATES FIXTURES WITH INTEGRAL BATTERY PACK FOR EMERGENCY SERVICE, U.O.N.		DISCONNECT (SAFETY) SWITCH "200/3/150" DENOTES AMPERES/POLE/FUSE, "NF" DENOTES NON-FUSED, "N3R" DENOTES NEMA 3R	A	AMPERES	EA				EACH
	LUMINAIRE TYPE : INDICATE BY LIPPERCASE LETTER SEE LIGHTING EXTURE SCHEDULE.		30A/240V NON FUSED DISCONNECT SWITCH	A/C, AC	AIR CONDITIONING UNIT	EC				EMPTY CONDUIT/ ELECTRICAL CONTRACTOR
	CIRCUIT NUMBER : INDICATED BY NUMBER		60A/240V NON FUSED DISCONNECT SWITCH	AF	AMPERE FRAME/AMP FUSE	EF				EXHAUST FAN
	SWITCHING INDICATED BY LOWER CASE LETTERS.		EXHAUST FAN WITH LIGHT (COORDINATE EXACT CONTROL WITH MECHANICAL VENDOR/EQUIPMENT MANUFACTURER).	AFF	ABOVE FINISHED FLOOR	EM				EMERGENCY
	●EM DENOTES LUMINAIRE ON EMERGENCY CIRCUIT.				AS	AMP SWITCH				EMT
●NL	DENOTES FIXTURES DESIGNATED AS NIGHTLIGHT, WIRED TO 24 HOURS UNSWITCHED CIRCUIT.			AIC	AMPS INTERRUPTING CAPACITY	EQUIP				EQUIPMENT
		RECEPTACLES AND OUTLETS		AT	AMP TRIP	ER				EXISTING TO BE RELOCATED
			DUPLEX CONVENIENCE RECEPTACLE	ATS	AUTOMATIC TRANSFER SWITCH	ETR				EXISTING TO REMAIN
			DEDICATED POWER OUTLET "D" DENOTES DEDICATED POWER OUTLET, "GFI" DENOTES GROUND FAULT INTERRUPTER, "WP" DENOTES WEATHERPROOF.	AUTO	AUTOMATIC	EWf				ELECTRIFIED WORKSTATION FURNITURE
			CEILING MOUNTED DUPLEX OUTLET	AWG	AMERICAN WIRE GAUGE	EWH				ELECTRIC WATER HEATER
			QUAD OUTLET	C	CONDUIT	FA				FIRE ALARM
WIRING SYSTEMS			JUNCTION BOX	C/B,CB	CIRCUIT BREAKER	FBO				FURNISHED BY OTHERS, INSTALLED & WIRED BY EC
	POWER OR LIGHTING CIRCUITRY HOMERUN WITH PANELBOARD DESIGNATION, NUMBER WHERE USED INDICATES CIRCUIT NUMBER. IT SHALL CONSISTS OF 1#12 Ø, 1#12 N. & 1#12 G. IN 3/4"C, UNLESS OTHERWISE NOTED.		20A WALL SWITCH U.O.N.	CKT	CIRCUIT	FDR				FEEDER
	POWER OR LIGHTING CIRCUITRY HOMERUN WITH PANELBOARD DESIGNATION, NUMBER WHERE USED INDICATES CIRCUIT NUMBER. IT SHALL CONSISTS OF 2#12 Ø, 2#12 N. & 2#12 G. IN 3/4"C, UNLESS OTHERWISE NOTED.		TIMER SWITCH	CLG	CEILING	FIBO				FURNISHED & INSTALLED BY OTHERS, WIRED BY EC
	POWER OR LIGHTING CIRCUITRY HOMERUN WITH PANELBOARD DESIGNATION, NUMBER WHERE USED INDICATES CIRCUIT NUMBER. IT SHALL CONSISTS OF 3#12 Ø, 3#12 N. & 3#12 G. IN 3/4"C, UNLESS OTHERWISE NOTED.		WALL OCCUPANCY SENSOR	COMM	COMMUNICATION	FIXT				FIXTURE
	UNDERGROUND		MOTOR SWITCH	CT	CURRENT TRANSFORMER	FL				FLOOR
	EXISTING		CEILING OCCUPANCY SENSOR	CU	COPPER	FLUOR				FLOUORESCENT
	NEW	POWER DISTRIBUTION		°C	DEGREE CELSIUS	G				GROUND
ELECTRICAL DRAWING LIST			DISTRIBUTION PANELBOARD, SURFACE OR FLUSH MOUNTED.	°F	DEGREE FAHRENHEIT	GFI				GROUND FAULT INTERRUPTER
E001	ELECTRICAL SYMBOLS & ABBREVIATIONS	COMMUNICATIONS		DIA	DIAMETER	GP				GENERAL PURPOSE
E002	ELECTRICAL SPECIFICATIONS-1		TELEPHONE/DATA OUTLET, 4"SQARE OUTLET BOX WITH SINGLE GANG COLLAR AND BLANK PLATE. PROVIDE 3/4" E.C., U.O.N., UP TO HUNG CEILING AND TERMINATE WITH 90° ELBOW, BUSHING AND DRAG WIRE.	DISC	DISCONNECT	HC				HUNG CEILING
E003	ELECTRICAL SPECIFICATIONS-2		DATA OUTLET, ELECTRICAL CONTRACTOR TO PROVIDE MUD RING AND PULL STRING TO ABOVECEILING	DN	DOWN	HP				HORSEPOWER
E100	ELECTRICAL LIGHTING PLAN		CEILING MOUNTED DATA OUTLET	DP	DISTRIBUTION PANEL	HWH				HOW WATER HEATER
E200	ELECTRICAL POWER PLAN	ANNOTATION		DWH	DOMESTIC WATER HEATER	HZ				HERTZ
E201	ELECTRICAL POWER PLAN-ROOF		INDICATES MOUNTING HEIGHT, CENTER LINE TO FINISHED FLOOR.	DWG	DRAWING	IC				INTERRUPTING CAPACITY
E300	ELECTRICAL DETAILS		KEYED NOTE REFERENCE	JB	JUNCTION BOX	PP				POWER PANEL
E400	ELECTRICAL RISER DIAGRAM AND PANEL SCHEDULE		DETAIL REFERENCE: DETAIL NUMBER INDICATED ON TOP; DRAWING NUMBER INDICATED ON BOTTOM	KCMIL	ONE THOUSAND CIRCULAR MILS	PVC				POLYVINYL CHLORIDE
<div>CODE COMPLIANCE</div> <div>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTHING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</div> <div>a. VIRGINIA BUILDING CODE 2018 ADOPTS IBC 2018</div> <div>b. VIRGINIA MECHANICAL CODE 2018 ADOPTS IMC 2018</div> <div>c. VIRGINIA PLUMBING CODE 2018 ADOPTS IPC 2018</div> <div>d. VIRGINIA FUEL GAS CODE 2018 ADOPTS IFGC 2018</div> <div>e. VIRGINIA ELECTRICAL CODE 2017 ADOPTS NEC 2017</div>				KV	KILOVOLT	PWR				POWER
				KVA	KILOVOLT-AMPERES	R				REMOVE
				KW	KILOWATTS	RE				RELOCATED EXISTING
				LP	LIGHTING PANEL	REC				RECEPTACLE
				LTG	LIGHTING	RGS				RIGID GALVANIZED STEEL
				MAX	MAXIMUM	RR				REMOVE & RELOCATE
				MC	MOTOR CONTROLLER	SECT				SECTION
				MCB	MAIN CIRCUIT BREAKER	SPDT				SINGLE POLE DOUBLE THROW
				MER	MECHANICAL EQUIPMENT ROOM	SPST				SINGLE POLE SINGLE THROW
				MIN	MINIMUM	SPEC				SPECIFICATION
		MLO	MAIN LUGS ONLY	SW	SWITCH					
		MTD	MOUNTED	SWBD	SWITCHBOARD					
		MTS	MANUAL TRANSFER SWITCH	SYM	SYMMETRICAL					
		N	NEUTRAL	SYS	SYSTEMS					
		NE	NEW DEVICE TO REPLACE EXISTING	TELE	TELEPHONE					
		NIC	NOT IN CONTRACT	TEMP	TEMPERATURE					
		NL	NIGHT LIGHT	TXF	TOILET EXHAUST FAN					
		NTS	NOT TO SCALE	TYP	TYPICAL					
		OC	ON CENTER	UON	UNLESS OTHERWISE NOTED					
		P	POLES	V	VOLT/VOLTAGE					
		PB	PULLBOX	VA	VOLT AMPERE					
		PC	PERSONAL COMPUTER	VAV	VARIABLE AIR VOLUME					
		ø	PHASE	VFD	VARIABLE FREQUENCY DRIVE					
		PNL	PANEL	VP	VAPORPROOF					
		W	WATT	WP	WEATHER PROOF					
		W	WIRE	XPFR	TRANSFORMER					
		WH	WALL HEATER	ZRT	ZONE REGISTER TERMINALS					
		E	EXISTING	IG	ISOLATED GROUND					
		TR	TAMPER RESISTANCE	RTU	ROOF TOP UNIT					

NY ENGINEERS

NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25

4. Revision 3 : 06.07.24

3. Revision 2 : 04.24.24

2. Revision 1 : 03.05.24

1. Permit set : 01.31.24

PREPARED BY : NYE

REVIEWED BY : NYE

PROJECT NUMBER  
OS230050.00

DRAWING TITLE  
ELECTRICAL SYMBOLS  
& ABBREVIATIONS

DRAWING NUMBER  
E001

SHEET 1 OF



ELECTRICAL SPECIFICATIONS

1. GENERAL:

- A. THE "GENERAL CONDITIONS OF THE CONTRACT FOR CONSTRUCTION," AIA DOCUMENT A201, LATEST EDITION, AND THESE SPECIFICATIONS AS APPLICABLE ARE PART OF THIS CONTRACT.
- B. DRAWING ARE DIAGRAMMATIC AND INDICATE GENERAL ARRANGEMENT OF SYSTEMS AND WORK. CONDUIT ROUTING IS SHOWN. DO NOT DIAGRAMMATICALLY AND DOES NOT SHOW ALL OFFSETS, DROPS AND RISES OF RUNS. THE CONTRACTOR SHALL ALLOW IN HIS PRICE FOR ROUTING OF CONDUIT TO AVOID OBSTRUCTIONS. COORDINATION WITH EXISTING SERVICES, INCLUDING THOSE OF OTHER TRADES, IS REQUIRED, MAINTAIN HEADROOM AND SPACE CONDITIONS.
- C. BIDDERS, BEFORE SUBMITTING PROPOSALS, SHALL VISIT AND CAREFULLY EXAMINE THE AREA AFFECTED BY THIS WORK TO FAMILIARIZE THEMSELVES WITH THE EXISTING CONDITIONS AND THE DIFFICULTIES THAT WILL ATTEND THE EXECUTION OF THIS WORK. SUBMISSION OF A PROPOSAL WILL BE CONSTRUED AS EVIDENCE THAT SUCH AN EXAMINATION HAS BEEN MADE, AND LATER CLAIMS WILL NOT BE RECOGNIZED FOR EXTRA LABOR, EQUIPMENT, OR MATERIALS, REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WHICH COULD HAVE BEEN FORESEEN HAD SUCH AN EXAMINATION BEEN MADE.
- D. DISCONNECT, REMOVE AND/OR RELOCATE EXISTING MATERIAL, EQUIPMENT AND OTHER WORK AS NOTED OR REQUIRED FOR PROPER INSTALLATION OF NEW WORK.
- E. THE CONTRACTOR SHALL KEEP ALL EQUIPMENT AND MATERIALS, AND ALL PARTS OF THE BUILDING EXTERIOR SPACES AND ADJACENT STREETS, SIDEWALKS AND PAVEMENTS, FREE FROM MATERIAL AND DEBRIS RESULTING FROM THE EXECUTION OF THIS WORK. EXCESS MATERIALS WILL NOT BE PERMITTED TO ACCUMULATE EITHER ON THE INTERIOR OR THE EXTERIOR.
- F. SEAL OPENINGS THROUGH PARTITIONS, WALLS AND FLOORS WITH MINERAL WOOL OR OTHER NONCOMBUSTIBLE MATERIAL, UNLESS OTHERWISE NOTED.
- G. PROVIDE ALL NECESSARY FLASHING AND COUNTER FLASHING TO MAINTAIN THE WATERPROOFING INTEGRITY OF THE BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF CONDUIT AND EQUIPMENT, PROVIDE EQUIPMENT CURBS AS REQUIRED.
- H. ALL EXISTING MATERIAL, EQUIPMENT AND CONSTRUCTION DEBRIS TO BE REMOVED UNDER THIS CONTRACT SHALL BECOME THE PROPERTY OF THE CONTRACTOR WITH THE EXCEPTION OF SPECIFIC EQUIPMENT AND APPARATUS REQUESTED BY THE BUILDING REPRESENTATIVE, ARCHITECT OR AS NOTED TO BE RELOCATED ON THE DRAWINGS. REMOVED EQUIPMENT SHALL BE PROPERLY DISPOSED OF BY THIS CONTRACTOR.
- I. THE CONTRACTOR'S PROPOSAL FOR ALL WORK SHALL BE PREDICATED ON THE PERFORMANCE OF THE WORK DURING REGULAR WORKING HOURS. WHEN SO DIRECTED, HOWEVER, THE CONTRACTOR SHALL INSTALL WORK DURING OVERTIME HOURS AND THE ADDITIONAL COST TO BE CHARGED THEREFORE SHALL BE ONLY THE "PREMIUM" PORTION OF THE WAGES PAID.
- J. UNLESS OTHERWISE SPECIFICALLY NOTED OR SPECIFIED, INCLUDE ALL CUTTING AND PATCHING OF EXISTING FLOORS, WALLS, PARTITIONS AND OTHER MATERIALS IN THE EXISTING BUILDING. THE CONTRACTOR SHALL RESTORE THESE AREAS TO ORIGINAL CONDITION.
- K. ALL MATERIAL AND EQUIPMENT SHALL BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- L. INSURANCE: PROVIDE IN ACCORDANCE WITH OWNER/BUILDING REQUIREMENTS AND SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND ENGINEER.
- M. THE FINAL ACCEPTANCE SHALL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, TESTED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATED OF INSPECTION AND APPROVAL.

2. GENERAL PROVISIONS FOR ELECTRICAL WORK:

A. DEFINITIONS:

- 1) "PROVIDE": TO FURNISH, INSTALL AND CONNECT UP COMPLETE AND READY FOR SAFE AND REGULAR OPERATION THE PARTICULAR WORK REFERRED TO UNLESS SPECIFICALLY OTHERWISE NOTED.
- 2) "INSTALL": TO ERECT, MOUNT AND CONNECT COMPLETE WITH RELATED ACCESSORIES.
- 3) "FURNISH" OR "SUPPLY": TO PURCHASE, PROCURE, ACQUIRE, AND DELIVER COMPLETE WITH RELATED ACCESSORIES.
- 4) "WORK": LABOR, MATERIALS, EQUIPMENT, APPARATUS, CONTROLS, ACCESSORIES AND OTHER ITEMS REQUIRED FOR PROPER AND COMPLETE INSTALLATION.
- 5) "WIRING": RACEWAY, FITTINGS, WIRE, BOXES, AND RELATED ITEMS.
- 6) "CONCEALED": EMBEDDED IN MASONRY OR OTHER CONSTRUCTION, INSTALLED IN FURRED SPACES, WITHIN DOUBLE PARTITIONS OR HUNG CEILINGS, IN TRENCHES, IN CRAWL SPACES, OR IN ENCLOSURES.
- 7) "EXPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.
- 8) "SIMILAR" OR "EQUAL": EQUAL IN MATERIALS, WEIGHT, SIZE, DESIGN AND EFFICIENCY OF SPECIFIED PRODUCT.

- B. TEMPORARY LIGHT AND POWER: PROVIDE TEMPORARY LIGHT AND POWER SYSTEMS AT EARLIEST POSSIBLE DATE WITHIN THE CONSTRUCTION AREAS FOR THE REQUIREMENTS OF ALL TRADES AS HEREIN DESCRIBED. EXTEND SYSTEMS TO NEW CONSTRUCTION AS SOON AS PHYSICALLY POSSIBLE. MAINTAIN SYSTEM DURING WORKING OWNER, PROVIDE ALL REQUIRED MAINTENANCE, INCLUDING LAMPS AND SOCKETS.

C. QUALITY ASSURANCE

- 1) QUALITY OF MATERIALS: ALL EQUIPMENT SHALL BE NEW SPECIFICATION GRADE, FREE FROM DEFECTS AND LISTED BY APPROVED TESTING AGENCY AND BEARING THEIR LABEL MATERIALS AND EQUIPMENT OF SIMILAR APPLICATION SHALL BE OF SAME MANUFACTURER, EXCEPT AS NOTED.
- 2) GUARANTEE: ALL MATERIALS AND WORKMANSHIP SHALL BE GUARANTEED AS DEFINED IN PARAGRAPH 2.C.
- 3) CURRENT CHARACTERISTICS:
- a. SERVICE: 120/208 VOLT, 3 PHASE, 4 WIRE, 60 HERTZ WITH GROUNDED NEUTRAL.
- b. DISTRIBUTION: 120/208 VOLT, 3 PHASE, 4 WIRE, 60 HERTZ WITH GROUNDED NEUTRAL.

4) HEIGHTS OF OUTLETS:

- a. FROM FINISHED FLOOR TO CENTERLINE OF OUTLETS FOR:
- RECEPTACLES AND TELEPHONES: 1 FT-6 IN.
- WALL SWITCHES: 4 FT-0 IN.
- WALL FIXTURES: 7 FT-0 IN.
- MOTOR CONTROLLERS: 5 FT-0 IN.
- CLOCKS: 7 FT 6 IN

- b. EXCEPTIONS: AT JUNCTION OF DIFFERENT WALL FINISH MATERIALS, ON MOLDING OR BREAK IN WALL SURFACE, IN VIOLATION OF CODE, OR AS NOTED OR DIRECTED.

D. PRODUCT DELIVERY, STORAGE AND HANDLING

- 1) MOVING OF EQUIPMENT: WHERE NECESSARY, SHIP IN CARTED SECTIONS OF SIZE TO PERMIT PASSING THROUGH AVAILABLE SPACES.
- 2) ACCESSIBILITY: FOR OPERATION, MAINTENANCE AND REPAIR, MINOR DEVIATIONS SHALL BE PERMITTED, CHANGES OF MAGNITUDE OR INVOLVING EXTRA COST ARE NOT PERMISSIBLE WITHOUT REVIEW. GROUP CONCEALED ELECTRICAL EQUIPMENT REQUIRING ACCESS WITH EQUIPMENT FREELY ACCESSIBLE THROUGH ACCESS DOORS.

E. MATERIALS

- 1) NAMEPLATES: PROVIDE BLACK LAMICOID SHEET WITH 3/4 IN. WHITE LETTERING, FASTENED WITH EPOXY CEMENT FOR EACH DISCONNECT SWITCH, CIRCUIT BREAKER, PANEL, CABINET, TRANSFORMER, ENCLOSURE, MOTOR CONTROLLER AND THE LIKE. NAMEPLATES SHALL DESCRIBE THE NAME AND NUMBER OF EACH COMPONENT.
- 2) CABLE TAGS: TAG EACH CONDUCTOR PASSING THROUGH SPLICE OR PULLBOX WITH A WHITE LINEN TAG, INDICATING POINT OF ORIGIN AND TERMINATION OF THE CIRCUIT.
- 3) INSERTS AND SUPPORTS:
- a. INSERTS: STEEL, SLOTTED TYPE, FACTORY PAINTED.
- SINGLE ROD: SIMILAR TO GRINNELL FIG. 281.
- MULT-ROD: SIMILAR TO FEE AND MASON SERIES 9000 WITH END CAPS AND CLOSURE STRIPS.
- CLIP FORM NAILS FLUSH WITH INSERTS.
- MAXIMUM LOADING 75 PERCENT OF RATING.
- b. SUPPORTS FROM BUILDING CONSTRUCTION: INSERTS, BEAM CLAMPS, STEEL FISHPLATES (IN CONCRETE FILL ONLY), CANTILEVER BRACKETS OR OTHER MEANS. SUBMIT FOR REVIEW.
- c. GROUPED LINES AND SERVICES: TRAPEZE HANGERS OF BOLTED ANGLES OR CHANNELS.
- d. WHERE BUILDING CONSTRUCTION IS INADEQUATE: PROVIDE ADDITIONAL FRAMING. SUBMIT FOR REVIEW.

- F. PAINT SHALL BE THE BEST GRADE FOR ITS PURPOSE. DELIVER IN ORIGINAL SEALED CONTAINERS AND APPLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. COLORS SHALL BE AS SELECTED BY ARCHITECT OR ENGINEER. UTILIZE GALVANIZED IRON PRIMER ON PANEL AND PULL BOXES, AFTER FABRICATION. UTILIZE HOT DIPPED GALVANIZED OR DIPPED IN ZINC BASED PRIMER FOR: OUTLET BOXES, JUNCTION BOXES, CONDUIT HANGERS, RODS, INSERTS AND SUPPORTS. ZINC BASED PRIMER WITH FINISH TO MATCH SURROUNDINGS SHALL BE USED FOR MARKED SURFACES OF STEEL EQUIPMENT AND RACEWAYS. A FIELD-APPLIED ZINC BASED PRIME COAT SHALL BE UTILIZED FOR STEEL OR IRONWORK.

- G. BRUSH AND CLEAN WORK PRIOR TO CONCEALING, PAINTING AND ACCEPTANCE. PAINTED EXPOSED WORK SOILED OR DAMAGED, CLEAN AND REPAIR TO MATCH ADJOINING WORK BEFORE FINAL ACCEPTANCE. REMOVE DEBRIS FROM INSIDE AND OUTSIDE OF MATERIAL AND EQUIPMENT.

- H. FINAL LOCATIONS AND MOUNTING ORIENTATIONS OF ALL SWITCHES, RECEPTACLES AND LIGHT FIXTURES SHALL BE VERIFIED WITH ARCHITECT.

- I. ALL ACCESS DOOR LOCATIONS SHALL BE REVIEWED BY ARCHITECT PRIOR TO INSTALLATION.

3. SCOPE OF WORK:

- A. SCOPE OF WORK SHALL CONSIST OF PROVIDING LABOR, MATERIALS, EQUIPMENT, SERVICES AND FEES NECESSARY FOR COMPLETE AND SAFE INSTALLATION IN CONFORMING WITH NATIONAL AND LOCAL CODES AND AUTHORITIES HAVING JURISDICTION, AS INDICATED ON DRAWINGS AND HEREIN SPECIFIED.
- B. ALL DRAWINGS, PLANS, DETAILS, SPECIFICATIONS AND SPECIFICATION ADDENDA ARE MADE PART OF THIS CONTRACT AND SHALL APPLY TO ALL WORK UNDER THE CONTRACT UNLESS OTHERWISE AMENDED, MODIFIED, SUPPLIED OR SPECIFIED HEREIN.
- C. THE CONTRACTOR SHALL FURNISH A WRITTEN GUARANTEE TO REPLACE OR REPAIR PROMPTLY AND ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED FOR ANY WORKMANSHIP AND EQUIPMENT IN WHICH DEFECTS DEVELOP WITHIN ONE YEAR FROM THE DATE OF FINAL CERTIFICATE FOR PAYMENT AND/OR FROM DATE OR ACTUAL USE OF EQUIPMENT OR OCCUPANCY OF SPACES BY OWNER. INCLUDING THE VARIOUS PARTS OF THE WORK, WHICHEVER, DATE IS EARLIER, THIS WORK SHALL BE DONE AS DIRECTED BY THE OWNER. THIS GUARANTEE SHALL ALSO PROVIDED THAT WHERE DEFECTS OCCUR, THE CONTRACTOR WILL ASSUME RESPONSIBILITY OF OTHER TRADES AFFECTED BY DEFECTS, REPAIRS OR REPLACEMENTS IN EQUIPMENT SUPPLIED BY THE CONTRACTOR
- D. THE CONTRACTOR SHALL GIVE NECESSARY NOTICE, FILE DRAWINGS AND SPECIFICATIONS WITH ALL DEPARTMENTS HAVING JURISDICTION, WORK AND PAY ALL FEES THEREFORE. THE CONTRACTOR SHALL ARRANGE FOR INSPECTION AND TESTS OF ANY OR ALL PARTS OF THE WORK IF SO REQUIRED BY AUTHORITIES AND PAY ALL CHARGES FOR SAME. THE CONTRACTOR SHALL PAY ALL COSTS FOR, AND FURNISH TO THE OWNER BEFORE FINAL BILLING, ALL CERTIFICATES NECESSARY AS EVIDENCE THAT THE WORK INSTALLED CONFORMS WITH ALL REGULATIONS WHERE THEY APPLY TO THIS WORK.
- E. CONTRACTOR SHALL PERFORM ALL CONTROLLED INSPECTIONS IN ACCORDANCE WITH THE FLORIDA BUILDING CODE. SECURE ALL REQUIRED PERMITS AND APPROVALS AND TRANSMIT SAME TO OWNER. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL FEES.
- F. AREAS WITH NO ELECTRICAL WORK SHALL REMAIN AS IS. CONTRACTOR SHALL MAINTAIN CONTINUITY OF ALL ELECTRICAL SYSTEMS TO ALL AREAS NOT COVERED BY THIS RENOVATION AND SHALL PROVIDE 48 HOUR NOTICE TO LANDLORD OF ANY PLANNED POWER INTERRUPTIONS OR SIGNAL SYSTEM OUTAGES.

4. SHOP DRAWINGS

- A. PRIOR TO THE INSTALLATION OF ANY WORK AND PROCUREMENT OF EQUIPMENT, CONTRACTOR SHALL PROVIDE COMPLETE SETS OF COORDINATED SHOP DRAWINGS OF ALL NEW AND EXISTING EQUIPMENT, INDICATING CAPACITY, DIMENSIONS AND SEQUENCE OF OPERATION FOR WRITTEN APPROVAL BY THE ARCHITECT AND ENGINEER.

B. INDICATE ON EACH SHOP DRAWINGS SUBMITTED:

- 1) PROJECT NAME AND LOCATION
- 2) NAME OF ARCHITECT AND ENGINEER
- 3) ITEM IDENTIFICATION
- 4) APPROVAL STAMP OF PRIME CONTRACTOR

C. SUBMISSIONS:

- 1) SUBMISSIONS 11 IN. X 17 IN. OR SMALLER: IF THE SUBMISSION IS A CATALOG CUT, THEN THE CONTRACTOR SHALL SUBMIT ONE ORIGINAL AND TWO COPIES. OTHERWISE, HE SHALL SUBMIT THREE COPIES. THE ARCHITECT WILL FORWARD THE ORIGINAL AND ONE COPY (TWO COPIES WHEN NO ORIGINAL IS RECEIVED) TO THE ENGINEER. ALL CATALOG CUTS SHALL BE COMPLETE.
- 2) SUBMISSIONS LARGER THAN 11 IN. X 17 IN.: SUBMIT TWO PRINTS AND ONE PAPER SEPIA TO THE ARCHITECT. THE ARCHITECT WILL FORWARD ONE PRINT AND THE PAPER SEPIA TO THE ENGINEER.

D. SUBMIT SHOP DRAWINGS FOR THE FOLLOWING:

- 1) SAFETY/DISCONNECT SWITCHES
- 2) FUSES
- 3) CIRCUIT BREAKERS
- 4) PANELBOARDS/LOADCENTER (INCLUDING DIMENSIONS, SCHEDULES, AND CATALOG CUTS).
- 5) RACEWAYS
- 6) WIRE AND CABLE
- 7) WALL SWITCHES
- 8) INSERTION RECEPTACLES
- 9) MOMENTARY CONTACT SWITCHES
- 10) TIME SWITCHES
- 11) LIGHTING FIXTURES.

- E. ASSIST AND PROVIDE ALL NECESSARY INFORMATION, DIAGRAMS, SKETCHES, ETC. TO THE HVAC CONTRACTOR, FOR THE PREPARATION OF COORDINATED SHOP DRAWINGS INDICATING ROUTING OF FEEDERS, CONTROL CONDUITS, RECESSED FIXTURES AND ADJACENT NEARBY PIPING AND DUCTWORK WHERE APPLICABLE, CERTIFIED BY ALL TRADES THAT COORDINATION HAS BEEN ESTABLISHED. SUBMIT FOUR(4) BOOKBOUND OPERATING AND SERVICE MANUALS WHICH SHALL INCLUDE COPIES OF ALL SHOP DRAWING. PROVIDE SHOP DRAWINGS FOR PANELS, FIXTURES, WIRING DEVICES, CONDUIT, CABLE, DISCONNECT SWITCH, RELAYS, CONTRACTORS, AND OTHER SYSTEMS AS DIRECTED BY THE ENGINEER.

5. AS-BUILT DRAWINGS AND EQUIPMENT OPERATIONAL INSTRUCTIONS

- A. UPON COMPLETION AND ACCEPTANCE OF WORK, CONTRACTOR SHALL FURNISH WRITTEN INSTRUCTIONS AND EQUIPMENT MANUALS AND DEMONSTRATE TO THE OWNER THE PROPER OPERATION AND MAINTENANCE OF ALL EQUIPMENT AND APPARATUS FURNISHED UNDER THIS CONTRACT.

- B. THESE INSTRUCTIONS SHALL BE TYPED ON 8-1/2 IN. X 11 IN. PAPER AND BOUND IN THREE RING BINDERS WITH CLEAR ACETATE COVERS. CONTRACTOR SHALL GIVE THREE COPIES OF THE INSTRUCTIONS TO THE OWNER AND ONE COPY TO THE ENGINEER.

- C. THE INSTRUCTION BOOKLET SHALL BEAR THE NAME, ADDRESS AND TELEPHONE NUMBER OF THE PROJECT, ARCHITECT AND ENGINEER.

- D. REPRODUCIBLE "AS-BUILT" DRAWINGS SHALL BE PROVIDED INDICATING THE AS INSTALLED CONDITIONS OF THE WORK. "AS-BUILT" DRAWINGS SHALL BE PROVIDED TO THE ARCHITECT AFTER COMPLETION OF THE INSTALLATION.

6. LOW-VOLTAGE DISTRIBUTION EQUIPMENT:

- A. PROVIDE COMPLETE EQUIPMENT INCLUDING: SWITCHES, FUSES, CIRCUIT BREAKERS, PANELS AND TRANSFORMERS.
- B. ALL EQUIPMENT SHALL CONFORM TO NEMA, ANSI AND IEEE STANDARDS.
- C. DISCONNECT SWITCHES SHALL BE FUSED OR NONFUSED AS NOTED. VOLTAGE SHALL BE AS REQUIRED. SWITCHES SHALL BE HEAVY DUTY, EXCEPT AS NOTED, AND HORSEPOWER RATED FOR MOTOR LOADS. TOGGLE TYPE SWITCHES SHALL BE NONFUSED. LOAD BREAK, HAVING MAXIMUM RATINGS OF 20 AMP AT 600 VOLTS AND 30 AMP AT 240 VOLTS. TWO-POLE SWITCHES SHALL BE SIMILAR TO HART AND HEGEMAN NO. 6808F. THREE-POLE SWITCHES SHALL BE SIMILAR TO HART AND HEGEMAN NO. 7810F. KNIFE-BLADE TYPE SWITCHES SHALL BE LOAD BREAK. QUICK-MAKE- QUICK-BREAK, UL CLASS R UP TO 600 AMP. MAXIMUM RATING EXCEPT AS NOTED SHALL BE 800 AMP. ARC QUENCHERS SHALL BE PROVIDED. SWITCHES SHALL BE SIMILAR TO GENERAL ELECTRIC QMR. ALL SWITCH ENCLOSURES SHALL BE DEAD FRONT, NEMA TYPE 1, EXCEPT AS NOTED.

7. FUSES:

- A. CIRCUITS 0 TO 600 AMPERES SHALL BE PROTECTED BY FUSES SIMILAR TO CURRENT LIMITING BUSSMAN LOW-PEAK DUAL-ELEMENT TIME-DELAY LPN-RK (AMP)SP (250V) /LPS-RK (AMP)SP (600V) OR LPJ (AMP)SP (600V) (UL CLASS RK1 OR CLASS J), AND BE LISTED BY UL WITH AN INTERRUPTING RATING OF 300,000 AMPERES RMS SYMMETRICAL.
- B. MOTOR CIRCUITS - ALL INDIVIDUAL MOTOR CIRCUITS WITH FULL LOAD AMPERE RATINGS (FLA) OF 480 AMPERES OR LESS SHALL BE PROTECTED BY FUSES SIMILAR TO CURRENT LIMITING BUSSMANN LOW-PEAK DUAL-ELEMENT TIME-DELAY LPN-RK (AMP)SP (250V) /LPS-RK (AMP)SP (600V) OR LPJ (AMP)SP (600V) (UL CLASS RK1 OR CLASS J), AND BE LISTED BY UL WITH AN INTERRUPTING RATING OF 300,000 AMPERES RMS SYMMETRICAL.
- C. ALL FUSES SHALL BE PROVIDED BY SAME MANUFACTURER.
- D. PROVIDE 1 SPACE MATCHING FUSE FOR EACH SET OF 3.

- E. CIRCUIT BREAKERS: MOLDED CASE BREAKERS SHALL BE THERMAL-MAGNETIC, QUICK-MAKE-QUICK-BREAK, BOLT-ON TYPE, MANUALLY OPERATED WITH INSULATED TRIP-FREE HANDLE. MULTI-POLE TYPE BREAKERS SHALL CONTAIN INTERNAL TRIP BAR. TERMINALS SHALL BE SUITABLE FOR COPPER OR ALUMINUM CABLE. FURNISH AUXILIARY DEVICES WHERE REQUIRED FOR SHUNT-TRIPPING, OPEN AND CLOSE MOTOR OPERATOR AND ALARM INDICATION. ENCLOSURES SHALL BE DEAD FRONT, NEMA TYPE 1, EXCEPT AS NOTED. FRAME, IC AND INTERCHANGEABLE TRIPS SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED:

- 1) 120 VOLTS, 100-AMP FRAME: 10,000 AMPS, 1 POLE.
- 2) 120/240 VOLTS, 225-AMP FRAME: 22,000 AMPS MINIMUM

8. DISTRIBUTION PANELBOARDS, SWITCH AND FUSE:

- A. THREE PHASE 3 OR 4 WIRE WITH COPPER BUS BARS. ALL THROUGH BUS SHALL BE INSULATED.
- B. NEMA CLASS 1 CONSTRUCTION TO ACCOMMODATE FUSIBLE, INDIVIDUALLY ENCLOSED SWITCHES, FRONT REMOVABLE, SWITCH AND DOOR INTERLOCKS. COVERS TO BE PAD-LOCKABLE.
- C. PANELBOARD SHALL BE CONSTRUCTED OF CODE-GAUGE STEEL, GRAY FINISH OVER RUST INHIBITOR, FOR SURFACE MOUNTING. BOX AND PANEL FRAME SHALL BE FLANGED AND REINFORCED FOR RIGID SUPPORT OF INTERIOR AND ACCURATE ALIGNMENT OF INTERIOR WITH FRONT. TRIMS TO BE FASTENED TO BACK BOX WITH SCREWS.
- D. ALL BRANCH SWITCHES SHALL HAVE INDIVIDUAL ENGRAVED LAMICOID NAMEPLATES (BLACK WITH WHITE CORE).
- E. DISTRIBUTION PANELBOARD CONSTRUCTION MINIMUM SHORT CIRCUIT RATING 25,000 AMPERES, REMS SYMMETRICAL FOR ALL 120/208V APPLICATIONS. APPLICATIONS.
- F. DISCONNECTS

- 1) DISCONNECT SWITCHES SHALL CONFORM TO NEMA AND UL STANDARDS, AND SHALL BE HORSEPOWER RATED.

- 2) SWITCHING MECHANISM SHALL BE QUICK-MAKE, QUICK-BREAK, SINGLE THROW WITH EXTERNAL OPERATING HANDLE MECHANICALLY INTERLOCKED WITH ENCLOSURE COVER TO PROVIDE ACCESS TO INTERIOR WHEN DISCONNECT IS IN OFF POSITION ONLY. PROVIDE MEANS TO LOCK OPERATING HANDLE IN THE OPEN AND CLOSED POSITION. DESIGNATE ON THE ENCLOSURE THE OPEN AND CLOSED POSITION OF THE OPERATING HANDLE.

- 3) SWITCHES SHALL BE OF THE DOUBLE STATIONARY CONTACT TYPE.

- 4) SWITCHES SHALL BE EQUIPPED WITH REJECTION TYPE FUSE HOLDERS, FUSIBLE AS SHOWN ON THE DRAWINGS; PROVIDE COMPLETE WITH FUSES AS SCHEDULED.

G. INSTALLATION

- 1) DISTRIBUTION PANELBOARD SHALL BE MOUNTED TO STRUCTURAL STEEL CHANNEL (KINDORF) WHICH SHALL BE BOLTED TO THE WALL USING EXPANSION ANCHORS FOR LARGE PANELS.

H. IDENTIFICATION

- 1) PROVIDE NAMEPLATE AT EACH SWITCH IDENTIFYING THE LOAD SERVED.

- 2) NAMEPLATES SHALL BE MOUNTED ON THE FRONT COVER SECURED WITH SELF-TAPPING SCREWS OR NUTS AND BOLTS. NAMEPLATES SHALL BE LAMINATED PHENOLIC, BLACK WITH A MINIMUM OF 3/4" HIGH WHITE LETTERING.

- I. DISTRIBUTION AND SUB-DISTRIBUTION PANELBOARDS SHALL BE A MINIMUM OF 30" WIDE AND 10" DEEP.

- J. POWER PANELBOARDS SHALL BE SIMILAR TO GENERAL ELECTRIC TYPE "QMR," AS MANUFACTURED BY ATLAS SWITCH COMPANY, ELECTRIC SWITCHBOARD COMPANY OR APPROVED EQUAL.

- K. PANELBOARD SHALL HAVE MAIN CIRCUIT BREAKER OR MAIN LUGS AS INDICATED ON THE DRAWINGS. QUANTITY, POLES AND TRIP RATINGS OF BRANCH CIRCUIT BREAKERS TO BE AS INDICATED ON DRAWINGS.

- L. PANELBOARD SHALL HAVE ENGRAVED WHITE CORE, BLACK LAMACOID NAMEPLATE SCREWED ONTO PANE TRIM WITH DESIGNATION LISTED (PANELBOARD NAME, VOLTAGE, RATING OR MAINS IN AMPS).

B. MATERIALS

1) RACEWAYS:

- a. RIGID STEEL CONDUIT: FULL-WEIGHT PIPE, GALVANIZED, THREADED.
- b. ELECTROMETALLIC TUBING (EMT): THIN WALL PIPE, GALVANIZED, THREADLESS.
- c. FLEXIBLE STEEL CONDUIT: CONTINUOUS SINGLE STRIP, GALVANIZED.
- d. WIREWAYS: WIRE SHALL BE AS NOTED, MINIMUM NO. 16 GAUGE STEEL WITH GROUND CONTINUITY. FINISH SHALL BE BAKED ENAMEL. COVERS SHALL BE SCREW-ON.
- e. SURFACE METAL RACEWAY: SIZE AS NOTED. BASE 0.04 IN., COVER 0.25 IN. MATERIAL SHALL BE STEEL. FINISH SHALL BE BAKED ENAMEL. COVERS SHALL BE SCREW-ON.

2) FITTINGS AND ACCESSORIES:

- a. RIGID STEEL: NONSPLIT, THREADED, STEEL OR MALLEABLE IRON. ZINC DIE CAST NOT PERMITTED.
- b. ELECTROMETALLIC TUBING: COMPRESSION TYPE. GALVANIZED RIGID STEEL ELBOWS, 2 IN. OR LARGER.
- c. FLEXIBLE METALLIC CONDUIT: ANGLE WEDGE TYPE WITH INSULATED THROAT.
- d. BUSHINGS: METALLIC INSULATED TYPE.

NY ENGINEERS

NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25

4. Revision 3 : 06.07.24

3. Revision 2 : 04.24.24

2. Revision 1 : 03.05.24

1. Permit set : 01.31.24

PREPARED BY : NYE

REVIEWED BY : NYE

PROJECT NUMBER

OS230050.00

DRAWING TITLE

ELECTRICAL

SPECIFICATIONS -1

DRAWING NUMBER

E002

SHEET 2 OF 8



ELECTRICAL SPECIFICATIONS (CONT.)

3) BOXES:

a. OUTLET BOXES: EXCEPT AS OTHERWISE REQUIRED BY CONSTRUCTION, DEVICES OR WIRING, BOXES SHALL BE STAMPED STEEL, 4 IN. SQUARE OR OCTAGON FOR FIXTURES. BOXES ABOVE CEILING SHALL BE 1-1/2 IN. DEEP. BOXES IN CEILING OR SLAB SHALL BE 3 IN. DEEP. BOXES IN WALL FOR FIXTURES SHALL BE 2-3/4 IN. DEEP. BOXES IN WALL FOR RECEPTACLES AND SWITCHES SHALL BE 1-1/2 IN. DEEP. FURNISH WITH RAISED COVERS AND FIXTURE STUDS WHERE REQUIRED. WITHOUT FIXTURE OR DEVICE, FURNISH BLANK COVER. OFFSET BACK-TO-BACK OUTLETS WITH MINIMUM 6 IN. SEPARATION.

b. JUNCTION AND PULL BOXES: GALVANIZED SHEET STEEL WITH SCREW-ON COVERS, EXCEPT AS NOTED. FURNISH WITH INSULATED SUPPORTS FOR CABLES. LOCATIONS SHALL BE AS NOTED OR REQUIRED AND ACCESSIBLE. PROVIDE BARRIERS IN NEW AND RENOVATED BOXES BETWEEN 120/208 VOLT AND 265/460 VOLT WIRING AND BETWEEN EMERGENCY AND NORMAL WIRING. FLOOR BOXES SHALL BE SUITABLE FOR CONDUIT AND DEVICES NOTED. RAISED OUTLETS SHALL BE HUBBELL #B2414 SERIES WITH ABOVE FLOOR FITTING. TELEPHONE, BUSHED HOLE, POWER, DUPLEX RECEPTACLE OR OTHER AS NOTED. INCREASE SIZE TO SUIT AS NECESSARY. FLUSH OUTLETS SHALL BE HUBBELL #B2414 SERIES WITH FLUSH FLOOR FITTING FOR TELEPHONE AND FLUSH DUAL FLAP COVER WITH DUPLEX RECEPTACLE FOR POWER AS NOTED. INCREASE SIZE TO SUIT AS NECESSARY.

c. PROVIDE RACEWAYS ONLY AS HEREIN SPECIFIED, EXCEPT AS NOTED. RACEWAYS SHALL BE RUN CONCEALED, EXCEPT AS NOTED.

PROVIDE RACEWAY SUPPORT UTILIZING CEILING TRAPEZE, STRAP HANGERS, OR WALL BRACKETS. PROVIDE U-BOLTS AT EACH FLOOR LEVEL OF RISER RACEWAYS AND CONNECTED TO ACCEPTABLE SUPPORTS. PROVIDE RISER CLAMPS AT EACH FLOOR LEVEL OF RISER RACEWAYS AND RESTING ON SLAB. FOR THROUGH-THE-FLOOR SYSTEMS, UTILIZE AN ASSEMBLY SIMILAR TO HUBBELL FIRE RATED POKE-THROUGH-FLOOR BOX SYSTEM. FOR ABOVE FLOOR FITTINGS TELEPHONE SHALL BE BUSHED HOLE AND POWER SHALL BE DUPLEX RECEPTACLE OR OTHER AS NOTED. PROVIDE SEPARATION BARRIER BETWEEN POWER AND TELEPHONE COMPARTMENTS. PROVIDE JUNCTION BOX ON UNDERSIDE OF FLOOR. PACK FITTING TO RESTORE FIRE RATING OF FLOOR.

SECURE ALL RACEWAYS TO SUPPORTS WITH PIPE STRAPS OR U-BOLTS. SPACING OF SUPPORTS SHALL BE A MINIMUM OF 10 FT ON CENTER FOR METALLIC RACEWAY AND AS REQUIRED FOR NONMETALLIC RACEWAY. SPACING SHALL BE 5 FT ON CENTER FOR WIREWAYS AND PER CODE AND AS NOTED FOR OTHERS. MOUNT SUPPORTS TO STRUCTURE MASONRY WITH TOGGLE BOLTS ON HOLLOW MASONRY, EXPANSION SHIELDS OR INSERTS IN CONCRETE AND BRICK, MACHINE SCREWS ON METAL, BEAM CLAMPS ON FRAMEWORK, WOOD SCREWS ON WOOD, AND PAN THROUGH STRAPS IN METAL DECK, NAILS, RAWL PLUGS OR WOOD PLUGS SHALL NOT BE PERMITTED. WHERE REQUIRED BY STRUCTURE, FURNISH THROUGH BOLTS AND FISHPATES.

EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND POURED CONCRETE, RUN VERTICALLY ONLY.

MAINTAIN GROUNDING CONTINUITY OF INTERRUPTED METALLIC RACEWAYS WITH GROUND CONDUCTOR, AND IN FLEXIBLE CONDUIT FOR FEEDERS AND MOTOR TERMINAL CONNECTIONS.

EMPTY RACEWAYS OVER 10 FT LONG: PROVIDE FISH OR PULL WIRE, GALVANIZED OR NYLON ROPE.

RIGID STEEL CONDUIT SHALL BE PERMITTED FOR FEEDERS AND BRANCH CIRCUITS. PAINT MALE THREADS OF FIELD-THREADED CONDUIT WITH GRAPHITE-BASE PIPE COMPOUND AND BUTT CONDUIT ENDS. TOUCH UP MARRED SURFACES AND FIELD-CUT THREADS. CRC-COLD GALVANIZED. EMT SHALL BE PERMITTED FOR BRANCH CIRCUITS ONLY, IN DRY LOCATIONS, DRY WALLS, HUNG CEILINGS, HOLLOW BLOCK WALLS AND FURRED SPACES. EMT SHALL NOT BE PERMITTED IN RAISED FLOORS. FLEXIBLE STEEL CONDUIT SHALL BE UTILIZED FOR SHORT CONNECTIONS WHERE RIGID CONDUIT IS IMPRACTICAL. FROM OUTLET BOX TO RECESSED LIGHTING FIXTURE: PROVIDE MINIMUM 4 FT AND MAXIMUM 6 FT LENGTHS. FOR FINAL CONNECTION TO MOTOR TERMINAL BOX, TRANSFORMER AND OTHER VIBRATING EQUIPMENT: PROVIDE WITH POLYVINYL SHEATHING AND GROUND CONDUCTOR. MINIMUM LENGTH: 18 IN. WITH SLACK. CONNECT GROUND CONDUCTOR TO ENCLOSURE OR RACEWAY AT EACH END. FOR EXPANSION JOINT CROSSINGS, CROSS AT RIGHT ANGLES AND ANCHOR ENDS.

CUT CONDUIT ENDS SQUARE. REAM SMOOTH. PAINT MALE THREADS OF FIELD THREADED RACEWAYS WITH GRAPHITE BASE PIPE COMPOUND. DRAW UP TIGHT WITH RACEWAY COUPLING.

ALL COUPLINGS SHALL BE COMPRESSION TYPE. NO SET SCREW FITTINGS.

EXPANSION FITTINGS SHALL BE INSTALLED AT RIGHT ANGLES WITH CLIP JOINT CENTERED IN EXPANSION JOINT. PROVIDE A LENGTH OF RUN IN ACCORDANCE MANUFACTURER'S RECOMMENDATIONS. PRESET FITTINGS SHALL ALLOW FOR TEMPERATURE VARIATION.

RACEWAYS PASSING THROUGH FIRE-RATED CONSTRUCTION: SEAL OPENING WITH FIRE SEALANT.

d. PROVIDE CABLE SUPPORTS IN ACCORDANCE WITH NATIONAL ELECTRIC CODE ARTICLE 300.19. CABLE SUPPORTS SHALL UTILIZE A ONE-PIECE PLUG WITH POZI-GRIP WEDGING PLUG AS MANUFACTURED BY OZ-GEDNEY. TYPE SF SHALL BE USED FOR ARMORED CABLE.

INSTALL CABLE SUPPORTS AT THE TOP OF A VERTICAL RISE AND PROVIDE INTERMEDIATE ADDITIONAL SUPPORTS AS REQUIRED TO LIMIT SUPPORTED CONDUCTOR LENGTHS TO NOT GREATER THAN THOSE SPECIFIED IN TABLE 300.19(A).

a. ERECT WALL AND SWITCH OUTLETS IN ADVANCE OF FURRING AND FIREPROOFING. OUTLET BOXES SHALL BE SET SQUARE AND TRUE WITH BUILDING FINISH. SECURE TO BUILDING STRUCTURE BY ADJUSTABLE STRAP IRON OR GROUT IN WITH MASONRY. VERIFY OUTLET LOCATIONS IN FINISHED SPACES WITH ARCHITECTURAL DRAWINGS OF INTERIOR DETAILS AND FINISHES. PROVIDE BARRIERS BETWEEN SWITCHES CONNECTED TO DIFFERENT PHASES FOR VOLTAGES EXCEEDING 150 VOLTS TO GROUND.

d. PANEL, JUNCTION AND PULL BOXES SHALL BE LOCATED CLEAR OF OTHER TRADES. CONCEAL JUNCTION AND PULL BOXES IN FINISHED SPACES. WHERE NECESSARY, REROUTE RACEWAYS OR MAKE OTHER ARRANGEMENTS FOR CONCEALMENT. BOXES SHALL BE ACCESSIBLE. SUPPORT BOXES FROM BUILDING STRUCTURE, INDEPENDENT OF CONDUIT. PROVIDE FLOOR-TO-CEILING CHANNELS FOR MOUNTING ON DRYWALL AND LIGHTWEIGHT CONSTRUCTION. OUTLET BOXES FOR FIXTURES RECESSED IN HUNG CEILINGS SHALL BE ACCESSIBLE THROUGH OPENING CREATED BY REMOVAL OF FIXTURE. SECURE TO BLACK IRON SUPPORT. MOTOR TERMINAL BOXES: COORDINATE WITH MOTOR BRANCH CIRCUIT CONDUIT AND WIRING; ADD BOX VOLUME WHERE REQUIRED.

e. FIRE SEALANTS: PROVIDE FOR RACEWAYS AND WIRE PASSING THROUGH FLOOR SLOTS, SLEEVES OR OPENINGS IN FIRE-PARTITIONS ROOMS.

f. PERFORM CONTINUITY TESTS OF RESISTANCE OF FEEDER CONDUITS FROM SERVICE TO POINT OF FINAL DISTRIBUTION USING 1 CONDUCTOR RETURN. MAXIMUM RESISTANCE SHALL BE 25 OHMS.

9. WIRE AND CABLE:

a. PROVIDE WIRE AND CABLE COMPLETE WITH ACCESSORIES. SIZE REFERENCE SHALL BE AWG EXCEPT AS NOTED.

b. CONDUCTORS SHALL BE COPPER, ASTM STANDARD SOLID (NO. 10 AND SMALLER) OR STRANDED (NO. 8 AND LARGER). GENERAL USE CABLING SHALL BE NO. 12 MINIMUM. AT 120 VOLTS AND OVER 100 FT CIRCUIT LENGTH PROVIDE NO. 10 MINIMUM. AT 265 VOLTS AND OVER 200 FT CIRCUIT LENGTH PROVIDE NO. 10 MINIMUM.

c. CONTROL AND ALARM CABLING, EXCEPT AS NOTED, SHALL BE NO. 14 MINIMUM. AT 120 VOLTS AND OVER 200 FT CIRCUIT LENGTH PROVIDE NO. 12 MINIMUM. OTHER VOLTAGES AND PHASES: ADJUST CABLE SIZING AS REQUIRED TO MAINTAIN VOLTAGE DROP. INCREASE RACEWAY SIZES FOR LARGER WIRE AS REQUIRED.

d. INSULATION SHALL BE RUBBER AND THERMOPLASTIC MEETING ASTM AND IPCEA STANDARDS. TYPE THW OR THWN SHALL BE UTILIZED FOR FEEDERS AND BRANCH CIRCUITS EXCEPT AS NOTED. TYPE SFF-2 SHALL BE UTILIZED FOR BRANCH CIRCUITS LOCATED IN WIRING CHANNELS OF CONTINUOUS FLUORESCENT FIXTURES AND IN AMBIENT TEMPERATURES OVER 90 DEG C. FOR UNGROUNDED ISOLATED BRANCH CIRCUITS PROVIDE CROSS-LINKED POLYETHYLENE INSULATION (TYPE XHHW).

e. ARMORED CABLE (BX) SHALL BE UTILIZED FOR BRANCH CIRCUITS IN DRY HOLLOW LOCATIONS, HUNG CEILINGS, AND BLOCK WALLS. WHEN USED IN LIEU OF WIRING IN CONDUIT, STATE IN PROPOSAL THAT PRICE IS BASED UPON THE USE OF HOSPITAL GRADE 'BX'.

f. COLOR CODING SHALL BE AS FOLLOWS:

120/208 VOLT SYSTEM:  
BLACK FOR A PHASE  
RED FOR B PHASE  
BLUE FOR C PHASE

1) NEUTRAL WIRE SHALL UTILIZE WHITE OUTER COVERING THROUGHOUT. EQUIPMENT GROUND WIRE SHALL UTILIZE GREEN OUTER COVERING THROUGHOUT.

WHERE COLOR-CODED CABLE IS NOT AVAILABLE, CERTIFY IN WRITING AND REQUEST PERMISSION TO OVERLAP CONDUCTORS WITH 6 IN. OF COLOR TAPING IN ACCESSIBLE LOCATIONS.

g. PROVIDE FLAMEPROOF LINEN OR FIBER TAGS IN ACCESSIBLE LOCATIONS. FOR FEEDERS INDICATE FEEDER NUMBER, SIZE, PHASE AND POINTS OF ORIGIN AND TERMINATIONS. FOR CONTROL AND ALARM WIRING INDICATE TYPE (CONTROL OR ALARM), SIZE OF WIRE, AND POINTS OF ORIGIN AND TERMINATIONS.

h. TERMINATIONS, SPLICES AND TAPS UNDER 600 VOLTS: COPPER CONDUCTORS NO. 10 AND SMALLER SHALL UTILIZE COMPRESSION-TYPE OF TWIST-ON SPRING-LOADED CONNECTORS AND CLEAR NYLON-INSULATED COVERING. COPPER CONDUCTORS NO. 8 AND LARGER SHALL UTILIZE MECHANICAL BOLTED PRESSURE OR HYDRAULIC COMPRESSION TYPE USING MANUFACTURER'S RECOMMENDED TOOLING. CABLE LUGS AND CONNECTORS SHALL UTILIZE COMPRESSION TYPE OF SAME METAL AS CONDUCTOR. PROVIDE TO MATCH CABLE, WITH MARKING INDICATING SIZE AND TYPE. COPPER LUG CONNECTIONS TO BUS BARS: USE ANTISEIZE COMPOUND ON TANG.

i. NOT MORE THAN 3 LIGHTING OR CONVENIENCE OUTLET CIRCUITS SHALL BE INSTALLED IN ONE CONDUIT UNLESS OTHERWISE INDICATED. PULL NO THERMOPLASTIC WIRES AT TEMPERATURES LOWER THAN 32 DEG F. PROVIDE SEPARATE RACEWAYS FOR CONDUCTORS OF 120/208 AND 265/460 VOLT SYSTEMS, EXCEPT 460 VOLT MOTOR BRANCH CIRCUIT WIRING AND RELATED 120 VOLT CONTROL WIRING. THERMOPLASTIC WIRES SHALL NOT BE INSTALLED IN COMPUTER AREA RAISED FLOORS.

j. LEAVE WIRES WITH SUFFICIENT SLACK TO PERMIT MAKING FINAL CONNECTIONS.

k. PERFORM CONTINUITY AND INSULATION TESTS. MEGGER TEST 100 PERCENT OF FEEDERS, 10 PERCENT OF BRANCH CIRCUITS AND ALL MOTOR BRANCH CIRCUITS OVER 25 HP.

PERFORM TESTS PRIOR TO CONNECTING EQUIPMENT AND IN PRESENCE OF AUTHORIZED REPRESENTATIVES. SUBMIT WRITTEN REPORT OF RESULTS. CORRECT OR REPLACE CABLE TESTING BELOW MANUFACTURER'S STANDARDS.

10. WIRING DEVICES:

a. WIRING DEVICES SHALL BE SPECIFICATION GRADE UNLESS OTHERWISE SPECIFIED. ALL DEVICES SHALL BE FLUSH MOUNTED, UNLESS OTHERWISE NOTED. PROVIDE COMPLETE MATERIAL AND ACCESSORIES AS NOTED.

b. LOCAL WALL SWITCHES SHALL BE ROCKER TYPE, QUIET OPERATING, RATED 20 AMP, 120/208 VOLT, AC. SIMILAR TO LEVITON DECORA SERIES A5621 (SINGLE POLE), A5623 (3-WAY) AND A5624 (4-WAY).

c. STRAIGHT BLADE RECEPTACLES SHALL BE COMMERCIAL SPECIFICATION GRADE DUPLEX CONVENIENCE 125 VOLTS, 2 POLE, 3 WIRE, U GROUND SLOT, DECORA SERIES BY LEVITON. GROUNDED, EXCEPT AS NOTED.

1)SINGLE GANG, RECESSED, DUPLEX RECEPTACLE: TAMPER RESISTANT, 2--POLE, 3--WIRE GROUNDING, 15A, 125V, NEMA 5-20R; LEVITON 689 SERIES (COLOR AS SPECIFIED BY ARCHITECT).

2)USB CHARGER/ DUPLEX TAMPER-RESISTANT RECEPTACLE: TAMPER RESISTANT,

e. DEVICE PLATES: SEE ARCHITECT FOR TYPE. FOR RECEPTACLES WITH OTHER THAN 120 VOLT, INSCRIBED VOLTAGE AVAILABLE.

f. COLORS: COORDINATE COLORS WITH ARCHITECT.

g. MOUNTING ORIENTATION OF RECEPTACLES (HORIZONTAL OR VERTICAL): COORDINATE WITH ARCHITECT.

11. LIGHTING FIXTURES:

a. FIXTURES TO BE AS SPECIFIED BY ARCHITECT AND SHALL BE COMPLETELY FACTORY ASSEMBLED, WIRED AND EQUIPPED WITH ALL NECESSARY SOCKETS, BALLASTS, SUPPORTING HARDWARE AND ACCESSORIES. REFER TO DRAWINGS FOR INDIVIDUAL FIXTURE DESCRIPTIONS.

b. FIXTURE CATALOG NUMBERS USED TO ILLUSTRATE EQUIPMENT TYPE DO NOT NECESSARILY DENOTE REQUIRED MOUNTING EQUIPMENT OR ACCESSORIES. PROVIDE ACCESSORIES TO SUIT.

c. BALLAST: CLASS P, HIGH POWER FACTOR, LOWEST AVAILABLE NEMA RATED NOISE LEVEL, ET1 AND CBM APPROVED. ENERGY SAVING TYPE. TRIGGER START FOR 24-INCH LAMPS AND RAPID START FOR 48-INCH. TWO LAMP BALLASTS; NO THREE LAMP BALLASTS. BALLASTS SHALL BE ADVANCE MAGNETEK, UNIVERSAL OR EQUAL.

d. LED DRIVERS SHALL BE ELECTRONIC TYPE, LABELED AS COMPLIANT WITH RADIO FREQUENCY INTERFERENCE (RFI) REQUIREMENTS OF FCC TITLE 47, PART 15 AND COMPLY WITH NEMA SSL 1 "ELECTRONIC DRIVERS FOR LED DEVICES, ARRAYS OR SYSTEMS". LED DRIVERS SHALL HAVE A SOUND RATING OF "A", HAVE A MINIMUM EFFICIENCY OF 85% AND BE RATED FOR A THD OF LESS THAN 20% AT ALL INPUT VOLTAGES.

e. DIMMABLE LED DRIVERS SHALL BE CAPABLE OF DIMMING WITHOUT LED STROBING OR FLICKER ACROSS THEIR FULL DIMMING RANGE. PROVIDE TYPE OF LED DRIVER AS PER LIGHTING FIXTURE SCHEDULE. DIMMABLE LED DRIVERS SHALL BE 0-10V WHERE NOT INDICATED.

f. CONTINUOUS ROW, TWO LAMP STRIP FIXTURES SHALL BE STAGGERED TYPE.

g. EXIT SIGNS SHALL BE PRECISION DIE-CAST ALUMINUM HOUSING WITH LASER-FORMED ACRYLIC LEGEND. EXIT SIGNS SHALL COMPLY WITH UL 924 AND BE MEA APPROVED FOR USE. AC POWERED WITH PREMIUM LONG-LIFE NICKEL CADMIUM BATTERY WITH STANDARD UL LISTED 3-HOUR RUN TIME. PROVIDE WITH INTEGRAL AUTOMATIC CHARGER IN A SELF CONTAINED POWER PACK. LED INDICATOR WITH PUSH TO TEST SWITCH.

12. GROUNDING AND BONDING:

a. PROVIDE GROUNDING SYSTEM IN ACCORDANCE WITH (2017) NATIONAL ELECTRICAL CODE) AND THESE SPECIFICATIONS. THE WIRING SYSTEM SHALL BE INSTALLED AS REQUIRED TO PROVIDE A CONTINUOUSLY GROUNDED SYSTEM. WHERE FLEXIBLE CONDUIT IS USED FOR PART OF A CONDUIT RUN, EXCEPT LIGHTING BRANCH CIRCUITS, AN INSULATED GROUNDING CONDUCTOR SHALL BE PROVIDED IN THE CONDUIT AND CONNECTED TO GROUNDING BUSHINGS AT EACH END OF THE RUN.

b. USE EXOTHERMIC WELDING PROCESS FOR INACCESSIBLE CONNECTIONS.

c. EXTEND EXISTING SYSTEM GROUND TO INCLUDE ALL THE ELECTRICAL EQUIPMENT IN THE SCOPE OF WORK.

d. WHERE FLEXIBLE METALLIC CONDUIT IS USED AN INTERNAL BONDING CONDUCTOR SHALL BE INSTALLED.

e. IN ADDITION, FURNISH A SEPARATE INSULATED GREEN EQUIPMENT GROUND CONDUCTOR WHERE INDICATED ON DRAWINGS AND FOR THE FOLLOWING BRANCH CIRCUITS:  
1) CIRCUITS SERVING ANY WALL BOX DIMMER.

2) CIRCUITS SERVING ANY ISOLATED GROUND RECEPTACLES. TERMINATE GROUND DIRECTLY AT AN EQUIPMENT GROUNDING CONDUCTOR TERMINAL OF THE SOURCE AT THE SOURCE , OR AS OTHER WISE NOTED ON DRAWINGS.

3) CIRCUITS SERVING ANY DUPLEX OR SIMPLEX COMPUTER RECEPTACLES

4) ANY CIRCUIT SERVED VIA AN ISOLATION TRANSFORMER OR COMPUTER POWER DISTRIBUTION UNIT.

13. PANEL BOARDS:

a. PANEL BOARDS SHALL BE OF THE DEAD FRONT TYPE  
  
MANUFACTURED IN CODE GAUGE AND SIZE BOXES FOR MOUNTING AS INDICATED ON PLANS COMPLETE WITH TRIM, DOORS AND LOCKS. ALL LOCKS SHALL BE KEYED ALIKE.

b. CIRCUIT BREAKERS SHALL BE OF THE BOLT-ON THERMAL MAGNETIC MOLDED CASE TYPE. AND SHALL HAVE THE TRIP RATINGS AND NUMBER OF POLES SHOWN IN SCHEDULES ON THE CONTRACT DRAWINGS. FOR BLANK (SPACE) COMPARTMENTS, PROVIDE FULL RATED BUS. MINIMUM GUTTER SPACES SHALL BE 5-3/4". SIDES, TOP AND BOTTOM, INCREASE FOR THROUGH FEEDERS. PROVIDE 25% COPPER GROUND BUS AND 100% COPPER NEUTRAL BUS AND INCREASE NEUTRAL BUS INDICATED.

c. LOCKING TABS SHALL BE PROVIDED ON ALL CIRCUIT BREAKERS SERVING EMERGENCY LIGHTING, FIRE ALARM SYSTEM, SECURITY SYSTEMS AND OTHER EMERGENCY OR CRITICAL EQUIPMENT AND AS NOTED ON THE CONTRACT DRAWINGS. A TOTAL OF 5 SPARE LOCKING TABS SHALL BE FURNISHED TO THE OWNER.

d. BUSES SHALL BE HARD DRAWN COPPER OF 98 PERCENT CONDUCTIVITY AND SHALL HAVE CROSS SECTIONAL AREAS LARGE ENOUGH TO LIMIT THE TEMPERATURE RISE, WHEN CARRYING FULL LOAD, TO 35 DEGREES C. ABOVE AN AMBIENT INSIDE THE ENCLOSURE OF 55 DEGREES C. AS DEFINED IN IEEE STANDARD RULES. MAIN BUS CAPACITY SHALL BE AS SHOWN ON THE CONTRACT DRAWINGS.

e. ENCLOSURES SHALL BE SURFACE OR FLUSH AS INDICATED. TRIMS SHALL BE SECURED TO PANEL WITH MACHINE SCREWS. COVERS SHALL BE HINGED DOOR-IN-DOOR CONSTRUCTION WITH CYLINDER LOCKS AND CATCHES. LOCKS MUST BE COMPATIBLE WITH BUILDING STANDARD KEY SYSTEM AND WHEN NONE EXISTS, THEY SHALL BE SIMILAR TO A YALE NO. 911 KEY.

f. DISTRIBUTION AND SUB-DISTRIBUTION PANELBOARD SHALL BE A MINIMUM OF 30" WIDE AND 10" DEEP.

g. ALL STANDARD PANELBOARDS SHALL BE A MINIMUM OF 20" WIDE AND 5 3/4" DEEP.

h. FURNISH ALL PANELBOARDS WITH FEED-THRU LUGS UNLESS OTHERWISE INDICATED ON THE DRAWINGS.

i. ALL NEW PANELBOARDS SHALL BE PROVIDED WITH AN ENGRAVED WHITE CORE LAMACOID NAMEPLATE, WITH 3/4 IN. WHITE LETTERING ON A BLACK BACKGROUND, WITH DESIGNATION LISTED (PANELBOARD NAME), FASTENED WITH EPOXY CEMENT OR OVAL HEAD CHROME PLATED MACHINE SCREWS.

j. THE CIRCUIT DIRECTORY SHALL BE TYPEWRITTEN AND PROVIDED INSIDE EACH PANEL DOOR TO INDICATE EQUIPMENT AND/OR AREA SERVED. DIRECTORY HOLDER SHALL BE METAL FRAME WITH CLEAR PLASTIC, TRANSPARENT COVER. THE TYPEWRITTEN LIST INDICATING CIRCUIT NUMBERS, OUTLETS SUPPLIED AND THEIR LOCATIONS SHALL BE PROVIDED.

k. TIE-BARS SHALL NOT BE USED TO CREATE MULTI-POLE CIRCUITS. MAXIMUM 42 CIRCUITS ALLOWED.

l. ONLY ONE WIRE SHALL BE INSTALLED UNDER EACH CIRCUIT BREAKER LUG.

m. SHORT CIRCUIT RATING OF PANELBOARDS SHALL NOT BE LESS THAN AS INDICATED ON THE CONTRACT DRAWINGS OR SPECIFIED HEREIN. WHERE NOT INDICATED OR SPECIFIED THE MINIMUM SHORT CIRCUIT RATING SHALL BE EQUAL TO THE INTERRUPTING CAPACITY OF THE LOWEST RATED CIRCUIT BREAKER IN THE PANELBOARD, BUT IN NO CASE LESS THAN 10,000 AMPERES R.M.S. SYMMETRICAL FOR 208Y/120 VOLT SYSTEM. SERIES RATED PANELBOARDS SHALL BE USED TO ACHIEVE REQUIRED SHORT CIRCUIT RATINGS.

n. FOR ALL EXISTING PANELBOARDS, CONTRACTOR SHALL PROVIDE NEW CIRCUIT BREAKERS TO REPLACE EXISTING AS REQUIRED AS INDICATED ON DRAWINGS.

NY ENGINEERS

NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 4967A,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25

4. Revision 3 : 06.07.24

3. Revision 2 : 04.24.24

2. Revision 1 : 03.05.24

1. Permit set : 01.31.24

PREPARED BY : NYE

REVIEWED BY : NYE

PROJECT NUMBER  
OS230050.00

DRAWING TITLE  
ELECTRICAL  
SPECIFICATIONS -2

DRAWING NUMBER


E003

SHEET 3 OF 8










ELECTRICAL POWER PLAN GENERAL NOTES:

1. PROVIDE GFCI PROTECTION FOR PERSONNEL FOR ALL SINGLE PHASE RECEPTACLES RATED 50AMP OR LESS & THREE PHASE RECEPTACLES RATED 100AMP OR LESS INSTALLED IN KITCHEN AREA PER NEC 210.8(B)2. GFI PROTECTION SHALL BE PROVIDED AT BREAKER WHERE RECEPTACLES ARE NOT READILY ACCESSIBLE PER NEC 210.8 DUE TO STATIONARY KITCHEN EQUIPMENT.
2. REFER TO "KITCHEN EQUIPMENT SCHEDULE" FOR DESCRIPTION AND POWER REQUIREMENTS OF EACH DEVICE IN KITCHEN. COORDINATE EXACT LOCATION AND MOUNTING HEIGHT OF ALL JUNCTION BOXES, RECEPTACLES, ETC. WITH KITCHEN EQUIPMENT VENDOR PRIOR TO ROUGH-IN.
3. E.C. SHALL MAKE ALL FINAL CONNECTIONS TO KITCHEN EQUIPMENT, FURNISH AND INSTALL ALL JUNCTION BOXES, RECEPTACLES, COVER PLATES, PULL BOXES, CONDUIT AND WIRING AS REQUIRED. COORDINATE WITH FOOD SERVICE DRAWINGS AND MANUFACTURER'S INSTRUCTIONS FOR LOCATION OF ALL EQUIPMENT CONNECTION LOCATIONS AND REQUIREMENTS.
4. E.C. SHALL PULL ALL LOW VOLTAGE WIRING FOR POS SYSTEM, AND PHONE. COORDINATE WITH OWNER'S VENDOR.
5. FLEXIBLE CONDUIT INSTALLED IN KITCHEN FOR FINAL EQUIPMENT CONNECTION SHALL BE LIQUID TIGHT CONDUIT WITH NEOPRENE JACKET.
6. ENCLOSURES FOR ALL ELECTRICAL PANELS, CIRCUIT BREAKER ENCLOSURES, DISCONNECT SWITCHES, WALL SWITCHES, CONTRACTOR ENCLOSURES, PUSHBUTTONS, ETC WITHIN KITCHEN AREA SHALL BE FOOD GRADE, RECESSED MOUNTED, UNLESS OTHERWISE NOTED.
7. E.C. SHALL COORDINATE WITH THE OWNER/KITCHEN EQUIPMENT VENDOR FOR THE EXACT MOUNTING HEIGHT/LOCATIONS OF THE RECEPTACLES FOR THE KITCHEN EQUIPMENT PRIOR TO ROUGH-IN.
8. COORDINATE POWER REQUIREMENTS FOR SECURITY SYSTEM WITH OWNER/SECURITY VENDOR.
9. COORDINATE POWER REQUIREMENTS FOR MUSIC SYSTEM WITH OWNER/L.V. VENDOR.

# ELECTRICAL POWER PLAN KEYED WORK NOTES:




- A PROVIDE (2) CAT 6 HOME RUN TO EACH POS STATION AND ONE (1) QUAD 20 AMPS RECEPTACLE FOR POS. COORDINATE WITH OWNER PRIOR TO ROUGH-IN FOR EXACT HEIGHT.
- B OUTLET FOR CAMERA/SOUND SYSTEM. E.C. TO COORDINATE EXACT MOUNTING HEIGHT WITH OWNER/ARCHITECT.
- C PROVIDE (1) DUPLEX RECEPTACLE AND (1) CAT6 DATA CABLE AND CONNECTION FOR EACH TV. COORDINATE WITH OWNER IN FIELD FOR FINAL LOCATION, MOUNTING HEIGHT BEFORE COMMENCING ANY WORK. BASE BID ACCORDINGLY.
- D DUPLEX OUTLET FOR OPEN CLOSE SIGN. E.C. TO COORDINATE EXACT LOCATION, MOUNTING HEIGHT & POWER REQUIREMENT WITH SIGN VENDOR PRIOR TO ROUGH-IN. BASE BID ACCORDINGLY.
- E OUTLETS TO BE LOCATED ABOVE COUNTERTOP HEIGHT. E.C. TO COORDINATE EXACT LOCATION WITH OWNER/ARCHITECT.
- F DUPLEX OUTLET, COORDINATE MOUNTING HEIGHT WITH OWNER/ARCHITECT PRIOR TO ROUGH-IN.
- G E.C. TO COORDINATE WITH FIRE SUPPRESSION SYSTEM VENDOR FOR ITS POWER REQUIREMENTS AND OTHER DETAILS BEFORE COMMENCING ANY WORK. BASE BID ACCORDINGLY.
- H E.C. TO COORDINATE WITH KITCHEN EQUIPMENT VENDOR/ MANUFACTURER FOR EXACT POWER REQUIREMENTS, EXACT MOUNTING HEIGHT, LOCATION BEFORE COMMENCING ANY WORK. BASE BID ACCORDINGLY.
- I EXISTING 200A(M.C.B.), 120/208V, 3--PHASE, 4--WIRE ELECTRICAL PANEL "A" (PROVIDED BY LL) TO REMAIN. E.C. TO FIELD VERIFY THE EXACT SIZE, LOCATION & OPERABLE CONDITION OF THE PANEL, REPLACE IF INOPERABLE. BASE BID ACCORDINGLY.
- J NEW 125A(M.L.O) 120/208V, 3--PHASE, 4--WIRE ELECTRICAL PANEL "B". E.C SHALL COORDINATE EXACT LOCATION WITH OWNER/ARCHITECT.
- K ELECTRICAL CONTRACTOR SHALL VERIFY THE INSTALLATION OF ELECTRICAL PANELS IN COMPLIANCE WITH N.E.C. ARTICLE 110.26(A) AND (B). E.C. SHALL FIELD VERIFY THAT THE PANELS ARE UNOBSTRUCTED AND THE AREA WHERE THE PANELS ARE PLACED SHALL NOT BE USED AS A STORAGE SPACE.
- L ELECTRICAL CONTRACTOR SHALL COORDINATE DISCONNECT AND FUSE REQUIREMENT FOR MECHANICAL UNIT WITH MECHANICAL CONTRACTOR AND EQUIPMENT MANUFACTURER PRIOR TO ROUGH-IN AND PROVIDE AS REQUIRED. COORDINATE LOCATION OF DISCONNECT WITH OWNER AND MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN. LOCATE AS REQUIRED TO MAINTAIN NEC CLEARANCES.
- M ELECTRICAL CONTRACTOR SHALL COORDINATE FOR EXACT LOCATION OF MECHANICAL EQUIPMENTS WITH MECHANICAL DRAWINGS.





<b>A</b>	ELECTRICAL CONTRACTOR SHALL COORDINATE, DISCONNECT AND FUSE REQUIREMENT FOR MECHANICAL UNIT WITH MECHANICAL CONTRACTOR AND EQUIPMENT MANUFACTURER PRIOR TO ROUGH-IN AND PROVIDE AS REQUIRED. COORDINATE LOCATION OF DISCONNECT WITH OWNER AND MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN. LOCATE AS REQUIRED TO MAINTAIN NEC CLEARANCES.
<b>B</b>	ELECTRICAL CONTRACTOR SHALL COORDINATE FOR EXACT LOCATION OF MECHANICAL EQUIPMENTS WITH MECHANICAL DRAWINGS.
<b>C</b>	INTERCONNECT KEF-1(N) & KEF-2(N) WITH HOOD-1(N). E.C TO COORDINATE WITH MECHANICAL DRAWINGS.

ALOHHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25	
4. Revision 3 : 06.07.24	
3. Revision 2 : 04.24.24	
2. Revision 1 : 03.05.24	
1. Permit set : 01.31.24	
PREPARED BY : NYE	
REVIEWED BY : NYE	
PROJECT NUMBER OS230050.00	
DRAWING TITLE ELECTRICAL POWER PLAN-ROOF	
DRAWING NUMBER	
E201	
SHEET	6 OF 8





1. WHEN SENSOR ACTIVATES, LOAD TURNS ON.
2. LOAD TURNS OFF, WHEN SENSOR TIMES OUT.

18-3 AWG STRANDED WIRE SHIELDED OR NON-SHIELDED

OAC-DT-0501, OAC-DT-1000, OAC-DT-2000  
OAC-U-0501, OAC-U-1000, OAC-U-2000  
OAC-P-0500, OAC-P-1500

## SP20-MV




- ① TYPICAL FOR WOOD AND METAL STUD ROUGH-IN
- ② PLASTER RINGS NOT SHOWN
- ③ LOCATE ALL OUTLET BOXES IN ACCORDANCE WITH ARCHITECTURAL AND MECHANICAL DRAWINGS, AND WITH ALL APPLICABLE SHOP DRAWINGS.

**NEARBY ENGINEERS**  
82 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.257.3455  
[WWW.NY-ENGINEERS.COM](http://WWW.NY-ENGINEERS.COM)

4	WIF
E-300	N.T.S



2	DE
E300	N.T.



NOTES:

2. OCCUPANCY/VACANCY SENSOR SHALL BE "SENSOR SWITCH" OF APPROVED MAKES. ALL EXPOSED CONTROL WIRING SHALL BE IN CONDUIT.

1. ALL CONDUCTORS IN VERTICAL RACEWAYS SHALL BE SUPPORTED IN ACCORDANCE WITH ARTICLE 300.19 OF THE NEC. CABLE SUPPORTS SHALL BE LOCATED AT THE INTERVALS REQUIRED BY THE NEC.
2. CABLE SUPPORT SYSTEM SHALL BE AS MANUFACTURED BY O-Z GEDNEY WITH pOZI-GRIP "S-STYLE" WEDGING PLUG OR APPROVED EQUAL.
3. FOR THREADLESS CONDUIT (RIGID, IMC OR EMT) ATTACH CONDUIT BODY TO MALE THREADS OF A SET SCREW OR COMPRESSION CONNECT, AS PERMITTED BY SPECIFICATIONS.
4. PROVIDE PULL BOX AT EACH LOCATION OF CABLE SUPPORTS. PULL BOX SHALL BE SIZED AS PER CODE TO ACCOMMODATE ALL CONDUITS.



① FOR CONCRETE BLOCK WALLS, CENTER CAULK CP-25 OR PUTTY 303 WITHIN WALL WITH DAMMING ON BOTH SIDES.

② RECOMMENDATIONS BASED ON PRODUCT PERFORMANCE PER  
ASTM E-514 (1999) AND 1999 EDITION OF CLASSIFICATION  
FIRE STOP SYSTEMS 49, 33 AND 91.

③ WET INSTALLED DEPTH OF CAULK CP-25 OR PUTTY 303  
DEPENDS ON TYPE AND SIZE OF PIPE:

WET DEPTH	PIPE SIZE	FIRE RATING
1" (25mm)	MAX. 6" (153mm)	2 HRS.
2" (51mm)	MAX. 6" (152mm)	3 HRS.

④ UP TO 40% SHRINKAGE OF CP-25 OR PUTTY 303 IS  
ACCEPTABLE AFTER WET DEPTH INSTALLATION.

⑤ OPTIONS TO MAKING TAP TO PREVENT SAGGING:

- INSTALL ADDITIONAL DAMMING MATERIAL OVER  
PRODUCT TO HOLD IT IN PLACE.
- REMOVE PRODUCT FROM CONTAINER AND ALLOW  
TO AIR CURE IN SMALL BATCHES FOR 12 HRS.  
THEN HAND FORD TO INSTALL.

⑥ WHEN ANNUAL SCALE EXCEEDS 3/4" (19mm), A 28 AWG  
METAL COVER PLATE MUST BE MECHANICALLY SECURED  
ATOP THE 3M FIRE BARRIER APPLICATION, OR TIGHTLY  
TACK A NON-FLAMMABLE DAMMING MATERIAL ATOP  
INSTALLED CAULK OR PUTTY.

# ALOHA HOLA AT RAILYARD

Revision 3 : 06.07.24

Revision 1 : 03.05.24

PREPARED BY : NYE

OS230050.00


ELECTRICAL DETAILS

---

E300

---






### ELECTRICAL RISER KEYED NOTES:

- A** EXISTING 200A, 120/208V, 3-PHASE, 4 WIRE ELECTRICAL METER AND BREAKER SWITCH (PROVIDED BY LL) IN THE EXISTING METER CENTER FOR THE TENANT'S SPACE SHALL REMAIN. E.C. SHALL COORDINATE WITH LANDLORD/BASE BUILDING FOR THE EXACT LOCATION OF THE EXISTING METER CENTER AND EXACT POWER DISTRIBUTION IN THE FIELD. E.C SHALL VERIFY THE OPERABLE CONDITION OF EXISTING METER & BREAKER SWITCH, REPLACE IF INOPERABLE. BASE BID ACCORDINGLY.
- B** EXISTING 200A, 120/208V, 3-PHASE, 4-WIRE ELECTRICAL INCOMING SERVICE FEEDER TO THE ELECTRICAL PANEL "A" IN THE TENANT'S SPACE TO REMAIN( PROVIDED BY LL). E.C. SHALL GET INFORMATION ABOUT THE EXISTING POWER DISTRIBUTION PRIOR TO COMMENCING ANY WORK AND INFORM ENGINEER ON RECORD FOR ANY DISCREPANCIES. BASE BID ACCORDINGLY.
- C** EXISTING 200A(M.C.B), 120/208V, 3-PHASE, 4-WIRE ELECTRICAL PANEL "A" (PROVIDED BY LL) TO REMAIN. E.C. TO FIELD VERIFY THE EXACT SIZE, LOCATION & OPERABLE CONDITION OF THE PANEL, REPLACE IF INOPERABLE. BASE BID ACCORDINGLY.
- D** NEW 125A(M.L.O.), 120/208V, 3-PHASE, 4-WIRE ELECTRICAL PANEL "B". E.C. SHALL COORDINATE EXACT LOCATION WITH ARCHITECTURE/OWNER/LL.

### EQUIPMENT LIST

ITEM NO.	DESCRIPTION	VOLTAGE	PHASE	AMPS	kW
1	48" PREP TABLE	120	1	2	0.24
11	72" PREP TABLE	120	1	5.4	0.65
16	TANKLESS WATER HEATER	120	1	1.5	0.18
18	TV	120	1	3	0.36
19	SODA FOUNTAIN	120	1	1.5	0.18
23	POS WITH PRINTER	120	1	1.5	0.18

NOTE:- E.C SHALL COORDINATE WITH EQUIPMENT MANUFACTURER FOR TH EXACT POWER REQUIREMENT BEFORE COMMENCING ANY WORK. BASE BID ACCORDINGLY.



### ELECTRICAL GENERAL NOTE:

- A.** ABOVE RISER DIAGRAM IS FOR REFERENCE PURPOSES ONLY. E.C. SHALL VERIFY EXACT POWER DISTRIBUTION IN FIELD AND INFORM ENGINEER ON RECORD FOR ANY DISCREPANCY.
- B.** E.C. SHALL VERIFY INCOMING SERVICE AMPERAGE, WIRE SIZING AND DISTRIBUTION.
- C.** ELECTRICAL CONTRACTOR TO COORDINATE FAULT CURRENT (Isc) RATING WITH UTILITY COMPANY AND AHJ PRIOR TO COMMENCING ANY WORK.
- D.** E.C. TO VERIFY OPERABLE CONDITIONS OF EXISTING DEVICES IN FIELD. REPLACE/RECTIFY IF FOUND IN OPERABLE. BASE BID ACCORDINGLY.
- E.** EXISTING ELECTRICAL DISTRIBUTION TO BE MAINTAINED AND UTILIZED TO SERVE PROJECT SPACE. POWER RISER DIAGRAM INDICATED FOR REFERENCE PURPOSES ONLY.
- F.** ELECTRICAL CONTRACTOR SHALL COORDINATE WITH OWNER/LANDLORD/BASE BUILDING FOR THE EXACT SCOPE OF WORK/LIABILITIES.

### PANEL SCHEDULE:

PANEL: A (E)										MOUNTING: SURFACE						
208Y/120		VOLTS,		3		PHASE,		4		WIRE		PANEL LOCATION: BACK KITCHEN				
MAIN CB: 200A		MLO: NA				BUS: 225A		MIN,		FED FROM: EXISTING ELECTRICAL DISCONNECT						
*NOTE: LIGHTING, R: RECEPTACLES, K:KITCHEN/EQUIPMENTS, C: REFRIGERATION, H: HVAC, M: MOTOR, O:OTHER/MISCELLANEOUS *																
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	MINIMUM BRANCH CIRCUIT	PER PHASE (KVA)			MINIMUM BRANCH CIRCUIT	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.		
						A	B	C								
1	20	LIGHTING INDOOR DINING AREA	L	0.22	2#12, 1#12G, 3/4"C	0.76			2#12, 1#12G, 3/4"C	0.54	R	RECEPTACL_CAMERA/SPEAKER	20	2		
3	20	LIGHTING BACK KITCHEN, RESTROOM AREA	L	0.61	2#12, 1#12G, 3/4"C		0.79		2#12, 1#12G, 3/4"C	0.18	R	RECEPTACL_OPEN CLOSE SING	20	4		
5	20	LIGHTING - J. BOX EXT SIGNAGE	L	1.20	2#12, 1#12G, 3/4"C			1.56	2#12, 1#12G, 3/4"C	0.36	R	RECEPTACL_POS(#23)	20	6		
7	20	LIGHTING SERVICE AREA	L	0.26	2#12, 1#12G, 3/4"C	0.62			2#12, 1#12G, 3/4"C	0.36	R	RECEPTACL_POS(#23)	20	8		
9	20	LIGHTING OUTDOOR DINING AREA	L	0.50	2#12, 1#12G, 3/4"C		0.74		2#12, 1#12G, 3/4"C	0.24	R	48" PREP TABLE(#1)	20	10		
11	20	WATER HEATER	O	0.42	2#12, 1#12G, 3/4"C			1.14	2#12, 1#12G, 3/4"C	0.72	R	RECEPTACL_TV(#18)	20	12		
13	20	LIGHTING - J. BOX EXT SIGNAGE	L	1.20	2#12, 1#12G, 3/4"C	1.70			2#12, 1#12G, 3/4"C	0.80	L	TIMER	20	14		
15	20	RECEPTACLE EXTERIOR	R	0.36	2#12, 1#12G, 3/4"C		0.60		2#12, 1#12G, 3/4"C	0.24	E	48" PREP TABLE(#1)	20	16		
17	20	HOOD FIRE SUPPRESSION SYSTEM	O	0.50	2#12, 1#12G, 3/4"C			1.35	2#12, 1#12G, 3/4"C	0.85	O	RCP-1	20	18		
19	20	72" PREP TABLE(#11)	E	0.62	2#12, 1#12G, 3/4"C	1.12			2#12, 1#12G, 3/4"C	0.50	L	HOOD LIGHT/CONTROL PANEL	20	20		
21	20	LIGHTING INDOOR DINING AREA	L	0.11	2#12, 1#12G, 3/4"C		0.35		2#12, 1#12G, 3/4"C	0.24	E	48" PREP TABLE(#1)	20	22		
23	20	RECEPTACLE RESTROOM	R	0.36	2#12, 1#12G, 3/4"C			0.54	2#12, 1#12G, 3/4"C	0.18	R	RECEPTACL_OPEN CLOSE SING	20	24		
25	20	SPARE				0.03			2#12, 1#12G, 3/4"C	0.03	M	EF-1(N)	20	26		
27	20	SODA FOUNTAIN(#19)	E	1.00	2#12, 1#12G, 3/4"C		1.03		2#12, 1#12G, 3/4"C	0.03	M	EF-2(N)	20	28		
29	20	SPARE						0.54	2#12, 1#12G, 3/4"C	0.54	R	RECEPTACLE-ROOF	20	30		
31			O	11.23		11.77			2#12, 1#12G, 3/4"C	0.54	R	RECEPTACLE_INDOOR SEATING	20	32		
33	125-3P	PANEL B	O	11.23	#1, #6G, 11/4"C		11.53		2#12, 1#12G, 3/4"C	0.36	R	RECEPTACLE_INDOOR SEATING	20	34		
35			O	11.23				11.23				SPARE	20	36		
37	20	SPARE				0.00						SPARE	20	38		
39	20	SPARE					0.00					SPARE	20	40		
41	20	SPARE						0.00				SPARE	20	42		
TOTAL LOAD (KVA)						16.00	15.10	16.36								

### ELECTRICAL PANEL SCHEDULE GENERAL NOTE:

1. ALL THE CIRCUITING SHOWN FOR THE PANEL SCHEDULES A(E) IS FOR THE REFERENCE PURPOSE ONLY. E.C. SHALL GATHER INFORMATION ABOUT THE EXISTING CONDITIONS, VERIFY THE EXACT COMBINATION OF EXISTING CIRCUIT BREAKERS AVAILABLE IN THE EXISTING PANEL SCHEDULES IN FIELD AND REARRANGE THE CIRCUITING PER THE REQUIREMENTS BEFORE COMMENCING ANY WORK. ALL THE NEWLY REQUIRED BREAKERS (BASED ON THE EXISTING CIRCUIT BREAKER ARRANGEMENT) IN THE PANEL SCHEDULE SHALL BE TAKEN INTO THE CONSIDERATION FOR THE BIDDING. E.C. SHALL VERIFY THE EXACT SIZE OF THE EXISTING ELECTRICAL PANELS AND INFORM ENGINEER ON RECORD FOR ANY DISCREPANCY. BASE BID ACCORDINGLY. E.C SHALL ENSURE THE COMPATIBILITY OF THE NEWLY ADDED BREAKERS IN THE EXISTING PANEL.

PANEL: B (N)										MOUNTING: SURFACE								
208Y/120		VOLTS,		3		PHASE,		4		WIRE		PANEL LOCATION: BACK KITCHEN						
MAIN CB:		NA		MLO:		125A		BUS:		125A		MIN:		FED FROM: PANEL A				
*NOTE: L: LIGHTING, R: RECEPTACLES, K: KITCHEN/EQUIPMENTS, C: REFRIGERATION, H: HVAC, M: MOTOR, O: OTHER/MISCELLANEOUS *																		
A	CKT NO.	TRIP AMPS		DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	MINIMUM BRANCH CIRCUIT	PER PHASE (KVA)			MINIMUM BRANCH CIRCUIT	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.		
								A	B	C								
	1				H	0.88		6.27				5.39	H			2		
	3	20-3P	KEF-1(N)		H	0.88	3#12, #12G, 3/4"	6.27	6.27		3#8, #10G, 3/4"	5.39	H	RTU-1(E)	50-3P	4		
	5				H	0.88				6.27		5.39	H			6		
	9	20-3P	KEF-2(N)		H	0.79	3#12, #12G, 3/4"		1.52		2#10, #12G, 3/4"	0.73	H	AHU-1(N)	20-2P	8		
	13				H	1.57		1.57		0.89	2#12, 1#12G, 3/4"	0.73	H			10		
	15	20-3P	KSE-1(N)		H	1.57	3#10, #12G, 3/4"		1.57			0.10	M	MOTORIZED DAMPER		12		
	17				H	1.57				1.57				SPACE		14		
	19	50-2P	ACCU-1(N)		H	3.12	2#8, #10G, 3/4"	3.12						SPACE		16		
	21				H	3.12			3.12					SPACE		18		
	23	20	SPARE					0.00			0.00			SPACE		20		
	25	20	SPARE											SPACE		22		
	27	20	SPARE						0.00					SPACE		24		
	29	20	SPARE							0.00				SPACE		26		
	31								0.00					SPACE		28		
	33									0.00				SPACE		30		
35										0.00			SPACE		32			
37								0.00					SPACE		34			
39									0.00				SPACE		36			
41										0.00			SPACE		38			
TOTAL LOAD (KVA)								12.48	12.48	8.73								

### PANEL SCHEDULE KEYED NOTES:

- A** ELECTRICAL CONTRACTOR SHALL COORDINATE WITH OWNER/LANDLORD FOR THE EXACT DETAILS/LIABILITIES TO UNDERSTAND THE SCOPE OF WORK FOR PANELS AND BREAKERS IN IT.

**NY ENGINEERS**

NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25

4. Revision 3 : 06.07.24

3. Revision 2 : 04.24.24

2. Revision 1 : 03.05.24

1. Permit set : 01.31.24

PREPARED BY : NYE

REVIEWED BY : NYE

PROJECT NUMBER  
OS230050.00

DRAWING TITLE  
ELECTRICAL RISER  
DIAGRAM & PANEL  
SCHEDULES

DRAWING NUMBER

**E400**

SHEET 8 OF 8



PLUMBING SYMBOLS LIST	
	VENT PIPING
	UNGD. SANITARY PIPING
	UNGD. GREASE WASTE PIPING
	EXISTING UNGD. SANITARY PIPING
	SANITARY PIPING
	GREASE WASTE PIPING
	COLD WATER PIPING
	HOT WATER PIPING
	HOT WATER RETURN PIPING
	GAS PIPING
	P-TRAP
	PIPE UP
	PIPE DROP
	PIPE CAP
	ISOLATION VALVE
	GAS VALVE
	BACKFLOW PREVENTER
	FLOOR SINK
	FLOOR DRAIN
	POINT OF CONNECTION
	CLEANOUT
	BALANCING VALVE
	GAS PRESSURE REGULATOR
PLUMBING ABBREVIATIONS	
CO-1	CLEANOUT
SAN	SANITARY
GSAN	GREASE SANITARY
EX.SAN	EXISTING SANITARY
V	VENT
W	WASTE
LAV-1	LAVATORY
WC-1	WATER CLOSET
EX.	EXISTING
FD-1	FLOOR DRAIN
CW	COLD WATER
HW	HOT WATER
HWR	HOT WATER RETURN
TYP.	TYPICAL
DN	DOWN
AFF	ABOVE FINISH FLOOR
BFP	BACK FLOW PREVENTER
WH-1	WATER HEATER
ET-1	EXPANSION TANK
RCP-1	RECIRCULATION PUMP
M	WATER METER
PRV	PRESSURE REDUCING VALVE
UNGD	UNDERGROUND
GI-1	GREASE TRAP

- BUILDING DEPARTMENT PLUMBING NOTES**
- ALL PLUMBING SYSTEMS (SANITARY, WASTE, VENT, WATER) AND ASSOCIATED EQUIPMENT SHALL BE INSTALLED, OPERATED AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF 2018 VIRGINIA PLUMBING CODE.
  - INSTALLATION OF UNDERGROUND PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF 2018 VIRGINIA PLUMBING CODE SECTION 702.2
  - PROTECTION OF PIPING AND PLUMBING SYSTEM COMPONENTS AS PER 2018 VIRGINIA PLUMBING CODE SECTION 305.
  - TRENCHING, EXCAVATION AND BACKFILL AS PER 2018 VIRGINIA PLUMBING CODE SECTION 306.
  - RODENT PROOFING AS PER 2018 VIRGINIA PLUMBING CODE SECTION 304.
  - MATERIALS USED IN PLUMBING SYSTEMS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION 2018 VIRGINIA PLUMBING CODE 303, 605, 702, 902.
  - EQUIPMENT CONNECTIONS AND JOINING OF PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF 2018 VIRGINIA PLUMBING CODE CHAPTERS 4, 5, 6, 7, 8 AND 9.
  - DEEP SEAL TRAPS FOR FLOOR DRAINS SHALL BE PROVIDED AS PER 2018 VIRGINIA PLUMBING CODE SECTION 1002, AND CLEAN-OUTS SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION 2018 VIRGINIA PLUMBING CODE SECTION 708.
  - VERTICAL AND HORIZONTAL PIPING SHALL BE SUPPORTED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION 2018 VIRGINIA PLUMBING CODE SCTION 308.
  - WATER SUPPLY SYSTEMS SHALL BE INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF 2018 VIRGINIA PLUMBING CODE CHAPTER 6 SECTION 601, 602, 603, 604, 606, 607, 608, 610, 611 AND 613.
  - THE SANITARY DRAINAGE SYSTEM SHALL BE SIZED AND INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF 2018 VIRGINIA PLUMBING CODE CHAPTER 7 SECTION 701, 704, 705, 706, 707, 708, 709 AND 710.
  - VENT PIPING FOR THE SANITARY DRAINAGE SYSTEM SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF 2018 VIRGINIA PLUMBING CODE CHAPTER 9 SECTIONS 901 THROUGH 2018 VIRGINIA PLUMBING CODE SECTION 919.
  - INSPECTION AND TESTING OF PLUMBING PIPING SYSTEMS SHALL BE IN ACCORDANCE WITH SECTION 2018 VIRGINIA PLUMBING CODE SECTION 107 AND 312.
  - INSPECTION AND TESTING OF GAS PIPING SYSTEMS SHALL BE IN ACCORDANCE WITH SECTION 406 OF 2018 VIRGINIA FUEL GAS CODE.

PLUMBING DRAWING LIST	
P001	PLUMBING SYMBOLS, ABBREVIATIONS, NOTES & SPECIFICATIONS
P002	PLUMBING NOTES & SPECIFICATIONS
P101	PLUMBING WASTE AND VENT FLOOR PLAN
P102	PLUMBING DOMESTIC WATER AND GAS FLOOR PLAN
P103	PLUMBING GAS ROOF PLAN
P501	PLUMBING DETAILS
P601	PLUMBING SCHEDULES & RISERS

- PLUMBING SPECIFICATIONS**
- BASIC PLUMBING REQUIREMENTS, MATERIALS AND METHODS
  - SCOPE
  - PROVIDE ALL MATERIAL, TOOLS, SUPERVISION AND LABOR INCLUDING ALL MISCELLANEOUS AND INCIDENTAL ITEMS REQUIRED FOR COMPLETE AND OPERABLE PLUMBING INSTALLATIONS AS SHOWN OR DESCRIBED ON THE DRAWINGS AND IN THESE SPECIFICATIONS.
  - THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL NEW CONDITIONS AND MATERIALS WITHIN THE CONSTRUCTION AREA. ANY DAMAGE CAUSED BY THE CONTRACTOR SHALL BE REPAIRED TO THE OWNER'S SATISFACTION.
  - OBTAIN ALL PERMITS, PAY ALL PERMIT FEES AND SCHEDULE ALL REQUIRED INSPECTIONS. COPIES OF ALL PERMITS AND INSPECTION CERTIFICATES SHALL BE FORWARDED TO THE OWNER FOR RECORD.
  - THE GENERAL CONDITIONS OF THE CONTRACT AND ALL DIVISION 1 REQUIREMENTS APPLY TO THE WORK OF THIS SECTION.
  - THE CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID TO DETERMINE CONDITIONS AND THE EXTENT OF THE WORK. BY COMMENCING WORK, THE CONTRACTOR ACKNOWLEDGES HIS CONFIRMATION OF ALL CONDITIONS AS ACCEPTABLE WITH REFERENCE TO HIS CONTRACT, SCOPE OF WORK AND BID PRICE SUCH THAT NO ADDITIONAL COMPENSATION SHALL BE FORTHCOMING FOR UNFORESEEN EXISTING CONDITIONS.
  - IN ALL AREAS SUBJECT TO FREEZING CONDITIONS, THE CONTRACTOR SHALL PROVIDE FREEZE PROTECTION FOR ALL DOMESTIC WATER PIPING INSTALLED UNDER HIS CONTRACT.
  - ALL ELECTRICAL REQUIREMENTS SHALL BE COORDINATED WITH THE CONTRACTOR FOR ELECTRICAL WORK. THIS CONTRACTOR IS RESPONSIBLE FOR ALL LOW VOLTAGE WIRING FOR EQUIPMENT INSTALLED UNDER HIS CONTRACT. THE CONTRACTOR FOR ELECTRICAL WORK IS RESPONSIBLE FOR LINE VOLTAGE POWER WIRING ONLY.
  - COLOR AND FINISH SELECTIONS FOR ALL MATERIALS, INCLUDING PAINTING OF PIPING, SHALL BE AS DIRECTED AND/OR APPROVED BY THE ARCHITECT.
  - MINOR DETAILS NOT SHOWN OR SPECIFIED, BUT NECESSARY FOR THE PROPER AND ACCEPTABLE CONSTRUCTION, INSTALLATION OR OPERATION OF ANY PART OF THE WORK AS DETERMINED BY THE ENGINEER SHALL BE INCLUDED AS IF SPECIFIED OR INDICATED ON THE DRAWINGS.
  - THIS CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL REQUIREMENTS FOR THE INSTALLATION, CONNECTION, EXTENSION OR MODIFICATION TO ALL UTILITY SERVICES WITH RESPECTIVE PROVIDERS INCLUDING PAYMENT OF ALL ASSOCIATED FEES.
  - THE CONTRACTOR IS RESPONSIBLE FOR ALL PAINTING ASSOCIATED WITH CUTTING AND PATCHING. ALL PAINTING IN AREAS WITH COMPLETE FINISH RENOVATIONS SHALL BE PROVIDED BY THE GENERAL CONTRACTOR.
  - SUBMITTALS
  - SUBMITTAL REQUIREMENTS SHALL BE COORDINATED WITH THE ARCHITECT AND AUTHORITIES HAVING JURISDICTION. UNLESS OTHERWISE DIRECTED, CONTRACTOR SHALL PROVIDE SUBMITTALS AS LISTED BELOW.
    - PIPE AND FITTINGS
    - VALVES
    - HANGERS AND SUPPORTS
    - PLUMBING PIPING LAYOUT
    - TESTS
    - PLUMBING FIXTURES
    - WATER HEATERS & ACCESSORIES
    - FLOOR DRAINS
    - MIXING VALVES
    - BACKFLOW PREVENTER
    - ALL SCHEDULED PLUMBING EQUIPMENT
  - SUBMITTALS FROM SUPPLIERS OR MANUFACTURERS WHICH DO NOT BEAR THE STAMP OF THE SUBMITTING CONTRACTOR INDICATING THAT THE CONTRACTOR HAS REVIEWED THE SUBMITTAL FOR CONFORMANCE WITH THE PROJECT REQUIREMENTS WILL BE RETURNED REJECTED.
  - THE ENGINEER'S REVIEW OF SUBMITTALS IS A COURTESY WHICH DOES NOT RELIEVE THE CONTRACTOR FROM CONFORMING WITH THE CONSTRUCTION DOCUMENTS, REGARDLESS OF THE ACTION INDICATED BY THE SHOP DRAWINGS STAMP.
  - REVIEW OF SHOP DRAWINGS BY THE ENGINEER SHALL BE LIMITED TO THE INITIAL REVIEW, AND A SECOND REVIEW OF ANY REQUIRED RESUBMITTED DATA IF THE ENGINEER IS REQUIRED TO REVIEW SHOP DRAWINGS FOR A THIRD (OR MORE) SUBMISSION OF THE SAME ITEM, THE CONTRACTOR SHALL BE LIABLE FOR COMPENSATING THE ENGINEER FOR THESE SUBSEQUENT REVIEWS AS PER THE ENGINEER'S CURRENT HOURLY RATE SCHEDULE.
  - SUBMIT PROOF OF APPROVAL AND/OR CONFIRMATION OF SATISFACTORY TEST RESULTS TO THE OWNER AND THE ARCHITECT.
  - SUBMIT TO THE OWNER'S MAINTENANCE PERSONNEL OPERATION AND MAINTENANCE DATA FOR ALL SYSTEM COMPONENTS, SERVICING REQUIREMENTS, INSPECTION DATA, REPLACEMENT PART NUMBERS AND AVAILABILITY AND CONTACT INFORMATION FOR SERVICE/SUPPLY COMPANY.
  - FOR ALL BELOW GRADE PIPING WHERE ACTUAL INSTALLATION DEVIATES FROM CONSTRUCTION DRAWINGS, THE CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS INDICATING BELOW GRADE PIPE LOCATIONS DIMENSIONED TO NEAREST COLUMN LINES.
  - RECORD AS-BUILT DRAWINGS SHALL BE SUPPLIED TO THE OWNER/TENANT AFTER COMPLETION OF THE WORK SHOWING ANY ALTERATIONS, ADDITIONS AND/OR DELETIONS TO THE SYSTEM(S) INSTALLED.
  - SUBSTITUTIONS
  - ALL EQUIPMENT SHALL BE PRODUCTS OF THE SPECIFIED MANUFACTURER OR MANUFACTURERS. ALL BIDS SHALL BE BASED ON THE SPECIFIED MANUFACTURER OR MANUFACTURER'S EQUIPMENT. FOR SUBSTITUTIONS OF OTHER MANUFACTURER'S EQUIPMENT TO BE CONSIDERED, THE SUBSTITUTION MUST BE INDICATED PRIOR TO BIDDING WITH THE REASON FOR THE PROPOSED SUBSTITUTION IDENTIFIED, AND THE PROPOSED CREDIT TO THE OWNER INDICATED. THE ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF ANY PROPOSED SUBSTITUTIONS.
  - THE CONTRACTOR ASSUMES ALL RESPONSIBILITY FOR COORDINATING THE WORK OF OTHER TRADES WHICH MAY BE AFFECTED BY SUBSTITUTIONS, INCLUDING ALL RELATED COSTS.
  - DEFINITIONS
  - FURNISH: TO PURCHASE, PROCURE, ACQUIRE AND DELIVER, COMPLETE WITH RELATED ACCESSORIES.

- B. INSTALL: TO ERECT, MOUNT AND CONNECT, COMPLETE WITH RELATED ACCESSORIES.
- C. PROVIDE: TO FURNISH AND INSTALL.
- D. PLUMBING CONTRACTOR, THE CONTRACTOR, THIS CONTRACTOR: THE CONTRACTOR FOR PLUMBING WORK WHICH IS SPECIFIED HEREIN AND SHOWN ON THESE DRAWINGS.
- E. REFER TO THE 2018 VIRGINIA PLUMBING CODE FOR ADDITIONAL DEFINITIONS.
- 1.05 DRAWINGS
- A. THE DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED TO ILLUSTRATE THE GENERAL ARRANGEMENT AND ROUTING OF PIPING AND GENERAL LOCATIONS OF EQUIPMENT. PRECISE LOCATIONS OF EQUIPMENT, RISERS AND STACKS, AND ROUTING AND ELEVATION OF ALL PIPING SYSTEMS SHALL BE COORDINATED IN THE FIELD WITH THE ARCHITECT, ARCHITECTURAL DRAWINGS, THE WORK OF OTHER TRADES, EXISTING AND NEW BUILDING CONDITIONS AND/OR THE PREFERENCES OF THE OWNER/TENANT AS CONSTRUCTION PROCEEDS. ALL PIPING SHALL BE INSTALLED CONCEALED IN FINISHED SPACES, UNLESS NOTED OTHERWISE.
- B. PROVIDE ALL NECESSARY INCIDENTAL MATERIALS AND ACCESSORIES REQUIRED TO MAKE THE WORK COMPLETE IN ALL RESPECTS, EVEN IF NOT PARTICULARLY SHOWN OR SPECIFIED.
- C. REFER TO PLUMBING EQUIPMENT/FIXTURE SCHEDULE ON THE DRAWINGS FOR ALL FIXTURE AND EQUIPMENT SPECIFICATIONS.
- D. REFER TO FIXTURE CONNECTION SIZE SCHEDULE FOR ALL FIXTURE ROUGHING SIZE REQUIREMENTS.
- E. VERIFY ALL INDICATED CONDITIONS BEFORE STARTING WORK AND REPORT ANY DISCREPANCIES. THE DRAWINGS REFLECT CONDITIONS WHICH CAN BE REASONABLY INTERPRETED FROM THE EXISTING VISIBLE CONDITIONS OR FROM DRAWINGS AND INFORMATION FURNISHED BY THE OWNER.
- F. LOCATE ALL FIXTURES AND EQUIPMENT AS PER THE FINAL ARCHITECTURAL DRAWINGS.
- 1.06 PRODUCTS
- A. SANITARY AND VENT PIPING:
- ABOVE GRADE PIPING SHALL BE HUBLESS CAST IRON PIPE WITH STAINLESS STEEL COUPLINGS AND ELASTOMERIC GASKETS WITH A MINIMUM NO. OF BANDS PER COUPLING AS PER CISPI 301.
  - SLOPE OF DRAINAGE SYSTEM SHALL BE 1/8" PER FOOT OF RUN FOR PIPE OVER 3" (I.D.) AND 1/4" PER FOOT OF RUN FOR PIPE 3" AND SMALLER (I.D.). VENT PIPING SHALL BE PITCHED TO DRAIN. SLOPE FOR GREASE SANITARY PIPING SHALL BE MINIMUM 1/4" PER FOOT RUN FOR PIPE OVER 3".
  - ALL CAST IRON SOIL PIPE AND FITTINGS SHALL BE MARKED WITH THE COLLECTIVE TRADEMARK OF THE CAST IRON SOIL PIPE INSTITUTE (CISPI) AND BE LISTED BY NSF INTERNATIONAL.
- B. DOMESTIC WATER PIPING:
- ABOVE GRADE WATER PIPING SHALL BE TYPE 'L' HARD-DRAWN COPPER TUBE.
  - FITTINGS IN DOMESTIC WATER PIPING SHALL BE WROUGHT COPPER OR CAST BRASS.
  - JOINTS SHALL BE MADE WITH LEAD-FREE SOLDER.
  - THE ENTIRE DOMESTIC WATER DISTRIBUTION SYSTEM SHALL BE INSULATED INCLUDING ALL VALVES, FITTINGS, ETC.
  - COMPLY WITH NSF 61 FOR MATERIALS FOR WATER-SERVICE PIPING AND SPECIALTIES FOR DOMESTIC WATER.
  - ALL DOMESTIC WATER PIPING ABOVE GRADE SHALL BE FIRE-RETARDANT, FACTORY-APPLIED JACKET. PROVIDE COLD WATER PIPING WITH FACTORY-APPLIED VAPOR BARRIER.
  - INSULATION REQUIREMENT SHOULD COMPLY SECTION C404.4 REFER WITH 2018 VIRGINIA ENERGY CONSERVATION CODE TABLE C403.11.3.

MINIMUM PIPE INSULATION THICKNESS				
FLUID OPERATING TEMPERATURE RANGE AND USAGE (°F)	INSULATION CONDUCTIVITY		NOMINAL PIPE OR TUBE SIZE (INCHES)	
	CONDUCTIVITY BTU-IN./ (H·FT²·°F)	MEAN RATING TEMPERATURE, °F	<1	>8
141-200	0.25-0.29	125	1.5	2.0
105-140	0.21-0.28	100	1.0	1.5
40-60	0.21-0.27	75	0.5	1.0

NOMINAL PIPE SIZE (INCHES)	MIXIMUM PIPING LENGTH (FEET)	
	PUBLIC LAV	OTHER FIXTURES
3/8"	3'	50'
1/2"	2'	43'
3/4"	0.5'	21'
1"	0.5'	13'
1 1/4"	0.5'	8'
1 1/2"	0.5'	6'
2" OR LARGER	0.5'	4'

9. AS PER 2018 VIRGINIA ENERGY CONSERVATION CODE EDITION, C404.7 WATER DISTRIBUTION SYSTEM HAVING ONE OR MORE RECIRCULATION PUMPS THAT PUMP WATER FROM A HEATED-WATER SUPPLY PIPE BACK TO THE HEATED-WATER SOURCE THROUGH A COLD-WATER SUPPLY PIPE SHALL BE A DEMAND RECIRCULATION WATER SYSTEM. PUMPS SHALL HAVE CONTROLS THAT COMPLY WITH BOTH OF THE FOLLOWING:
- THE CONTROL SHALL START THE PUMP UPON RECEIVING A SIGNAL FROM THE ACTION OF A USER OF A FIXTURE, SENSING THE PRESENCE OF A USER OF A FIXTURE OR SENSING THE FLOW OF HOT OR TEMPERED WATER TO A FIXTURE.
  - THE CONTROL SHALL LIMIT THE TEMPERATURE OF THE WATER ENTERING THE COLD-WATER PIPING TO 104°F(40°C).

- AS PER 2018 VIRGINIA ENERGY CONSERVATION CODE, C404.6.1, HEATED-WATER CIRCULATION SYSTEMS SHALL BE PROVIDED WITH A CIRCULATION PUMP. THE SYSTEM RETURN PIPE SHALL BE A DEDICATED RETURN PIPE OR A COLD WATER SUPPLY PIPE. CONTROLS FOR CIRCULATING HOT WATER SYSTEM PUMPS SHALL START THE PUMP BASED ON THE IDENTIFICATION OF A DEMAND FOR HOT WATER WITHIN THE OCCUPANCY. THE CONTROLS SHALL AUTOMATICALLY TURN OFF THE PUMP WHEN THE WATER IN THE CIRCULATION LOOP IS AT THE DESIRED TEMPERATURE AND WHEN THERE IS NO DEMAND FOR HOT WATER.
- MIXING VALVES
- VALVE BODY SHALL BE MADE OF CAST BRASS. THE INTERNAL COMPONENTS SHALL BE MADE OF BRASS OR STAINLESS STEEL.
- TYPES A, C & D VALVES: VALVE SHUTS OFF IN FULL COLD POSITION AND MUST PASS THROUGH COLD RANGE BEFORE DELIVERING WARM, AND/OR HOT WATER. TEMPERATURE LIMIT SET AT 105°F MAXIMUM DELIVERY TEMPERATURE. IF ONE SUPPLY SHOULD FAIL, THE OTHER WILL AUTOMATICALLY AND INSTANTLY SHUT DOWN. DELIVERY CAPACITY IS 5GPM @ 45 PSIG DIFFERENTIAL.
- TYPES OF VALVES: TYPE A- THERMOSTATICALLY OPERATED BY MEANS OF BI-METALLIC STRIP, OR EXPANSION BELLOW; TYPE B- SINGLE HANDLE MECHANICAL MIXER, OR INDIVIDUAL HOT AND COLD CONTROL VALVES; TYPE C- PRESSURE BALANCING SHOWER VALVE/PISTON OPERATED MIXING VALVE; TYPE D- BALANCED PRESSURE OPERATION, WITH INTEGRAL DIAL THERMOMETER INDICATING DELIVERED WATER TEMPERATURE.
- EACH ELEMENT SHALL BE CONTROLLED BY AN INDIVIDUALLY MOUNTED THERMOSTAT AND HIGH TEMPERATURE CUT-OFF SWITCH. ALL INTERNAL CIRCUITS SHALL BE FUSED. THE OUTER JACKET SHALL BE OF BAKED ENAMEL FINISH AND SHALL BE PROVIDED WITH FULL SIZE CONTROL COMPARTMENT FOR PERFORMANCE OF SERVICE AND MAINTENANCE THROUGH HINGED FRONT PANEL AND SHALL ENCLOSE THE TANK WITH FOAM INSULATION, ELECTRICAL JUNCTION BOX WITH HEAVY DUTY TERMINAL BLOCK SHALL BE PROVIDED. THE DRAIN VALVE SHALL BE LOCATED IN THE FRONT FOR EASE OF SERVICING.
- HANGERS AND SUPPORTS:
- HANGERS SHALL BE STANDARD STEEL, MALLEABLE OR WROUGHT IRON, AS MANUFACTURED BY GRINNELL OR APPROVED EQUAL SUITABLE FOR THE TYPE OF CONSTRUCTION. PIPING SHALL NOT BE HUNG FROM OTHER PIPE.
- SECTIONS OF INDIVIDUAL PIPE RUNS SHALL BE SUPPORTED BY CLEVIS HANGERS.
- ALL EQUIPMENT SHALL BE PROVIDED WITH APPROVED SUPPORTS.
- PROVIDE SEISMIC RESTRAINTS IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES AND STANDARDS AND THE REQUIREMENTS OF AUTHORITIES HAVING JURISDICTION.
- UNLESS OTHERWISE INDICATED OR REQUIRED BY AUTHORITIES HAVING JURISDICTION, THE FOLLOWING SHALL BE PROVIDED WITH SEISMIC RESTRAINTS AS REQUIRED BY THE 2018 VIRGINIA BUILDING CODE, SECTION 1610.6.4: ALL EQUIPMENT AND MACHINERY, ALL NEW PIPING 2"-1/2" AND LARGER (1-1/4" AND LARGER INBOILER/MECHANICAL ROOMS) WITH HANGERS GREATER THAN 12" IN LENGTH FROM THE TOP OF PIPE TO THE STRUCTURE.
- SUPPORTS SHALL BE PROVIDED IN STRICT ACCORDANCE WITH THE RECOMMENDATIONS OF THE PIPING MANUFACTURER.
- GAS PIPING
- ALL GAS PIPING WORK SHALL COMPLY WITH 2018 VIRGINIA FUEL GAS CODE, LOCAL UTILITY GAS REQUIREMENTS.
- FURNISH AND INSTALL ALL NECESSARY GAS PIPING TO ALL EQUIPMENT REQUIRING GAS SUPPLY.
- PROVIDE A LUBRICATED GAS VALVE AT ALL CONNECTIONS TO EQUIPMENT.
- ALL GAS PIPING AND INSTALLATION SHALL BE IN ACCORDANCE WITH RULES AND REGULATIONS OF LOCAL UTILITY GAS COMPANY AND OTHER AUTHORITIES HAVING JURISDICTION.
- PROVIDE ADEQUATE SUPPORT FOR ALL PIPING.
- GAS PIPING SHALL BE BLACK STEEL SCHEDULE 40 THREADED PIPE CONFORMING TO ANSI B36-20.
- FITTINGS SHALL BE MALLEABLE IRON.
- HOT WATER RE-CIRCULATING PUMP
- IN-LINE PUMP: SINGLE STAGE VOLUTE TYPE PUMP SHALL BE MADE OF CAST IRON OR FORGED LEAD-FREE BRONZE IMPELLER.
- THE PUMP SHALL HAVE A GROUND AND POLISHED STEEL SHAFT WITH A HARDENED INTEGRAL THRUST COLLAR. THE SHAFT SHALL BE SUPPORTED BY TWO HORIZONTAL SLEEVE BEARINGS DESIGNED TO CIRCULATE OIL. THE PUMPS ARE TO BE EQUIPPED WITH A MECHANICAL SEAL WITH CARBON SEAL FACE ROTATING AGAINST CERAMIC SEAT. THE MOTOR SHALL BE NON-OVERLOADING AT ANY POINT ON PUMP CURVE.
- DIRECT CONNECT PUMP TO ELECTRIC MOTOR WITH FLEXIBLE COUPLING. THE MOTOR SHALL BE OF THE DRIP-PROOF, SLEEVE- BEARING, QUIET OPERATING, RUBBER-MOUNTED CONSTRUCTION. EQUIPMENT MOTOR WITH BUILT-IN THERMAL OVERLOAD PROTECTION.
- INSTALL IN-LINE CIRCULATING PUMPS BETWEEN PIPE FLANGES IN PIPING SYSTEMS. INSTALL OVERHEAD PIPE SUPPORTS, BOTH SIDES OF IN-LINE PUMPS, INSTALLED IN HORIZONTAL PIPING RUNS.

**NY ENGINEERS**  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 4967A,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25
4. Revision 3 : 06.07.24
3. Revision 2 : 04.24.24
2. Revision 1 : 03.05.24
1. Permit set : 01.31.24
PREPARED BY : NYE
REVIEWED BY : NYE
PROJECT NUMBER OS230050.00
DRAWING TITLE PLUMBING SYMBOLS, ABBREVIATIONS, NOTES AND SPECIFICATIONS
DRAWING NUMBER <b>P001</b>
SHEET 1 OF 7




H. VALVES:			
1. PROVIDE GATE VALVES, BUTTERFLY OR BALL VALVES FOR SHUT-OFF DUTY ON MAIN AND BRANCH SUPPLY LINES. FOR ALL PIPE RUNS 2" AND SMALLER, PROVIDE BALL FOR ALL PIPE RUNS LARGER THAN 2" AND SMALLER THAN 4", PROVIDE GATE VALVES. PIPING 4" AND LARGER, PROVIDE BUTTERFLY VALVES FOR SHUT-OFF DUTY.			
2. ALL FIXTURES WITH THE EXCEPTION O FLUSHOMETER-EQUIPPED WATER CLOSETS AND URINALS SHALL HAVE STOP VALVES TO CONTROL SUPPLY TO THE FIXTURE. WHERE SUPPLIES ARE EXPOSED PROVIDE CHROME-PLATED STOPS WITH CHROME-PLATED ESCUTCHEONS ON PIPING PENETRATIONS.			
3. ALL PLUMBING FIXTURES AND EQUIPMENT TO HAVE SHUT-OFF VALVES ON SUPPLY LINES.			
4. ALL BRANCH LINES TO HAVE SHUT-OFF VALVES.			
5. ALL VALVES SHALL BE ACCESSIBLE. PROVIDE ACCESS DOORS WHERE REQUIRED FOR VALVE ACCESS.			
6. PROVIDE GLOBE VALVES FOR THROTTLING/BALANCING OF THE HOT WATER CIRCULATING SYSTEM.			
I. SLEEVES AND ESCUTCHEONS:			
1. SLEEVES THROUGH STRUCTURAL CONCRETE MEMBERS AND SLEEVES FOR WALLS BELOW GRADE AND FLOORS ON GRADE SHALL BE STANDARD WEIGHT GALVANIZED SCHEDULE 40 STEEL PIPE. SLEEVES THROUGH OTHER THAN STRUCTURAL COMPONENTS OF THE BUILDING SHALL BE 20 GAGE GALVANIZED SHEET METAL WITH LOCK SEAM JOINTS. USG THERMAFIBER SAFING INSULATION SHALL BE INSTALLED BETWEEN PIPE AND SLEEVE.			
2. PIPE ESCUTCHEON PLATES SHALL BE INSTALLED WHERE EXPOSED PIPING PASSES THROUGH WALLS, CEILINGS, AND FLOORS AND SHALL BE MINIMUM 20 GAGE STEEL. PROVIDE CHROME PLATED ESCUTCHEON PLATES IN FINISHED AREAS.			
J. DRAINAGE ACCESSORIES			
1. GENERAL:			
a. INSTALL THE WORK OF THIS SECTION IN ACCORDANCE WITH THE MANUFACTURER'S PRINTED INSTALLATION INSTRUCTIONS, UNLESS OTHERWISE SPECIFIED.			
b. SECURE EXTERNAL COMPONENTS IN PLACE WITH VANDAL RESISTANT FASTENERS OR DEVICES WHICH CANNOT BE REMOVED WITHOUT SPECIAL TOOLS.			
K. DEVICES:			
a. CLEANOUT & CLEANOUT PLUG			
• THREADED PIPE FITTING OR CAST IRON FERRULE WITH GAS TIGHT CLEANOUT PLUG			
• PLUG SHOULD BE CAST BRASS OR BRONZE, WITH THREADED END, AND RAISED OR COUNTERSUNK HEAD.			
• LUBRICATE THREADS OF CLEANOUT PLUG WITH ANTI-SEIZE LUBRICANT BEFORE FINAL INSTALLATION.			
b. CLEANOUT WALL PLATE			
• IT SHOULD BE ROUND, STAINLESS STEEL OR POLISHED CHROME PLATED BRONZE COVER PLATE WITH STAINLESS STEEL VANDAL RESISTANT FASTENER TO SECURE TO CLEANOUT PLUG.			
c. CLEANOUT DECK PLATE			
• IT SHOULD BE STANDARD DUTY FLOOR CLEANOUT FITTING WITH COATED CAST IRON BODY; ROUND, POLISHED NICKEL BRONZE SCORIATED TOP SECURED TO CLEANOUT PLUG WITH STAINLESS STEEL VANDAL RESISTANT FASTENER; THREADED HEIGHT ADJUSTMENT, CAST IRON HEAD, GAS TIGHT CLEANOUT PLUG, AND CONNECTION TO MATCH PIPING OPTION SELECTED.			
• GRILLE FREE AREA SHOULD BE AT LEAST EQUAL TO CROSS-SECTION AREA OF PIPE TO WHICH CONNECTION MADE AND MADE OF POLISHED NICKEL BRONZE, WITH REMOVABLE GRATE, EITHER PERFORATED OR BAR TYPE. GRATE ATTACHED TO GRILLE BODY WITH VANDAL RESISTANT FASTENER.			
L. INDIRECT WASTE FLOOR SINK			
a. IT SHOULD BE COMBINATION OF FUNNEL DRAIN AND P TRAP WITH POLISHED CHROME PLATED CAST BRASS CONSTRUCTION WITH 4" TOP DIA., 4" DEEP WITH THREADED OUTLET.			
M. INSTALL PIPING TO CONSERVE BUILDING SPACE. DO NOT INTERFERE WITH USE OF BUILDING SPACE AND THE WORK OF OTHER TRADES. ALL PIPING RUN IN CEILING SHALL BE INSTALLED TIGHT TO THE STRUCTURE ABOVE.			
N. INSTALL PIPING TO ALLOW FOR EXPANSION AND CONTRACTION WITHOUT STRESSING PIPE, JOINTS OR CONNECTED EQUIPMENT. PROVIDE PIPE ANCHORS, GUIDES AND EXPANSION JOINTS OR LOOPS IN ALL HOT WATER AND HOT WATER CIRCULATING MAIN SUPPLY PIPING AND SEGMENTS OF SUCH PIPE THAT EXCEED 30'-0" IN LENGTH.			
O. IN ALL AREAS WITH FINISHED SURFACES, SYSTEM PIPING AND COMPONENTS SHALL BE CONCEALED ABOVE OR WITHIN FINISHED SURFACES.			
P. REDUCTIONS IN PIPE SIZES SHALL BE MADE WITH ONE-PIECE REDUCING FITTINGS. BUSHINGS ARE NOT ACCEPTABLE. USE FLANGED FITTINGS AT THE BASE OF RISERS.			
Q. VENT PENETRATIONS THROUGH THE ROOF SHALL BE FLASHED.			
R. IF WATER PRESSURE EXCEEDS 80 PSI, A WATER PRESSURE REDUCING VALVE SHALL BE INSTALLED IN WATER PIPING AT CONNECTION TO MAIN.			
S. PROVIDE DIELECTRIC FITTINGS BETWEEN DISSIMILAR METALS.			
T. PIPE BACKFLOW PREVENTER DRAINS TO FLOOR DRAIN OR OTHERAPPROVED INDIRECT WASTE SOURCE.			
U. PROVIDE ACCESS DOORS/PANELS FOR SERVICE AND ACCESS TO ALL VALVES AND OTHER SYSTEM COMPONENTS ENCLOSED IN WALLS AND CEILINGS. ACCESS DOORS SHALL BE FURNISHED BY THIS CONTRACTOR, INSTALLED BY THE GENERAL CONTRACTOR.			
V. ALL FIXTURES REQUIRING VACUUM BREAKERS SHALL BE EQUIPPED WITH INTEGRAL VACUUM BREAKERS.			
W. ANY PENETRATIONS THROUGH FIRE RATED PARTITIONS, FLOORS, OR CEILINGS SHALL BE STEEL SLEEVED AND SEALED WITH 3M BRAND UL RATED FIRE BARRIER CAULK OR APPROVED EQUAL.			
X. WHEN THE WATER PIPING SYSTEM IS COMPLETE, THOROUGHLY FLUSH ALL DIRT, SEDIMENT, SOLDER, ETC., OUT OF THE SYSTEM, REMOVING ALL STRAINERS, VALVE STEM SEATS, ETC., REQUIRED TO ACCOMPLISH THE FLUSHING.			
Y. AT ALL INDIRECT WASTE DRAINS, MAINTAIN AIR GAP AS REQUIRED BY CODE.			
Z. INSTALL SLEEVES FOR ALL PIPES WHICH PASS THROUGH WALLS, FLOORS,AND CEILINGS. WHERE PIPES ARE TO BE INSULATED, THE SLEEVE SHALL BE LARGE ENOUGH TO ACCOMMODATE INSULATION. SLEEVES SHALL BE FLUSH WITH FINISHED SURFACES AT BOTH ENDS. ON FINISHED SURFACES IN EXPOSED AREAS PROVIDE ESCUTCHEONS COMPATIBLE WITH FINISH.			
AA. PROVIDE WATER HAMMER ARRESTERS ON SUPPLY PIPING TO ALL FLUSHOMETER VALVES AND QUICK-CLOSING VALVES.			
AB. UNLESS OTHERWISE INDICATED, TRAPS SEALS AT ALL FLOOR DRAINS SHALL BE MAINTAINED BY AN APPROVED TRAP PRIMING DEVICE.			
AC. MAINTAIN ALL REQUIRED AND RECOMMENDED CLEARANCES FOR ALL PLUMBING SYSTEM COMPONENTS AND EQUIPMENT.			
AD. MAINTAIN MINIMUM 10'-'-0" CLEARANCE BETWEEN ALL PLUMBING V.T.R.S AND ALL OUTDOOR AIR INTAKES. OFFSET VENT STACKS AND STACK VENTS IF AND AS REQUIRED BELOW ROOF TO MAINTAIN SUCH CLEARANCE WHETHER OR NOT SUCH OFFSET IS INDICATED ON THE DRAWINGS. PROVIDE ALL REQUIRED SEISMIC SUPPORTS.			
2. INSTALLATION			
2.01 GENERAL			
A. ALL WORK WHICH REQUIRES DISRUPTION OF THE ROOFING SHALL BE DONE BY A CONTRACTOR CERTIFIED BY THE ROOFING MANUFACTURER AS REQUIRED TO MAINTAIN ANY EXISTING ROOF WARRANTIES.			
B. EXTERIOR INSTALLATIONS TO BE WEATHER PROOF IN ALL RESPECTS.			
C. EXTERIOR MATERIALS AND EQUIPMENT SHALL BE PAINTED TO PREVENT CORROSION, COLOR PER ARCHITECT.			
D. COORDINATE THE PLUMBING WORK WITH ALL OTHER AFFECTED WORK AND THE CONSTRUCTION SCHEDULE.			
E. REAM PIPE AND TUBE ENDS. REMOVE BURRS. BEVEL PLAIN AND FERROUS END PIPE.			
F. REMOVE SCALE AND FOREIGN MATERIAL, FROM INSIDE AND OUTSIDE, BEFORE ASSEMBLY.			
G. PREPARE PIPING CONNECTIONS TO EQUIPMENT WITH FLANGES AND UNIONS.			
H. COORDINATION WITH THE WORK OF OTHER TRADES IS REQUIRED. PROVIDE OFFSETS IN PIPING SYSTEMS OR MINOR DEVIATIONS TO THE INDICATED PIPE ROUTING IN ORDER TO COORDINATE THE PLUMBING WORK WITH THE WORK OF ALL OTHER TRADES AND THE GENERAL BUILDING CONDITIONS.			
I. NO DOMESTIC WATER PIPING SHALL BE INSTALLED IN UNHEATED SPACES.			
J. PRIOR TO DISCONNECTING AND CONNECTING NEW WORK TO EXISTING SYSTEMS, THE PLUMBING CONTRACTOR SHALL NOTIFY THE PROPERTY MANAGER AND OFFER A PROPOSED SCHEDULE OF WORK. ESB WILL AUTHORIZE CONNECTIONS AND COORDINATE NECESSARY SHUT DOWNS AND DRAIN DOWNS AS REQUIRED. SHUT DOWNS AND DRAIN DOWNS MAY BE PERFORMED BY THE PLUMBING CONTRACTOR ONLY AFTER RECEIVING ESB AUTHORIZATION, AND SHOULD BE PERFORMED UNDER SUPERVISION OF ESB PERSONNEL. THREE (3) DAYS ADVANCE NOTICE TO THE PROPERTY MANAGER IS REQUIRED.			
K. THE PLUMBING CONTRACTOR IS ADVISED THAT DUE TO THE NATURE OF THE OPERATIONS AND TENANT REQUIREMENTS, CONNECTIONS TO EXISTING SYSTEMS MAY HAVE TO BE MADE AFTER REGULAR WORKING HOURS. THE PROPERTY MANAGER WILL ADVISE THE PLUMBING CONTRACTOR OF THE TIME CONSTRAINTS UPON RECEIPT AND APPROVAL OF THE PLUMBING CONTRACTOR'S REQUEST FOR SHUT DOWN AND CONNECTION TO EXISTING SYSTEMS.			
L. WHEN CONNECTING TO EXISTING STACKS AND RISERS, PROVISION IS TO BE MADE FOR FUTURE CONNECTIONS BY PROVIDING CAPPED AND VALVED OUTLETS ON DOMESTIC WATER RISERS AND PLUGGED OUTLETS ON THE SANITARY AND VENT STACKS.			
2.02 ABOVE GRADE			
A. INSTALL PLUMBING PIPING IN ACCORDANCE WITH RECOGNIZED INDUSTRY PRACTICES TO ENSURE THAT PIPING COMPLIES WITH REQUIREMENTS AND SERVES INTENDED PURPOSES.			
B. ROUTE PIPING IN AN ORDERLY MANNER, PLUMB AND PARALLEL TO BUILDING STRUCTURE. MAINTAIN GRADIENT, SLOPE PIPING AND ARRANGE SYSTEMS TO DRAIN. IN DOMESTIC WATER SYSTEMS, PROVIDE DRAIN VALVES AT MAIN SHUT-OFF VALVES AND ALL LOW POINTS IN PIPING.			
C. USE EXISTING CONNECTIONS AT MAINS WHERE AVAILABLE FOR NEW BRANCH PIPING. LOCATE ALL RISERS AND PIPING BEFORE CONSTRUCTION COMMENCES AND TAKE CARE NOT TO DAMAGE SAME. ANY DAMAGE OCCURRING TO THE EXISTING PIPING WILL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.			
2.03 INSULATION (PIPE AND FITTINGS)			
A. PIPING			
COVER ALL HOT WATER PIPE WITH 1" THICK FOR PIPE SIZE UP TO 1¼" AND 1½" THICK FOR PIPE SIZE 1½" AND GREATER WITH MANVILLE MICRO-LOK AP-T PLUS FIBERGLASS INSULATION. COVER ALL COLD WATER PIPE WITH ½" THICK FOR PIPE SIZE UP TO 1¼" AND 1" THICK FOR PIPE SIZE 1½" AND GREATER WITH 1" MANVILLE MICRO-LOK AP-T PLUS FIBERGLASS INSULATION. FITTINGS AND VALVES SHALL BE INSULATED. INSTALL ALL INSULATION AS PER MANUFACTURERS RECOMMENDATIONS. ALL INSULATION MATERIAL SHALL COMPLY WITH THE 2018 INTERNATIONAL BUILDING CODE REQUIREMENT OF A FLAME SPREAD RATING NOT TO EXCEED 25 AND A SMOKE DEVELOPED RATING NOT TO EXCEED 50. ALL PIPE INSULATION SHALL COMPLY WITH 2018 VIRGINIA ENERGY CONSERVATION CODE.			
3. TESTING			
A. AT THE COMPLETION OF THE PLUMBING WORK, COMPLETELY TEST THE ENTIRE INSTALLATION OF ALL SYSTEMS FOR PROPER OPERATION AND COMPLIANCE WITH APPLICABLE CODES AND LOCAL REQUIREMENTS. CORRECT ALL DEFICIENCIES FOUND.			
B. TESTING OF THE INSTALLED SYSTEMS SHALL BE MADE BY THE CONTRACTOR IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER.			
C. THE CONTRACTOR SHALL NOT COVER UP OR PERMANENTLY CONCEAL PIPING, DEVICES OR ANY PORTION OF NEWLY CONSTRUCTED PLUMBING SYSTEM(S) UNTIL SUCH SYSTEM, OR PORTION OF THE SYSTEM, HAS BEEN TESTED IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER AND INSPECTED BY THE LOCAL INSPECTOR AND APPROVED IN WRITING, EXCEPT PIPING PASSING THROUGH FLOORS, WALLS, PARTITIONS, OR BEAMS, FOR DISTANCES EQUAL TO THE THICKNESS OF SUCH FLOOR, WALL, PARTITION OR BEAM.			
D. THIS CONTRACTOR SHALL NOTIFY THE VARIOUS DEPARTMENTS, BUREAUS AND INDIVIDUALS AT LEAST TWO WEEKS IN ADVANCE OF THE TIME THAT THE TESTS ARE TO BE CONDUCTED.			
E. ALL DEFECTIVE PARTS SHALL BE REPLACED OR CORRECTED BY THIS CONTRACTOR AND AN EXTRA TEST OR TESTS SHALL BE MADE UNTIL THE OPERATION IS SATISFACTORY. ALL ARRANGEMENTS AND EXPENSES NECESSARY TO CONDUCT ALL TESTS REQUIRED BY THESE SPECIFICATIONS AND THE VARIOUS AGENCIES HAVING JURISDICTION OVER THE WORK INSTALLED UNDER THIS CONTRACT SHALL BE MADE BY THIS CONTRACTOR. NO EXTRA COMPENSATION WILL BE ALLOWED FOR THESE TESTS, THE COST THEREOF BEING INCLUDED IN THE LUMP SUM BID FOR THIS CONTRACT.			
F. WHERE ANY EVIDENCE OF STOPPAGE IS FOUND IN PIPING OR EQUIPMENT, THIS CONTRACTOR SHALL DISCONNECT, CLEAN, REPAIR AND RECONNECT ALL OBSTRUCTED PIPING OR EQUIPMENT AND SHALL ALSO PAY FOR ALL NECESSARY CUTTING AND REPAIRS TO ADJOINING WORK.			
G. ALL PIPING AND EQUIPMENT SHALL BE THOROUGHLY CLEANED INSIDE AND OUT, OF DIRT, CUTTINGS, OILS AND OTHER FOREIGN SUBSTANCES AND SHALL BE LEFT CLEAN.			
H. ALL REQUIRED TESTS SHALL BE WITNESSED BY LOCAL AUTHORITIES AND THE OWNER'S REPRESENTATIVE.			
I. ALL EQUIPMENT WILL BE FACTORY TESTED.			
J. CONTRACTOR SHALL IDENTIFY TO THE OWNER'S REPRESENTATIVE ANY LEAKS OR DAMAGE THAT OCCURS AS A RESULT OF SYSTEM TESTING. CONTRACTOR SHALL TAKE NECESSARY PRECAUTIONS TO LIMIT ANY POTENTIAL DAMAGE. CORRECTIVE ACTION REQUIRED AS A RESULT OF TESTING SHALL BE PERFORMED IMMEDIATELY AND AT THE CONTRACTOR'S EXPENSE.			
K. REPORT IN WRITING TO AUTHORITIES HAVING JURISDICTION, THE ARCHITECT AND THE OWNER THE RESULTS OF ALL TESTING.			
L. TESTING REQUIREMENTS			
a. TEST ALL DOMESTIC WATER PIPING HYDROSTATICALLY TO 125 PSIG			
b. HYDROSTATIC TEST PRESSURES SHALL REMAIN CONSTANT WITH NO VARIATION FOR 120 MINUTES.			
c. TESTS SHALL BE WITNESSED BY THE BUILDING ENGINEER.			
d. THE PLUMBING CONTRACTOR WILL BE HELD RESPONSIBLE FOR ALL DAMAGE DUE TO TEST FAILURES AND LEAKAGE IN THE TEST AREA AND ADJACENT TENANT OR ESB SPACES.			
M. REFILL ENTIRE POTABLE HOT AND COLD WATER SUPPLY SYSTEM WITH CHLORINE SOLUTION (HTH OLIN CHEMICAL CORP.) AT A STRENGTH TO MEET STANDARDS OF THE DEPARTMENT OF HEALTH, AND FOR A PERIOD OF RETENTION AS STIPULATED.			
N. THOROUGHLY FLUSH PIPING SYSTEM WITH FRESH WATER IMMEDIATELY PRIOR TO FINAL ACCEPTANCE.			
O. INSPECTION & TESTING SHALL BE AS PER 2018 VIRGINIA PLUMBING CODE SECTION 312.			
4. WARRANTY			
A. EQUIPMENT, MATERIALS AND WORKMANSHIP FURNISHED UNDER THIS CONTRACT SHALL BE GUARANTEED BY THE CONTRACTOR FOR A PERIOD OF ONE YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THE WORK BY THE OWNER. THE CONTRACTOR SHALL KEEP THE WORK IN GOOD REPAIR FOR ONE YEAR AFTER THE DATE OF FINAL APPROVAL. THE CONTRACTOR SHALL, AT HIS OWN EXPENSE, PROMPTLY CORRECT AND REPAIR ANY AND ALL BREAKS, FAILURES OR WEAR DUE TO FAULTY MATERIALS, WORKMANSHIP OR EQUIPMENT. ALL SETTLEMENTS OF SURFACES THAT MAY OCCUR WITHIN THAT PERIOD SHALL ALSO BE PROMPTLY REPAIRED.			

ALOHA HOLA AT RAILYARD

**NY ENGINEERS**  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 4967A,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

5. Revision 4 : 01.08.25
4. Revision 3 : 06.07.24
3. Revision 2 : 04.24.24
2. Revision 1 : 03.05.24
1. Permit set : 01.31.24
PREPARED BY : NYE
REVIEWED BY : NYE
PROJECT NUMBER OS230050.00
DRAWING TITLE PLUMBING NOTES AND SPECIFICATIONS
DRAWING NUMBER  P002
SHEET 2 OF 7





- GENERAL NOTES**
1. PROVIDE TRAP PRIMER FOR ALL FLOOR DRAINS AS PER THE LOCAL JURISDICTION.
  2. CONTRACTOR TO FIELD VERIFY THE EXISTING SANITARY PIPING SIZE, LOCATION & INVERT ON SITE.
  3. CONTRACTOR TO COORDINATE WITH KITCHEN CONSULTANT/ARCHITECT FOR FINAL EQUIPMENT SELECTION.
  4. CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SLAB PENETRATION AS PER STRUCTURAL REQUIREMENT.


- WASTE AND VENT PLAN KEY NOTES**
1. CONNECT NEW 4" SANITARY PIPING TO EXISTING 4" SANITARY PIPE. CONTRACTOR TO FIELD VERIFY EXACT SIZE, LOCATION AND INVERT ON SITE.
  2. ROUTE INDIRECT WASTE FROM 3 COMPARTMENT SINK TO FLOOR SINK WITH APPROVED AIR GAP.
  3. GREASE TRAP SCHIER GB-75 OR EQUIVALENT SHALL BE PROVIDED. CONTRACTOR SHALL COORDINATE FINAL LOCATION WITH MANUFACTURER. THE GREASE MANAGEMENT EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH ALL APPLICABLE CODES AND SHALL BE INSTALLED WITH STRICT ADHERENCE TO THE MANUFACTURER'S INSTALLATION INSTRUCTIONS, REQUIREMENTS, AND RECOMMENDATIONS.

**NY ENGINEERS**  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25	△
4. Revision 3 : 06.07.24	△
3. Revision 2 : 04.24.24	△
2. Revision 1 : 03.05.24	
1. Permit set : 01.31.24	
PREPARED BY : NYE	
REVIEWED BY : NYE	
PROJECT NUMBER OS230050.00	
DRAWING TITLE PLUMBING WASTE & VENT FLOOR PLAN	
DRAWING NUMBER  P101	
SHEET	3 OF 7






- GENERAL NOTES**
- CW/HW/HWR PIPING TO BE PROVIDED WITH INSULATION AS PER VIRGINIA ENERGY CONSERVATION CODE 2018 (REFER SHEET P001).
  - PROVIDE BRANCH PRV IF PRESSURE EXCEEDS 80 PSI.
  - CONTRACTOR TO COORDINATE WITH KITCHEN CONSULTANT/ARCHITECT FOR FINAL EQUIPMENT SELECTION.
  - CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SLAB PENETRATION AS PER STRUCTURAL REQUIREMENT.
  - PROVIDE ACCESS PANELS FOR WATER HAMMER ARRESTOR, SHUT-OFF VALVES AS REQUIRED.
  - PROVIDE TRAP PRIMER FOR ALL FLOOR DRAINS AS PER THE LOCAL JURISDICTION.
  - CONTRACTOR TO PROVIDE ASSE1056 APPROVED BFP FOR WATER CONNECTION AT 3 COMP SINK IF CHEMICAL DISPENSER USED.

- WATER AND GAS PLAN KEY NOTES**
- CONNECT NEW 1-1/4" WATER PIPING TO EXISTING WATER PIPING WITH NEW 1-1/4" WATER SUB-METER AND BFP. CONTRACTOR TO FIELD VERIFY EXACT SIZE AND LOCATION OF THE EXISTING PIPING ON SITE. PROVIDE WATER SUB-METER IN CEILING WITH REMOTE READER AT THE GIVEN LOCATION.
  - ROVIDE ASSE 1070 APPROVED THERMOSTATIC MIXING VALVE FOR ALL HAND SINKS AND PUBLIC LAVATORIES.
  - NEW 1-1/4" RPZ WATTS MODEL 007M20T WITH QUARTER TURN (QT) VALVE. INSTALL BFP ASSEMBLY AS PER LOCAL REGULATIONS AND MANUFACTURER'S INSTRUCTIONS. CONTRACTOR TO FIELD VERIFY AND PROVIDE NEW IF NOT EXISTING.
  - NO TAP-OFF TO BE TAKEN BEFORE BFP.
  - PROVIDE ASSE 1022 APPROVED DUAL CHECK WITH ATMOSPHERIC VENT SECONDARY BFP FOR ISODA FOUNTAIN.
  - REFER RISER DIAGRAM FOR WATER PIPE SIZING.
  - CONTRACTOR TO PROVIDE COLD WATER CONNECTION FOR CLEANING PURPOSE, IF REQUIRED.















Property of NY Engineers



- ROOF GAS PLAN KEY NOTE
- 1 CONNECT NEW 1-1/4" NEW GAS PIPING TO EXISTING GAS PIPING. CONTRACTOR TO FIELD VERIFY EXACT PRESSURE, SIZE AND LOCATION OF GAS METER AND COORDINATE WITH LANDLORD/UTILITY COMPANY.
- 2 PROVIDE SENSUS VENTED REGULATOR WITH IRV SET DISCHARGE AT 8"-10" W.C. (PIPE DISCHARGE MINIMUM 10' AWAY FROM FRESH AIR INTAKE WITH RETURN BEND ON DISCHARGE).





NY ENGINEERS  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25  
4. Revision 3 : 06.07.24  
3. Revision 2 : 04.24.24  
2. Revision 1 : 03.05.24  
1. Permit set : 01.31.24  
PREPARED BY : NYE  
REVIEWED BY : NYE  
PROJECT NUMBER  
OS230050.00  
DRAWING TITLE  
PLUMBING DETAILS  
DRAWING NUMBER  
P501  
SHEET 6 OF 7



PLUMBING FIXTURE SCHEDULE									
LEGEND	PLUMBING FIXTURE	CONNECTION SIZE - INCHES							REMARKS
		TRAP	SOIL/WASTE	VENT	COLD WATER	HOT WATER	FILTER WATER	THERMOSTATIC MIXING VALVE	
WC-1	WATER CLOSET	-	4"	2"	¾"	-	-	-	FLUSH TANK
LAV-1	LAVATORY	2"	2"	1½"	½"	½"	-	PROVIDE	P-TRAP
2	HAND SINK	2"	2"	1½"	½"	½"	-	PROVIDE	P-TRAP
14	MOP SINK	3"	3"	2"	¾"	¾"	-	PROVIDE	P-TRAP
15	3-COMPARTMENT SINK	-	3"	2"	¾"	¾"	-	PROVIDE	I.W. FROM 3CS SPILLS INTO FLOOR SINK
19	SODA FOUNTAIN	-	1"	2"	½"	-	-	-	I.W. FROM SODA FOUNTAIN SPILLS INTO FLOOR SINK
FS-1	FLOOR SINK	3"	3"	2"	-	-	-	-	P-TRAP
FD-1	FLOOR DRAIN	3",4"	3",4"	2"	-	-	-	-	P-TRAP

NOTE: CONTRACTOR TO COORDINATE WITH ARCHITECTURAL DRAWINGS FOR ALL PLUMBING FIXTURES SPECIFICATIONS AND MOUNTING HEIGHT INSTALLATION.

HOT WATER HEATER							
TAG No.	MAX INPUT (MBH)	FLOW (GPM)	FIXTURES SERVING	QUANTITY	TYPE	THERMAL EFFICIENCY %	REMARKS
WH-1	299	6.5@90°F	3-COMPARTMENT SINK, MOP SINK, HAND SINK, LAVATORY	1	GAS TANKLESS TYPE WATER HEATER	97	NORITZ NCC300DV -DIMENSIONS 18.9"LX32.7"HX14.2"W

RECIRCULATING PUMP SCHEDULE						
MARK	SERVICE	QTY	GPM	TOTAL HEAD FT.	MOTOR HP	MANUFACTURER & REMARKS
RCP-1	HW RECIRCULATION	1	2	10	0.115	GRUNDFOS UP 15-18 B5 W/AQUASTAT + TIMER

EXPANSION TANK SCHEDULE					
ITEM	SERVICE	QTY	GALLONS	MAKE	REMARKS
EXPANSION TANK (ET-1)	HOT WATER	1	2	AMTROL ST-5	DIMENSIONS- 13"(H)x8"(DIA.) SHIPPING WEIGHT- 5 LBS

GREASE TRAP SIZING CALCULATION								
FIXTURE	QUANTITY	DIMENSIONS			VOLUME		PERCENTAGE USAGE(%)	ACTUAL USAGE (GALLONS)
		LENGTH(IN)	WIDTH(IN)	DEPTH(IN)	CUBIC INCHES	GALLONS		
3 COMP. SINK	1	21	18	14	15876	68.7	0.75	51.5
MOP SINK	1	18	20	8	2880	12.5	0.75	9.4
HAND SINK	2	11	11	5	1210	5.2	0.75	3.9
FLOOR DRAIN	2					0.0	1	2.5
FLOOR SINK	1					0.0	1	2.5
TOTAL:								73.8
PROPOSED GREASE TRAP								GB-75
NOTE: EMERGENCY FLOOR DRAINS NOT CONSIDERED IN THE CALCULATION AS THEY WILL MOSTLY NOT BE IN OPERATION DURING ACTIVE KITCHEN USAGE.								

GREASE TRAP SCHEDULE (GI-1)				
QTY	FLOW RATE (GPM)	GREASE CAPACITY (LBS)	MAKE	REMARKS
1	75	861	SCHIER GB-75	DIMENSIONS-39-3/4"(H)x47"(L)x33"(W) SHIPPING WEIGHT- 190 LBS 90-DAY PUMPOUT CYCLE

THE CONTRACTOR SHALL PROVIDE ALL REQUIRED ACCESSORIES FOR SATISFACTORILY WORKING AS PER SITE CONDITIONS. PROVIDE OPTIONAL PP3 PUMPOUT PORT KIT TO ELIMINATE THE NEED OF UNSANITARY EQUIPMENT IN BUILDING IF REQUIRED.


GREASE PRODUCTION CALCULATIONS				
MEALS SERVED PER DAY	GREASE PRODUCTION VALUE	PUMP OUT DAYS	PRODUCED GREASE	REMARK
100	0.035 LBS PER SERVING (CHINESE: HIGH / NO FLATWARE)	90	100 * 0.035 * 90 = 315 LBS OF FOG	PROVIDED GREASE INTERCEPTOR OF CAPACITY 861 LBS

GAS LOAD SUMMARY			
EQUIPMENT TAG	QTY.	SIZE	MBH LOAD
RTU-1(E)	1	3/4"	180
KSF-1(N)	1	3/4"	211.7
GAS FRYERS	3	3/4"	450
GAS RANGE	1	3/4"	128
60" GRIDDLE	1	3/4"	135
WATER HEATERS	1	1-1/4"	299
TOTAL GAS LOAD(MBH)			1403.7


GAS PIPE SIZING PER VIRGINIA FUEL GAS CODE (2018)	
HIGH PRESSURE SYSTEM (AS PER VIRGINIA FGC TABLE 402.4(5)) INLET PRESSURE - 2.0 PSI PRESSURE DROP - 1.0 PSI LONGEST LENGTH - 170'(APPROX)	
LOW PRESSURE SYSTEM (AS PER VIRGINIA FGC TABLE 402.4(2)) INLET PRESSURE - <2 PSI PRESSURE DROP - 0.5 PSI LONGEST LENGTH - 50'(APPROX)	

NATURAL GAS PIPING SYSTEM  
PROVIDE A COMPLETE GAS PIPING SYSTEM TO SERVE GAS EQUIPMENT FURNISHED BY OTHERS, AS NOTED ON THE DRAWINGS. PROVIDE EITHER THREADED STEEL OR MALLEABLE IRON PIPE WITH MALLEABLE FITTINGS OR WELDED STEEL. PROVIDE ALL UNIONS, SHUT-OFF VALVES AND DIRT LEGS REQUIRED BY NFPA-54 AND GOVERNING LOCAL CODES AND AT EACH GAS APPLIANCE CONNECTION. PROVIDE ALL TESTS, METERS, INSPECTIONS, HANGERS AND EQUIPMENT CONNECTIONS REQUIRED FOR A COMPLETE AND OPERATING SYSTEM.


- NOTES:
1. GAS PIPING TO BE SCHEDULE 40 STEEL PIPE W/125 CAST IRON SCREWD FITTINGS
  2. GAS SYSTEM TO BE INSTALLED BY QUALIFIED LICENSED CONTRACTOR.
  3. VERIFY ALL EQUIPMENT BTU'S PRIOR TO INSTALLATION; ADJUST PIPE SIZE ACCORDING VIRGINIA FUEL GAS CODE, 2018, TABLES 402.4(2) & 402.4(5).



1 PLUMBING RISER - SANITARY & VENT  
NTS.



2 PLUMBING RISER - DOMESTIC WATER  
NTS.



3 PLUMBING RISER - GAS  
NTS.

**NY ENGINEERS**  
NEARBY ENGINEERS  
382 NE 191ST STREET SUITE 49674,  
MIAMI, FL 33179  
PH-914.287.3455  
WWW.NY-ENGINEERS.COM

ALOHA HOLA AT RAILYARD

5. Revision 4 : 01.08.25	4
4. Revision 3 : 06.07.24	3
3. Revision 2 : 04.24.24	2
2. Revision 1 : 03.05.24	1
1. Permit set : 01.31.24	
PREPARED BY : NYE	
REVIEWED BY : NYE	
PROJECT NUMBER OS230050.00	
DRAWING TITLE PLUMBING SCHEDULES & RISERS	
DRAWING NUMBER	
P601	
SHEET 7 OF 7	