

MECHANICAL SYMBOLS LIST		
AC-1	TXF-1	EQUIPMENT SYMBOL
<b>AIR DEVICES</b>		
		CEILING DIFFUSER SUPPLY
<b>DUCT ACCESSORIES</b>		
	BACKDRAFT DAMPER	
	VOLUME DAMPER W/ ACCESS DOOR	
<b>MECHANICAL ABBREVIATIONS</b>		
BD	BACKDRAFT DAMPER	
RTU	ROOF TOP UNIT	
VD	VOLUME DAMPER	
CFM	CUBIC FEET PER MINUTE	
COP	COEFFICIENT OF PERFORMANCE	
EA	EXHAUST AIR	
FC	FLEXIBLE CONNECTION	
CDE	CEILING DIFFUSER EXHAUST	
OA	OUTSIDE AIR	
RA	RETURN AIR	
SA	SUPPLY AIR	
SP	STATIC PRESSURE	
CDS	CEILING DIFFUSER SUPPLY	
CDR	CEILING DIFFUSER RETURN	
MAU	MAKE-UP AIR UNIT	
KEF	KITCHEN EXHAUST FAN	
TEF	TOILET EXHAUST FAN	
SG	SUPPLY GRILLE	
WMS	WIRE MESH SCREEN	
IEER	INTEGRATED ENERGY EFFICIENCY RATIO	
<b>GENERAL ABBREVIATIONS</b>		
DN	DOWN	
EFF	EFFICIENCY	
UP	UP	
EQUIP	EQUIPMENT	
EXH	EXHAUST	
(E)	EXISTING	
FPM	FEET PER MINUTE	
FT	FEET	
HP	HORSEPOWER	
Hz	HERTZ	
IN	INCHES	
KW	KILOWATT	
LB	POUND	
MAX	MAXIMUM	
MBH	THOUSAND BRITISH THERMAL UNITS PER HOUR	
MCA	MINIMUM CIRCUIT AMPS	
MECH	MECHANICAL	
MFR	MANUFACTURER	
MIN	MINIMUM	
MOPC	MAXIMUM OVERCURRENT PROTECTION	
N/A	NOT APPLICABLE	
NTS	NOT TO SCALE	
PH	PHASE	
PLBG	PLUMBING	
RPM	REVOLUTIONS PER MINUTE	
SPEC	SPECIFICATION	
SF	SQUARE FEET	
TEMP	TEMPERATURE	
TON	TONS OF REFRIGERATION	
VEL	VELOCITY	
VFD	VARIABLE FREQUENCY DRIVE	
WB	WET BULB TEMPERATURE	
<b>CODE COMPLIANCE</b>		
<p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTHING IN THESE DRAWINGS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p>		
A.	2024 OHIO ENERGY CODE (BASE CODE - IECC 2021)	
B.	2024 OHIO BUILDING CODE (BASE CODE - IBC 2021)	
C.	2024 OHIO MECHANICAL CODE (BASE CODE - IMC 2021)	
D.	2024 OHIO PLUMBING CODE (BASE CODE - IPC 2021)	
E.	2021 OHIO FUEL GAS CODE (BASE CODE - IFGC 2021)	

**GENERAL NOTES**

- CONTRACTOR SHALL SURVEY THE AREA OF THIS WORK BEFORE SUBMITTING A BID AND SHALL BE RESPONSIBLE FOR NOTIFYING THE ARCHITECT OF ANY CONDITIONS WHICH WOULD PREVENT THE INSTALLATION OF THE WORK AS SHOWN ON DRAWINGS.
- ALL APPLICABLE CODES, LAWS AND REGULATIONS GOVERNING OR RELATING TO ANY PORTION OF THIS WORK ARE HEREBY INCORPORATED INTO AND MADE A PART OF THESE SPECIFICATIONS, AND THEIR PROVISIONS SHALL BE CARRIED OUT BY THE CONTRACTOR WHO SHALL INFORM THE OWNER, PRIOR TO SUBMITTING A PROPOSAL, OF ANY WORK OR MATERIALS WHICH VIOLATE ANY OF THE ABOVE LAWS AND REGULATIONS. ANY WORK DONE BY THE CONTRACTOR CAUSING SUCH VIOLATION SHALL BE CORRECTED BY THE CONTRACTOR.
- BEFORE PROCEEDING WITH ANY WORK IN OCCUPIED OR USED AREAS, THE CONTRACTOR SHALL APPLY TO OWNER FOR PERMISSION TO ENTER SUCH AREAS. THE CONTRACTOR IS OBLIGED TO PERFORM HIS WORK ONLY AT THE TIMES DESIGNATED BY OWNER. THERE WILL BE NO ADDITIONAL COMPENSATION FOR THE WORK PERFORMED AFTER HOURS OR ON OFF-DAYS WITHOUT PRIOR WRITTEN APPROVAL.
- THE WORK IN THE BUILDING SHALL BE DONE WHEN AND AS DIRECTED, AND IN A MANNER SATISFACTORY TO THE OWNER. THE WORK SHALL BE PERFORMED SO AS TO CAUSE THE LEAST POSSIBLE INCONVENIENCE AND DISTURBANCE TO THE PRESENT OCCUPANTS.
- THE CONTRACTOR'S PROPOSAL FOR ALL WORK SHALL BE PREDICATED ON THE PERFORMANCE OF THE WORK DURING REGULAR WORKING HOURS. WHEN SO DIRECTED, HOWEVER, THE CONTRACTOR SHALL INSTALL WORK IN OVERTIME AND THE ADDITIONAL COST TO BE CHARGED THEREFORE SHALL BE ONLY THE "PREMIUM" PORTION OF THE WAGES PAID.
- CONTRACTOR SHALL ASCERTAIN THE APPROPRIATE METHOD FOR BRINGING EQUIPMENT INTO AND OUT OF THE BUILDING TO POSITION UNIT IN LOCATION SHIPPED ON THE PLANS WHERE NECESSARY. EQUIPMENT SHALL BE SHIPPED FROM MANUFACTURER IN SECTIONS OF SIZE SUITABLE FOR MOVING THROUGH RESTRICTIVE SPACES. COORDINATE WITH BUILDING OWNER APPROPRIATE TIMES OF DAY SUCH EQUIPMENT MAY BE MOVED THROUGH ALL AREAS.
- DISCONNECT, REMOVE AND/OR RELOCATE EXISTING MATERIAL, EQUIPMENT AND OTHER WORK AS NOTED OR REQUIRED FOR PROPER INSTALLATION OF NEW SYSTEM.
- WHERE PENETRATIONS THROUGH FIRE RATED WALLS ARE NOT FIRE PROOFED THIS CONTRACTOR SHALL BE RESPONSIBLE TO SEAL SAME TO MAINTAIN THE RATED INTEGRITY.
- CONNECT NEW WORK TO EXISTING WORK IN NEAT AND APPROVED MANNER. RESTORE EXISTING WORK DISTURBED WHILE INSTALLING NEW WORK TO ACCEPTABLE CONDITION AS DETERMINED BY ARCHITECT.
- PLAN INSTALLATION OF NEW WORK AND CONNECTIONS TO EXISTING WORK TO INSURE MINIMUM INTERFERENCE WITH REGULAR OPERATION OF EXISTING FACILITIES. ALL SYSTEM SHUTDOWNS AFFECTING OTHER AREAS SHALL BE COORDINATED WITH BUILDING OWNER. INSTALL ISOLATION VALVES AT POINT OF CONNECTION TO THE EXISTING PIPING. PROVIDE TEMPORARY DUCT CAPS AND/OR CONNECTIONS TO MINIMIZE SHUTDOWN TIME.
- SUPPORT ALL DUCTWORK AND PIPING FROM BUILDING STRUCTURE AND/OR FRAMING IN AN APPROVED MANNER. WHERE OVERHEAD CONSTRUCTION DOES NOT PERMIT FASTENING OR SUPPORTS FOR EQUIPMENT, FURNISH ADDITIONAL FRAMING. INSERTS SHALL BE STEEL, SLOTTED TYPE AND FACTORY PAINTED. MULTI-ROD SHALL BE SIMILAR TO FEE & MASON SERIES 9000 WITH END CAPS AND CLOSURE STRIPS. MAXIMUMLOADING INCLUDING PIPES, DUCTWORK CONTENTS AND COVERING SHALL NOT EXCEED 75% OF RATED INSERT CAPABILITY WHEN SUPPORTING FROM BUILDING USE BEAM CLAMPS IN APPROVED MANNER.
- PROVIDE ALL NECESSARY FLASHING AND COUNTER FLASHING TO MAINTAIN THE WATERPROOFING INTEGRITY OF THIS BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF PIPES, DUCTS, LOUVERS, CONDUIT, AND EQUIPMENT. PROVIDE EQUIPMENT CURBS AND DUNNAGE STEEL AS REQUIRED.
- SEAL OPENINGS AROUND DUCTS AND PIPING THROUGH PARTITIONS, WALLS, AND FLOORS WITH MINERAL WOOL OR OTHER NONCOMBUSTIBLE MATERIAL (FIBERGLASS INSULATION IS NOT ACCEPTABLE).
- INSTALL WORK SO AS TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE AND REPAIR. MINOR DEVIATIONS FROM DRAWINGS MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST SHALL NOT BE MADE WITHOUT APPROVAL.
- ACCESS DOORS ARE REQUIRED FOR ALL BUILDING SERVICE VALVES THAT RUN THROUGH THE SPACE, AND ACCESS DOOR SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL. COORDINATE ALL LOCATIONS OF ACCESS DOORS WITH THE ARCHITECT.
- REMOVABLE ACCESS TILE AND/OR ACCESS DOOR ARE REQUIRED IN HUNG CEILINGS, SHAFTS AND WALLS FOR ALL VOLUME AND FIRE DAMPERS, AUTOMATIC DAMPERS AND ALL OTHER MECHANICAL EQUIPMENT AND DEVICES. HVAC CONTRACTOR TO FURNISH ACCESS LOCATION REQUIREMENTS TO GENERAL CONTRACTOR. ACCESS TILE IDENTIFICATION: PROVIDE BUTTONS, TABS, AND MARKERS TO IDENTIFY LOCATION OF CONCEALED VALVES, DAMPERS AND EQUIPMENT.
- THE CONTRACTOR SHALL KEEP ALL EQUIPMENT AND MATERIALS, AND ALL PARTS OF THE BUILDING, EXTERIOR SPACES AND ADJACENT STREETS, SIDEWALKS AND PAVEMENTS, FREE FROM MATERIAL AND DEBRIS RESULTING FROM THE EXECUTION OF THIS WORK. EXCESS MATERIALS WILL NOT BE PERMITTED TO ACCUMULATE EITHER ON THE INTERIOR OR THE EXTERIOR.
- UNLESS OTHERWISE SPECIFICALLY SPECIFIED, INCLUDE ALL CUTTING AND PATCHING OF EXISTING FLOORS, WALLS, PARTITIONS AND OTHER MATERIALS IN THE EXISTING BUILDING. THE CONTRACTOR SHALL RESTORE THESE AREAS TO ORIGINAL CONDITION.
- MATERIALS AND WORKMANSHIP, UNLESS OTHERWISE NOTED, SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- ALL EQUIPMENT SHALL BE PROVIDED WITH ONE YEAR WARRANTY PARTS AND LABOR AND FIVE YEARS ON COMPRESSORS. WARRANTY PERIOD BEGINS UPON PROJECT ACCEPTANCE.
- ALL MATERIAL AND EQUIPMENT TO BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR HIS WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF THE SAME WHICH MAY BE DAMAGED, LOST, OR STOLEN WITHOUT ADDITIONAL COST TO THE OWNER.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FAILURE OF ANY DUCTWORK SYSTEM OR EQUIPMENT TO FUNCTION PROPERLY UPON COMPLETION OF HIS WORK UPON SAID SYSTEM OR EQUIPMENT.
- SUBMIT SHOP DRAWING OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES.
- ALL MATERIAL AND EQUIPMENT TO BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- SUBMISSION OF A PROPOSAL SHALL BE CONSTRUED AS EVIDENCE THAT A CAREFUL EXAMINATION OF THE PORTIONS OF THE EXISTING BUILDING, EQUIPMENT, ETC., WHICH AFFECT THIS WORK AND THE ACCESS TO SUCH SPACES, HAS BEEN MADE AND THAT THE CONTRACTOR IS FAMILIAR WITH EXISTING CONDITION AND DIFFICULTIES THAT WILL AFFECT THE EXECUTION OF THE WORK. LATER CLAIMS SHALL NOT BE MADE FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WHICH COULD HAVE BEEN FORESEEN DURING SUCH AN EXAMINATION.
- INSURANCE: IN ACCORDANCE WITH BUILDING REQUIREMENTS THE CONTRACTOR SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND ENGINEER.
- THE FINAL ACCEPTANCE WILL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, BALANCED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATES OF INSPECTION AND APPROVAL.
- SPECIFICATIONS ARE OF SIMPLIFIED FORM AND INCLUDE INCOMPLETE SENTENCES. WORDS OR PHRASES SUCH AS "THE CONTRACTOR SHALL," "SHALL BE," "FURNISH," "PROVIDE," "A," "THE" AND "ALL" HAVE BEEN OMITTED FOR BREVITY.
- WHERE A CONFLICT EXISTS BETWEEN THE DRAWINGS, THE SPECIFICATIONS OR ANY OTHER CONSTRUCTION DOCUMENT, THE ONE WITH THE MOST STRINGENT REQUIREMENT(S) SHALL APPLY. DEFINITIONS:

  - "PROVIDE": TO SUPPLY, INSTALL AND CONNECT UP COMPLETE AND READY FOR SAFE AND REGULAR OPERATION THE PARTICULAR WORK REFERRED TO UNLESS SPECIFICALLY OTHERWISE NOTED.
  - "INSTALL": TO ERECT, MOUNT AND CONNECT COMPLETE WITH RELATED ACCESSORIES.

**SCOPE OF WORK**

**SCOPE OF WORK**

- THE WORK UNDER CONTRACT INCLUDES ALL LABOR, MATERIALS AND APPLIANCES NECESSARY FOR THE FURNISHING, INSTALLING AND TESTING, COMPLETE AND READY FOR SAFE OPERATION OF THE SYSTEMS AS DESCRIBED IN THE SPECIFICATIONS, FLOOR PLAN(S) DESIGN, DETAIL DRAWINGS, NOTES, RFIS, ETC. FOR THIS PROJECT. WORK SHALL BE INSTALLED IN A NEAT, WORKMANLIKE MANNER.
- THE CONTRACTOR SHALL GIVE NECESSARY NOTICE, FILE DRAWINGS AND SPECIFICATIONS WITH THE DEPARTMENT HAVING JURISDICTION, OBTAIN PERMITS OR LICENSES NECESSARY TO CARRY OUT THIS WORK AND PAY ALL FEES THEREFOR. THE CONTRACTOR SHALL ARRANGE FOR INSPECTION AND TESTS OF ANY OR ALL PARTS OF THE WORK IF SO REQUIRED BY AUTHORITIES AND PAY ALL CHARGES FOR SAME. THE CONTRACTOR SHALL PAY ALL COSTS FOR, AND FURNISH TO THE OWNER BEFORE FINAL BILLING, ALL CERTIFICATES NECESSARY AS EVIDENCE THAT THE WORK INSTALLED CONFORMS WITH ALL REGULATIONS WHERE THEY APPLY TO THIS WORK.
- THE CONTRACTOR SHALL FURNISH A WRITTEN GUARANTEE TO REPLACE OR REPAIR PROMPTLY AND ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED FOR ANY WORKMANSHIP AND EQUIPMENT IN WHICH DEFECTS DEVELOP WITHIN ONE YEAR FROM THE DATE OF FINAL CERTIFICATE FOR PAYMENT AND/OR FROM DATE OF ACTUAL USE OF EQUIPMENT OR OCCUPANCY OF SPACES, BY OWNER, INCLUDED UNDER THE VARIOUS PARTS OF THE WORK, WHICHEVER DATE IS EARLIER. THIS WORK SHALL BE DONE AS DIRECTED BY THE OWNER. THIS GUARANTEE SHALL ALSO PROVIDE THAT WHERE DEFECTS OCCUR, THE CONTRACTOR WILL ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED IN REPAIRING AND REPLACING WORK OF OTHER TRADES AFFECTED BY DEFECTS, REPAIRS OR REPLACEMENTS IN EQUIPMENT SUPPLIED BY THE CONTRACTOR.
- PROVIDE VIBRATION ISOLATORS FOR ALL PIPING SUPPORTS CONNECTED TO AND WITHIN 50 FT. OF ISOLATED EQUIPMENT (EXCEPT AT BASE ELBOW SUPPORTS AND ANCHOR POINTS) THROUGHOUT MECHANICAL EQUIPMENT ROOMS. DO THE SAME FOR SUPPORTS OF STEAM MAINS WITHIN 50 FT. OF BOILER OR PRESSURE-REDUCING VALVES.
- PROVIDE VIBRATION ISOLATORS FOR ALL PIPING SUPPORTS OF STEAM MAINS WITHIN 50 FT. OF BOILERS AND PRESSURE-REDUCING VALVES.
- MAINTAIN A MINIMUM 6'-8" CLEARANCE TO THE UNDERSIDE OF PIPES, DUCTS, CONDUITS, SUSPENDED EQUIPMENT, ETC., THROUGHOUT ACCESS ROUTES IN MECHANICAL ROOMS.
- LOCATE ALL TEMPERATURE, PRESSURE, AND FLOW MEASURING DEVICES IN ACCESSIBLE LOCATIONS WITH THE STRAIGHT SECTION OF PIPE OR DUCT UP, AND DOWNSTREAM AS RECOMMENDED BY THE MANUFACTURER FOR GOOD ACCURACY.
- ALL MECHANICAL ROOM DOORS SHALL BE A MINIMUM OF 4'-0" WIDE.
- WHERE BEAMS ARE INDICATED TO BE PENETRATED WITH DUCTWORK OR PIPING, COORDINATE DUCTWORK AND PIPING LAYOUT WITH BEAM OPENING SIZE AND OPENING LOCATIONS. COORDINATION SHALL BE DONE PRIOR TO THE FABRICATION OF DUCTWORK, CUTTING OF PIPING, OR FABRICATION OF BEAMS.
- ALL MISCELLANEOUS STEEL REQUIRED TO ENSURE PROPER INSTALLATION AND AS SHOWN IN THE DETAILS FOR PIPING, DUCTWORK, AND EQUIPMENT (UNLESS OTHERWISE NOTED) SHALL BE FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR.
- PROVIDE ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS WHERE REQUIRED, TO SERVICE DAMPERS, VALVES, SMOKE DETECTORS, AND OTHER CONCEALED MECHANICAL EQUIPMENT. ACCESS PANELS SHALL BE TURNED OVER TO THE GENERAL CONTRACTOR FOR INSTALLATION. ACCESS PANELS SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL.
- MECHANICAL EQUIPMENT, DUCTWORK, AND PIPING SHALL NOT BE SUPPORTED FROM A METAL DECK.
- ALL EQUIPMENT, PIPING, DUCTWORK, ETC., SHALL BE SUPPORTED AS DETAILED, SPECIFIED AND REQUIRED TO PROVIDE A VIBRATION-FREE INSTALLATION.
- ALL DUCTWORK, PIPING, AND EQUIPMENT SUPPORTED FROM STRUCTURAL STEEL SHALL BE COORDINATED WITH THE GENERAL CONTRACTOR. ALL ATTACHMENTS TO STEEL BAR JOISTS, TRUSSES, OR JOIST GIRDERS SHALL BE AT PANEL POINTS. PROVIDE BEAM CLAMPS MEETING MSS STANDARDS. WELDING TO STRUCTURAL MEMBERS SHALL NOT BE PERMITTED. THE USE OF C-CLAMPS SHALL NOT BE PERMITTED.
- ALL ROOF-MOUNTED EQUIPMENT CURBS FOR EQUIPMENT PROVIDED BY THE MECHANICAL CONTRACTOR SHALL BE FURNISHED BY THE MECHANICAL CONTRACTOR AND INSTALLED BY THE GENERAL CONTRACTOR.
- LOCATIONS AND SIZES OF ALL FLOOR, WALL, AND ROOF OPENINGS SHALL BE COORDINATED WITH ALL OTHER TRADES INVOLVED.
- ALL OPENINGS IN FIRE WALLS DUE TO DUCTWORK, PIPING, CONDUIT, ETC., SHALL BE FIRE STOPPED WITH A PRODUCT SIMILAR TO 3M OR APPROVED EQUAL.

**MECHANICAL NOTES**

GENERAL:

- PROVIDE ALL MATERIAL AND EQUIPMENT AND PERFORM ALL LABOR REQUIRED TO INSTALL COMPLETE AND OPERABLE MECHANICAL SYSTEMS AS INDICATED ON THE DRAWINGS, AS SPECIFIED AND AS REQUIRED BY CODE.
- CONTRACT DOCUMENT DRAWINGS FOR MECHANICAL WORK (HVAC, PLUMBING, AND FIRE PROTECTION) ARE DIAGRAMMATIC AND ARE INTENDED TO CONVEY SCOPE AND GENERAL ARRANGEMENT ONLY.
- THE LOCATIONS OF ALL ITEMS SHOWN ON THE DRAWINGS OR CALLED FOR IN THE SPECIFICATIONS THAT ARE NOT FIXED BY DIMENSIONS ARE APPROXIMATE ONLY. THE EXACT LOCATIONS NECESSARY TO SECURE THE BEST CONDITIONS AND RESULTS MUST BE DETERMINED BY THE PROJECT SITE CONDITIONS AND SHALL HAVE THE APPROVAL OF THE ENGINEER BEFORE BEING INSTALLED. DO NOT SCALE DRAWINGS.
- THE LOCATION OF EXISTING UNDERGROUND UTILITIES IS APPROXIMATELY SHOWN. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK. THE CONTRACTOR SHALL PAY FOR AND REPAIR ALL DAMAGES CAUSED BY FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UNDERGROUND UTILITIES UNLESS OTHERWISE INDICATED.
- WHEN MECHANICAL WORK (HVAC, PLUMBING, SHEET METAL, FIRE PROTECTION, ETC.) IS SUBCONTRACTED, IT SHALL BE THE MECHANICAL CONTRACTOR'S RESPONSIBILITY TO COORDINATE SUBCONTRACTORS AND THE ASSOCIATED CONTRACTS. WHEN DISCREPANCIES ARISE PERTAINING TO WHICH CONTRACTOR PROVIDES A PARTICULAR ITEM OF THE MECHANICAL CONTRACT OR WHICH CONTRACTOR PROVIDES FINAL CONNECTIONS FOR A PARTICULAR ITEM OF THE MECHANICAL CONTRACT, IT SHALL BE BROUGHT TO THE ATTENTION OF THE MECHANICAL CONTRACTOR, WHOSE DECISION SHALL BE FINAL.
- COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, ELECTRICAL WORK, ETC., SHOWN ON OTHER CONTRACT DOCUMENT DRAWINGS.
- INSTALL ALL MECHANICAL EQUIPMENT AND APPURTENANCES IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, CONTRACT DOCUMENTS, AND APPLICABLE CODES AND REGULATIONS.
- WHERE TWO OR MORE ITEMS OF THE SAME TYPE OF EQUIPMENT ARE REQUIRED, THE PRODUCT OF ONE MANUFACTURER SHALL BE USED.
- COORDINATE ALL EQUIPMENT CONNECTIONS WITH MANUFACTURER'S CERTIFIED DRAWINGS. COORDINATE AND PROVIDE ALL DUCT AND PIPING TRANSITIONS REQUIRED FOR FINAL EQUIPMENT CONNECTIONS TO FURNISHED EQUIPMENT. FIELD VERIFY AND COORDINATE ALL DUCT AND PIPING DIMENSIONS BEFORE FABRICATION.
- ALL CONTROL WIRE AND CONDUIT SHALL COMPLY WITH THE NATIONAL ELECTRIC CODE AND ELECTRICAL DIVISION OF THE SPECIFICATION.
- PROVIDE VIBRATION ISOLATION FOR ALL MECHANICAL EQUIPMENT TO PREVENT TRANSMISSION OF VIBRATION TO BUILDING STRUCTURE.
- PROVIDE VIBRATION ISOLATORS FOR ALL PIPING SUPPORTS CONNECTED TO AND WITHIN 50 FT. OF ISOLATED EQUIPMENT (EXCEPT AT BASE ELBOW SUPPORTS AND ANCHOR POINTS) THROUGHOUT MECHANICAL EQUIPMENT ROOMS. DO THE SAME FOR SUPPORTS OF STEAM MAINS WITHIN 50 FT. OF BOILER OR PRESSURE-REDUCING VALVES.
- PROVIDE VIBRATION ISOLATORS FOR ALL PIPING SUPPORTS OF STEAM MAINS WITHIN 50 FT. OF BOILERS AND PRESSURE-REDUCING VALVES.
- MAINTAIN A MINIMUM 6'-8" CLEARANCE TO THE UNDERSIDE OF PIPES, DUCTS, CONDUITS, SUSPENDED EQUIPMENT, ETC., THROUGHOUT ACCESS ROUTES IN MECHANICAL ROOMS.
- LOCATE ALL TEMPERATURE, PRESSURE, AND FLOW MEASURING DEVICES IN ACCESSIBLE LOCATIONS WITH THE STRAIGHT SECTION OF PIPE OR DUCT UP, AND DOWNSTREAM AS RECOMMENDED BY THE MANUFACTURER FOR GOOD ACCURACY.
- ALL MECHANICAL ROOM DOORS SHALL BE A MINIMUM OF 4'-0" WIDE.
- WHERE BEAMS ARE INDICATED TO BE PENETRATED WITH DUCTWORK OR PIPING, COORDINATE DUCTWORK AND PIPING LAYOUT WITH BEAM OPENING SIZE AND OPENING LOCATIONS. COORDINATION SHALL BE DONE PRIOR TO THE FABRICATION OF DUCTWORK, CUTTING OF PIPING, OR FABRICATION OF BEAMS.
- ALL MISCELLANEOUS STEEL REQUIRED TO ENSURE PROPER INSTALLATION AND AS SHOWN IN THE DETAILS FOR PIPING, DUCTWORK, AND EQUIPMENT (UNLESS OTHERWISE NOTED) SHALL BE FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR.
- PROVIDE ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS WHERE REQUIRED, TO SERVICE DAMPERS, VALVES, SMOKE DETECTORS, AND OTHER CONCEALED MECHANICAL EQUIPMENT. ACCESS PANELS SHALL BE TURNED OVER TO THE GENERAL CONTRACTOR FOR INSTALLATION. ACCESS PANELS SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL.
- MECHANICAL EQUIPMENT, DUCTWORK, AND PIPING SHALL NOT BE SUPPORTED FROM A METAL DECK.
- ALL EQUIPMENT, PIPING, DUCTWORK, ETC., SHALL BE SUPPORTED AS DETAILED, SPECIFIED AND REQUIRED TO PROVIDE A VIBRATION-FREE INSTALLATION.
- ALL DUCTWORK, PIPING, AND EQUIPMENT SUPPORTED FROM STRUCTURAL STEEL SHALL BE COORDINATED WITH THE GENERAL CONTRACTOR. ALL ATTACHMENTS TO STEEL BAR JOISTS, TRUSSES, OR JOIST GIRDERS SHALL BE AT PANEL POINTS. PROVIDE BEAM CLAMPS MEETING MSS STANDARDS. WELDING TO STRUCTURAL MEMBERS SHALL NOT BE PERMITTED. THE USE OF C-CLAMPS SHALL NOT BE PERMITTED.
- ALL ROOF-MOUNTED EQUIPMENT CURBS FOR EQUIPMENT PROVIDED BY THE MECHANICAL CONTRACTOR SHALL BE FURNISHED BY THE MECHANICAL CONTRACTOR AND INSTALLED BY THE GENERAL CONTRACTOR.
- LOCATIONS AND SIZES OF ALL FLOOR, WALL, AND ROOF OPENINGS SHALL BE COORDINATED WITH ALL OTHER TRADES INVOLVED.
- ALL OPENINGS IN FIRE WALLS DUE TO DUCTWORK, PIPING, CONDUIT, ETC., SHALL BE FIRE STOPPED WITH A PRODUCT SIMILAR TO 3M OR APPROVED EQUAL.

## SPECIFICATIONS

### SECTION 0001 - NOTICE TO BIDDERS

#### 1.1 BIDDERS REPRESENTATIONS

- A. THE BIDDER BY MAKING A BID REPRESENTS THAT:  
THE BIDDER HAS READ AND UNDERSTANDS THE BIDDING DOCUMENTS, TO THE EXTENT THAT SUCH DOCUMENTATION RELATES TO THE WORK FOR WHICH THE BID IS SUBMITTED, AND FOR OTHER PORTIONS OF THE PROJECT, IF ANY, BEING BID CONCURRENTLY OR PRESENTLY UNDER CONSTRUCTION.
- B. THE BID IS MADE IN COMPLIANCE WITH THE BIDDING DOCUMENTS.
- C. THE SPECIFICATIONS AND DRAWINGS ARE INTENDED TO SERVE JOINTLY AS A BASIS FOR THE BIDDER TO SUBMIT A CONTRACT PRICE FOR THE MATERIAL AND LABOR.
- D. SHOULD CONFLICTS OR DISCREPANCIES OCCUR WITHIN THE BIDDING DOCUMENTS, THE ITEM OR ITEMS IN DISPUTE THAT REPRESENT THE GREATER COST SHALL PREVAIL IN THE FINAL BID.
- E. THE BID IS BASED UPON THE MATERIALS, EQUIPMENT AND SYSTEMS REQUIRED BY THE BIDDING DOCUMENTS WITHOUT EXCEPTION.

#### 1.2 EXISTING CONDITIONS AND COORDINATION

- A. THE BIDDER HAS VISITED THE SITE, BECOME FAMILIAR WITH LOCAL CONDITIONS UNDER WHICH THE WORK IS TO BE PERFORMED AND HAS CORRELATED THE BIDDER'S PERSONAL OBSERVATIONS WITH THE REQUIREMENTS OF THE PROPOSED BIDDING DOCUMENTS.
- B. THE BIDDER SHALL PROPOSE COORDINATION OF WORK SUCH THAT CONFLICTS WITH OTHER TRADES AND SPACE ALLOCATIONS ARE AVOIDED.

#### 1.3 RESPONSIBILITIES

- A. THE BIDDER UNDERSTANDS THAT ANY CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR THE TIMELY COMPLETION AND ACCEPTANCE OF THEIR WORK AND THAT ANY ITEMS DAMAGED, LOST OR STOLEN DURING TIME OF CONSTRUCTION SHALL BE REPAIRED OR REPLACED WITHOUT ANY ADDITIONAL COST TO THE OWNER.
- B. THE BIDDER UNDERSTANDS THAT ANY PROPOSED WORK IN OCCUPIED TENANT SPACES SHALL BE PERFORMED DURING TIMES OF NON-TENANT OCCUPANCY OR AS SCHEDULED OR DIRECTED BY THE BUILDING MANAGER.
- C. THE BIDDER UNDERSTANDS THAT ANY PROPOSED SHUT-DOWN OF EXISTING SYSTEMS DURING CONSTRUCTION SHALL BE PRE-ARRANGED WITH THE BUILDING MANAGER AND THAT SUCH SHUT-DOWNS ARE TO BE KEPT TO A MINIMUM.

END OF SECTION 0001

### SECTION 0101 - QUALITY OF WORK

#### 1.1 WORKMANSHIP

- A. ALL WORK SHALL BE FREE FROM DEFECTS IN MATERIALS AND WORKMANSHIP FOR A PERIOD OF ONE YEAR FROM DATE OF FINAL ACCEPTANCE.
- B. ALL DEFECTS WHICH DEVELOP OR ARE DISCOVERED WITHIN THIS PERIOD SHALL BE REPAIRED BY THE CONTRACTOR TO THE SATISFACTION OF THE ARCHITECT OR BUILDING MANAGER AT NO ADDITIONAL COST TO THE OWNER.
- C. UPON COMPLETION OF THE WORK THE CONTRACTOR SHALL REMOVE FROM THE SITE, ALL TOOLS, DEMOLISHED APPLIANCES AND ANY SURPLUS MATERIAL.

#### 1.2 CODE COMPLIANCE

- A. ALL WORK SHALL MEET ALL STATE AND LOCAL CODES HAVING JURISDICTION.

END OF SECTION 0101

### SECTION 0102 - REQUIRED DOCUMENTS

#### 1.1 SHOP DRAWINGS

- A. A SET OF PRINTS FOR ANY MECHANICAL WORK INCLUDING BUT NOT LIMITED TO, DUCTWORK AND PIPING LAYOUT SHALL BE SUBMITTED FOR APPROVAL TO THE ENGINEER PRIOR TO CONSTRUCTION OR PURCHASE OF MATERIALS.

#### 1.2 SUBMITTALS

- A. EQUIPMENT SUBMITTALS OF ALL PROPOSED MECHANICAL AND AUXILIARY EQUIPMENT INCLUDING ALL ACCESSORIES SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW. ALL PERTINENT MODELS, SIZES, ACCESSORIES AND CHOICES SHALL BE CLEARLY CHECKED, PRINTED OR OTHERWISE INDICATED ON THE SUBMITTALS.

#### 1.3 RECORD DRAWINGS

- A. UPON COMPLETION OF THE WORK, A RECORD DRAWING SHALL BE SUBMITTED TO THE OWNER DEPICTING ALL SUBSEQUENT CHANGES, ADDITIONS AND OR CORRECTIONS TO THE CONTRACT DRAWINGS AND OR CONTRACT SCOPE MADE DURING CONSTRUCTION. THIS DRAWING SHALL REPRESENT A COMPLETE RECORD OF THE WORK INSTALLED.

#### 1.4 EQUIPMENT OPERATING INSTRUCTIONS

- A. ON COMPLETION AND ACCEPTANCE OF WORK, THIS CONTRACTOR SHALL FURNISH WRITTEN INSTRUCTIONS, EQUIPMENT MANUALS AND DEMONSTRATE TO THE OWNER THE PROPER OPERATION AND MAINTENANCE OF ALL EQUIPMENT AND APPARATUS FURNISHED UNDER THIS CONTRACT.
- B. THESE INSTRUCTIONS SHALL BE TYPED ON 8-1/2 IN. X 11 IN. PAPER AND BOUND IN THREE-RING BINDERS WITH CLEAR ACETATE COVERS. THE CONTRACTOR SHALL GIVE THREE COPIES OF THE INSTRUCTIONS TO THE OWNER AND ONE ELECTRONIC COPY TO THE ENGINEER.

- C. THE INSTRUCTION BOOKLET SHALL BE ORGANIZED IN SECTIONS, WITH ONE SECTION PER SYSTEM. THE COVER OF THE INSTRUCTION BOOKLET SHALL BEAR THE NAME, ADDRESS AND PHONE NUMBER OF THE PROJECT, ARCHITECT, ENGINEER, MECHANICAL CONTRACTOR AND SUBCONTRACTORS.

END OF SECTION 0102

### SECTION 230517 - SLEEVES AND SLEEVE SEALS FOR HVAC PIPING

#### 1.1 SLEEVE-SEAL SYSTEMS

- A. FIELD-ASSEMBLED, MODULAR SEALING-ELEMENT UNIT FOR FILLING ANNUAL SPACE BETWEEN PIPING AND SLEEVE.
- 1. SEALING ELEMENTS: EPDM RUBBER OR NBR.
- 2. PRESSURE PLATES: CARBON STEEL, PLASTIC, STAINLESS STEEL.
- 3. CONNECTING BOLTS AND NUTS: CARBON STEEL WITH CORROSION-RESISTANT COATING, STAINLESS STEEL.
- B. MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, AVAILABLE MANUFACTURERS OFFERING PRODUCTS THAT MAY BE INCORPORATED INTO THE WORK INCLUDE, BUT ARE NOT LIMITED TO, THE FOLLOWING:
- 1. ADVANCE PRODUCTS & SYSTEMS, INC.
- 2. CALPICO, INC.
- 3. METRAFLEX COMPANY (THE).
- 4. PIPELINE SEAL AND INSULATOR, INC.
- 5. PROCO PRODUCTS, INC.

#### 1.2 SLEEVE-SEAL FITTINGS

- A. MANUFACTURED PLASTIC, SLEEVE-TYPE, PLASTIC OR RUBBER WATER-STOP ASSEMBLY MADE FOR IMBEDDING IN CONCRETE SLAB OR WALL.
- B. A. NON-SHRINK, FACTORY PACKAGED.
- 1.4 SLEEVE AND SLEEVE-SEAL SCHEDULE
- A. USE SLEEVES AND SLEEVE SEALS FOR THE FOLLOWING PIPING-PENETRATION APPLICATIONS:
- 1. INTERIOR PARTITIONS:
- a. PIPING SMALLER THAN NPS 6 (DN 150): GALVANIZED-STEEL-PIPE SLEEVES, PVC-PIPE SLEEVES.
- b. PIPING NPS 6 (DN 150) AND LARGER: GALVANIZED-STEEL-SHEET SLEEVES.

END OF SECTION 230517

### SECTION 230518 - ESCUTCHEONS FOR HVAC PIPING

#### PART 2 - PRODUCTS

- 2.1 ESCUTCHEONS
- A. ONE-PIECE, CAST-BRASS TYPE: WITH POLISHED, CHROME-PLATED AND ROUGH-BRASS FINISH AND SETSCREW FASTENER.
- B. ONE-PIECE, DEEP-PATTERN TYPE: DEEP-DRAWN, BOX-SHAPED BRASS WITH CHROME-PLATED FINISH AND SPRING-CLIP FASTENERS.
- C. ONE-PIECE, STAMPED-STEEL TYPE: WITH CHROME-PLATED FINISH AND SPRING-CLIP FASTENERS.

#### 2.2 FLOOR PLATES

- A. ONE-PIECE FLOOR PLATES: CAST-IRON FLANGE WITH HOLES FOR FASTENERS.

#### PART 3 - EXECUTION

- 3.1 INSTALLATION
- A. INSTALL ESCUTCHEONS FOR PIPING PENETRATIONS OF WALLS, CEILINGS, AND FINISHED FLOORS.
- B. INSTALL ESCUTCHEONS WITH ID TO CLOSELY FIT AROUND PIPE, TUBE, AND INSULATION OF PIPING AND WITH OD THAT COMPLETELY COVERS OPENING.
- 1. ESCUTCHEONS FOR NEW PIPING:
  - a. PIPING WITH FITTING OR SLEEVE PROTRUDING FROM WALL: ONE-PIECE, DEEP-PATTERN TYPE.
  - b. INSULATED PIPING: ONE-PIECE, STAMPED-STEEL TYPE.
  - c. BARE PIPING AT WALL AND FLOOR PENETRATIONS IN FINISHED SPACES: ONE-PIECE, CAST-BRASS TYPE WITH POLISHED, CHROME-PLATED FINISH OR STAMPED-STEEL TYPE.
  - d. BARE PIPING AT CEILING PENETRATIONS IN FINISHED SPACES: ONE-PIECE, CAST-BRASS TYPE WITH POLISHED, CHROME-PLATED FINISH OR STAMPED-STEEL TYPE.
- 3.2 FIELD QUALITY CONTROL
- A. REPLACE BROKEN AND DAMAGED ESCUTCHEONS AND FLOOR PLATES USING NEW MATERIALS.

### SECTION 230529 - HANGERS AND SUPPORTS FOR HVAC PIPING AND EQUIPMENT

#### 1.1 PERFORMANCE REQUIREMENTS

- A. DELEGATED DESIGN: DESIGN TRAPEZE PIPE HANGERS AND EQUIPMENT SUPPORTS, INCLUDING COMPREHENSIVE ENGINEERING ANALYSIS BY A QUALIFIED PROFESSIONAL ENGINEER, USING PERFORMANCE REQUIREMENTS AND DESIGN CRITERIA INDICATED.
- B. STRUCTURAL PERFORMANCE: HANGERS AND SUPPORTS FOR HVAC PIPING AND EQUIPMENT SHALL WITHSTAND THE EFFECTS OF GRAVITY LOADS AND STRESSES WITHIN LIMITS AND UNDER CONDITIONS INDICATED ACCORDING TO ASCE/SEI 7.
- 1. DESIGN SUPPORTS FOR MULTIPLE PIPES CAPABLE OF SUPPORTING COMBINED WEIGHT OF SUPPORTED SYSTEMS, SYSTEM CONTENTS, AND TEST WATER.
- 2. DESIGN EQUIPMENT SUPPORTS CAPABLE OF SUPPORTING COMBINED OPERATING WEIGHT OF SUPPORTED EQUIPMENT AND CONNECTED SYSTEMS.
- 3. DESIGN SEISMIC-RESTRAINT HANGERS AND SUPPORTS FOR PIPING AND EQUIPMENT AND OBTAIN APPROVAL FROM AUTHORITIES HAVING JURISDICTION.

END OF SECTION 230529

### SECTION 230548 - TESTING, ADJUSTING, AND BALANCING FOR HVAC PIPING AND EQUIPMENT

#### 1.1 SUMMARY

- A. TESTING, ADJUSTING, AND BALANCING FOR THE FOLLOWING:

#### 1.2 SUBMITTALS

- A. SHOP DRAWINGS: SIGNED AND SEALED BY A PROFESSIONAL ENGINEER

#### 1.3 QUALITY ASSURANCE

- A. AWS D1.1/D1.1M, "STRUCTURAL WELDING CODE - STEEL."

#### 1.4 COMPONENTS

- A. METAL PIPE HANGERS AND SUPPORTS: CARBON OR STAINLESS STEEL

#### B. TRAPEZE PIPE HANGERS: CARBON OR STAINLESS STEEL

- C. FIBERGLASS PIPE HANGERS: -CLEVIS, CENTURY COMPOSITES, COOPER B-LINE

#### D. METAL FRAMING SYSTEMS: FMFA MANUFACTURER

#### E. FIBERGLASS STRUT SYSTEMS: COOPER B-LINE

#### F. THERMAL-HANGER SHIELD INSERTS:

#### G. FASTENER SYSTEMS: POWDER-ACTUATED FASTENERS OR MECHANICAL-EXPANSION ANCHORS

#### H. PIPE STANDS: COMPACT, LOW TYPE, SINGLE PIPE, HIGH TYPE, SINGLE PIPE, HIGH TYPE, MULTIPLE PIPES, CURB-MOUNTED TYPE

#### I. EQUIPMENT SUPPORTS.

END OF SECTION 230529

### 1. AIR SYSTEMS: CONSTANT VOLUME.

#### 1.2 QUALITY ASSURANCE

- A. THE CONTRACTOR SHALL PROCURE THE SERVICES OF A TESTING, ADJUSTING AND BALANCING (TAB) SPECIALIST WHO SPECIALIZES IN HEATING, VENTILATION AND AIR CONDITIONING SYSTEMS. THE TAB AGENT SHALL HAVE THE FOLLOWING QUALIFICATIONS: AABC, NEBB OR TABB CERTIFIED.

#### 1.3 EXECUTION

- A. THE TAB SPECIALIST SHALL PERFORM FLOW MEASUREMENTS OF ALL EXISTING AIR AND HYDRONIC SYSTEMS THAT ARE TO REMAIN OR TO BE INCORPORATED INTO NEW WORK PRIOR TO THE STARTING OF WORK IN THE PROJECT SCOPE. A REPORT OF THESE MEASUREMENTS, INDICATING ANY AND ALL DEFICIENCIES SHALL BE SUBMITTED FOR OWNER REVIEW.

- B. THE TAB SPECIALIST SHALL PERFORM FLOW MEASUREMENTS OF ALL NEW AIR AND HYDRONIC SYSTEMS AS LISTED ABOVE IN THE PROJECT SCOPE. A REPORT OF THESE MEASUREMENTS, INDICATING ANY AND ALL DEFICIENCIES SHALL BE SUBMITTED FOR OWNER REVIEW.

- C. THE REPORT SHALL INDICATE A SCHEMATIC DIAGRAM INDICATING LOCATIONS OF ALL EQUIPMENT TESTED AND MEASUREMENT LOCATIONS.

- D. PRIOR TO FINAL INSPECTION OF THE WORK, THE TAB SPECIALIST SHALL BALANCE ALL SYSTEMS AS INDICATED ABOVE TO THE REQUIREMENTS OF THE DESIGN.

- E. THE CONTRACTOR SHALL HAVE FURNISH AND INSTALL ALL ADDITIONAL BALANCING EQUIPMENT, PRESSURE TAPS, GAUGES AND OTHER EQUIPMENT AS REQUIRED FOR A PROPERLY BALANCED SYSTEM AT NO ADDITIONAL COST TO THE OWNER. SUCH ADDITIONAL EQUIPMENT SHALL ADHERE IN STRICT ACCORDANCE WITH THE RESPECTIVE EQUIPMENT MANUFACTURER'S RECOMMENDATIONS.

- F. THE CONTRACTOR SHALL HAVE THE TESTING AND BALANCING SPECIALIST COORDINATE ALL WORK OF THIS SECTION WITH THE BUILDING MANAGER. BALANCING WORK SHALL NOT CONFLICT WITH OTHER WORK SO AS TO MAINTAIN COMPLETION WITHIN THE SPECIFIED TIME.

- G. ALL INSTRUMENTS USED FOR TAB SHALL BE MAINTAINED IN GOOD WORKING CONDITION AND ACCURATELY CALIBRATED.

- H. TOLERANCES: PLUS OR MINUS 5 PERCENT OF DESIGN VALUES.

- I. INSPECTIONS: RANDOM CHECKS BY OWNER OR ARCHITECT TO VERIFY FINAL TESTING, ADJUSTING, AND BALANCING REPORT.

- J. ADDITIONAL TESTS: RANDOM TESTS WITHIN 90 DAYS OF COMPLETING TAB TO VERIFY BALANCE CONDITIONS AND SEASONAL TESTS.

END OF SECTION 230593

### SECTION 230713 - DUCT INSULATION

#### 1.1 QUALITY ASSURANCE

#### B. AIR-MOUNTING SYSTEMS:

- 1. AIR MOUNTS: FREESTANDING, SINGLE OR MULTIPLE, COMPRESSED-AIR BELLOWS.
- 2. RESTRAINED AIR MOUNTS: HOUSED COMPRESSED-AIR BELLOWS.

#### C. RESTRAINED VIBRATION ISOLATION ROOF-CURB RAILS: FACTORY-ASSEMBLED, FULLY ENCLOSED, INSULATED, AIR- AND WATERTIGHT CURB RAIL; WITH SPRING ISOLATORS MOUNTED ON ELASTOMERIC ISOLATION PADS, AND SNUBBER BUSHINGS.

#### D. VIBRATION ISOLATION EQUIPMENT BASES:

- 1. STEEL BASE: FACTORY-FABRICATED, WELDED, STRUCTURAL-STEEL BASES AND RAILS.
- 2. INERTIA BASE: FACTORY-FABRICATED, WELDED, STRUCTURAL-STEEL BASES AND RAILS READY FOR FIELD-APPLIED, CAST-IN-PLACE CONCRETE

#### 1.2 FIELD QUALITY CONTROL

#### A. TESTING: BY EITHER: OWNER-ENGAGED AGENCY,

#### CONTRACTOR-ENGAGED AGENCY, OR CONTRACTOR.

#### PART 2 PRODUCTS

#### 1.1 VIBRATION ISOLATORS & SEISMIC-RESTRAINT DEVICES

- A. AVAILABLE MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, MANUFACTURERS OFFERING PRODUCTS THAT MAY BE INCORPORATED INTO THE WORK INCLUDE, BUT ARE NOT LIMITED TO, THE FOLLOWING:

#### B. MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY ONE OF THE FOLLOWING:

#### 1. ACE MOUNTINGS CO., INC.

#### 2. AMBER/BOOTH COMPANY, INC.

#### 3. CALIFORNIA DYNAMICS CORPORATION.

#### 4. HILTI, INC.

#### 5. ISOLATION TECHNOLOGY, INC.

#### 6. KINETICS NOISE CONTROL.

#### 7. LOOS & CO.; CABLEWARE DIVISION.

#### 8. MASON INDUSTRIES.

#### 9. TOLCO INCORPORATED; A BRAND OF NIBCO INC.

#### 10. UNISTRUT; TYCO INTERNATIONAL, LTD.

MECHANICAL GENERAL NOTES	
A. PROVIDE ALL NEW DUCTWORK AS SHOWN. DUCT WORK ABOVE CEILING TO BE INSULATED ACCORDING TO 2024 OHIO ENERGY CONSERVATION CODE.	
B. FLEXIBLE AIR CONNECTORS SHALL BE TESTED IN ACCORDANCE WITH UL 181. SUCH DUCTS SHALL BE LISTED AND LABELED AS CLASS 0 OR CLASS 1 FLEXIBLE AIR CONNECTORS. FLEXIBLE AIR CONNECTORS SHALL BE LIMITED IN LENGTH TO 14 FEET.	
C. TEST & BALANCE SYSTEM PRIOR TO CLOSEOUT OF PROJECT. PROVIDE A DETAILED REPORT TO OWNER, ARCHITECT, & ENGINEER.	
D. ALL DUCTWORK SHALL BE FABRICATED, INSTALLED, SEALED, AND INSULATED PER THE LATEST ISSUE OF SMACNA LOW-VELOCITY DUCT MANUAL.	
E. DUCT SIZES SHOWN ON DRAWINGS ARE CLEAR INSIDE DIMENSION.	
F. THE CONTRACTOR SHALL VERIFY EXACT LOCATION OF TRUSSES AND MODIFY DUCTWORK ACCORDINGLY.	
G. PROVIDE FIRE OR FIRE+SMOKE DAMPER WHEREVER DUCTS ARE CROSSING FIRE+SMOKE RATED WALLS/BARRIERS/SLABS. COORDINATE WITH ARCHITECTURAL DRAWING FOR FIRE RATING OF THE WALLS.	
H. DUCT TO EXHAUST FAN CONNECTIONS SHALL BE FLANGED, GASKETED AND BOLTED TO THE INLET OF THE FAN FOR SIDE-INLET UTILITY FANS APPROVED GASKETED CONNECTIONS MAY BE PROVIDED.	
I. ALL WORK SHALL BE SUBJECT TO THE ACCEPTANCE AND APPROVAL OF THE ARCHITECT AND OWNER. THE ARCHITECT SHALL BE NOTIFIED OF ANY AND ALL DISCREPANCIES BETWEEN FIELD CONDITIONS AND THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH THAT PORTION OF THE WORK. FAILURE OF PROPER NOTIFICATION DOES NOT RELIEVE THE CONTRACTOR. THE CONTRACTOR SHALL CORRECT ANY AND ALL WORK ARISING FROM SUCH FAILURE TO COORDINATE DISCREPANCIES TO THE SATISFACTION OF THE ARCHITECT WITHOUT ADDITIONAL COST TO THE OWNER.	
J. THE CONTRACTOR SHALL, UPON COMPLETION OF PROJECT, PERFORM A COMPLETE TEST AND BALANCE OF ALL EQUIPMENT. PROVIDE A WRITTEN REPORT TO THE ARCHITECT. ALL CAPACITIES MUST BE SET TO WITHIN $\pm 10\%$ OF AMOUNTS INDICATED ON THE FLOOR PLAN AND SCHEDULES.	
K. PROVIDE DUCT INSULATION AS SPECIFIED WITH MINIMUM VALUES AS FOLLOWS: R-6 SUPPLY & RETURN DUCT INSULATION IN UNCONDITIONED SPACES WITHIN BUILDING. R-12 SUPPLY & 12 RETURN DUCT INSULATION WITHIN BUILDING ENVELOPE ASSEMBLY.	
L. EQUIPMENT SIZES, DIMENSIONS AND REQUIRED CONNECTIONS SHALL BE VERIFIED WITH THE ACTUAL EQUIPMENT SELECTED VENDOR DRAWINGS BEFORE FABRICATION OF DUCTWORK, PIPING ETC.	

#### MECHANICAL FLOOR PLAN KEY NOTES


- 1 PROVIDE NEW 7-DAY PROGRAMMABLE THERMOSTAT WITH LOCKING COVER. LOCATE THERMOSTAT IN MANAGER'S OFFICE. PROVIDE REMOTE SENSOR LOCATED 48" A.F.F. NEAR LOCATION INDICATED. COORDINATE LOCATION ON SITE WITH GENERAL CONTRACTOR AND EQUIPMENT. AVOID LOCATING NEAR OR ABOVE SOURCES OF HEAT. INTERLOCK WITH ASSOCIATED RTU. CONFIRM FINAL LOCATION WITH ARCHITECT/OWNER.
- 2 INSTALL TYPE-I GREASE EXHAUST HOOD, SUPPORT HOOD PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. PROVIDE TRAPEZE HANGERS FOR ALL THREAD SUPPORT UNDER DUCTWORK AS REQUIRED. TRANSITION FROM HOOD CONNECTION TO WELDED KITCHEN EXHAUST DUCT SIZES SHOWN. THE HOOD AND DUCT SHALL HAVE AN APPROVED FIRE PROTECTION. THE FIRE-EXTINGUISHING SYSTEM SHALL BE INTERCONNECTED TO THE FUEL OR CURRENT SUPPLY SO THAT THE FUEL OR CURRENT SUPPLY IS AUTOMATICALLY SHUT OFF TO ALL EQUIPMENT UNDER THE HOOD WHEN THE SYSTEM IS ACTUATED. REFER TO HOOD SCHEDULE AND DRAWINGS FOR HOOD SPECIFICATIONS AND FOR BALANCE OF MAKE-UP AIR AND SUPPLY TO HOOD.
- 3 FURNISH AND INSTALL MANUAL VOLUME DAMPER IN EACH SUPPLY AIR DUCT CONNECTED TO HOOD SUPPLY AIR PLENUM. REFER TO HOOD SCHEDULE FOR REQUIRED AIRFLOW AT EACH CONNECTION.
- 4 20"X16" GREASE EXHAUST DUCT FROM HOOD UP THRU ROOF TO KITCHEN EXHAUST FAN. PROVIDE FIRE WRAP ON DUCT RATED FOR 0" CLEARANCE TO COMBUSTIBLES.
- 5 EXTEND FULL SIZE SUPPLY & RETURN DUCTWORK FROM ROOFTOP UNITS TO SPACE. EXTEND AS SHOWN. TRANSITION DUCT AS NECESSARY TO MAKE CONNECTION. ACOUSTICALLY LINE THE FIRST 10'-0" OF BOTH SUPPLY AND RETURN MAIN DUCTS.
- 6 CONTRACTOR TO PROVIDE TEMPERATURE SENSOR IN RETURN AIR DUCT & WIRE BACK TO RTUs.
- 7 DUCT MOUNTED SMOKE DETECTOR SHALL BE FURNISHED/INSTALLED BY MECHANICAL CONTRACTOR IN RETURN AIR DUCT AND WIRED BY ELECTRICAL CONTRACTOR TO SHUT DOWN CORRESPONDING RTU & MAU UNDER ALARM CONDITIONS. ALL WIRING SHALL BE IN CONDUIT PER NEC. SMOKE DETECTOR SHALL BE SYSTEM SENSOR MODEL DH100ACDCLP OR EQUAL.
- 8 PROVIDE AND INSTALL EMERGENCY MANUAL SHUTDOWN PUSH BUTTON FOR HOOD. PUSH BUTTON SHALL BE IN THE PATH OF EGRESS, A MINIMUM OF 10' AWAY FROM THE HOOD AND A MAXIMUM OF 20'.
- 9 GREASE DUCT TO BE PROVIDED WITH KITCHEN EQUIPMENT AND INSTALLED BY MECHANICAL CONTRACTOR. INSTALL PER MANUFACTURER'S INSTRUCTIONS.
- 10 EXTEND MAKE-UP AIR DUCT FROM HOOD COLLAR UP TO MOUNTED MAKE-UP AIR UNIT ON ROOF MAU-1(N).
- 11 8"Ø TOILET EXHAUST DUCT UP THRU ROOF TO TEF-1(N).
- 12 PROVIDE 1" DOOR UNDERCUT OR 6"X6" DOOR GRILLE.
- 13 PROVIDE 3"Ø/5"Ø CONCENTRIC VENT FOR WATER HEATER INTAKE & EXHAUST VENT. INSTALL AS PER MANUFACTURER'S RECOMMENDATION/INSTRUCTIONS. MAINTAIN A MINIMUM 10'-0" DISTANCE AWAY FROM ANY BUILDING/OUTSIDE AIR INTAKES.

#### KITCHEN EXHAUST NOTES

1. ALL TYPE I GREASE DUCT SHALL BE WRAPPED WITH TWO LAYERS OF 3M™ FIRE BARRIER DUCT WRAP 615+ DUCT ENCLOSURE SYSTEM PROVIDING 2-HOUR FIRE RESISTANT PROTECTION. WRAP SHALL CONSIST OF 3" PERIMETER AND LONGITUDINAL OVERLAPS WITH ZERO CLEARANCE TO COMBUSTIBLES. DUCT WRAP SHALL COMPLY WITH THE REQUIREMENTS OF NFPA 96 AND ICC-ES EVALUATION REPORT NO. ESR-1255. DUCT WRAP IS UL LISTED. DUCT WRAP SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.
2. MATERIAL - STEEL NOT LESS THAN 0.0575 INCH (NO. 16 GAGE) IN THICKNESS, WITH JOINTS AND SEAMS MADE WITH A CONTINUOUS LIQUID-TIGHT WELD MADE ON THE EXTERNAL SURFACE OF THE DUCT SYSTEM.
3. ALL TURNS IN KITCHEN EXHAUST DUCT SHALL BE ACHIEVED WITH THE USE OF A 1.5 RADIUS/WIDT SMOOTH RADIUS ELBOW. REFERENCE DETAILS.
4. HORIZONTAL DUCT SERVING TYPE I HOODS SHALL BE SLOPED NOT LESS THAN 2% TOWARD HOOD.
5. A PERFORMANCE TEST SHALL BE CONDUCTED UPON COMPLETION AND BEFORE FINAL APPROVAL OF THE INSTALLATION OF A VENTILATION SYSTEM SERVING COMMERCIAL COOKING APPLIANCES. THE TEST SHALL VERIFY THE RATE OF EXHAUST AIRFLOW, MAKEUP AIRFLOW, AND PROPER OPERATION AS SPECIFIED IN THE MECHANICAL CODE (INCLUDING CAPTURE AND CONTAINMENT TEST). THE PERMIT HOLDER SHALL FURNISH THE NECESSARY TEST EQUIPMENT AND DEVICES REQUIRED TO PERFORM THE TESTS. COORDINATE ALL TESTS WITH AHJ, INCLUDING FINAL REPORT/SUBMITTAL AND WITNESS REQUIREMENTS.
6. SLOPE ALL HORIZONTAL GREASE DUCT 1" PER FOOT WHERE SPACE ALLOWS, BUT NOT LESS THAN 1/4" PER FOOT AS REQUIRED BY AHJ.
7. CONTRACTOR TO PROVIDE AND INSTALL ALL CODE REQUIRED FIRE RATED ACCESS DOORS IN GREASE DUCTS AT ALL LOCATIONS REQUIRED BY CODE AND LOCAL AUTHORITY HAVING JURISDICTION.
8. PROVIDE CLEANOUTS IN ALL KITCHEN EXHAUST DUCTWORK AT EVERY CHANGE OF DIRECTION AND AT EVERY 12' OF DUCT. PROVIDE ACCESS PANELS AT ALL GREASE DUCT CLEANOUTS. PROVIDE AS PER LOCAL CODE.
9. COORDINATE HOOD INSTALLATION WITH HOOD PLANS. HOOD OPERATION, CAPTURE, SIZE AND ACCESSORIES ARE BASED ON EQUIPMENT AND CLEARANCES INDICATED IN PLANS. FIELD VERIFY AND COORDINATE HOODS WITH EQUIPMENT FURNISHED. COORDINATE HOOD CONNECTIONS WITH HOOD PLANS AND MANUFACTURER PRIOR TO FABRICATION.
10. COORDINATE INTERLOCKS AND HOOD CONTROLS WITH HOOD PLANS AND HOOD MANUFACTURER PRIOR TO INSTALLATION.

#### IMPORTANT NOTE:

PROVIDE COPY OF TEST AND BALANCE REPORT TO MECHANICAL INSPECTOR AT TIME OF HAVING FINAL INSPECTION




1 MECHANICAL FLOOR PLAN  
M-3 3/16" = 1'-0"


PROJECT NO.: 13257  
DRAWN BY: NYE  
CHECKED BY: NYE  
ISSUED DATE:  
ISSUED REVISIONS:  
A  
B  
C  
D  
E  
F  
G  
H

MECHANICAL GENERAL NOTES	
A.	COORDINATE LOCATIONS AND SIZES OF ROOF OPENINGS WITH OWNER AND STRUCTURAL ENGINEERS.
B.	EQUIPMENT SIZES, DIMENSIONS AND REQUIRED CONNECTIONS SHALL BE VERIFIED WITH THE ACTUAL EQUIPMENT SELECTED VENDOR DRAWINGS BEFORE FABRICATION OF DUCTWORK, PIPING ETC.
C.	CONTRACTOR SHALL COORDINATE ALL ELECTRICAL REQUIREMENTS FOR ALL HVAC BASED ON ACTUAL EQUIPMENT SELECTED PRIOR TO INSTALLATION.
D.	CONTRACTOR SHALL COORDINATE EQUIPMENT WEIGHTS AND SUPPORTS BASED ON ACTUAL EQUIPMENT SELECTED.
E.	ALL SOURCE OF MECHANICAL INTAKE SHALL MAINTAIN 10 LINEAR FEET SEPARATION BETWEEN ANY SOURCE OF EXHAUST. CONTRACTOR IS RESPONSIBLE TO ADJUST DUCT LENGTH AS NEEDED.
F.	THE CONTRACTOR SHALL VERIFY EXACT LOCATION OF TRUSSES AND MODIFY DUCTWORK ACCORDINGLY.
G.	RTU,MAU & EXHAUST FAN WEIGHTS ARE INCLUDED ROOF CURBS AND/OR ADAPTORS.

MECHANICAL ROOF PLAN KEY NOTES	
①	COORDINATE FINAL LOCATION OF EQUIPMENT WITH STRUCTURAL ENGINEER/DRAWINGS.
②	NEW ROOFTOP UNIT IS PROVIDED. PROVIDE FLEXIBLE CONNECTORS ON SUPPLY AND RETURN DUCT CONNECTIONS. SET OUTSIDE AIR AS INDICATED ON ROOFTOP UNIT SCHEDULES. MECHANICAL CONTRACTOR SHALL SCRIBE INTO UNIT POSITION OF OUTSIDE AIR DAMPER AND LABEL OUTSIDE AIR VOLUME AND PERCENT OF OUTSIDE AIR. TRANSITION AND CONNECT SUPPLY AND RETURN DUCTWORK FROM BELOW. COORDINATE ROUTING THROUGH STRUCTURAL TRUSSES AND OFFSET AS REQUIRED IN CURB SPACE.
③	ROUTE CONDENSATE DRAIN FROM RTU-1(N), RTU-2(N) & RTU-3(N) TO THE EXISTING ROOF DRAIN POINT ON THE ROOF. SUCH PIPING SHALL MAINTAIN A MINIMUM HORIZONTAL SLOPE IN THE DIRECTION OF NOT LESS THAN 1/8 TH UNIT VERTICAL IN 12 UNITS HORIZONTAL (1% SLOPE). CONDENSATE SHALL NOT DISCHARGE INTO A STREET, ALLEY OR OTHER AREAS SO AS TO CAUSE NUISANCE. CONTRACTOR TO FIELD VERIFY EXACT LOCATION OF EXISTING ROOF DRAIN POINT. INSTALL & ROUTE CONDENSATE DRAIN PIPING AS PER MANUFACTURER'S RECOMMENDATION/INSTRUCTIONS.
④	PROVIDE ROOF MOUNTED TOILET EXHAUST FAN. MAINTAIN A MINIMUM OF 10'-0" FROM ALL OUTSIDE AIR INTAKES & A MINIMUM OF 40" ABOVE ROOF.
⑤	PROVIDE ROOF MOUNTED GREASE EXHAUST FAN. MAINTAIN A MINIMUM OF 10'-0" FROM ALL OUTSIDE AIR INTAKES & A MINIMUM OF 40" ABOVE ROOF.
⑥	CONTRACTOR TO FIELD VERIFY THAT THE LOCATION OF ANY EXHAUST SOURCE SHOULD BE AT LEAST 10' AWAY FROM THE OUTSIDE AIR INTAKE OPENING OF RTUs & MAU.
⑦	PROVIDE MAKE-UP AIR UNIT AND ROOF CURB. PROVIDE FLEXIBLE CONNECTION ON THE SUPPLY DUCT CONNECTION TRANSITION TO DUCT SIZE INDICATED. FIELD VERIFY EXISTING CONDITIONS PRIOR TO BID.
⑧	CONTRACTOR TO VERIFY IN FIELD THAT THE PENETRATIONS/DROPS OF NEW ROOFTOP UNITS DO NOT CLASH WITH ANY WALLS OR KITCHEN HOOD BELOW. NOTIFY ARCHITECT/OWNER OF ANY DISCREPANCIES PRIOR TO BID AND START OF WORK.
⑨	PROVIDE 3"Ø CONCENTRIC VENT FOR WATER HEATER INTAKE & EXHAUST VENT. INSTALL AS PER MANUFACTURER'S RECOMMENDATION/INSTRUCTIONS. MAINTAIN A MINIMUM 10'-0" DISTANCE AWAY FROM ANY BUILDING/OUTSIDE AIR INTAKES.







ROOF TOP UNIT (GAS HEAT) SCHEDULE																					
UNIT ID	MANUFACTURER	MODEL	AREA SERVED	NOMINAL TONS	SUPPLY FAN			HEATING CAPACITY			COOLING CAPACITY			ELECTRICAL DATA				EER	IEER	THERMAL EFFICIENCY %	MAX OPERATING WEIGHT (LBS.)
					SUPPLY AIR CFM	OUTSIDE AIR CFM	MAX. ESP (IN. OF W.G.)	INPUT MBH	OUTPUT MBH	TOTAL MBH	SENSIBLE MBH	AMBIENT TEMP. DB	ENTERING TEMP. DB / WB (°F)	MCA (A)	MOCP (A)	VOLTS	PHASE	MCA (A)	MOCP (A)		
RTU-1(N)	CARRIER	48FEEM08B2A5-0A0AO (OR EQUIVALENT)	SEE PLAN	7.5	3000	500	1.0	180.0	148.0	93.4	71.1	95	80/67	208-230	3	37	45	11.2	15	82	1100
RTU-2(N)	CARRIER	48FEEM08B2A5-0A0AO (OR EQUIVALENT)	SEE PLAN	7.5	3000	500	1.0	180.0	148.0	93.4	71.1	95	80/67	208-230	3	37	45	11.2	15	82	1100
RTU-3(N)	CARRIER	48FEEM12B2A5-0A0AO (OR EQUIVALENT)	SEE PLAN	10	4000	600	1.0	224.0	181.0	123.9	92.5	95	80/67	208-230	3	52	60	11	15	81	1200
NOTES / ACCESSORIES -																					
1. CONTRACTOR TO BALANCE OUTSIDE AIR DAMPER ON RTUs TO MATCH VALUE MENTIONED IN EQUIPMENT SCHEDULE.																					
2. PROVIDE GFI OUTLET WITH IN USE WEATHERPROOF COVER FOR EACH UNIT.																					
3. REPLACE ALL AIR FILTERS WITH NEW MERV-13 FILTERS BEFORE HANDING OVER THE SPACE TO THE OWNER/TENANT.																					
4. BOTTOM DISCHARGE & RETURN CONFIGURATION.																					
5. UNIT TO BE PROVIDED WITH LOW LEAKAGE VOLUME CONTROL DAMPER, NEMA 3R DISCONNECT, FAN WITH VFD, VIBRATION ISOLATION SPRING SUPPORTED BLOWER, INTAKE HOOD, SCREEN INTAKE.																					
6. PROVIDE ENTHALPY ECONOMIZER WITH BAROMETRIC RELIEF & FDD FOR RTU-1(N), RTU-2(N) & RTU-3(N).																					
7. PROVIDE FLEXIBLE CONNECTION AT DUCT CONNECTION TO UNIT.																					
8. PROVIDE VIBRATION ISOLATOR FOR UNIT MOUNTING.																					
9. UNIT SHALL BE COMPLETE WITH GAS HEATING SECTION. GAS REGULATOR TO RECEIVE 4-13" GAS PRESSURE FROM MAIN.																					
10. PROVIDE SMOKE DETECTOR IN RETURN AIR SIDE OF RTU-1(N), RTU-2(N) & RTU-3(N). PROVIDE GLOBAL SHUTDOWN TO ALL HVAC UNITS UPON ACTIVATION OF A BUILDING'S FIRE ALARM SYSTEM.																					
11. PROVIDE ALL COMPRESSORS WITH 5 YEAR WARRANTY.																					
12. ANTI SHORT CYCLE TIMER.																					
13. PROVIDE 14" ROOF CURB. CONTRACTOR TO FIELD INSULATE.																					
14. CONNECT CONDENSATE DRAIN LINE FROM ALL RTUs ON THE ROOF TO THE NEAREST DRAIN POINT. CONNECT TO A DRAIN LINE VIA AIR GAP IN AN APPROVED MANNER.																					

MAKE-UP AIR UNIT SCHEDULE												
MARK	MANUFACTURER	MODEL	SERVICE	MOTOR HP	GAS HEATING CAPACITY (MBH)	MIN. GAS PRESSURE (IN. W.C.)	FAN		MAU ELECTRICAL DATA			MAX. WEIGHT (LBS.)
							AIR (CFM)	E.S.P. (IN. W.G.)	V/PH/HZ	MCA (A)	MOCP (A)	
MAU-1(N)	SELECT AIR SYSTEM	V3-HOX	HD-1(N) & HD-2(N)	3	319	8"	3880	0.75"	208-3-60	23.2	30	761
NOTES:												
1. PROVIDE ALL NECESSARY ACCESSORIES AS PER MANUFACTURER'S RECOMMENDATIONS.												
2. REFER TO CAPTIVE/REIRE DRAWINGS ON SHEET H-1 TO H-4 FOR SPECIFICATIONS AND MORE DETAILS. SCHEDULES SHOWN FOR REFERENCE ONLY.												
3. MAU-1(N) SHALL BE CONTROLLED BY HOOD CONTROLS.												

KITCHEN EXHAUST FAN SCHEDULE												
MARK	MANUFACTURER	MODEL	SERVICE	DRIVE TYPE	RPM	MOTOR HP	EXHAUST AIR DATA		ELECTRICAL DATA	MAX. WEIGHT		
							AIR (CFM)	E.S.P. (IN. W.G.)	VOLTAGE	FLA (LBS.)		
KEF-1(N)	COOK	VCR	HD-1(N)	BELT DRIVE	1725	1	2425	1.00	208	3	4.6	150
KEF-2(N)	COOK	VCR	HD-2(N)	BELT DRIVE	1725	1	2425	1.00	208	3	4.6	150
NOTES:												
1. FAN SHALL BE CONTROLLED BY HOOD CONTROLS. INTERLOCK WITH RTU-3(N) TO OPERATE IN OCCUPIED MODE WHILE KITCHEN EXHAUST FAN IS ENERGIZED.												
2. REFER TO COOK SYSTEM DRAWINGS ON SHEET H-1 TO H-4 FOR SPECIFICATIONS AND MORE DETAILS. SCHEDULES SHOWN FOR REFERENCE ONLY.												



# Another Broken Egg Cafe

# Kitchen Hood Drawings (1 of 4)

H-



**COOK**

# VCR

# **Upblast Centrifugal Exhaust Ventilator Roof Mounted/Belt Drive**

## **STANDARD CONSTRUCTION FEATURES:**

All aluminum housing - Backward inclined all

All aluminum housing - Backward inclined all aluminum wheel - Two piece top cap with stainless steel quick release latches - One piece bottom spinning - Welded curb cap corners - Lifting Lugs - Permanently lubricated ball bearing motors - Oil and heat resistant, static conducting belts - Adjustable pitch drives through 5 hp motor - Corrosion resistant fasteners - Regreasable bearings in cast iron pillow block housing, rated at 200,000 hours average life - All fans factory adjusted to specified fan RPM - Transit tested packaging.

Performance (*Bhp includes 11% drive loss)							
Qty	Catalog Number	Flow (CFM)	SP (inwc)	Fan RPM	Power* (HP)	FEG	FEI
2	180V7B	2425	1.00	1040	.746	n/a(<1HP)	1.46

Altitude (ft): 899 Temperature (F): 70

## Altitude (ft): 333 Motor Information

Motor Information						
HP	RPM	Volts/Ph/Hz	Enclosure	FLA	Mounted	VFD Rated
1	1725	208/3/60	ODP -PE	4.6	Yes	Yes

ELA based on NEC (2017) Table 430.25


## Sound Data: Inlet Sound Power by Octave Band

Sound Data Inlet Sound Power by Octave Band										
1	2	3	4	5	6	7	8	LwA	dBA	Sones
67	71	81	70	68	66	60	58	75	64	12.7

- Distance from Sound source 5 ft

**Accessories:**

- Premium Efficiency Motor (Min. 85.5%)
- DRIVES (1.5 SF) @ 1040 RPM
- DISCONNECT NEMA 3 PRE-WIRED
- UL762 (327Y-300DEG)
- KEYWAY GREASE TROUGH



v8.0.433.16592




**MARK: EF-1**

---

**PROJECT: ABE**

---


**DATE: 7/8/2025**



<b>Dimensions (inches)</b>	
<b>A</b>	24-13/16
<b>B</b>	39-7/16
<b>C</b>	35-7/8
<b>G</b>	3
<b>T Sq.</b>	30
<b>Roof Open. Sq.*</b>	25-1/2

NOTE: Accessories may affect dimensions shown.

**Weight(lbs)\*\*\* Shipping 149 Unit**  
\* Roof opening size for curbs supplied by Cook only.  
\*\*\*Includes fan, motor & accessories.



Page 1 of 2

# Another Broken Egg Cafe

---

JECT NO.: 13257  
WN BY: NYE  
CKED BY: NYE  
UED DATE: \_\_\_\_\_  
SSED REVISIONS: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_



**COOK**

# VCR

**MARK: EF-1**

---

**PROJECT: ABE**

---

**DATE: 7/8/2025**

## AMCA License Information




Loren Cook Company certifies that the 180V7B shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.

Performance certified is for installation type A: free inlet, free outlet. Power rating (BHP/kW) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).


# Another Broken Egg Cafe

---

PROPRIETARY



## PLAN VIEW



## CONTROLS SIDE VIEW

DESCRIPTION OF REVISION				PROJECT NAME:	ABE	
REV.	DATE	BY				
A	03-21-19	MMD	Increased Airflow, External Static Pressure & Motor Horsepower			
B	03-21-19	MMD	Increased Heating Capacity changed Burner Manufacturer from Midco			
-	-	-	-			

REF. NO./JOB NO.: V3 WTH DAMPER MODEL: V-H0X TAG: -

DRAWN BY: DATE: SCALE: NONE

CERTIFIED BY: DRAWING NO.: U:\HTR-SUBM\V-SERIES\33277

LIGHTING PLAN LEGENDS		POWER AND COMMUNICATION PLAN LEGEND		ELECTRICAL ABBREVIATIONS		ELECTRICAL SHEET GENERAL NOTES		ELECTRICAL SPECIFICATIONS	
	SWITCH TYPE (SUPERSCRIPT IN UPPERCASE)		WALL MOUNTED SIMPLEX RECEPTACLE, RATING SHALL BE SAME AS BREAKER OR AS NOTED	A	AMPERES	A.	CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH ALL EXISTING CONDITIONS THAT MAY AFFECT THE WORK. NO ADDITIONAL COMPENSATION WILL BE CONSIDERED FOR FAILURE TO DO SO.	1	GENERAL:
	20A, 120V SPST WALL SWITCH (ON)		20A, 120V WALL MOUNTED DUPLEX RECEPTACLE	AF	AMPERE FRAME / AMP FUSE	B.	CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS, TEST REPORTS, AND CERTIFICATIONS FOR TEMPORARY AND FINAL CERTIFICATE OF OCCUPANCY.		7) "EXPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.
	SWITCH TAG (SUBSCRIPT IN LOWERCASE)		20A, 120V WALL MOUNTED RECEPTACLE WITH USB OUTLET	AFF	ABOVE FINISHED FLOOR	C.	FIRE STOP ALL PENETRATIONS OF FIRE RATED CONSTRUCTION IN A CODE APPROVED MANNER IN ORDER TO MAINTAIN FIRE RATING. ALL PENETRATIONS SHALL BE SLEEVED AND SEALED WATERTIGHT.		8) "SIMILAR" OR "EQUAL": EQUAL IN MATERIALS, WEIGHT, SIZE, DESIGN AND EFFICIENCY OF SPECIFIED PRODUCT.
	WALL SWITCH WITH OCCUPANCY SENSOR		20A, 120V WALL MOUNTED HALF SWITCHED DUPLEX RECEPTACLE WITH SWITCH	AS	AMP SWITCH	D.	SECURE ALL SUPPORTS TO BUILDING STRUCTURE UTILIZING TOGGLE BOLTS (HOLLOW MASONRY), EXPANSION SHIELDS OR INSERTS (CONCRETE AND BRICK), MACHINE SCREWS (METAL), BEAM CLAMPS (FRAMEWORK), WOOD SCREWS (WOOD) OR PAN THRU STRAPS (METAL DECK), NAILS, RAWL PLUGS AND WOOD PLUGS ARE NOT PERMITTED. WHERE REQUIRED BY STRUCTURE, PROVIDE THRU BOLTS AND FISH PLATES. SUPPORT HORIZONTAL RUNS OF METALLIC RACEWAYS NOT MORE THAN 10 FT APART. SUPPORT RACEWAY RISERS AT EACH FLOOR LEVEL. RUN EXPOSED RACEWAYS PARALLEL WITH OR AT RIGHT ANGLES TO WALLS.		B. TEMPORARY LIGHT AND POWER: PROVIDE TEMPORARY LIGHT AND POWER SYSTEMS AT EARLIEST POSSIBLE DATE WITHIN THE CONSTRUCTION AREAS FOR THE REQUIREMENTS OF ALL TRADES AS HEREIN DESCRIBED. EXTEND SYSTEMS TO NEW CONSTRUCTION AS SOON AS PHYSICALLY POSSIBLE. MAINTAIN SYSTEM DURING WORKING HOURS. PROVIDE ALL REQUIRED MAINTENANCE, INCLUDING LAMPS AND SOCKETS.
	WALL SWITCH WITH VACANCY SENSOR		20A, 120V WALL MOUNTED FULL SWITCHED DUPLEX RECEPTACLE WITH SWITCH	AIC	AMPS INTERRUPTING CAPACITY	E.	BIDDERS, BEFORE SUBMITTING PROPOSALS, SHALL VISIT AND CAREFULLY EXAMINE THE AREA AFFECTED BY THIS WORK TO FAMILIARIZE THEMSELVES WITH THE EXISTING CONDITIONS AND THE DIFFICULTIES WHICH WILL ATTEND THE EXECUTION OF THIS WORK. SUBMISSION OF A PROPOSAL WILL BE CONSTRUED AS EVIDENCE THAT SUCH AN EXAMINATION HAS BEEN MADE, AND LATER CLAIMS WILL NOT BE RECOGNIZED FOR EXTRA LABOR, EQUIPMENT, OR MATERIALS, REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WHICH COULD HAVE BEEN FORESEEN HAD SUCH AN EXAMINATION BEEN MADE.		C. QUALITY ASSURANCE
	WALL SWITCH WITH TIMER		20A, 120V WALL MOUNTED GFCI DUPLEX RECEPTACLE	ATS	AUTOMATIC TRANSFER SWITCH	F.	LEAVE WIRES WITH SUFFICIENT SLACK TO PERMIT MAKING FINAL CONNECTIONS. RACEWAYS OVER 10 FT LONG IN WHICH WIRING IS NOT INSTALLED: FURNISH FISH WIRE.		1) QUALITY OF MATERIALS: ALL EQUIPMENT SHALL BE NEW SPECIFICATION GRADE, FREE FROM DEFECTS AND LISTED BY APPROVED TESTING AGENCY AND BEARING THEIR LABEL MATERIALS AND EQUIPMENT OF SIMILAR APPLICATION SHALL BE OF SAME MANUFACTURER, EXCEPT AS NOTED.
	WALL SWITCH WITH DIMMER & TIMER		20A, 120V CEILING MOUNTED DUPLEX RECEPTACLE	AUTO	AUTOMATIC	G.	INSTALL WORK SO AS TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE AND REPAIR. MINOR DEVIATIONS FROM DRAWING MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST SHALL NOT BE MADE WITHOUT APPROVAL.		2) GUARANTEE: ALL MATERIALS AND WORKMANSHIP SHALL BE GUARANTEED AS DEFINED IN PARAGRAPH 2.C.
	3 WAY WALL SWITCH (SPDT)		20A, 120V FLOOR MOUNTED DUPLEX RECEPTACLE	AWG	AMERICAN WIRE GAUGE	H.	VERIFY LOCATIONS OF OUTLETS AND SWITCHES IN FINISHED ROOMS WITH ARCHITECTURAL DRAWINGS OF INTERIOR DETAILS AND FINISH. IN CENTERING OUTLETS AND LOCATING BOXES AND OUTLETS, ALLOW FOR OVERHEAD PIPES, DUCTS AND MECHANICAL EQUIPMENT, EQUIPMENT, VARIATIONS IN FIREPROOFING AND PLASTERING, WINDOW AND DOOR TRIM, PANELING, HUNG CEILINGS AND THE LIKE. CORRECT ANY INACCURACY RESULTING FROM FAILURE TO DO SO WITHOUT EXPENSE TO OWNER.		3) HEIGHTS OF OUTLETS: REFER TO ARCHITECTURAL AND/OR INTERIOR DESIGNER'S PLANS FOR DEVICE HEIGHTS IN NON BOH SPACES.
	4 WAY / INTERMEDIATE WALL SWITCH (DPDT)		20A, 120V WALL MOUNTED QUAD RECEPTACLE	C	CONDUIT	I.	CONTRACTOR SHALL PROVIDE A WARRANTY ON ALL MATERIALS, EQUIPMENT, AND WORKMANSHIP FOR A PERIOD OF ONE YEAR FROM THE DATE OF FINAL ACCEPTANCE.		a. FROM FINISHED FLOOR TO CENTERLINE OF OUTLETS FOR:
	WALL SWITCH WITH SPEED REGULATOR		20A, 120V WALL MOUNTED SPECIAL RECEPTACLE, RATING SHALL BE SAME AS BREAKER OR AS NOTED	CB	CIRCUIT BREAKER	J.	ALL UNUSED MATERIALS AND DEBRIS SHALL BE LEGALLY REMOVED AND DISPOSED OF AWAY FROM THE PREMISES ON A DAILY BASIS.		- RECEPTACLES AND TELEPHONES: 1 FT-6 IN.
	MOTOR RATED WALL SWITCH		ISOLATED GROUND RECEPTACLE	CKT	CIRCUIT	K.	CONTRACTOR SHALL PATCH, PAINT, AND RESTORE EXISTING SURFACES DAMAGED DURING THE COURSE OF THIS CONSTRUCTION TO PRE-EXISTING CONDITIONS OR BETTER.		- WALL SWITCHES: 4 FT-0 IN.
	ThERMOSTAT WALL SWITCH		DATA OUTLET - QUANTITY AS INDICATED	CLG	CEILING	L.	MINIMUM SIZE OF CONDUIT SHALL BE $\frac{3}{4}$ ", AND TYPE SHALL BE ELECTRICAL METALLIC TUBING (EMT), UNLESS OTHERWISE NOTED. PROVIDE NYLON DRAG LINE AND CONDUIT CAP FOR ALL EMPTY CONDUITS.		- WALL FIXTURES: 7 FT-0 IN.
	MO		TELEPHONE OUTLET - QUANTITY AS INDICATED	COMM	COMMUNICATION	M.	CONNECT CONDUIT TO MOTOR CONDUIT TERMINAL BOXES WITH FLEXIBLE CONDUIT (MINIMUM 18 IN. LENGTH AND 50% SLACK). DO NOT TERMINATE IN OR FASTEN RACEWAYS TO MOTOR FOUNDATION.		- MOTOR CONTROLLERS: 5 FT-0 IN.
	PC		DATA / TELEPHONE COMBINATION OUTLET - QUANTITY AS INDICATED	CT	CURRENT TRANSFORMER	N.	PULL AND JUNCTION BOXES WHERE INDICATED ON THE DRAWINGS, SHALL BE CONSIDERED SHOWN AT THEIR APPROXIMATE LOCATION. THE CONTRACTOR SHALL LOCATE THEM AS FIELD CONDITIONS DICTATE. ADDITIONAL PULL AND JUNCTION BOXES NOT SHOWN ON DRAWINGS SHALL BE PROVIDED WHERE REQUIRED BY APPLICABLE CODE PROVISIONS OR WHERE CALLED FOR BY FIELD CONDITIONS. PULL AND JUNCTION BOXES SHALL BE SURFACE TYPE IN UNFINISHED AREAS AND INSTALLED CONCEALED IN FINISHED AREAS, AND ALL COVERS TO PULL & JUNCTION BOXES SHALL BE READILY ACCESSIBLE.		- CLOCKS: 7 FT 6 IN
	OS		DATA RACK + TELEPHONE DISTRIBUTION BOARD - AS REQUIRED	CU	COPPER	O.	SUPPORT PANEL, JUNCTION AND PULLBOXES INDEPENDENTLY TO BUILDING STRUCTURE WITH NO WEIGHT BEARING ON RACEWAYS.		b. EXCEPTIONS: AT JUNCTION OF DIFFERENT WALL FINISH MATERIALS, ON MOLDING OR BREAK IN WALL SURFACE, IN VIOLATION OF CODE, OR AS NOTED OR DIRECTED.
	OS		TAMPER RESISTANT DUPLEX RECEPTACLE	'C	DEGREE CELSIUS	P.	FOR EXACT LOCATION AND MOUNTING HEIGHT OF LIGHTING FIXTURES AND SWITCH/RECEPTACLE OUTLETS, REFER TO ARCHITECTURAL REFLECTED CEILING AND POWER PLANS.		c. REFER TO ARCHITECTURAL AND/OR INTERIOR DESIGNER'S PLANS FOR DEVICE HEIGHTS IN NON BOH SPACES.
	VS		CABLE TV OUTLET	CL	CURRENT LIMITER	Q.	ALL ELECTRICAL ACCESSORIES AND EQUIPMENT INSTALLED OUTSIDE OR EXPOSED TO WEATHER SHALL HAVE NEMA 3R ENCLOSURES AND SHALL BE TIGHTLY GASKETED FOR A COMPLETE RAIN-TIGHT INSTALLATION. ALL BUILDING EXTERIOR MOUNTED RECEPTACLES SHALL BE GFCI RATED AND MOUNTED IN WEATHERPROOF ENCLOSURE.		D. PRODUCT DELIVERY, STORAGE AND HANDLING
	DS		NON FUSED DISCONNECT SWITCH - RATING EQUAL TO OR MORE THAN BREAKER RATING	DWG	DRAWING	R.	THE CONTRACTOR'S PROPOSAL FOR ALL WORK SHALL BE PREDICATED ON THE PERFORMANCE OF THE WORK DURING REGULAR WORKING HOURS. WHEN SO DIRECTED, HOWEVER, THE CONTRACTOR SHALL INSTALL WORK DURING OVERTIME HOURS AND THE ADDITIONAL COST TO BE CHARGED THEREFOR SHALL BE ONLY THE "PREMIUM" PORTION OF THE WAGES PAID.		a. MOVING OF EQUIPMENT: WHERE NECESSARY, SHIP IN CARTED SECTIONS OF SIZE TO PERMIT PASSING THROUGH AVAILABLE SPACES.
	TC		DAY LIGHT SENSOR CEILING MOUNTED	DPSP	DOUBLE POLE SINGLE THROW	S.	UNLESS OTHERWISE SPECIFICALLY NOTED OR SPECIFIED, INCLUDE ALL CUTTING AND PATCHING OF EXISTING FLOORS, WALLS, PARTITIONS AND OTHER MATERIALS IN THE EXISTING BUILDING. THE CONTRACTOR SHALL RESTORE THESE AREAS TO ORIGINAL CONDITION.		b. ACCESSIBILITY: FOR OPERATION, MAINTENANCE AND REPAIR, MINOR DEVIATIONS SHALL BE PERMITTED. CHANGES OF MAGNITUDE OR INVOLVING EXTRA COST ARE NOT PERMISSIBLE WITHOUT REVIEW. GROUP CONCEALED ELECTRICAL EQUIPMENT REQUIRING ACCESS WITH EQUIPMENT FREELY ACCESSIBLE THROUGH ACCESS DOORS.
	LC		TIME CLOCK - DUAL CHANNEL	DPDT	DOUBLE POLE DOUBLE THROW	T.	ALL MATERIAL AND EQUIPMENT SHALL BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.		E. MATERIALS
	LC		LIGHTING CONTACTOR	E	EXISTING	U.	INSURANCE: PROVIDE IN ACCORDANCE WITH OWNER/BUILDING REQUIREMENTS AND SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND ENGINEER.		1) NAMEPLATES: PROVIDE BLACK LAMACOID SHEET WITH 3/4 IN. WHITE LETTERING, FASTENED WITH EPOXY CEMENT FOR EACH DISCONNECT SWITCH, CIRCUIT BREAKER, PANEL, CABINET, TRANSFORMER, ENCLOSURE, MOTOR CONTROLLER AND THE LIKE. NAMEPLATES SHALL DESCRIBE THE NAME AND NUMBER OF EACH COMPONENT.
	LG		BUG EYE - EMERGENCY LIGHT WITH BATTERY	ER	EXISTING TO BE RELOCATED	V.	THE FINAL ACCEPTANCE SHALL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, TESTED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATE OF INSPECTION AND APPROVAL.		2) CABLE TAGS: TAG EACH CONDUCTOR PASSING THROUGH SPLICE OR PULLBOX WITH A WHITE LINEN TAG, INDICATING POINT ORIGIN AND TERMINATION OF THE CIRCUIT.
	LG		ILLUMINATED EXIT SIGN	ETR	EXISTING TO REMAIN	W.	GENERAL PROVISIONS FOR ELECTRICAL WORK:		3) INSERTS AND SUPPORTS:
	LG		ILLUMINATED DIRECTIONAL SIGN	EOR	ENGINEER OF RECORD	X.	A. DEFINITIONS:		a. INSERTS: STEEL, SLOTTED TYPE, FACTORY PAINTED.
	LG		BUG EYE & EXIT SIGN COMBO WITH BATTERY	E.C.	ELECTRICAL CONTACTOR	Y.	1) "PROVIDE": TO FURNISH, INSTALL AND CONNECT UP COMPLETE AND READY FOR SAFE AND REGULAR OPERATION THE PARTICULAR WORK REFERRED TO UNLESS SPECIFICALLY OTHERWISE NOTED.		- SINGLE ROD: SIMILAR TO GRINNELL FIG. 281.
				FA	FIRE ALARM	Z.	2) "INSTALL": TO ERECT, MOUNT AND CONNECT COMPLETE WITH RELATED ACCESSORIES.		- MULTI-ROD: SIMILAR TO FEE AND MASON SERIES 9000 WITH END CAPS AND CLOSURE STRIPS.
				G	GROUND		3) "FURNISH" OR "SUPPLY": TO PURCHASE, PROCURE, ACQUIRE AND DELIVER COMPLETE WITH RELATED ACCESSORIES.		- CLIP FORM NAILS FLUSH WITH INSERTS.
				GFI	GROUND FAULT INTERRUPTER		4) "WORK": LABOR, MATERIALS, EQUIPMENT, APPARATUS, CONTROLS, ACCESSORIES AND OTHER ITEMS REQUIRED FOR PROPER AND COMPLETE INSTALLATION.		- MAXIMUM LOADING 75 PERCENT OF RATING.
				G.C.	GENERAL CONTRACTOR		5) "WIRING": RACEWAY, FITTINGS, WIRE, BOXES, AND RELATED ITEMS.		b. SUPPORTS FROM BUILDING CONSTRUCTION: INSERTS, BEAM CLAMPS, STEEL FISHPLATES (IN CONCRETE FILL ONLY), CANTILEVER BRACKETS OR OTHER MEANS. SUBMIT FOR REVIEW.
				HD	HAND DRYER		6) "CONCEALED": EMBEDDED IN MASONRY OR OTHER CONSTRUCTION, INSTALLED IN FURRED SPACES, WITHIN DOUBLE PARTITIONS OR HUNG CEILINGS, IN TRENCHES, IN CRAWL SPACES, OR IN ENCLOSURES.		c. GROUPED LINES AND SERVICES: TRAPEZE HANGERS OF BOLTED ANGLES OR CHANNELS.
				HP	HORSEPOWER				d. WHERE BUILDING CONSTRUCTION IS INADEQUATE: PROVIDE ADDITIONAL FRAMING. SUBMIT FOR REVIEW.
				HZ	HERTZ				F. SUBMIT ELECTRICAL POWER SYSTEM STUDIES INCLUDING SUPPORTING DATA AND RECOMMENDATIONS FOR THE FOLLOWING:
				IG	ISOLATED GROUND		1) SHORT CIRCUIT CURRENT AND PROTECTIVE DEVICE COMBINATION.		1) SHORT CIRCUIT CURRENT AND PROTECTIVE DEVICE COMBINATION.
				IC	INTERRUPTING CAPACITY		2) ARC FLASH HAZARD ANALYSIS.		2) ARC FLASH HAZARD ANALYSIS.
				JB	JUNCTION BOX				EQUIPMENT SHOP DRAWINGS SHALL NOT BE SUBMITTED UNTIL THESE STUDIES HAVE BEEN COMPLETED.
				KCMIL	ONE THOUSAND CIRCULAR MILS				G. PAINT SHALL BE THE BEST GRADE FOR ITS PURPOSE. DELIVER IN ORIGINAL SEALED CONTAINERS AND APPLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. COLORS SHALL BE AS SELECTED BY ARCHITECT OR ENGINEER. UTILIZE GALVANIZED IRON PRIMER ON PANEL AND PULL BOXES, AFTER FABRICATION. UTILIZE HOT DIPPED GALVANIZED OR DIPPED IN ZINC BASED PRIMER FOR: OUTLET BOXES, JUNCTION BOXES, CONDUIT HANGERS, RODS, INSERTS AND SUPPORTS. ZINC BASED PRIMER WITH FINISH TO MATCH SURROUNDINGS SHALL BE USED FOR MARRED SURFACES OF STEEL EQUIPMENT AND RACEWAYS. A FIELD-APPLIED ZINC BASED PRIME COAT SHALL BE UTILIZED FOR STEEL OR IRONWORK.
				KV	KILOVOLT				H. BRUSH AND CLEAN WORK PRIOR TO CONCEALING, PAINTING AND ACCEPTANCE. PAINTED EXPOSED WORK SOILED OR DAMAGED; CLEAN AND REPAIR TO MATCH ADJOINING WORK BEFORE FINAL ACCEPTANCE. REMOVE DEBRIS FROM INSIDE AND OUTSIDE OF MATERIAL AND EQUIPMENT.
				KVA	KILOVOLT-AMPERES				I. FINAL LOCATIONS AND MOUNTING ORIENTATIONS OF ALL SWITCHES, RECEPTACLES AND LIGHT FIXTURES SHALL BE VERIFIED WITH ARCHITECT.
				KW	KILOWATTS				J. ALL ACCESS DOOR LOCATIONS SHALL BE REVIEWED BY ARCHITECT PRIOR TO INSTALLATION.
				LP	LIGHTING PANEL				
				LL	LANDLORD				
				LTG	LIGHTING				
				MAX	MAXIMUM				
				MCB	MAIN CIRCUIT BREAKER				
				MIN	MINIMUM				
				MLO	MAIN LUGS ONLY				
				N	NEUTRAL				
				NIC	NOT IN CONTRACT				
				NL	NIGHT LIGHT				
				NTS	NOT TO SCALE				
				PP	POWER PANEL				
				PVC	POLYVINYL CHLORIDE				
				PWR	POWER				
				R	REMOVE				
				RE	RELOCATED EXISTING				
				RR	REMOVE & RELOCATE				
				SPDT	SINGLE POLE DOUBLE THROW				

ELECTRICAL SPECIFICATIONS									
3. SCOPE OF WORK:	5. AS-BUILT DRAWINGS AND EQUIPMENT OPERATIONAL INSTRUCTIONS	10. DISCONNECTS	14. WIRE AND CABLE:	16. ELECTRICAL WIRING METHOD:					
A. SCOPE OF WORK SHALL CONSIST OF PROVIDING LABOR, MATERIALS, EQUIPMENT, SERVICES AND FEES NECESSARY FOR COMPLETE AND SAFE INSTALLATION IN CONFORMING WITH THE APPLICABLE CODES WITH LOCAL AMENDMENTS, AND ALL OTHER APPLICABLE INDUSTRY, NATIONAL AND LOCAL CODES AND AUTHORITIES HAVING JURISDICTION, AS INDICATED ON DRAWINGS AND HEREIN SPECIFIED.	A. UPON COMPLETION AND ACCEPTANCE OF WORK, CONTRACTOR SHALL FURNISH WRITTEN INSTRUCTIONS AND EQUIPMENT MANUALS AND DEMONSTRATE TO THE OWNER THE PROPER OPERATION AND MAINTENANCE OF ALL EQUIPMENT AND APPARATUS FURNISHED UNDER THIS CONTRACT.	A. DISCONNECT SWITCHES SHALL CONFORM TO NEMA AND UL STANDARDS, AND SHALL BE HORSEPOWER RATED.	A. PROVIDE WIRE AND CABLE COMPLETE WITH ACCESSORIES. SIZE REFERENCE SHALL BE AWG EXCEPT AS NOTED.	A. ALL CONDUIT SHALL BE RUN CONCEALED IN SO FAR AS IS PRACTICABLE. CONDUITS SHALL BE EXPOSED ONLY WHERE SO INDICATED ON THE DRAWINGS OR IN UNFINISHED AREAS SUCH AS ELECTRICAL AND BOILER ROOMS.					
B. ALL DRAWINGS, PLANS, DETAILS, SPECIFICATIONS AND SPECIFICATION ADDENDA ARE MADE PART OF THIS CONTRACT AND SHALL APPLY TO ALL WORK UNDER THE CONTRACT UNLESS OTHERWISE AMENDED, MODIFIED, SUPPLIED OR SPECIFIED HEREIN.	B. THESE INSTRUCTIONS SHALL BE TYPED ON 8-1/2 IN. X 11 IN. PAPER AND BOUND IN THREE RING BINDERS WITH CLEAR ACETATE COVERS. CONTRACTOR SHALL GIVE THREE COPIES OF THE INSTRUCTIONS TO THE OWNER AND ONE COPY TO THE ENGINEER.	B. SWITCHING MECHANISM SHALL BE QUICK-MAKE, QUICK-BREAK, SINGLE THROW WITH EXTERNAL OPERATING HANDLE MECHANICALLY INTERLOCKED WITH ENCLOSURE COVER TO PROVIDE ACCESS TO INTERIOR WHEN DISCONNECT IS IN OFF POSITION ONLY. PROVIDE MEANS TO LOCK OPERATING HANDLE IN THE OPEN AND CLOSED POSITION. DESIGNATE ON THE ENCLOSURE THE OPEN AND CLOSED POSITION OF THE OPERATING HANDLE.	B. PROVIDE RACEWAYS ONLY AS HEREIN SPECIFIED, EXCEPT AS NOTED. RACEWAYS SHALL BE RUN CONCEALED, EXCEPT AS NOTED.	B. MINIMUM CONDUIT SIZE SHALL BE 3/4" UNLESS NOTED OTHERWISE ON THE PLANS.					
C. THE CONTRACTOR SHALL FURNISH A WRITTEN GUARANTEE TO REPLACE OR REPAIR PROMPTLY AND ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED FOR ANY WORKMANSHIP AND EQUIPMENT IN WHICH DEFECTS DEVELOP WITHIN ONE YEAR FROM THE DATE OF FINAL CERTIFICATE FOR WORK AND FROM DATE OF ACTUAL USE OF EQUIPMENT OR OCCUPANCY OF SPACES BY OWNER, INCLUDED UNDER THE VARIOUS PARTS OF THE WORK, WHICHEVER DATE IS EARLIER. THIS WORK SHALL BE DONE AS DIRECTED BY THE OWNER. THIS GUARANTEE SHALL ALSO BE PROVIDED THAT WHERE DEFECTS OCCUR, THE CONTRACTOR WILL ASSUME RESPONSIBILITY OF OTHER TRADES AFFECTED BY DEFECTS, REPAIRS OR REPLACEMENTS IN EQUIPMENT SUPPLIED BY THE CONTRACTOR.	C. THE INSTRUCTION BOOKLET SHALL BEAR THE NAME, ADDRESS AND TELEPHONE NUMBER OF THE PROJECT, ARCHITECT AND ENGINEER.	C. SWITCHES SHALL BE OF THE DOUBLE STATIONARY CONTACT TYPE.	C. PROVIDE RACEWAY SUPPORT UTILIZING CEILING TRAPEZE, STRAP HANGERS, OR WALL BRACKETS. PROVIDE U-BOLTS AT EACH FLOOR LEVEL OF RISER RACEWAYS AND CONNECTED TO ACCEPTABLE SUPPORTS. PROVIDE RISER CLAMPS AT EACH FLOOR LEVEL OF RISER RACEWAYS AND RESTING ON SLAB. FOR THROUGH-THE-FLOOR SYSTEMS, UTILIZE AN ASSEMBLY SIMILAR TO HUBBELL FIRE RATED POKE-THROUGH-FLOOR BOX SYSTEM. FOR ABOVE FLOOR FITTINGS, TELEPHONE SHALL BE BUSHED HOLE AND POWER SHALL BE DUPLEX RECEPTACLE OR OTHER AS NOTED. PROVIDE SEPARATION BARRIER BETWEEN POWER AND TELEPHONE COMPARTMENTS. PROVIDE JUNCTION BOX ON UNDERSIDE OF FLOOR. PACK FITTING TO RESTORE FIRE RATING OF FLOOR.	C. RIGID METAL CONDUIT: HOT DIPPED GALVANIZED, MILD STEEL PIPE, ZINC COATED THREADS WITH AN OUTER COATING OF ZINC BICHROMATE, AS MANUFACTURED BY TRIANGLE, REPUBLIC, WHEATLAND OR EQUAL.					
D. THE CONTRACTOR SHALL GIVE NECESSARY NOTICE, FILE DRAWINGS AND SPECIFICATIONS WITH ALL DEPARTMENTS HAVING JURISDICTION, WORK AND PAY ALL FEES THEREFORE. THE CONTRACTOR SHALL ARRANGE FOR INSPECTION AND TESTS OF ANY OR ALL PARTS OF THE WORK IF SO REQUIRED BY AUTHORITIES AND PAY ALL CHARGES FOR SAME. THE CONTRACTOR SHALL PAY ALL COSTS FOR, AND FURNISH TO THE OWNER BEFORE FINAL BILLING, ALL CERTIFICATES NECESSARY AS EVIDENCE THAT THE WORK INSTALLED CONFORMS WITH ALL REGULATIONS WHERE THEY APPLY TO THIS WORK.	D. REPRODUCIBLE "AS-BUILT" DRAWINGS SHALL BE PROVIDED INDICATING THE AS INSTALLED CONDITIONS OF THE WORK. "AS-BUILT" DRAWINGS SHALL BE PROVIDED TO THE ARCHITECT AFTER COMPLETION OF THE INSTALLATION.	D. SWITCHES SHALL BE EQUIPPED WITH REJECTION TYPE FUSE HOLDERS, FUSIBLE AS SHOWN ON THE DRAWINGS; PROVIDE COMPLETE WITH FUSES AS SCHEDULED.	D. INSULATION SHALL BE RUBBER AND THERMOPLASTIC MEETING ASTM AND IPECA STANDARDS. TYPE THW OR THHN SHALL BE UTILIZED FOR FEEDERS AND BRANCH CIRCUITS EXCEPT AS NOTED. TYPE SFF-2 SHALL BE UTILIZED FOR BRANCH CIRCUITS LOCATED IN WIRING CHANNELS OF CONTINUOUS FLUORESCENT FIXTURES AND IN AMBIENT TEMPERATURES OVER 90 DEG C. FOR UNGROUNDED ISOLATED BRANCH CIRCUITS PROVIDE CROSS-LINKED POLYETHYLENE INSULATION (TYPE XHHW).	D. INTERMEDIATE METAL CONDUIT (IMC): HOT DIPPED GALVANIZED, MILD STEEL PIPE, ZINC COATED THREADS WITH AN OUTER COATING OF ZINC BICHROMATE AS MANUFACTURED BY TRIANGLE, REPUBLIC, WHEATLAND OR EQUAL.					
E. CONTRACTOR SHALL PERFORM ALL CONTROLLED INSPECTIONS IN ACCORDANCE WITH THE NEC BUILDING CODE. SECURE ALL REQUIRED PERMITS AND APPROVALS AND TRANSMIT SAME TO OWNER. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL FEES.	F. LOW-VOLTAGE DISTRIBUTION EQUIPMENT:	11. INSTALLATION	E. INSULATION SHALL BE RUBBER AND THERMOPLASTIC MEETING ASTM AND IPECA STANDARDS. TYPE THW OR THHN SHALL BE UTILIZED FOR FEEDERS AND BRANCH CIRCUITS EXCEPT AS NOTED. TYPE SFF-2 SHALL BE UTILIZED FOR BRANCH CIRCUITS LOCATED IN WIRING CHANNELS OF CONTINUOUS FLUORESCENT FIXTURES AND IN AMBIENT TEMPERATURES OVER 90 DEG C. FOR UNGROUNDED ISOLATED BRANCH CIRCUITS PROVIDE CROSS-LINKED POLYETHYLENE INSULATION (TYPE XHHW).	E. FLEXIBLE METAL CONDUIT: GALVANIZED OR ZINC METALIZED STEEL, SINGLE STRIP INTERLOCKED CONSTRUCTION AS MANUFACTURED BY TRIANGLE, ANACONDA, AMERICAN FLEXIBLE CONDUIT, ELECTRIC-FLEX, OR EQUAL.					
F. AREAS WITH NO ELECTRICAL WORK SHALL REMAIN AS IS. CONTRACTOR SHALL MAINTAIN CONTINUITY OF ALL ELECTRICAL SYSTEMS TO ALL AREAS NOT COVERED BY THIS RENOVATION AND SHALL PROVIDE 48 HOUR NOTICE TO LANDLORD OF ANY PLANNED POWER INTERRUPTIONS OR SIGNAL SYSTEM OUTAGES.	G. IDENTIFICATION	A. DISTRIBUTION PANEL BOARD SHALL BE MOUNTED TO STRUCTURAL STEEL CHANNEL (KINDOF) WHICH SHALL BE BOLTED TO THE WALL USING EXPANSION ANCHORS FOR LARGE PANELS.	F. ELECTRIC METALLIC TUBING (EMT): HOT DIPPED GALVANIZED, MILD STEEL TUBE, ZINC COATED, AS MANUFACTURED BY TRIANGLE, REPUBLIC, WHEATLAND OR EQUAL.						
4. SHOP DRAWINGS	H. PANEL BOARD SHALL HAVE ENGRAVED WHITE CORE, BLACK LAMACOID NAMEPLATE SCREWED ONTO PANE TRIM WITH DESIGNATION LISTED (PANEL BOARD NAME, VOLTAGE, RATING OR MAINS IN AMPS).	B. IDENTIFICATION	G. RIGID METAL CONDUIT: TYPE MC, COPPER CONDUCTOR, 600 VOLT THERMOPLASTIC INSULATION, 90 DEG. C, INTERLOCKED STEEL TAPE ARMOR.						
A. PRIOR TO THE INSTALLATION OF ANY WORK AND PROCUREMENT OF EQUIPMENT, CONTRACTOR SHALL PROVIDE COMPLETE SETS OF COORDINATED SHOP DRAWINGS OF ALL NEW AND EXISTING EQUIPMENT, INDICATING CAPACITY, DIMENSIONS AND SEQUENCE OF OPERATION FOR WRITTEN APPROVAL BY THE ARCHITECT AND ENGINEER.	I. PANEL BOARD SHALL HAVE MAIN CIRCUIT BREAKER OR MAIN LUGS AS INDICATED ON THE DRAWINGS. QUANTITY, POLES AND TRIP RATINGS OF BRANCH CIRCUIT BREAKERS TO BE AS INDICATED ON DRAWINGS.	C. DISCONNECT SWITCHES SHALL BE FUSED OR NONFUSED AS NOTED. VOLTAGE SHALL BE AS REQUIRED. SWITCHES SHALL BE HEAVY DUTY, EXCEPT AS NOTED, AND HORSEPOWER RATED FOR MOTOR LOADS. TOGGLE TYPE SWITCHES SHALL BE NONFUSED, LOAD BREAKING MAXIMUM RATING OF 20 AMP AT 600 VOLTS AND 10 AMP AT 120 VOLTS. TWO POLE SWITCHES SHALL BE SIMILAR TO HART AND HEEGEMAN NO. 6808P. THREE-POLE SWITCHES SHALL BE SIMILAR TO HART AND HEEGEMAN NO. 7810F. KNIFE-BLADE TYPE SWITCHES SHALL BE LOAD BREAK, QUICK-MAKE, QUICK-BREAK, UL CLASS R UP TO 600 AMP, MAXIMUM RATING EXCEPT AS NOTED SHALL BE 800 AMP. ARC QUENCHERS SHALL BE PROVIDED. SWITCHES SHALL BE SIMILAR TO GENERAL ELECTRIC QMR. ALL SWITCH ENCLOSURES SHALL BE DEAD FRONT, NEMA TYPE 1, EXCEPT AS NOTED.	H. METAL CLAD CABLE, NFPA 70 ARTICLE 330 TYPE MC:						
B. INDICATE ON EACH SHOP DRAWINGS SUBMITTED:	J. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	K. ARMORED CABLE: TYPE AC, COPPER CONDUCTOR, 600 VOLT THERMOPLASTIC INSULATION, 90 DEG. C.							
1) PROJECT NAME AND LOCATION	K. PANEL BOARD SHALL HAVE ENGRAVED WHITE CORE, BLACK LAMACOID NAMEPLATE SCREWED ONTO PANE TRIM WITH DESIGNATION LISTED (PANEL BOARD NAME, VOLTAGE, RATING OR MAINS IN AMPS).	L. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	M. ANY EXPOSED RACEWAY SHALL BE RUN TRUE, PLUMB AND PARALLEL OR PERPENDICULAR TO BUILDING LINES.						
2) NAME OF ARCHITECT AND ENGINEER	L. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	N. ALL CONDUCTORS SHALL BE COPPER.							
3) ITEM IDENTIFICATION	M. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	O. RACEWAYS SHALL BE SEALED WHERE ENTERING PULL BOXES OR STRUCTURES.							
4) APPROVAL STAMP OF PRIME CONTRACTOR	N. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	P. SINGLE CONDUCTOR CABLES SHALL BE USED FOR FEEDERS AND BRANCH CIRCUIT WIRING (EXCEPT WHERE AC AND MC CABLE IS USED). MINIMUM SIZE WIRE SHALL BE #12 AWG UNLESS OTHERWISE INDICATED AND SHALL BE SIZED TO CONFORM TO NORMAL NEC VOLTAGE DROPS. WIRE SIZES #10 AWG AND SMALLER SHALL BE SOLID, #8 AWG AND LARGER SHALL BE STRANDED.							
C. SUBMISSIONS:	O. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	Q. FEEDERS AND ALL WIRING IN MOIST OR WET LOCATIONS UNDERGROUND OR UNDER THE SLAB SHALL BE 600 VOLT CODE TYPE THHN-THWN. BRANCH CIRCUIT WIRING IN DRY LOCATIONS, ABOVE GRADE, IN THE INTERIOR OF THE BUILDING SHALL BE 600 VOLT CODE TYPE THHN-THWN OR XHHW.							
1) SUBMISSIONS 11 IN. X 17 IN. OR SMALLER: IF THE SUBMISSION IS A CATALOG CUT, THEN THE CONTRACTOR SHALL SUBMIT ONE ORIGINAL AND TWO COPIES, OTHERWISE, HE SHALL SUBMIT THREE COPIES. THE ARCHITECT WILL FORWARD THE ORIGINAL AND ONE COPY (TWO COPIES WHEN NO ORIGINAL IS RECEIVED) TO THE ENGINEER. ALL CATALOG CUTS SHALL BE COMPLETE.	P. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	R. WIRING TO RECESSED FIXTURE AND WITHIN FIXTURE RACEWAYS SHALL BE TYPE THHN, #12 AWG MINIMUM.							
2) SUBMISSIONS LARGER THAN 11 IN. X 17 IN.: SUBMIT TWO PRINTS AND ONE PAPER SEPIA TO THE ARCHITECT. THE ARCHITECT WILL FORWARD ONE PRINT AND THE PAPER SEPIA TO THE ENGINEER.	Q. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	S. EQUIPMENT GROUND: GREEN CONDUCTOR SHALL BE USED.							
D. SUBMIT SHOP DRAWINGS FOR THE FOLLOWING:	R. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	T. COLOR CODING SHALL BE AS FOLLOWS:							
1) SAFETY/DISCONNECT SWITCHES	S. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	1. 120/208 VOLT SYSTEM:							
2) FUSES	T. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	2. BLACK FOR A PHASE							
3) CIRCUIT BREAKERS	U. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	3. RED FOR B PHASE							
4) DISTRIBUTION EQUIPMENT INCLUDING SWITCHBOARDS, TRANSFORMERS, PANELBOARDS AND LOAD CENTERS.	V. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	4. BLUE FOR C PHASE							
5) RACEWAYS	W. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	X. NEUTRAL WIRE SHALL UTILIZE WHITE OUTER COVERING THROUGHOUT. EQUIPMENT GROUND WIRE SHALL UTILIZE GREEN OUTER COVERING THROUGHOUT.							
6) WIRE AND CABLE	X. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	Y. WHERE COLOR-CODED CABLE IS NOT AVAILABLE, CERTIFY IN WRITING AND REQUEST PERMISSION TO OVERLAP CONDUCTORS WITH 6 IN. OF COLOR TAPE IN ACCESSIBLE LOCATIONS.							
7) LIGHTING CONTROL DEVICES	Z. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	A. PROVIDE FLAMEPROOF LINEN OR FIBER TAGS IN ACCESSIBLE LOCATIONS. FOR FEEDERS INDICATE FEEDER NUMBER, SIZE, PHASE AND POINTS OF ORIGIN AND TERMINATIONS. FOR CONTROL AND ALARM WIRING INDICATE TYPE (CONTROL OR ALARM), SIZE OF WIRE, AND POINTS OF ORIGIN AND TERMINATIONS.							
8) INSERTION RECEPTACLES	AA. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	B. TERMINATIONS, SPLICES AND TAPS UNDER 600 VOLTS: COPPER CONDUCTORS NO. 10 AND SMALLER SHALL UTILIZE COMPRESSION-TYPE OF TWIST-ON SPRING-LOADED CONNECTORS AND CLEAR NYLON ISOLATED COVERING. COPPER CONDUCTORS NO. 8 AND LARGER SHALL UTILIZE MECHANICAL BOLT-TERMINATION OR THERMOPLASTIC COMPRESSION TYPE USING MANUFACTURER'S RECOMMENDED TOOLS. CABLE LUGS AND CONNECTORS SHALL UTILIZE COMPRESSION-TYPE OF SAME METAL AS CONDUCTOR. PROVIDE TO MATCH CABLE, WITH MARKING INDICATING SIZE AND TYPE. COPPER LUG CONNECTIONS TO BUS BARS: USE ANTISEIZE COMPOUND ON TANG.							
9) MOMENTARY CONTACT SWITCHES	AB. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	C. NOT MORE THAN 3 LIGHTING OR CONVENIENCE OUTLET CIRCUITS SHALL BE INSTALLED IN ONE CONDUIT UNLESS OTHERWISE INDICATED. PULL NO THERMOPLASTIC WIRES AT TEMPERATURES LOWER THAN 32 DEG F. PROVIDE SEPARATE RACEWAYS FOR CONDUCTORS OF 120/208 AND 265/460 VOLT SYSTEMS, EXCEPT 460 VOLT MOTOR BRANCH CIRCUIT WIRING AND RELATED 120 VOLT CONTROL WIRING. THERMOPLASTIC WIRES SHALL NOT BE INSTALLED IN COMPUTER AREA RAISED FLOORS.							
10) TIME SWITCHES	AC. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	D. LEAVE WIRES WITH SUFFICIENT SLACK TO PERMIT MAKING FINAL CONNECTIONS.							
11) LIGHTING FIXTURES, BALLASTS AND LAMPS.	AD. EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS). FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.	E. PERFORM							

## LIGHTING, FIXTURE LEGEND

FXTR#	SYMBOL	DESCRIPTION	LOCATION	HEIGHT	MODEL #
C-1	○	PENDANT - METAL	OVER BAR	8'-0" AFF	HILITE PENDANT, BR47 RUST ITEM # H-SLBN988BC CORD MOUNT SIZE: 8" Dia x 4.75H; WATTAGE: 100 WATT; BULB: SOFT LT LED, LAMPS: 1, 120v
C-2	○	CHANDELIER - GLASS GLOBE	DINING ROOM	10'-0" AFF (CENTER OF FIXTURE)	KICHLER - CHANDELIER, SKU # 43119BK, FINISH: BLACK; SIZE: 47" W x 53 1/2" H; WATTAGE: 40 W (SOFT WHITE BULB) (INCANDESCENT)
C-3	○	WALL SCONCE COPPER	OVER DECOR MIRROR WINDOW	REFERENCE ELEVATIONS	HILITE GOOSENECK, 152-OLD NICKEL (ARM & CAP) w/ 44- POLISHED COPPER SHADE; SIZE: 13.25" H x 12" W x 18" WATTAGE: 200 WATT; BULB: SOFT LIGHT LED, LAMPS: 1, 120v
C-4	○	PENDANT LOFT SHADE	CENTER OVER TABLES	8'-0" AFF	LOFT SHADE VISUAL COMFORT, ITEM # 5202DR-NP FINISH: DARK IRON; SIZE: 20.5" H x 19.5" W x 10D; BULB: 60W SOFT WHITE LED EQ; CANDLE BASE 4#PER FIXTURE
C-5	---	LED STRIP LIGHT	BAR LIQUOR STEPS	N/A	LUMINI PREMIUM GRADE WARM DIMMING LINED STRIP, MODEL #LLWD68, CCT: 1900K, 2400K, 2700K, 5.5W
C-6	△	BLACK TRACK LIGHTING (2', 4', & 8' TRACK LENGTHS) w/ SPOT LIGHTS 5' APART TYP.	DINING ROOM	11'-0" AFF BTM OF TRACK	JUNO TRACK & TRACK FIXTURES, SKU #: R#BL (LENGTHS VARY), TRACK LIGHT R 6001-G2; FINISH: BLACK; WATTAGE: 10 WATT PER LAMP; BULB: LED
C-7	○	CAN LIGHT	RESTROOM & RESTROOM VESTIBULE	MOUNTED IN CEILING GRID OR DRYWALL SOFFIT	LITELINE 6" RECESSED CAN LIGHT, MODEL # R456-17F-20WHWH P-510 FINISH: 17W TRIM: WHITE, CCT LIGHT COLOR: SOFT LT, 3000K
C-8	---	2x4	BACK OF HOUSE & OFFICE	MOUNTED IN CEILING GRID	TCP 2x4" LAY-IN LED FIXTURE - WHITE TRIM, MODEL NUMBER: DTF-4UZDB1CC, 4400L WATT, 46W
C-9	○	CEILING FAN	DINING ROOM	13'-0" AFF	MINKAAL INTERIOR CEILING FAN, ITEM# F524-CL, FINISH: COAL, SIZE: 52" SWEEP NO LAMPING, 57.72W
C-10		NOT USED			
EXIT	EXIT	EXIT DIRECTION SIGN	ABOVE DOOR OR BULKHEAD		NAVILITE EXIT LIGHT W/ BATTERY BACKUP; MODEL: TP-U-R-W-EM,2.5W
EM	---	WALL MOUNTED EMERGENCY LIGHTING	WHERE NOTED ON DRAWINGS		ASTRALITE - HEAD EMERGENCY LIGHT; MODEL: EEU-U-R-W-EM,2W
EM1	---	EXIT SIGN	ABOVE DOOR (INTERIOR)		NAVILITE EXIT / EMERGENCY COMBINATION LIGHT; MODEL: #NXP3CRWH (OR EXISTING),5.4W
EM2	---	REMOTE HEAD (IF NOT EXISTING)	ABOVE DOOR (EXTERIOR)		EXTONTRONIX, (SINGLE) REMOTE LAMPS FOR LED EXIT, COMBO OR EMERGENCY UNITS (WEATHERPROOF) MODEL: MLED1-W-WP; FINISH: WHITE (OR EXISTING)

## LIGHTING FIXTURE SCHEDULE NOTES:

A. ALL (NEW) LIGHTING FIXTURES SHOWN ON THE LIGHTING FIXTURES SCHEDULE ARE SUBJECT TO THE ARCHITECTS APPROVAL. E.C. SHALL COORDINATE MAKE, MODEL, FINISHES, AND OTHER CRITICAL PARAMETERS WITH THE ARCHITECT BEFORE PURCHASING.

B. THE ADDITIONAL ACCESSORIES (VIZ. DRIVERS AND CURRENT LIMITERS) REQUIRED FOR THE PROPER WORKING OF THE LIGHTING FIXTURES MIGHT NOT BE PROVIDED BY THE VENDOR. E.C. SHALL PURCHASE IT SEPARATELY.

C. ALL LIGHTING FIXTURES ARE RATED FOR 120V UNLESS OTHERWISE NOTED.

D. ALL EMERGENCY LIGHTING FIXTURES AND EXIT SIGNS SHALL HAVE A MINIMUM OF 90 MINUTES OF BATTERY BACKUP OR AS REQUIRED BY AHJ.

E. WATTS PER FACE FOR EXIT SIGNS SHALL NOT EXCEED 5 WATTS.

F. ALL LIGHTING CONTROLS SHALL BE PER AHJ AND CODE COMPLIANCE.

G. ALL LIGHT FIXTURES OVER FOOD SERVICE AREA SHALL HAVE LENS COVERS OR SHATTER PROOF BULBS.

LIGHT SWITCHING SCHEDULE							
CIRCUIT #	CONTACTOR#	AUTO. CONTROL	SWITCH#	SWITCH TYPE	SWITCH BANK	LOAD IN VA	NOTES
C-3	L1	TIME CLOCK	a	DIMMER	SB	480	1,2
C-3	L1	TIME CLOCK	b	DIMMER	SB	400	1,2
C-5	L2	TIME CLOCK	c	DIMMER	SB	250	1,2
C-5	L2	TIME CLOCK	d	DIMMER	SB	360	1,2
C-5	L2	TIME CLOCK	e	DIMMER	SB	102	1,3
C-1	L3	TIME CLOCK	f	DIMMER	SB	782	1,2
C-1	L3	TIME CLOCK	g	DIMMER	SB	119	1,2
B-2	L4	TIME CLOCK	-	-	-	1200	-

1- COORDINATE EXACT LOADING CAPACITY OF THE SWITCH AND SENSOR WITH THE VENDOR.

2- NUMBER OF SENSOR AND SWITCHES REQUIRED MAY VARY BASED ON THE LOADING CAPACITY OF THE SENSOR AND SWITCH.

## LIGHTING PLAN GENERAL NOTES

A. ALL LIGHT FIXTURES NOT ON THE OCCUPANCY SENSOR/OTHER AUTOMATIC CONTROL SHALL BE CONTROLLED BY TIMER-CONTROLLED LIGHTING CONTACTOR(S), UON.

B. THE OCCUPANCY SENSOR, TIMERS, AND OTHER APPROVED LIGHTING CONTROLS SHALL MATCH THE CONTROL FUNCTION REQUIREMENT SPECIFIED IN THE IECC C405.2.

C. LIGHTING CONTROLS (SENSORS AND SWITCHES) SHALL BE RATED FOR LINE VOLTAGE (UON); ELSE PROVIDE POWER BASE.

D. THE OCCUPANCY SENSORS SHALL BE SET TO TURN OFF THE LIGHTS WITHIN 20 MINUTES AFTER ALL OCCUPANTS LEAVE THE SPACE.

E. THE TIME CLOCK (MIN. 2 CHANNEL) SHALL BE SCHEDULED AS PER THE REQUIREMENT OF THE PROJECT SPACE. COORDINATE WITH OWNER/LANDLORD.


F. EMERGENCY LIGHT FIXTURES (BUG EYES) SHALL TURN ON DURING POWER FAILURE WHEREAS ALL EXIT SIGNS SHALL BE PERMANENTLY ON. E.C. TO WIRE THE FIXTURE ACCORDINGLY.

G. E.C. SHALL REARRANGE (IF REQUIRED) THE EMERGENCY FIXTURES TO PROVIDE INITIAL ILLUMINATION THAT IS NOT LESS THAN AN AVERAGE OF 1 FOOTCANDLE (11 LUX) AND A MINIMUM AT ANY POINT OF 0.1 FOOTCANDLE (1 LUX) MEASURED ALONG THE PATH OF EGRESS AT FLOOR LEVEL. ILLUMINATION LEVELS SHALL BE PERMITTED TO DECLINE TO 0.6 FOOTCANDLE (6 LUX) AVERAGE AND A MINIMUM AT ANY POINT OF 0.06 FOOTCANDLE (0.6 LUX) AT THE END OF THE EMERGENCY LIGHTING TIME DURATION. A MAXIMUM-TO-MINIMUM ILLUMINATION UNIFORMITY RATIO OF 40 TO 1 SHALL NOT BE EXCEEDED.

H. THE WATTAGE RATING OF THE CURRENT LIMITERS SHALL NOT EXCEED THE WATTAGE RATING INDICATED ON THE PLAN.

## LIGHTING PLAN KEYED NOTES: (○)

- COORDINATE THE EXACT LOCATION OF THE MANUAL OVERRIDE SWITCH WITH THE ARCHITECT AND OWNER. THE SWITCH SHALL BE CAPABLE OF TURNING OFF THE CONTROLLED LIGHTING (CONNECTED VIA TIME CLOCK AND CONTACTORS) IMMEDIATELY UPON ACTIVATION, WITH A MAXIMUM OVERRIDE DURATION OF 2 HOURS.
- LOOP ALL EMERGENCY LIGHT FIXTURES, AND EXIT SIGNS AND CONNECT TO THE NEAREST LIGHTING BRANCH CIRCUIT AHEAD OF ALL SWITCHING AND CONTROLS AS PER STATE AND LOCAL CODES.
- E.C. SHALL COORDINATE THE EXACT LOCATION OF THE LIGHTING AND FAN SWITCH BANK IN THE FIELD. ALL THE SWITCHES TAGGED AS (\$ @ SB/\$ @ SB1) IN THE PLAN SHALL BE INSTALLED IN THE SWITCH BANK. REFER TO THE LIGHTING PLAN FOR THE NUMBER OF THE SWITCHES REQUIRED. E.C. SHALL LABEL EACH SWITCH WITH THE AREA IT CONTROLS FOR EASY IDENTIFICATION.
- COORDINATE WITH THE W.I.C. VENDOR FOR THE LIGHTING FIXTURES, SWITCHES, AND ELECTRICAL CONNECTION REQUIREMENTS. PROVIDE JUNCTION BOX, CIRCUIT, AND SWITCH FOR WALK-IN COOLER AS REQUIRED.
- THE E.C. SHALL COORDINATE WITH ARCHITECT/OWNER FOR THE EXACT LOCATION FOR JUNCTION BOX/ DISCONNECT SWITCH FOR EXTERIOR SIGNAGE IN THE FIELD. EXTERIOR SIGNAGE TO BE CONTROLLED BY PHOTOCELL.
- COORDINATE EXACT LOCATION OF TIME CLOCK & LIGHTING CONTACTOR WITH ARCHITECT/OWNER.
- COORDINATE WITH THE HEAT LAMP VENDOR FOR THE LIGHTING FIXTURES, SWITCHES, AND ELECTRICAL CONNECTION REQUIREMENTS. PROVIDE JUNCTION BOX, CIRCUIT, AND SWITCH FOR THE TRACK AND LIGHTS AS REQUIRED.
- THE HOOD LIGHTINGS ARE THE INTEGRAL PART OF THE HOOD SYSTEM, AND SEPARATE CIRCUITS AND CONTROLS ARE NOT REQUIRED. ELSE PROVIDE A DEDICATED SWITCH FOR THE HOOD LIGHTING CONTROL AND CONNECT IT TO THE HOOD CIRCUIT.
- E.C. TO COORDINATE EXACT MAKE/MODEL OF PHOTOCELL WITH EQUIPMENT MANUFACTURER.
- SHOW WINDOW RECEPTACLES, INSTALL WITHIN 18" ABOVE THE TOP OF THE SHOW WINDOW.
- THE LIGHTING FIXTURES IN THE DAYLIGHT ZONE SHALL BE CONTROLLED THROUGH THE DAYLIGHT SENSOR. THE DAYLIGHT SENSOR SHALL MATCH THE CONTROL FUNCTION REQUIREMENT OF THE IECC.



## EQUIPMENT SCHEDULE GENERAL NOTES:

A. ALL ELECTRICAL WORK FOR FOOD SERVICE EQUIPMENT SHALL BE COMPLETELY INTERWIRED BY ELECTRICAL CONTRACTOR. FINAL CONNECTIONS TO EQUIPMENT JUNCTION BOX OR PULL BOX, AND ALL ELECTRICAL WORK FROM PANEL BOARDS, TO BE BY THE ELECTRICAL CONTRACTOR.

B. THE ELECTRICAL CONTRACTOR SHALL PROVIDE ALL ROUGH-IN AND FINAL CONNECTION TO THE FOOD SERVICE EQUIPMENT. ALL WORK TO BE IN COMPLIANCE WITH ALL NATIONAL, STATE AND LOCAL CODES APPLICABLE.

C. VERIFY OUTLET RATING AND CONFIGURATION WITH EQUIPMENT SUPPLIER PRIOR TO ROUGH-IN.

D. VERIFY EXACT LOCATION AND MOUNTING HEIGHTS OF ALL OUTLETS WITH EQUIPMENT SUPPLIER PRIOR TO ROUGH-IN.

E. ELECTRICAL CONTRACTOR TO FURNISH AND INSTALL ALL PLUGS AND CORDS REQUIRED. ALL CORDS SHALL BE NEMA RATED AND UL APPROVED FOR MANUFACTURER AND EQUIPMENT.

F. ELECTRICAL CONTRACTOR TO FURNISH AND INSTALL ALL JUNCTION BOXES, PVC OR METAL CONDUIT, CONVENIENCE OUTLETS WITH COVERS, SWITCHES CONNECTORS, CONTROLS, AND OTHER ACCESSORIES THAT ARE NOT AN INTEGRAL PART OF THE FOOD SERVICE EQUIPMENT AS REQUIRED TO MAKE FINAL CONNECTIONS TO THE FOOD SERVICE EQUIPMENT FOR A COMPLETE AND FUNCTIONAL OPERATION MEETING ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES AND ORDINANCES.

G. ELECTRICAL CONTRACTOR TO FURNISH AND INSTALL ALL DISCONNECTS OR CIRCUIT BREAKERS AS REQUIRED BY CODES FOR EACH CONNECTION. COORDINATE LOCATION WITH THE KITCHEN EQUIPMENT CONTRACTOR.

H. ELECTRICAL CONTRACTOR TO FURNISH AND INSTALL WALL SWITCH FOR FACTORY INSTALLED LIGHTING FIXTURES IN EXHAUST VENTILATOR HOODS PER APPLICABLE STATE AND LOCAL CODES APPLICABLE. ELECTRICAL CONTRACTOR SHALL PROVIDE WIRE AND CONNECTION TO EACH LIGHT FIXTURE. THE ELECTRICAL CONTRACTOR SHALL FULLY CONCEAL ALL WIRING BETWEEN POWER SOURCE, WALL SWITCH, AND JUNCTION BOX ON HOOD. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ANY INNER WIRING OF LIGHT FIXTURES BETWEEN VENTILATOR HOOD SECTIONS AS REQUIRED. ALL WIRING WITHIN HOOD AND POWER SOURCE TO BE IN STRICT ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, NFPA #96 AND ALL OTHER APPLICABLE CODES.

I. IN ACCORDANCE WITH NFPA #96 AND MANUFACTURER'S RECOMMENDATIONS, THE ELECTRICAL CONTRACTOR SHALL FURNISH AND INSTALL A PUSH BUTTON STATION WITH PILOT LIGHT FOR VENTILATOR FAN MOTORS. THE ELECTRICAL CONTRACTOR IS TO BE RESPONSIBLE FOR, AND TO PROVIDE ALL REQUIRED WIRING FROM POWER SUPPLY THROUGH FAN SWITCH TO FAN MOTOR(S) AND PROVIDE MAGNETIC STARTERS AND FULLY INTERWIRE SYSTEM WITH ALL POWER INTERRUPTION DEVICE(S) BUILT INTO HOOD AND FIRE PROTECTION SYSTEM AS REQUIRED BY NFPA #96, NATIONAL, STATE, AND/OR LOCAL CODES APPLICABLE. ELECTRICAL CONTRACTOR TO PROVIDE LOCK-OUT DEVICES ON CONTROL BOXES FOR EXHAUST HOOD FANS, SYSTEM AND FIRE PROTECTION SYSTEM.

J. ELECTRICAL CONTRACTOR TO PROVIDE, INSTALL AND FULLY WIRE SHUNT-TRIP BREAKERS FOR SHUT DOWN OF FUEL AND POWER TO COOKING EQUIPMENT AS REQUIRED BY NFPA #96 AND ALL OTHER NATIONAL, STATE, OR LOCAL CODES APPLICABLE. THE HOLDING COILS FOR SHUNT-TRIP BREAKERS SHALL BE WIRED TO A 120 VOLT/SINGLE PHASE CONTROL CIRCUIT BY THE ELECTRICAL CONTRACTOR AND EXTENDED THROUGH A CONTACTOR AND MAINTAINED BY A PRESSURE SWITCH LOCATED AT THE MOUNTING BRACKET OF THE CHEMICAL CYLINDER FOR HOOD PROTECTION. THE ELECTRICAL CONTRACTOR SHALL ALSO PROVIDE, INSTALL, AND FULLY INTERWIRE WITH POWER SHUTDOWN RELAY SWITCH, AND ADDITIONAL RELAY OR SWITCHES REQUIRED TO INTERFACE FIRE PROTECTION SYSTEM WITH FAN VENTILATOR MOTORS AND BUILDING ALARM SYSTEMS AS REQUIRED BY NFPA #96, NATIONAL, STATE, AND LOCAL CODES APPLICABLE. COORDINATE WITH FIRE SUPPRESSION CONTRACTOR FOR LOCATION OF FIRE SUPPRESSION SYSTEM, AND GAS SHUT-OFF VALVE AS PART OF THE COMPLETE SYSTEM AS APPLICABLE.

K. AT THE REMOTE FIRE CABLE PULL, ELECTRICAL TRADES TO PROVIDE EMPTY JUNCTION BOX AT 54" AFF AND CONDUIT CONCEALED IN WALL TO 6" ABOVE FINISHED CEILING. COORDINATE EXACT REQUIREMENTS WITH FOOD SERVICE EQUIPMENT TRADE AND FIRE SUPPRESSION CONTRACTOR.

L. ELECTRICAL CONTRACTOR SHALL INTERWIRE DISPOSER CONTROL SWITCH AND TO TIME DELAY/RELAY, MAGNETIC STARTER, DISPOSER MOTOR, AND SOLENOID VALVE WITH WATER TIGHT CONDUIT AS REQUIRED PER LOCAL CODES.

M. ELECTRICAL CONTRACTOR SHALL INTERWIRE THROUGH TIME CLOCK FOR LOW TEMPERATURE COMPRESSOR AND WALK-IN COMPARTMENT BLOWER COIL FAN MOTORS AND DEFROST ELEMENT POWER SOURCE AS PART OF MAIN POWER SOURCE PROVIDE ALL WIRING AND CONDUIT WITH DISCONNECT. (VERIFY REQUIREMENTS WITH EQUIPMENT SUPPLIER)

N. ELECTRICAL CONTRACTOR SHALL PROVIDE FINAL CONNECTION TO A JUNCTION BOX MOUNTED ON TOP OF A PREFABRICATED REFRIGERATOR AND/OR FREEZER WALL AT APPROXIMATELY 8'-6" AFF. INTERWIRE THE LIGHT ADJACENT TO THE DOOR WITH THE FACTORY MOUNTED LIGHT SWITCH. ALL CONDUIT SHALL BE RUN EXPOSED ON TOP OF WALK-IN, NO EXPOSED CONDUIT WILL BE ALLOWED ON INSIDE OF WALK-IN. ELECTRICAL SERVICE REQUIRED FOR WALK-IN SHALL BE AS SHOWN FOR LIGHTS, DOOR AND DOOR FRAME HEATER, THRESHOLD PLATE HEATERS (WHERE SPECIFIED), HEATED PRESSURE RELIEF PORT (ON FREEZERS) AND ALARM SYSTEMS (WHERE SPECIFIED). (VERIFY REQUIREMENTS WITH EQUIPMENT SUPPLIER)

O. ELECTRICAL CONTRACTOR TO PROVIDE THE REQUIRED POWER SUPPLY AND FINAL CONNECTIONS TO THE TERMINAL BLOCK AT THE CONDENSING UNIT AND TO FULLY INTERWIRE TO ANY ADDITIONAL COMPONENTS, INCLUDE THE PROPER SIZE DISCONNECTS OR CIRCUIT BREAKERS. ALL WIRING FOR LOW AND MEDIUM TEMPERATURE CONDENSING UNIT TO BE ROUTED THROUGH DEFROST TIME CLOCK AND THEN WIRED TO EVAPORATOR COIL FOR PROPER POWER SUPPLY WITH THE REQUIRED QUANTITY OF WIRES. THE EVAPORATOR COIL DEFROST HEATER AND FAN MOTOR VOLTAGES AND LOADS ARE AS NOTED ON PLAN. VERIFY LOCATION OF COMPRESSORS AND COORDINATE WITH REFRIGERATION CONTRACTOR FOR FINAL CONNECTIONS. (VERIFY REQUIREMENTS WITH EQUIPMENT SUPPLIER)

P. ALL 15AMP AND 20AMP, 125V-2P-3W RECEPTACLES IN KITCHEN AREAS SHALL BE GFCI TYPE RECEPTACLES PER N.E.C. 210-8(B). ALL 208V-2P-3/4W AND 208V-3P-3/4W RECEPTACLES IN KITCHEN AREAS SHALL BE GFCI TYPE RECEPTACLES PER N.E.C. 210-8(B).

## ELECTRICAL EQUIPMENT SCHEDULE

TAG	QUANTITY	EQUIPMENT DESCRIPTION	MAKE	MODEL	LOAD IN VA	VOLTS	PHASE	AMPS	CONNECTION	NOTES
1	1	WALK-IN COOLER	NORLAKE	CUSTOM	TBD	TBD	TBD	TBD		1,2,3
01.a	1	REACH-IN FREEZER	AVANTCO	17853FHC	1440	115	1	14.4	NEMA 5-20P	1,2,3
3	1	BAG IN BOX SYRUP TANK RACK SYSTEM		TBD	1000	120	1	8.3	NEMA 5-20P	1,2,3
20	2	SOUS VIDE COOKER	VACPAK-IT	1865VC280	1800	120	1	15	NEMA 5-20P	1,2,3
21	1	PLANETARY MIXER	AVANTCO	177MX10H	550	120	1	4.58	NEMA 5-15P	
22	1	CONVECTION OVEN	COOKING PERFORMANCE GROUP	351FGC200NK	708	120	1	5.9	NEMA 5-15P	
24	1	27" SANDWICH PREP TABLE	AVANTCO	178APT27HC	360	115	1	3.6	NEMA 5-15P	
26	1	72" CHEF BASE	AVANTCO	178CBE72HC	487	115	1	6.5	NEMA 5-15P	
27	1	48" GRIDDLE (THERMOSTATIC)	COOKING PERFORMANCE GROUP	351GTCPG48NL	TBD	120	1	TBD	TBD	2,5
28	1	24" GRIDDLE (THERMOSTATIC)	COOKING PERFORMANCE GROUP	351GTCPG24NL	TBD	120	1	TBD	TBD	2,5
30	2	GAS FRYER	AVANTCO	177FFE55N	TBD	120	1	TBD	TBD	2,5
31	1	SALAMANDER, GAS	COOKING PERFORMANCE GROUP	351536SBN36K	TBD	120	1	TBD	TBD	2,5
32	2	COUNTERTOP RANGE	COOKING PERFORMANCE GROUP	351RCPG24NL	TBD	120	1	TBD	TBD	2,5
35	1	EXHAUST HOOD		TBD	TBD	TBD	TBD	TBD		
37	3	SANDWICH/SALAD PREPARATION REFRIGERATOR	AVANTCO	178APT48HC	490	115	1	4.9	NEMA 5-15P	
40	2	WAFFLE GRIDDLES	GOLDEN WAFFLES	TRT SERIES	1300	120	1	10.8333333	NEMA 5-20P	1,2,3
41	3	FOOD PAN WARMER, COUNTERTOP	AVANTCO	177W50	120				NEMA 5-15P	
42	1	UNDERCOUNTER REFRIGERATOR	AVANTCO	178SSUC27RHC	210	115	1	2.2	NEMA 5-15P	
43	1	FRENCH FRY WARMER	VOLLRATH	92271500	500	120	1	4.2	NEMA 5-15P	
44	1	FOOD PAN WARMER/RETHEMALIZER, COUNTERTOP	SERVER PRODUCTS	71886090	500	120	1	4.2	NEMA 5-15P	
45	1	INDUCTION RANGE, COUNTERTOP	AVANTCO	177IC1800	1800	120	1	15	NEMA 5-15P	
46	2	MICROWAVE OVEN	SOLWAVE	180MW1000S	1000					
48	2	HEAT LAMP	HATCO	413GRAL840D3	3420	120	1	28.5	DIRECT	3,4
49	0	HEAT LAMP	HATCO	413GRAL96D3	3936	120	1	32.8	DIRECT	3,5
53	2	DECORATIVE LAMP	HATCO	DL-775	250	120	1	16	DIRECT	3
54	1	CONVEYOR TOASTER	HATCO	413TQ800HB	3.3	208	1	16	NEMA 6-20P	
55	1	27" SALAD/SANDWICH PREP STATION	AVANTCO	447APST27	265	115	1	2.3	NEMA 5-15P	2
58	1	ICE MAKER, CUBE STYLE	MANITOWOC	4991YT1500AB	4.49	208	1	18.5	HARDWIRE	2,3
64	1	DISHMACHINE	AUTO-CHLOR SYSTEM		2300	115	1	20	NEMA 5-20P	1,2,3
72	1	REFRIGERATED MERCHANDISER	AVANTCO	178GDC12FHC	510	115	1	5.3	NEMA 5-15P	
73	1	SODA DISPENSER		TBD	1500	120	1	12.2	TBD	1,2,3
76	1	COFFEE GRINDER		TBD	1100	120	1	9	NEMA 5-20P	1,2,3
77	1	DUAL COFFEE BREWER		TBD	4200	208	1	20	NEMA L-14-30-P	1,2,3
78	1	TEA BREWER		TBD	1700	120	1	14	NEMA 5-20P	1,2,3
B04	1	BACK BAR CABINET, REFRIGERATED	AVANTCO	178UBB88HC	325	115	1	3.5	NEMA 5-15P	
B05	1	BACK BAR CABINET, REFRIGERATED	AVANTCO	178UBB2HC	325	115	1	3.5	NEMA 5-15P	
B07	1	UNDER BAR GLASS WASHER		TBD	600	120	1	4.8	TBD	1,2,3

1- COORDINATE EXACT MAKE/MODEL NUMBER WITH THE OWNER/ARCHITECT.

2- COORDINATE EXACT POWER REQUIREMENT WITH THE EQUIPMENT VENDOR.

3- COORDINATE EXACT CONNECTION TYPE WITH THE VENDOR PRIOR TO ROUGH IN.

4- GC HOOKUP AND ROUTES WIRING TO BREAKER PANEL.

5- GAS FIRED EQUIPMENT, COORDINATE WITH PLUMBING.

## ELECTRICAL FLOOR PLAN KEY NOTES :

1. E.C. SHALL COORDINATE WITH THE PLUMBING CONTRACTOR FOR THE EXACT LOCATION AND ELECTRICAL CONNECTION REQUIREMENT OF THE UNIT IN THE FIELD. PROVIDE CIRCUIT AND CONTROL AS REQUIRED.

2. E.C. SHALL COORDINATE WITH THE ARCHITECT/OWNER FOR THE EXACT LOCATION OF THE NEW METER, DISCONNECT & ELECTRICAL PANELS IN THE FIELD. ALSO, ENSURE CLEAR WORKING AND DEDICATED SPACE AS PER NEC 110.26.

3. CIRCUITING FOR EQUIPMENT LOCATED IN BAR AREA TO BE ROUTED THROUGH BAR MILLWORK AS APPLICABLE. E.C. TO VERIFY THE EXACT CONDITIONS, ROUTING AND ALL REQUIREMENTS WITH MILLWORK AND KITCHEN EQUIPMENT VENDOR PRIOR TO BID.

4. PLYWOOD-BACKED OUTLETS FOR DATA AND TELEPHONE SERVICES. COORDINATE WITH THE ARCHITECT/OWNER/SERVICE PROVIDER FOR OTHER REQUIREMENTS. PROVIDE CONDUIT AND CONNECTION AS REQUIRED.

5. REMOTE PULL STATION FOR HOOD SUPPRESSION SYSTEM ACTIVATION. VERIFY EXACT REQUIREMENTS AND LOCATION(S) WITH KITCHEN EQUIPMENT CONTRACTOR (KEC) PRIOR TO ROUGH-IN.

6. ALL GENERAL RECEPTACLES IN THIS AREA SHALL BE TAMPER RESISTANT AS PER NEC 406.12.

7. E.C. SHALL COORDINATE EXACT OUTLET & POWER REQUIREMENT & EXACT LOCATION FOR HOOD AND ANSUL SYSTEM WITH EQUIPMENT MANUFACTURER PRIOR TO PURCHASE & BID.

8. E.C. TO VERIFY IN FIELD THE LOCATION, POWER REQUIREMENTS AND ELECTRICAL CONNECTIONS FOR WALK-IN COOLER AND FREEZER PER MANUFACTURER'S SPECIFICATIONS, AND COORDINATE THE LOCATION OF UNITS WITH EQUIPMENT VENDOR. VERIFY ALL INFORMATION PRIOR TO BIDDING.

9. E.C. TO COORDINATE WITH MECHANICAL DRAWINGS/MANUFACTURER FOR MSDS, VVTs, AND EBDs LOCATION. PROVIDE A JUNCTION BOX FOR EACH ONE OF THEM AND WILL BE POWERED VIA CIRCUIT A:32. BASE BID ACCORDINGLY.

10. ELECTRICAL CONTRACTOR TO COORDINATE EXACT POWER REQUIREMENT WITH WALK-IN BOX MANUFACTURER AND MAKE POWER PROVISION ACCORDINGLY AND ALL CONDUITS ENTERING AND LEAVING THE WALK-IN COOLER/FREEZER SHALL BE SEALED. SEALANTS SHALL BE IDENTIFIED FOR USE WITH CABLE INSULATION, CONDUCTOR INSULATION, A BARE CONDUCTOR, A SHIELD, OR OTHER COMPONENTS.

## POWER PLAN GENERAL NOTES:

A. THE ARCHITECTURAL PLAN SHALL TAKE PRECEDENCE OVER THE ELECTRICAL DRAWING FOR EQUIPMENT LOCATION AND MOUNTING. THE LOCATION OF ALL ELECTRICAL EQUIPMENT NOT PROVIDED IN THE ARCHITECTURAL PLAN SHALL BE VERIFIED WITH THE ARCHITECT/OWNER BEFORE BID.

B. POWER AND LOCATION OF ALL THE MECHANICAL AND PLUMBING UNITS SHALL BE COORDINATED WITH THE RESPECTIVE CONTRACTORS BEFORE BID.

C. ELECTRICAL OUTLETS PLACED ON BOTH SIDES OF THE WALL PARTITION TO BE LOCATED OFFSET OF EACH OTHER.

D. ELECTRICAL OUTLETS AND DEVICES LOCATED IN DEMISING WALLS SHALL BE CLOSED AS PER THE FIRE STOP DETAIL TO MAINTAIN PARTITION FIRE RATING.

E. ALL PENETRATIONS TO THE WALK-IN FREEZER AND COOLER NEED TO BE SEALED INSIDE AND OUT AND SEAL SHALL BE RATED FOR THAT TEMPERATURE.


F. THE DISCONNECT SWITCHES FOR THE BRANCH CIRCUIT SHOWN ON THE PLAN SHALL BE RATED EQUAL TO OR HIGHER THAN THE BREAKER RATING. REFER TO BREAKER RATING IN THE PANEL SCHEDULE AND PROVIDE DISCONNECT AS NEEDED.

G. ALL 125V-250V RECEPTACLES SUPPLIED BY SINGLE-PHASE CIRCUITS RATED 150V OR LESS TO GROUND, 50A OR LESS, AND ALL RECEPTACLES SUPPLIED BY THREE-PHASE BRANCH CIRCUITS RATED 150V OR LESS TO GROUND, 100A OR LESS INSTALLED IN THE LOCATIONS SPECIFIED IN NEC 210.8(B)(1) THROUGH (12) SHALL HAVE GFCI PROTECTION.

H. GFI MARKED ON THE PLAN INDICATES THAT THE CIRCUIT SHALL BE GFI PROTECTED. E.C. SHALL PROVIDE A GFI RECEPTACLE DISCONNECT IN THE READILY ACCESSIBLE LOCATION. PROVIDE A GFI BREAKER IN THE PANEL IF THE RECEPTACLE IS NOT AVAILABLE OR NOT ACCESSIBLE WHEN INSTALLED IN THE DESIRED LOCATION.

I. COORDINATE THE EXACT LOCATION AND ELECTRICAL CONNECTION REQUIREMENTS OF THE DUCT SMOKE DETECTOR, MOTORIZED DAMPERS, AND THERMOSTATS IN THE FIELD WITH THE MECHANICAL DRAWING. PROVIDE WIRING AS REQUIRED.

J. WHEN WIRING TYPE AND INSULATION ARE NOT SPECIFIED IN THE DRAWING, THE CONTRACTOR SHALL PROVIDE ANY WIRING THAT IS APPROVED BY CODE AND SUITABLE FOR THE AREA OF USE. THE AREA INCLUDES BUT IS NOT LIMITED TO UNDERGROUND, OVERHEAD, WET LOCATION, PLUMIN SPACE, SHAFTS, FIRE PUMP, EMERGENCY SYSTEM, OFFICES, AND HEALTH CARE FACILITIES.



Property of NY Engineers

Diagram illustrating the Electrical Roof Power Plan. The plan shows various electrical components and their locations:

- RTU-1(N) 3P/NEMA-3R B-1,3,5
- RTU-2(N) 3P/NEMA-3R B-7,9,11
- RTU-3(N) 3P/NEMA-3R B-13,15,17 B-6
- MAU-1(N) B-14,16,18 3P/NEMA-3R MAU-1(N) 1,2
- KEF-1(N) 3P/NEMA-3R B-21,23,25
- KEF-2(N) 3P/NEMA-3R B-27,29,31
- TEF-1(N) 1P/NEMA-3R B-19

ELECTRICAL ROOF POWER PLAN GENERAL NOTES

A. ALL THE ELECTRICAL ELEMENTS, VIZ., CONDUITS, WIRING, AND DISCONNECT SWITCHES, SHALL BE RATED FOR EXTERIOR USE.

B. THE DISCONNECT SWITCHES FOR THE BRANCH CIRCUIT SHOWN ON THE PLAN SHALL BE RATED EQUAL TO OR HIGHER THAN THE BREAKER RATING. REFER TO BREAKER RATING IN THE PANEL SCHEDULE AND PROVIDE DISCONNECT AS NEEDED.

C. GFI MARKED ON THE PLAN INDICATES THAT THE CIRCUIT SHALL BE GFI PROTECTED. E.C. SHALL PROVIDE A GFI BREAKER IN THE PANEL FOR THE INDICATED CIRCUIT IF EITHER THE RECEPTACLE IS NOT AVAILABLE OR NOT ACCESSIBLE.

D. A 125-VOLT, SINGLE-PHASE, 15- OR 20-AMPERE-RATED RECEPTACLE OUTLET SHALL BE INSTALLED AT AN ACCESSIBLE LOCATION WITHIN 7.5 M (25 FT) OF THE EQUIPMENT AS SPECIFIED IN 210.63(A) AND (B) AS PER NEC 210.63

ELECTRICAL ROOF POWER PLAN KEY NOTES

1. E.C. SHALL COORDINATE WITH THE MECHANICAL CONTRACTOR FOR THE EXACT LOCATION AND ELECTRICAL CONNECTION REQUIREMENT OF THE HVAC UNIT IN THE FIELD. PROVIDE CIRCUIT AND CONTROLS AS REQUIRED.
2. MAU-1(N) SHALL BE CONTROLLED BY HOOD CONTROLS.
3. KEF FAN SHALL BE CONTROLLED BY HOOD CONTROLS. INTERLOCK RTU-3(N) TO OPERATE IN OCCUPIED MODE WHILE KITCHEN EXHAUST FAN IS ENERGIZED.
4. INTERLOCK WITH RTU-1(N).

PROJECT NO.: 13257  
DRAWN BY: NYE  
CHECKED BY: NYE  
ISSUED DATE:  
ISSUED REVISIONS:  
A  
B  
C  
D  
E  
F  
G  
H  
I  
J


Another Broken Egg Cafe  
Electrical Roof Power Plan


## Another Broken Egg Cafe

### Electrical Panel Schedule & Riser Diagram

PANEL: A (NEW)			MOUNTING: SURFACE														
208Y/120 VOLTS	3 PHASE			4 WIRE	DEMAND LOAD IN KVA 34.06			PANEL LOCATION: OFFICE			FED FROM: NEW DISC.						
MCB 125A																	
NOTE:																	
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD		LOAD TYPE	LOAD (KVA)	NOTES	PER PHASE (KVA)			NOTES	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD		TRIP AMPS	CKT NO.	
1	15	HOOD CONTROLS/LIGHTS		E	1.10	RWC	A	1.10					SPARE		20	2	
3	20	37 SANDWICH/SALAD PREPARATION REFRIGERATOR		E	0.53	RWC	B	0.78			RWC	0.25	L	53_HEAT LAMP DEC		20	4
5	20/2P	54 CONVEYOR TOASTER		E	1.65	RWC			1.90	RWC	0.25	L	53_HEAT LAMP DEC		20	6	
7				E	1.65			3.26		RWC	1.61	E	46 MICROWAVE OVEN		20	8	
9	20	SPARE						0.00					SPARE		20	10	
11	20	43 FRENCH FRY WARMER		E	0.50	RWC			1.20	RWC	0.70	E	41 FOOD PAN WARMER, COUNTERTOP		20	12	
13	20	24 SANDWICH/SALAD PREPARATION REFRIGERATOR		E	0.36	RWC		0.89		RWC	0.53	E	37 SANDWICH/SALAD PREPARATION REFRIGERATOR		20	14	
15		SHUNT TRIP						0.53		RWC	0.53	E	37 SANDWICH/SALAD PREPARATION REFRIGERATOR		20	16	
17	20	KDS SYSTEM		E	0.54	RWC			1.24	RWC	0.70	E	41 FOOD PAN WARMER, COUNTERTOP		20	18	
19	20	72 REFRIGERATED MERCHANDISER		E	0.61	RWC		1.31		RWC	0.70	E	41 FOOD PAN WARMER, COUNTERTOP		20	20	
21	30/2P	58 ICE MAKER, CUBE STYLE		E	1.92	RWC			3.53	RWC	1.61	E	46 MICROWAVE OVEN		20	22	
23				E	1.92				3.72	RWC	1.80	E	45 INDUCTION RANGE, COUNTERTOP		20	24	
25	20	22 CONVECTION OVEN		E	0.71	RWC		0.92		RWC	0.21	E	42 UNDERCOUNTER REFRIGERATOR		20	26	
27		SHUNT TRIP						0.50		RWC	0.50	E	44 FOOD PAN WARMER/REHEATRALIZER, COUNTERTOP		20	28	
29	20	03 BAG IN BOX		E	1.00	RWC			2.80	RWC	1.80	E	20 SOUS VIDE COOKER		20	30	
31	20	78 TEA BREWER + ADD URN		E	1.70	RWC		1.90			0.20	O	MECH. MISC. LOAD		20	32	
33	30/2P	77 DUAL COFFEE BREWER		E	2.10	RWC			3.60	RWC	1.50	E	73 SODA DISPENSER & ICE CHEST		20	34	
35				E	2.10				3.40	RWC	1.30	E	40 WAFFLE GRIDDLE		20	36	
37	20	76 COFFEE GRINDER		E	1.10	RWC		2.40		RWC	1.30	E	40 WAFFLE GRIDDLE		20	38	
39	20	26 72 CHEF BASE		E	0.75	RWC			4.17	RWC, GFI	3.42	E	48 HEAT LAMP		40	40	
41		SHUNT TRIP							3.42	RWC, GFI	3.42	E	48 HEAT LAMP		40	42	
									11.78		13.11		17.68				

PANEL: B (NEW)			MOUNTING: SURFACE													
208Y/120 VOLTS	3 PHASE			4 WIRE	DEMAND LOAD IN KVA 57.45			PANEL LOCATION: OFFICE			FED FROM: NEW DISC.					
MCB 225A																
NOTE:																
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD		LOAD TYPE	LOAD (KVA)	NOTES	PER PHASE (KVA)			NOTES	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD		TRIP AMPS	CKT NO.
1		RTU-1(N)		H	4.44	RWC, HACR	A	6.04		RWC	1.60	L	SHOW WINDOW RECEPTACLE		20	2
3	45/3P			H	4.44		B	6.04		RWC	1.60	L	SHOW WINDOW RECEPTACLE		20	4
5		RTU-2(N)		H	4.44	RWC, HACR		5.04		RWC	0.36	R	ROOF RECEPTACLE		20	6
7				H	4.44					RWC	0.60	E	B07 U. BAR GLASS WASH		20	8
9	45/3P	RTU-3(N)		H	4.44	RWC, HACR		4.84		RWC	0.40	E	B04 BACK BAR CABINET, REFRIGERATED		20	10
11				H	4.44			4.84		RWC	0.40	E	B05 BACK BAR CABINET, REFRIGERATED		20	12
13		TEF-1(N)		H	6.24	RWC, HACR		9.02		RWC, VIF	1.60	L	SHOW WINDOW RECEPTACLE		30/3P	14
15	60/3P			H	6.24			9.02		RWC, VIF	1.80	E	E20 SOUS VIDE COOKER		16	
17		KEF-1(N)		H	6.24	RWC, HACR				RWC, VIF	1.80	E	E20 SOUS VIDE COOKER		18	
19	15	KEF-2(N)		M	0.35	RWC		1.95		RWC, VIF	1.60	E	E20 SOUS VIDE COOKER		20	22
21				M	0.55	RWC, HACR			2.35	RWC, VIF	1.80	E	E20 SOUS VIDE COOKER		24	
23	15/3P	KEF-2(N)		M	0.55			0.55		RWC, VIF	1.80	E	E20 SOUS VIDE COOKER		26	
25		SHOW WINDOW RECEPTACLE		L	0.80	RWC			0.80				SPARE		28	
27		EXTERIOR SIGNAGE		L	1.20	RWC			1.20				SPARE		30	
29		64 DISH MACHINE		E	2.30	RWC, VIF		2.30					SPARE		32	
31	20	SPARE						0.00					SPARE		34	
33		SPARE						0.00					SPARE		36	
35		SPARE						0.00					SPARE		38	
37		SPARE						0.00					SPARE		40	
39		SPARE						0.00					SPARE		42	
41		SPARE						6.57					SPARE		42	
								6.74								







MANUAL MODE OPERATION:  
 1. PUSHBUTTON PRESS IS REQUIRED TO TURN LOAD ON.  
 2. LOAD TURNS OFF WHEN SENSOR TIMES OUT OR BY PRESSING PUSH BUTTON.  
 3. IF DAYLIGHT SENSOR IS ENABLED AND LIGHT LEVEL IS ABOVE SETPOINT, LOAD WILL NOT TURN ON.

AUTOMATIC MODE OPERATION:  
 1. WHEN SENSOR ACTIVATES LOAD TURNS ON.  
 2. PUSHBUTTON CAN BE USED TO TURN LOAD ON OR OFF. IF PUSHBUTTON IS USED TO TURN LOAD OFF, SENSOR MUST TIME OUT FIRST, BEFORE LOAD CAN TURN BACK ON AUTOMATICALLY.  
 3. IF DAYLIGHT SENSOR IS ENABLED AND LIGHT LEVEL IS ABOVE SETPOINT, LOAD WILL NOT TURN ON.

SENSOR TYPES INCLUDE:  
 ONW-D-1001-MV-N OR EQUAL


① PROVIDE SENSING CONDUCTOR TAPPED AHEAD OF ANY SWITCHES WHERE SWITCH SERVES EMERGENCY FIXTURES.



1 FIRE SUPPRESSION SYSTEM DETAIL  
E-7 NTS

2 OCCUPANCY/VACANCY-SINGLE LEVEL. WIRING DIAGRAM-LOW VOLTAGE WALL SWITCH SENSOR (NEUTRAL CONNECTION)  
E-7 NTS

3 LIGHTING CONTACTORS (LC) TYPICAL DETAIL  
E-7 NTS






OAC AND VAC MANUAL MODE OPERATION:

1. SWITCHES ARE REQUIRED TO TURN LOAD ON.
2. LOAD TURNS OFF WHEN SENSOR TIMES OUT OR WITH SWITCH.

OAC AUTOMATIC MODE OPERATION:

1. WHEN SENSOR ACTIVATES LOAD TURNS ON.
2. SWITCH CAN BE USED TO TURN LOAD ON OR OFF.

RECOMMENDED WIRE:  
 18-3 AWG STRANDED WIRE SHIELDED OR NON/SHIELDED



4 FIRE STOP DETAIL  
E-7 NTS

5 LOW VOLTAGE CEILING MOUNTED OCCUPANCY CEILING SENSOR WIRING DIAGRAM  
E-7 NTS

PROJECT NO.: 13257  
 DRAWN BY: NYE  
 CHECKED BY: NYE  
 ISSUED DATE:  
 ISSUED REVISIONS:  
 1  
 2  
 3  
 4  
 5  
 6  
 7  
 8

PLUMBING SYMBOLS LIST	
— GSAN —	GREASE SANITARY SEWER (UNDERFLOOR)
— SAN —	SANITARY SEWER (UNDERFLOOR)
— EX.GSAN —	EXISTING GREASE SANITARY SEWER (UNDERFLOOR)
— SAN —	EXISTING SANITARY SEWER (UNDERFLOOR)
— VENT PIPING —	VENT PIPING
— COLD WATER PIPING —	COLD WATER PIPING
— EXISTING COLD WATER PIPING —	EXISTING COLD WATER PIPING
— HOT WATER PIPING —	HOT WATER PIPING
— HOT WATER RETURN PIPING —	HOT WATER RETURN PIPING
— G —	GAS PIPING
— BALANCING VALVE —	BALANCING VALVE
— FLOOR DRAIN —	FLOOR DRAIN
— P-TRAP —	P-TRAP
— PIPE UP —	PIPE UP
— PIPE DROP —	PIPE DROP
— CLEANOUT —	CLEANOUT
— POINT OF CONNECTION —	POINT OF CONNECTION
— GAS SHUT-OFF VALVE —	GAS SHUT-OFF VALVE

#### PLUMBING ABBREVIATIONS

FCO	FLOOR CLEANOUT
CW	COLD WATER
HW	HOT WATER
SAN	SANITARY
GSAN	GREASE SANITARY
V	VENT
LAV	LAVATORY
WC	WATER CLOSET
RCP	RE-CIRCULATION PUMP
FS	FLOOR SINK
TYP.	TYPICAL
DN	DOWN
FD	FLOOR DRAIN
BFP	BACK FLOW PREVENTER
WH	WATER HEATER
N.I.C.	NOT IN CONTRACT
ET	EXPANSION TANK

PLUMBING DRAWING LIST	
P-1	PLUMBING SYMBOLS & SPECIFICATIONS
P-2	PLUMBING SANITARY FLOOR PLAN
P-3	PLUMBING WATER & GAS PIPING PLAN
P-4	GAS PIPING ROOF PLAN
P-5	PLUMBING DETAILS
P-6	PLUMBING SCHEDULES
P-7	PLUMBING WATER AND GAS RISERS
P-8	PLUMBING SANITARY RISER

#### BUILDING DEPARTMENT PLUMBING NOTES

- ALL PLUMBING SYSTEMS (SANITARY, WASTE, VENT, WATER, GAS) AND ASSOCIATED EQUIPMENT SHALL BE INSTALLED, OPERATED, AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF 2024 OHIO PLUMBING CODE (PC 2024).
- INSTALLATION OF UNDERGROUND PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 702.2
- PROTECTION OF PIPING AND PLUMBING SYSTEM COMPONENTS AS PER SECTION PC 305.
- TRENCHING, EXCAVATION AND BACKFILL AS PER SECTION PC 306.
- RODENT PROOFING AS PER PC 304
- MATERIALS USED IN PLUMBING SYSTEMS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 303, PC 605, PC 702, PC 902, PC 1102.
- EQUIPMENT CONNECTIONS AND JOINING OF PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTERS 4, 5, 6, 7 AND 9.
- DEEP SEAL TRAPS FOR FLOOR DRAINS SHALL BE PROVIDED AS PER PC 1002, AND CLEAN-OUTS SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 708
- DRAINAGE PIPE CLEANOUTS AS PER SECTION PC 708.
- VERTICAL AND HORIZONTAL PIPING SHALL BE SUPPORTED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 308
- WATER SUPPLY SYSTEMS SHALL BE INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 6 SECTION PC 601-603, 604, 606, 607, 608, 610
- THE SANITARY DRAINAGE SYSTEM SHALL BE SIZED AND INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 7 SECTION PC 701, 704, 705, 706, 707, 708, 711.
- VENT PIPING FOR THE SANITARY DRAINAGE SYSTEM SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 9 SECTION PC 901 THROUGH PC 912 THROUGH PC 917
- INSPECTION AND TESTING OF PLUMBING SYSTEMS SHALL BE IN ACCORDANCE WITH SECTION PC 312.
- GAS PIPING INSTALLATION SHALL BE IN ACCORDANCE WITH 2024 OHIO FUEL GAS CODE CHAPTER 4 (ADOPTS IFGC 2021).

#### PLUMBING SPECIFICATIONS:

1. BASIC PLUMBING REQUIREMENTS, MATERIALS AND METHODS
  - 1.01 SCOPE
    - A. PROVIDE ALL MATERIAL, TOOLS, SUPERVISION AND LABOR INCLUDING ALL MISCELLANEOUS AND INCIDENTAL ITEMS REQUIRED FOR COMPLETE AND OPERABLE PLUMBING INSTALLATIONS AS SHOWN OR DESCRIBED ON THE DRAWINGS AND IN THESE SPECIFICATIONS.
    - B. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING AND NEW CONDITIONS AND MATERIALS WITHIN THE CONSTRUCTION AREA. ANY DAMAGE CAUSED BY THE CONTRACTOR SHALL BE REPAIRED TO THE OWNER'S SATISFACTION.
    - C. OBTAIN ALL PERMITS, PAY ALL PERMIT FEES AND SCHEDULE ALL REQUIRED INSPECTIONS, COPIES OF ALL PERMITS AND INSPECTION CERTIFICATES SHALL BE FORWARDED TO THE OWNER FOR RECORD.
    - D. THE GENERAL CONDITIONS OF THE CONTRACT AND ALL DIVISION 1 REQUIREMENTS APPLY TO THE WORK OF THIS SECTION.
    - E. THE CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID TO DETERMINE CONDITIONS AND THE EXTENT OF THE WORK. BY COMMENCING WORK, THE CONTRACTOR ACKNOWLEDGES HIS CONFIRMATION OF ALL CONDITIONS AS ACCEPTABLE WITH REFERENCE TO HIS CONTRACT, SCOPE OF WORK AND BID PRICE SUCH THAT NO ADDITIONAL COMPENSATION SHALL BE FORTHCOMING FOR UNFORESEEN EXISTING CONDITIONS.
    - F. IN ALL AREAS SUBJECT TO FREEZING CONDITIONS, THE CONTRACTOR SHALL PROVIDE FREEZE PROTECTION FOR ALL DOMESTIC WATER PIPING INSTALLED UNDER HIS CONTRACT.
    - G. ALL ELECTRICAL REQUIREMENTS SHALL BE COORDINATED WITH THE CONTRACTOR FOR ELECTRICAL WORK. THIS CONTRACTOR IS RESPONSIBLE FOR ALL LOW VOLTAGE WIRING FOR EQUIPMENT INSTALLED UNDER HIS CONTRACT. THE CONTRACTOR FOR ELECTRICAL WORK IS RESPONSIBLE FOR LINE VOLTAGE POWER WIRING ONLY.
    - H. COLOR AND FINISH SELECTIONS FOR ALL MATERIALS, INCLUDING PAINTING OF PIPING, SHALL BE AS DIRECTED AND/OR APPROVED BY THE ARCHITECT.
    - I. MINOR DETAILS NOT SHOWN OR SPECIFIED, BUT NECESSARY FOR THE PROPER AND ACCEPTABLE CONSTRUCTION, INSTALLATION OR OPERATION OF ANY PART OF THE WORK AS DETERMINED BY THE ENGINEER SHALL BE INCLUDED AS IF SPECIFIED OR INDICATED ON THE DRAWINGS.
    - J. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL REQUIREMENTS FOR THE INSTALLATION, CONNECTION, EXTENSION OR MODIFICATION TO ALL UTILITY SERVICES WITH RESPECTIVE PROVIDERS INCLUDING PAYMENT OF ALL ASSOCIATED FEES.
    - K. THE CONTRACTOR IS RESPONSIBLE FOR ALL PAINTING ASSOCIATED WITH CUTTING AND PATCHING. ALL PAINTING IN AREAS WITH COMPLETE FINISH RENOVATIONS SHALL BE PROVIDED BY THE GENERAL CONTRACTOR.
  - 1.02 SUBMITTALS
    - A. SUBMITTAL REQUIREMENTS SHALL BE COORDINATED WITH THE ARCHITECT AND AUTHORITIES HAVING JURISDICTION. UNLESS OTHERWISE DIRECTED, CONTRACTOR SHALL PROVIDE SUBMITTALS AS LISTED BELOW.
      1. PIPE AND FITTINGS
      2. VALVES
      3. HANGERS AND SUPPORTS
      4. PLUMBING PIPING LAYOUT
      5. TEST PLATES
      6. PLUMBING FIXTURES
      7. WATER HEATERS & ACCESSORIES
      8. MIXING VALVES
      9. ALL SCHEDULED PLUMBING EQUIPMENT
    - B. SUBMITTALS FROM SUPPLIERS OR MANUFACTURERS WHICH DO NOT BEAR THE STAMP OF THE SUBMITTING CONTRACTOR INDICATING THAT THE CONTRACTOR HAS REVIEWED THE SUBMITTAL FOR CONFORMANCE WITH THE PROJECT REQUIREMENTS WILL BE RETURNED REJECTED.
    - C. THE ENGINEER'S REVIEW OF SUBMITTALS IS A COURTESY WHICH DOES NOT RELIEVE THE CONTRACTOR FROM CONFORMING WITH THE CONSTRUCTION DOCUMENTS, REGARDLESS OF THE ACTION INDICATED BY THE SHOP DRAWINGS STAMP.
    - D. REVIEW OF SHOP DRAWINGS BY THE ENGINEER SHALL BE LIMITED TO THE INITIAL REVIEW, AND A SECOND REVIEW OF ANY REQUIRED RESUBMITTED DATA. IF THE ENGINEER IS REQUIRED TO REVIEW SHOP DRAWINGS FOR A THIRD (3RD) SUBMISSION OF THE SAME ITEM, THE CONTRACTOR SHALL BE LIABLE FOR COMPENSATING THE ENGINEER FOR THESE SUBSEQUENT REVIEWS AS PER THE ENGINEER'S CURRENT HOURLY RATE SCHEDULE.
    - E. SUBMIT PROOF OF APPROVAL AND/OR CONFIRMATION OF SATISFACTORY TEST RESULTS TO THE OWNER AND THE ARCHITECT.
    - F. SUBMIT TO THE OWNER'S MAINTENANCE PERSONNEL OPERATION AND MAINTENANCE DATA FOR ALL SYSTEM COMPONENTS, SERVICING REQUIREMENTS, INSPECTION DATA, REPLACEMENT PART NUMBERS AND AVAILABILITY AND CONTACT INFORMATION FOR SERVICE/SUPPLY COMPANY.
    - G. FOR ALL BELOW GRADE PIPING WHERE ACTUAL INSTALLATION DEVIATES FROM CONSTRUCTION DRAWINGS, THE CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS INDICATING BELOW GRADE PIPE LOCATIONS DIMENSIONED TO NEAREST COLUMN LINES.
    - H. RECORD AS-BUILT DRAWINGS SHALL BE SUPPLIED TO THE OWNER/tenant AFTER COMPLETION OF THE WORK SHOWING ANY ALTERATIONS, ADDITIONS AND/OR DELETIONS TO THE SYSTEMS INSTALLED.
    - I. 1.03 SUBSTITUTIONS
      - A. ALL EQUIPMENT SHALL BE PRODUCTS OF THE SPECIFIED MANUFACTURER OR MANUFACTURERS. ALL BIDS SHALL BE BASED ON THE SPECIFIED MANUFACTURER OR MANUFACTURER'S EQUIPMENT. FOR SUBSTITUTIONS OF OTHER MANUFACTURER'S EQUIPMENT TO BE CONSIDERED, THE SUBSTITUTION MUST BE INDICATED PRIOR TO BIDDING WITH THE REASON FOR THE PROPOSED SUBSTITUTION IDENTIFIED, AND THE PROPOSED CREDIT TO THE OWNER INDICATED. THE ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF ANY PROPOSED SUBSTITUTIONS.
      - B. THE CONTRACTOR ASSUMES ALL RESPONSIBILITY FOR COORDINATING THE WORK OF OTHER TRADES WHICH MAY BE AFFECTED BY SUBSTITUTIONS, INCLUDING ALL RELATED COSTS.
  - 1.04 DEFINITIONS
    - A. FURNISH: TO PURCHASE, PROCURE, ACQUIRE AND DELIVER, COMPLETE WITH RELATED ACCESSORIES.
    - B. INSTALL: TO ERECT, MOUNT AND CONNECT, COMPLETE WITH RELATED ACCESSORIES.
    - C. PROVIDE: TO FURNISH AND INSTALL.
    - D. PLUMBING CONTRACTOR, THE CONTRACTOR, THIS CONTRACTOR: THE CONTRACTOR FOR PLUMBING WORK WHICH IS SPECIFIED HEREIN AND SHOWN ON THESE DRAWINGS.
  - 1.05 DRAWINGS
    - A. THE DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED TO ILLUSTRATE THE GENERAL ARRANGEMENT AND ROUTING OF PIPING AND GENERAL LOCATIONS OF EQUIPMENT. PRECISE LOCATIONS OF EQUIPMENT, RISERS AND STACKS, AND ROUTING AND ELEVATION OF ALL PIPING SYSTEMS SHALL BE COORDINATED IN THE FIELD WITH THE ARCHITECT, ARCHITECTURAL DRAWINGS, THE WORK OF OTHER TRADES, EXISTING AND NEW BUILDING CONDITIONS, AND THE PREFERENCE OF THE OWNER/tenant. IN CONSTRUCTION PROCESSES, ALL PIPING SHALL BE INSTALLED CONCEALED IN FINISHED SPACES, UNLESS NOTED OTHERWISE.
    - B. PROVIDE ALL NECESSARY INCIDENTAL MATERIALS AND ACCESSORIES REQUIRED TO MAKE THE WORK COMPLETE IN ALL RESPECTS, EVEN IF NOT PARTICULARLY SHOWN OR SPECIFIED.
    - C. REFER TO PLUMBING EQUIPMENT/FIXTURE SCHEDULE ON THE DRAWINGS FOR ALL FIXTURE AND EQUIPMENT SPECIFICATIONS.
    - D. REFER TO FIXTURE CONNECTION SIZE SCHEDULE FOR ALL FIXTURE ROUGHING SIZE REQUIREMENTS.
    - E. VERIFY ALL INDICATED CONDITIONS BEFORE STARTING WORK AND REPORT ANY DISCREPANCIES. THE DRAWINGS REFLECT CONDITIONS WHICH CAN BE REASONABLY INTERPRETED FROM THE EXISTING VISIBLE CONDITIONS OR FROM DRAWINGS AND INFORMATION FURNISHED BY THE OWNER.
    - F. LOCATE ALL FIXTURES AND EQUIPMENT AS PER THE FINAL ARCHITECTURAL DRAWINGS.
  - 1.06 PRODUCTS
    - A. SANITARY AND VENT PIPING:
      1. SANITARY PIPING SHALL BE HUBLESS CAST IRON PIPE WITH STAINLESS STEEL COUPLINGS AND ELASTOMERIC GASKETS WITH A MINIMUM 4 BANDS PER COUPLING. PVC PIPING AS PER OHIO CODE 2024, TABLE 702.1 AND TABLE 702.2 MAY BE USED IF APPROVED BY LOCAL AUTHORITIES.
      2. SLOPE OF DRAINAGE SYSTEM SHALL BE 1/8" PER FOOT OF RUN FOR PIPE OVER 3" (I.D.) AND 1/4" PER FOOT OF RUN FOR PIPE 2-1/2" AND SMALLER. VENT PIPING SHALL BE PITCHED TO DRAIN.
      3. ALL CAST IRON SOIL PIPE AND FITTINGS SHALL BE MARKED WITH THE COLLECTIVE TRADEMARK OF THE CAST IRON SOIL PIPE INSTITUTE (CISI) AND BE LISTED BY NSF INTERNATIONAL.
    - B. DOMESTIC WATER PIPING:
      1. ABOVE GRADE WATER PIPING SHALL BE TYPE 'L' HARD-DRAWN COPPER TUBE.
      2. FITTINGS IN DOMESTIC WATER PIPING SHALL BE WROUGHT COPPER OR CAST BRASS.
      3. JOINTS SHALL BE MADE WITH LEAD-FREE SOLDER.
      4. THE ENTIRE DOMESTIC WATER DISTRIBUTION SYSTEM SHALL BE INSULATED INCLUDING ALL VALVES, FITTINGS, ETC.
      5. COMPLY WITH NSF 61 FOR MATERIALS FOR WATER-SERVICE PIPING AND SPECIALTIES FOR DOMESTIC WATER.
      6. AS PER 2024 OHIO ENERGY CONSERVATION CODE (2021 IECC) C403.12, PIPING FROM A WATER HEATER TO THE TERMINATION OF HEATED WATER FIXTURE SUPPLY PIPE SHALL BE INSULATED IN ACCORDANCE WITH TABLE (C403.12) OF MINIMUM PIPE INSULATION THICKNESS.

MINIMUM PIPE INSULATION THICKNESS						
FLUID OPERATING TEMPERATURE RANGE AND USAGE (°F)	INSULATION CONDUCTIVITY (BTU IN/H FT² °F)	MEAN RATING (°F)	NOMINAL PIPE OR TUBE SIZE (INCHES)			
			<1	1 to < 1½	1½ to < 4	4 to < 8
141-200	0.25-0.29	125	1.5	1.5	2	2
105-140	0.21-0.28	100	1.0	1.0	1.5	1.5
40-60	0.21-0.27	75	0.5	0.5	1.0	1.0

7. WATER DISTRIBUTION SYSTEM AS PER 2024 OHIO ENERGY CONSERVATION CODE (2021 IECC), C404.6.1, HAVING ONE OR MORE RECYCLING PUMPS THAT PUMP WATER FROM A HEATED-WATER SOURCE THROUGH A COLD-WATER SUPPLY PIPE SHALL BE A DEMAND RECIRCULATION WATER SYSTEM. PUMPS SHALL HAVE CONTROLS THAT COMPLY WITH BOTH OF THE FOLLOWING:
  - a. THE CONTROL SHALL START THE PUMP UPON RECEIVING A SIGNAL FROM THE ACTION OF A USER OF A FIXTURE OR APPLIANCE, SENSING THE PRESENCE OF A USER OF A FIXTURE OR SENSING THE FLOW OF HOT OR TEMPERED WATER TO A FIXTURE FITTING OR APPLIANCE.
  - b. THE CONTROL SHALL LIMIT THE TEMPERATURE OF THE WATER ENTERING THE COLD-WATER PIPING TO 104°F (40°C).
8. AS PER 2024 OHIO ENERGY CONSERVATION CODE (2021 IECC) C404.6.1, HEATED-WATER CIRCULATION SYSTEMS SHALL BE PROVIDED WITH A CIRCULATION PUMP. THE SYSTEM RETURN PIPE SHALL BE A DEDICATED RETURN PIPE OR A COLD WATER SUPPLY PIPE. CONTROLS FOR CIRCULATING HOT WATER SYSTEM PUMPS SHALL START THE PUMP BASED ON THE IDENTIFICATION OF A DEMAND FOR HOT WATER WITHIN THE OCCUPANCY. THE CONTROLS SHALL AUTOMATICALLY TURN OFF THE PUMP WHEN THE WATER IN THE CIRCULATION LOOP IS AT THE DESIRED TEMPERATURE AND WHEN THERE IS NO DEMAND FOR HOT WATER.
9. HW SYSTEM PIPING IS DESIGNED AS PER 2024 OHIO PLUMBING CODE 607.2. THE DEVELOPED LENGTH OF HOT OR TEMPERED WATER PIPING, FROM THE SOURCE OF HOT WATER TO THE FIXTURES THAT REQUIRE HOT OR TEMPERED WATER, SHALL NOT EXCEED 50 FEET. RECIRCULATING SYSTEM PIPING AND HEAT-TRACED PIPING SHALL BE CONSIDERED TO BE SOURCES OF HOT OR TEMPERED WATER.


10. C. HANGERS AND SUPPORTS.
  1. HANGERS SHALL BE STANDARD STEEL, MALLEABLE OR WROUGHT IRON, AS MANUFACTURED BY GRINNELL OR APPROVED EQUAL, SUITABLE FOR THE TYPE OF CONSTRUCTION. PIPING SHALL NOT BE HUNG FROM OTHER PIPE.
  2. SECTIONS OF INDIVIDUAL PIPE RUNS SHALL BE SUPPORTED BY CLEVIS HANGERS.
  3. ALL EQUIPMENT SHALL BE PROVIDED WITH APPROVED SUPPORTS.
  4. PROVIDE SEISMIC RESTRAINTS IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES AND STANDARDS AND THE REQUIREMENTS OF AUTHORITIES HAVING JURISDICTION.
  5. SUPPORTS SHALL BE PROVIDED IN STRICT ACCORDANCE WITH THE RECOMMENDATIONS OF THE PIPING MANUFACTURER.
11. D. VALVES:
  1. PROVIDE GATE VALVES, BUTTERFLY OR BALL VALVES FOR SHUT-OFF DUTY ON MAIN AND BRANCH PIPE LINES. FOR ALL PIPE RUNS 2" AND SMALLER, PROVIDE BALL FOR ALL PIPE RUNS LARGER THAN 2" AND SMALLER THAN 4", PROVIDE GATE VALVES. PIPING 4" AND LARGER, PROVIDE BUTTERFLY VALVES FOR SHUT-OFF DUTY.
  2. ALL FIXTURES WITH THE EXCEPTION OF FLUSHOMETER-EQUIPPED WATER CLOSETS AND URINALS SHALL HAVE STOP VALVES TO CONTROL SUPPLY TO THE FIXTURE. WHERE SUPPLIES ARE EXPOSED, PROVIDE CHROME-PLATED STOPS WITH CHROME-PLATED ESCUTCHEONS ON PIPING PENETRATIONS.
  3. ALL PLUMBING FIXTURES AND EQUIPMENT TO HAVE SHUT-OFF VALVES ON SUPPLY LINES.
  4. ALL BRANCH LINES TO HAVE SHUT-OFF VALVES.
  5. ALL VALVES SHALL BE ACCESSIBLE. PROVIDE ACCESS DOORS WHERE REQUIRED FOR VALVE ACCESS.
  6. PROVIDE GLOBE VALVES FOR THROTTLING/BALANCING OF THE HOT WATER CIRCULATING SYSTEM.
12. E. GAS PIPING:
  1. GAS PIPING SHALL BE SIZED IN ACCORDANCE WITH PIPE SIZING TABLES OR SIZING EQUATIONS IN ACCORDANCE WITH 2024 OHIO FUEL GAS CODE SECTION 402.4.
  2. METALLIC PIPE SHALL COMPLY WITH SECTIONS 403.4.1 THROUGH 403.4.4.
  3. PIPING SYSTEM INSTALLATION SHALL COMPLY WITH SECTION 403.4.1 THROUGH 403.4.4.
  4. AS PER 2024 OHIO FUEL GAS CODE SECTION 404.4: UNDERGROUND PIPING, WHERE INSTALLED BELOW GRADE, SHALL BE ENCASED IN A PROTECTIVE PIPE SLEEVE. THROUGH THE OUTER FOUNDATION OR BASEMENT WALL OF A BUILDING, SHALL BE ENCASED IN A PROTECTIVE PIPE SLEEVE. THE ANNUAL SPACE BETWEEN THE GAS PIPING AND THE SLEEVE SHALL BE SEALED.
  5. PIPING INSTALLED UNDERGROUND BENEATH BUILDINGS IS PROHIBITED EXCEPT WHERE THE PIPING IS ENCASED IN A CONDUIT OF WROUGHT IRON OR STEEL PIPE DESIGNED TO WITHSTAND THE SUPERIMPOSED LOADS. THE CONDUIT SHALL BE PROTECTED FROM CORROSION IN ACCORDANCE WITH SECTION 404.11 AND SHALL BE INSTALLED IN ACCORDANCE WITH SECTION 404.11 OR 2024 OHIO FUEL GAS CODE 404.11.2.
  6. FUEL GAS CODE SECTION 404.12 AS PER 2024 OHIO FUEL GAS CODE SECTION 404.12: UNDERGROUND PIPING SYSTEMS SHALL BE INSTALLED A MINIMUM DEPTH OF 12 INCHES BELOW GRADE.
  7. THE GAS PIPING IS ENCASED IN A CONDUIT OF WROUGHT IRON OR STEEL PIPE TO WITHSTAND THE SUPERIMPOSED LOADS.
  8. SHUTOFF VALVES SHALL BE LOCATED IN PLACES SO AS TO PROVIDE ACCESS FOR OPERATION AND SHALL BE INSTALLED SO AS TO BE PROTECTED FROM DAMAGE.
  9. INSTALL PIPING TO CONSERVE BUILDING SPACE. DO NOT INTERFERE WITH USE OF BUILDING SPACE AND THE WORK OF OTHER TRADES. ALL PIPING RUN IN CEILING SHALL BE INSTALLED TIGHT TO THE STRUCTURE ABOVE.
  10. INSTALL PIPING TO ALLOW FOR EXPANSION AND CONTRACTION WITHOUT STRESSING PIPE, JOINTS OR CONNECTED EQUIPMENT. PROVIDE PIPE ANCHORS, GUIDES AND EXPANSION JOINTS OR LOOPS IN ALL HOT WATER AND HOT WATER CIRCULATING MAIN SUPPLY PIPING AND SEGMENTS OF SUCH PIPE THAT EXCEED 30'-0" IN LENGTH.
  11. IN ALL AREAS WITH FINISHED SURFACES, SYSTEM PIPING AND COMPONENTS SHALL BE CONCEALED ABOVE OR WITHIN FINISHED SURFACES.
  12. REDUCTIONS IN PIPE SIZES SHALL BE MADE WITH ONE-PIECE REDUCING FITTINGS. BUSHINGS ARE NOT ACCEPTABLE. USE FLANGED FITTINGS AT THE BASE OF RISERS.
  13. VENT PENETRATIONS THROUGH THE ROOF SHALL BE FLASHED.
  14. IF WATER PRESSURE EXCEEDS 8

# Another Broken Egg Cafe

Plumbing Sanitary Floor Plans

P-2

PROJECT NO.: 13257  
 DRAWN BY: NYE  
 CHECKED BY: NYE  
 ISSUED DATE:  
 ISSUED REVISIONS:  
 A  
 B  
 C  
 D  
 E  
 F  
 G  
 H  
 I  
 J  
 K  
 L  
 M  
 N  
 O  
 P  
 Q  
 R  
 S  
 T  
 U  
 V  
 W  
 X  
 Y  
 Z



**LANDLORD NOTES:**

1. CONTRACTOR SHALL BE RESPONSIBLE FOR PATCHING AND REPAIRING EXISTING FIRE RATED DEMISE WALL.
2. CONTRACTOR SHALL USE LANDLORDS ROOFER HOLDING THE WARRANTY PRESENTLY IN PLACE. ALL COST FOR ALL ROOFER WORK SHALL BE BY TENANT.

**GENERAL NOTES:**

1. CWHW PIPING TO BE PROVIDED WITH INSULATION AS PER 2021 INTERNATIONAL ENERGY CONSERVATION CODE (REFER SHEET P-1).
2. PROVIDE BRANCH PRV IF PRESSURE EXCEEDS 80 PSI.
3. CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SLAB PENETRATION AS PER STRUCTURAL REQUIREMENT.
4. PROVIDE ACCESS PANELS FOR WATER HAMMER ARRESTOR, & SHUT-OFF VALVES AS REQUIRED.
5. REFER RISER DIAGRAMS FOR ALL PIPE SIZES.
6. ANY ROOF PENETRATION SHALL BE PERFORMED BY LANDLORDS ROOFERS AT LANDLORD APPROVED, A BONDED ROOFER APPROVED IN ADVANCE BY LANDLORD.
7. PROVIDE TRAP PRIMER/ SEAL ON FLOOR DRAIN AS PER LOCAL JURISDICTION.

**SANITARY KEYED NOTES:**


- 1 CONNECT NEW 4" SANITARY LINE TO EXISTING 4" SANITARY WASTE LINE IN THE SPACE. CONTRACTOR TO FIELD VERIFY EXISTING SANITARY SIZE, ROUTING AND INVERT ON SITE.
- 2 CONNECT NEW 3" SANITARY LINE TO EXISTING 4" SANITARY WASTE LINE IN THE SPACE. CONTRACTOR TO FIELD VERIFY EXISTING SANITARY SIZE, ROUTING AND INVERT ON SITE.
- 3 CONNECT NEW 4" GREASE SANITARY LINE TO EXISTING GREASE SANITARY LINE IN THE SPACE. CONTRACTOR TO FIELD VERIFY EXISTING GREASE SANITARY SIZE, LOCATION, ROUTING AND INVERT ON SITE.
- 4 INDIRECT WASTE FROM CONVENTION OVEN TO ADJACENT FLOOR SINK WITH APPROVED AIR GAP.
- 5 INDIRECT WASTE FROM ICE MACHINE & ICE BIN TO ADJACENT FLOOR SINK WITH APPROVED AIR GAP.
- 6 INDIRECT WASTE FROM PRE-RINSE FAUCET ASSEMBLY & DISMACHINE TO ADJACENT FLOOR SINK WITH APPROVED AIR GAP.
- 7 INDIRECT WASTE FROM 3-COMPARTMENT TO ADJACENT FLOOR SINK WITH APPROVED AIR GAP.
- 8 INDIRECT WASTE FROM BANK N BOX SYRUP TANK RACK SYSTEM TO ADJACENT FLOOR SINK WITH APPROVED AIR GAP.
- 9 INDIRECT WASTE FROM 1-COMPARTMENT SINK TO ADJACENT FLOOR SINK WITH APPROVED AIR GAP.
- 10 INDIRECT WASTE FROM COCKTAIL STATION AND UNDER BAR GLASS WASHER TO ADJACENT FLOOR SINK WITH APPROVED AIR GAP.
- 11 ROUTE CONDENSATE DRAIN FROM WALK-IN COOLER TO MOP SINK WITH APPROVED AIR GAP.
- 12 CONNECT NEW 3" VENT LINE TO EXISTING VENT LINE AVAILABLE WITHIN THE SPACE. CONTRACTOR TO FIELD VERIFY EXISTING VENT LINE LOCATION AND SIZE. COORDINATE WITH OVERALL PLAN. REROUTE THE VENT LINE AS NEEDED. BASE BID ACCORDINGLY.
- 13 PROVIDE DRAIN TEMPERING VALVE (DTV) FOR DISH-MACHINE.

# Another Broken Egg Cafe

## Plumbing Water & Gas Piping Plan

PROJECT NO.: 13257  
 DRAWN BY: NYE  
 CHECKED BY: NYE  
 ISSUED DATE:

ISSUED REVISIONS:  
 A  
 A  
 A  
 A  
 A  
 A  
 A  
 A



**LANDLORD NOTES:**


1. CONTRACTOR SHALL BE RESPONSIBLE FOR PATCHING AND REPAIRING EXISTING FIRE RATED DEMISE WALL.
2. CONTRACTOR SHALL USE LANDLORDS ROOFER HOLDING THE WARRANTY PRESENTLY IN PLACE. ALL COST FOR ALL ROOFER WORK SHALL BE BY TENANT.

**GENERAL NOTES:**

1. COORDINATE ROOF PENETRATIONS WITH THE TENANT GENERAL CONTRACTOR AND LANDLORD. PROVIDE AND PAY REQUIRED ROOFING BY LANDLORD'S ROOFING CONTRACTOR.
2. CONTRACTOR IS RESPONSIBLE FOR ANY DAMAGE TO THE BUILDING STRUCTURE OR BUILDING UTILITIES CAUSED AS RESULT OF THE CONTRACTOR'S WORK UNDER THIS CONTRACT. IT IS RECOMMENDED THAT MASONRY/CONCRETE FLOORS/WALLS BE X-RAYED PRIOR TO ANY PENETRATIONS.
3. REFER RISER DIAGRAMS FOR ALL PIPE SIZES.
4. ANY ROOF PENETRATION SHALL BE PERFORMED BY LANDLORD'S ROOFERS AT LANDLORD OPTION, A BONDED ROOFER APPROVED IN ADVANCE BY LANDLORD.
5. PROVIDE GAS PRESSURE REGULATOR ON EACH GAS FIRED EQUIPMENT IF REQUIRED.


**GAS KEYED NOTES:**

- 1 CONTRACTOR TO MAKE SURE TO PROVIDE ADEQUATE INLET PRESSURE REQUIRED FOR MECHANICAL EQUIPMENTS.
- 2 CONTRACTOR TO FIELD VERIFY AND CONNECT NEW 3" GAS PIPE TO EXISTING GAS LINE.
- 3 CONTRACTOR TO FIELD VERIFY EXISTING GAS METER LOCATION AND CAPACITY IS EQUAL OR MORE THAN 2062 CFH. UPGRADE IF REQUIRED. PROVIDE NEW PRESSURE REGULATOR AND SET PRESSURE AT 14" OF W.C. IF REQUIRED. COORDINATE ALL WORK WITH LANDLORD/TENANT AND UTILITY COMPANY.



PROJECT NO.: 13257  
DRAWN BY: NYE  
CHECKED BY: NYE  
ISSUED DATE:  
ISSUED REVISIONS:  
A  
B  
C  
D  
E  
F  
G  
H

Another Broken Egg Cafe  
Gas Piping Roof Plan



PLUMBING FIXTURE SCHEDULE												
SYMBOL	DESCRIPTION	TRAP	SAN	VENT	C.W.	H.W.	REMARKS					
WC-1	WATER CLOSET	-	4"	2"	1/2"	-	FLUSH TANK					
LAV-1	LAVATORY	1-1/4"	1-1/2"	1-1/2"	1/2"	1/2"	PROVIDE MIXING VALVE					
FD-1	FLOOR DRAIN	3"	3"	2"	-	-						
FS-1	FLOOR SINK	3"	3"	2"	-	-						
UR-1	URINAL	2"	3"	2"	3/4"	-						
TD-1	TRENCH SINK	3"	3"	2"	-	-						
TPV-1	TRAP PRIMER VALVE	-	-	-	1/2"	-	PROVIDE DISTRIBUTION UNIT FOR MULTIPLE DRAIN CONNECTIONS.					
FCO-1	FLOOR CLEAN OUT	-	SEE PLANS	-	-	-						
WCO-1	WALL CLEAN OUT	-	SEE PLANS	-	-	-						
NOTES												
1. REFER TO SPECIFICATIONS FOR APPROVED EQUAL MANUFACTURERS												

KITCHEN EQUIPMENT SCHEDULE									
TAG NO.	DESCRIPTION	WASTE		VENT	CW	HW	NOTES		
		DIRECT	INDIRECT						
63	BAG IN BOX SYRUP TANK RACK SYSTEM	-	3/4"	-	1/2"	-	1 UNITS		
64	HAND SINK AND FAUCET	1-1/2"	-	-	1/2"	1/2"	4 UNITS		
65	ONE (1) COMPARTMENT SINK	1-1/2"	-	-	1/2"	1/2"	1 UNITS		
67	MOP SINK (BY GENERAL CONTRACTOR)	3"	-	-	3/4"	3/4"	1 UNITS		
22	CONVECTION OVEN	-	3"	-	1/2"	-	1 UNITS		
58	ICE MACHINE	-	3/4"	-	1/2"	-	1 UNITS		
59	ICE BIN	-	3/4"	-	-	-	1 UNITS		
60	WATER FILTRATION SYSTEM	-	-	-	1/2"	-	1 UNITS		
63	PRE-RINSE FAUCET ASSEMBLY	-	1-1/2"	-	1/2"	1/2"	1 UNITS		
64	DISHMACHINE	-	2"	-	-	3/4"	1 UNITS		
69	THREE (3) COMPARTMENT SINK	-	2"	-	1/2"	1/2"	1 UNITS		
73	SODA DISPENSER AND ICE CHEST COMBO	-	-	-	1/2"	-	1 UNITS		
77	COFFEE BREWER	-	-	-	1/2"	-	1 UNITS		
WH-1	WATER HEATER	-	1-1/2"	-	1"	-	SEE WATER HEATER SCHEDULE		
78	TEA BREWER	-	-	-	1/2"	-	1 UNITS		
B01	HAND SINK AND FAUCET	2"	-	-	1/2"	1/2"	1 UNITS		
B02	COCKTAIL STATION	-	1/2"	-	1/2"	1/2"	1 UNITS		
B07	UNDER BAR GLASSWASHER	-	1/2"	-	-	1/2"	1 UNITS		



PUMP SCHEDULE													
TAG	MANUFACTURER	MODEL NUMBER	SIZE	TYPE	SERVICE	CAPACITY		RPM	ELECTRICAL DATA			OPERATING WEIGHT (LBS)	REMARKS/OPTIONS
						GPM	HEAD (ft.)		V	PH	Hz		
RCP-1	BELL & GOSSETT	NBF-25	3/4"	WET ROTOR	HWR	3.0	12	2950	120	1	60	12	NOTE 1,2
REMARKS:													
1. ACCEPTABLE MANUFACTURERS: ARMSTRONG, BELL AND GOSSETT, GRUNDFOS, PACO, PATTERSON, TACO, OR WEINMAN.													
2. PROVIDE WITH AQUASTAT.													

EXPANSION TANKS										
UNIT	NUMBER	MANUFACTURER & MODEL NUMBER	MODEL	SERVICE	TANK VOLUME (GAL)	ACCEPTANCE VOLUME (GAL)	PRESSURE RATING (PSI)	DIMENSIONS DIAMETER (INCH) HEIGHT (INCH)	OPERATING WEIGHT (LBS)	NOTES
ET-1	1	AMTROL	ST-12C-DD	34	6.4	3.2	150	12 18	25	1

GENERAL NOTES:  
1. ACCEPTABLE MANUFACTURERS: AMTROL, BELL AND GOSSETT, TACO, OR THRUSH.

GREASE INTERCEPTOR CALCULATION				
TAG	Fixture	Quantity	DFU per Fixture	Total DFU
69	3 COMP. SINK	1	2	2
65	1 COMP. SINK	1	2	2
63	PRE.RINSE SINK	1	2	2
67	MOP SINK	1	2	2
64	HAND SINK	4	1	4
B01	HAND SINK	2	1	2
FS-1	FLOOR SINK	4	5	20
FD-1	FLOOR DRAIN	1	6	6
TD-1	TRENCH DRAIN	1	5	5
TOTAL DRAINAGE FIXTURE UNITS (DFU) CONNECTED TO GREASE INTERCEPTOR				
45				
Fixture units based on AS PER 2024 OHIO PLUMBING CODE , CHAPTER 7, SECTION 709, TABLE 709.1 AND TABLE 709.2. CONVERSION OF GPM VALUE BASED ON SECTION 709.3, FOR 45 DFU IS 22.5 GPM.				
AS PER 2024 OHIO PLUMBING CODE, CHAPTER 10, SECTION 1003.3.7 AND THE CAPACITY OF GREASE INTERCEPTOR IS PEAK DRAIN FLOW MULTIPLIED BY 30 MINUTES RETENTION TIME 22.5 (GPM) X 30 (MIN.) = 675 GALLONS.				
MINIMUM REQUIRED CAPACITY OF GREASE INTERCEPTOR FOR ABE CAFE = 1000 GALLONS				

BACKFLOW DEVICE SCHEDULE									
TAG	SERIES	SIZE	TYPE	USAGE			APPROVAL		
BFP-1	909	4"	DOUBLE CHECK VALVE ASSEMBLY	FIRE RISERS			ASSE 1015, AWWA 1013		
BFP-2	009QT	2"	REDUCED PRESSURE BACKFLOW PREVENTER	DOMESTIC WATER CONNECTION			ASSE 1015, AWWA 1013		
BFP-3	SD-3	3/8"	DUAL CHECK VALVE W/ ATMOSPHERIC VENT	CARBONATED BEVERAGE			ASSE 1022		
BFP-4	9D	1/2"	BACKFLOW PREVENTER W/ ATMOSPHERIC VENT	TEA MAKER, COFFEE MACHINE, JUICE DISPENSER, ETC			ASSE 1012		
BFP-5	007QTS	1/2"	DUAL CHECK VALVE	NON-CARBONATED BEVERAGE, SOFT SERVE ICE CREAM, WATER FILTER, HUMIDIFIER, EYE WASH, ETC			ASSE 1015		
BFP-6	8	3/4"	VACUUM BREAKER						




GAS PIPE SIZING PER 2021 INTERNATIONAL FUEL GAS CODE (IFGC 2021). TABLE NO. 402.4(2)	
INLET PRESSURE- LESS THAN 2 PSI SPECIFIC GRAVITY- 0.6 PRESSURE DROP 0.5' W.C.	
EQUIVALENT LENGTH OF PIPE = 140 + FITTINGS (+40%) = 200 FEET	
GAS NOTES:	
<ol style="list-style-type: none"> <li>1. PROVIDE SHUT-OFF VALVE AN ACCESSIBLE LOCATION, PROVIDE GAS PRESSURE REGULATOR FOR ALL GAS EQUIPMENT IF REQUIRED.</li> <li>2. CONTRACTOR SHALL VERIFY ACTUAL GAS PRESSURE AND LONGEST LENGTH OF RUN TO FARTHEST APPLIANCE PRIOR TO INSTALLATION AND NOTIFY ENGINEER IF CONDITION DIFFER THAN SHOWN ON THIS PLAN.</li> </ol>	

LOW GAS PRESSURE SIZING TABLE	
SIZE	GAS LOAD(CFH)
1/2"	34
3/4"	71
1"	134
1-1/4"	275
1-1/2"	412
2"	794
2-1/2"	1270
3"	2240

GAS EQUIPMENT PIPE SIZING CALCULATION					
TAG	DESCRIPTION	MANUFACTURER	MODEL NO.	SIZE	MBH
[27]	48" GRIDDLE (THERMOSTATIC)	COOKING PERFORMANCE GROUP	351GTCPG48NL	1"	120
[28]	24" GRIDDLE (THERMOSTATIC)	COOKING PERFORMANCE GROUP	351GTCPG24NL	3/4"	60
[30]	GAS FRYER	AVANTCO	177FFES50N	1"	170
[31]	SALAMANDER, GAS	COOKING PERFORMANCE GROUP	351S36SBN36K	3/4"	36
[32]	COUNTERTOP RANGE	COOKING PERFORMANCE GROUP	351RCPG24NL	1"	176
MAU-1(N)	MAKE UP AIR UNIT		REFER MECHICAL DRAWINGS	1 1/2"	319
RTU-1(N)	ROOF TOP UNIT		REFER MECHICAL DRAWINGS	1 1/4"	180
RTU-2(N)	ROOF TOP UNIT		REFER MECHICAL DRAWINGS	1 1/4"	180
RTU-3(N)	ROOF TOP UNIT		REFER MECHICAL DRAWINGS	1"	224
WH-1	(3)WATER HEATER	RINNAI	CX199I	2"	597
TOTAL LOAD					3" 2062

PROJECT NO.: 13257  
DRAWN BY: NYE  
CHECKED BY: NYE  
ISSUED DATE:  
ISSUED REVISIONS:  
A  
B  
C  
D  
E  
F  
G  
H



SANITARY RISER DIAGRAM  
NOT TO SCALE

Property of NY Engineers

PROJECT NO.: 13257  
DRAWN BY: NYE  
CHECKED BY: NYE  
ISSUED DATE:  
ISSUED REVISIONS: