

MECHANICAL LEGEND		ABBREVIATIONS	
	DUCT WIDTH X DEPTH	L	LENGTH
	CLEAR INSIDE DIMENSION	LAT	LEAVING AIR TEMPERATURE
	SUPPLY AIR DUCT SECTION UP - DOWN	LBS	POUNDS
	RETURN AIR DUCT SECTION UP - DOWN	LRA	LOCKED ROTOR AMPS
	EXHAUST AIR DUCT SECTION UP - DOWN	LTG	LIGHTING
	ROUND SUPPLY AIR DUCT SECTION UP - DOWN	LWT	LEAVING WATER TEMPERATURE
	ROUND RETURN AIR DUCT SECTION UP - DOWN	ALT	ALTERNATE
	ROUND EXHAUST AIR DUCT SECTION UP - DOWN	AMP	AMPERE
	SQUARE ELBOW W/TURNING VANES	AP	ACCESS PANEL
	DROP IN DUCT (DIRECTION OF FLOW)	ARCH ASSY	ARCHITECTURAL ASSY
	RISE IN DUCT (DIRECTION OF FLOW)	B	BOILER
	TAKE-OFF DAMPER/EXTRACTOR	BAS	BUILDING AUTOMATION SYSTEM
	MANUAL VOLUME DAMPER	BG	BELLOW GRADE
	FIRE DAMPER	BHP	BRAKE HORSEPOWER
	FIRE & SMOKE DAMPER	BLDG	BUILDING
	MOTORIZED DAMPER	BOP	BOTTOM OF PIPE
	RECTANGULAR TO ROUND TRANSITION	BTU	BRITISH THERMAL UNIT
	SUPPLY DIFFUSER	BTUH	BRITISH THERMAL UNITS PER HOUR
	SUPPLY GRILLE	C	COMMON
	EXHAUST GRILLE	CA	COMPRESSED AIR, COMBUSTION AIR
	RETURN GRILLE	CAP	CAPACITY
	CONDENSATE DRAIN PIPE	CB	CIRCUIT BREAKER
	CONDENSER WATER SUPPLY	CC	COOLING COIL
	CONDENSER WATER RETURN	CD	CEILING DIFFUSER
	CHILLED WATER SUPPLY	CFCI	CONTRACTOR FURNISHED,
	CHILLED WATER RETURN	CFI	CONTRACTOR INSTALLED
	GAS PIPE	CFM	CUBIC FEET PER MINUTE
	HEATING WATER SUPPLY	CFH	CUBIC FEET PER HOUR
	HEATING WATER RETURN	CH	CHILLER
	MAKEUP WATER	CLG	CEILING
	REFRIGERANT PIPE	CEF	CEILING EXHAUST FAN
	REDUCER	CMU	CONCRETE MASONRY UNIT
	UNION	COND	CONDENSER, CONDENSATE
	PIPE DOWN	CONT	CONTINUATION
	PIPE UP	COP	COEFFICIENT OF PERFORMANCE
	GAS PRESSURE REDUCING VALVE (GPR) WITH VENT	CRD	CEILING RADIATION DAMPER
	ISOLATION VALVE	CTE	CONNECT TO EXISTING
	SOLENOID VALVE	CU	CONDENSING UNIT
	BALL VALVE (2-1/2" AND SMALLER)	DB	DRY BULB, OR DECIBEL
	GLOBE VALVE	DDC	DIRECT DIGITAL CONTROL
	CHECK VALVE	DET	DETAIL
	BUTTERFLY VALVE (3" AND LARGER)	DIA	DIAMETER
	BALANCING VALVE	DIM	DIMENSION
	TWO WAY CONTROL VALVE	DN	DOWN
	THREE WAY CONTROL VALVE	DWG	DRAWING
	RELIEF(R), OR SAFETY(S) VALVE	(E)	EXISTING
	PUMP, IN SCHEMATIC PRESENTATION	EA	EXHAUST AIR
	THERMOSTAT	EAD	EXHAUST AIR DAMPER
	HUMIDISTAT	EAT	ENTERING AIR TEMPERATURE
	DUCT SMOKE DETECTOR	EF	EXHAUST FAN
	CARBON MONOXIDE DETECTOR	EFF	EFFICIENCY
	DUCT TEMP / HUMID SENSOR	EG	EXHAUST GRILLE
	NEW CONNECTION	EL	ELEVATION
	LIMIT OF DEMOLITION	ELEV	ELEVATION
	UNDERCUT	ENT	ENTERING
	SECTION TAKEN AT	EQUIP	EQUIPMENT
		ESP	EXTERNAL STATIC PRESSURE
		ET	EXPANSION TANK
		ETR	EXISTING TO REMAIN
		EWT	ENTERING WATER TEMPERATURE
		EXH	EXHAUST AIR
		EXT	EXTERIOR
		F	FARENNHEIT
		F/A	FROM ABOVE
		F/B	FROM BELOW
		FC	FORWARD CURVED
		FCU	FAN COIL UNIT
		FLA	FULL LOAD AMPS
		FLR	FLOOR
		FPM	FEET PER MINUTE
		FPS	FEET PER SECOND
		FT	FEET
		G	NATURAL GAS
		GA	GAUGE
		GAL	GALLON
		GALV	GALVANIZED
		GPM	GALLONS PER MINUTE
		GPR	GAS PRESSURE REDUCING VALVE
		GRILLE	GRILLE
		GSM	GALVANIZED SHEET METAL
		HC	HEATING COIL
		HP	HORSEPOWER, OR HEAT PUMP
		HTG.	HEATING
		HZ	HERTZ
		ID	INSIDE DIAMETER
		IN	INCHES
		KEF	KITCHEN EXHAUST FAN
		KW	KILOWATTS
		KWH	KILOWHOURS
			EQUIPMENT IDENTIFICATION
		XXX	SYMBOL OR TYPE (SEE SCHEDULE OR SPECIFICATIONS)
		X	IDENTIFICATION NUMBER (SEE SCHEDULE)
		XX	KEYNOTES
			AIR DEVICE IDENTIFICATION
			U= USAGE (S = SUPPLY, R = RETURN, E = EXHAUST, T = TRANSFER)
			CFM = AIR QUANTITY
			TYPE OF AIR DEVICE
			U-CFM-T SIZE
			NECK SIZE OF AIR DEVICE

IDAHO BUILDING DEPARTMENT NOTES	
1. ALL WORK SHALL COMPLY WITH APPLICABLE SECTIONS OF THE INTERNATIONAL BUILDING CODE (IBC), 2018, AND ALL OTHER APPLICABLE LOCAL AND STATE CODES.	
2. TESTING OF MECHANICAL SYSTEMS SHALL BE PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS OF THE INTERNATIONAL MECHANICAL CODE (IMC), 2018, INCLUDING BUT NOT LIMITED TO:	
A. VENTILATION SYSTEM BALANCING – IMC SECTION 403 B. SMOKE CONTROL SYSTEMS – IMC SECTION 513	
3. THE FOLLOWING COMPONENTS AND SYSTEMS SHALL CONFORM TO THE REFERENCED CODE SECTIONS OR APPLICABLE STANDARDS:	
A. STANDARDS OF HEATING – IMC SECTION 309 B. DUCT CONSTRUCTION AND INSTALLATION – IMC SECTION 603 C. AIR INTAKES AND EXHAUST OPENINGS – IMC SECTION 401.4 D. AIR FILTERS – IMC SECTION 605 E. FIRE AND SMOKE DAMPERS – IMC SECTIONS 606 & 607 F. SMOKE CONTROL SYSTEMS – IMC SECTION 513 G. PIPING AND INSULATION – IMC CHAPTER 12	
4. THE MINIMUM TEMPERATURE MAINTAINED IN OCCUPIED SPACES DURING THE HEATING SEASON SHALL BE 68°F (20°C), AS REQUIRED BY IMC SECTION 309.1.	
5. VENTILATION FOR ALL SPACES SHALL COMPLY WITH IMC CHAPTER 4.	
6. A STATEMENT SHALL BE PROVIDED BY THE OWNER OR RESPONSIBLE PARTY CONFIRMING THAT THE VENTILATION SYSTEM WILL BE MAINTAINED IN CONTINUOUS OPERATION DURING OCCUPANCY, AS REQUIRED BY IMC SECTION 403.3.	
7. ALL FIRE DAMPERS SHALL BE LISTED AND LABELED IN ACCORDANCE WITH UL 556 AND INSTALLED PER IMC SECTION 607 AND MANUFACTURER'S INSTRUCTIONS.	
8. COMBINATION FIRE/SMOKE DAMPERS AND SMOKE DAMPERS SHALL BE LISTED IN ACCORDANCE WITH UL 556 AND INSTALLED IN ACCORDANCE WITH IMC SECTION 607.	
9. CEILING RADIATION DAMPERS SHALL BE LISTED IN ACCORDANCE WITH UL 555C AND INSTALLED IN FIRE-RESISTANT CEILING ASSEMBLIES IN ACCORDANCE WITH IMC SECTION 607.6.2.	
10. REFER TO ARCHITECTURAL DRAWINGS FOR LOCATIONS AND TYPES OF REQUIRED FIRE-RATED WALLS AND SMOKE PARTITIONS.	
11. THESE PLANS ARE APPROVED ONLY FOR THE SCOPE OF WORK INDICATED ON THE PERMIT APPLICATION. ALL OTHER CONDITIONS, ELEMENTS, OR SYSTEMS NOT COVERED IN THIS REVIEW ARE SUBJECT TO FIELD INSPECTION AND VERIFICATION FOR CODE COMPLIANCE.	
GENERAL NOTES	
1. ALL EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.	
2. THE MECHANICAL EQUIPMENT HAS BEEN COORDINATED WITH THE ELECTRICAL DESIGN DRAWINGS BASED ON THE ELECTRICAL CHARACTERISTICS OF THE EQUIPMENT SPECIFIED.	
GENERAL HVAC NOTES	
1. PROVIDE ALL MATERIAL AND EQUIPMENT AND PERFORM ALL LABOR REQUIRED TO INSTALL COMPLETE AND OPERABLE MECHANICAL SYSTEMS AS INDICATED ON THE DRAWINGS, AS SPECIFIED, AND AS REQUIRED BY CODE.	
2. CONTRACT DOCUMENT DRAWINGS FOR MECHANICAL WORK (HVAC, PLUMBING, AND FIRE PROTECTION) ARE DIAGRAMMATIC AND ARE INTENDED TO CONVEY SCOPE AND GENERAL ARRANGEMENT ONLY.	
3. THE LOCATIONS OF ALL ITEMS SHOWN ON THE DRAWINGS OR CALLED FOR IN THE SPECIFICATIONS THAT ARE NOT FIXED BY DIMENSIONS ARE APPROXIMATE ONLY. DO NOT SCALE DRAWINGS.	
4. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, ELECTRICAL WORK, ETC., SHOWN ON OTHER CONTRACT DOCUMENT DRAWINGS.	
5. INSTALL ALL MECHANICAL EQUIPMENT AND APPURTENANCES IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, CONTRACT DOCUMENTS, AND APPLICABLE CODES AND REGULATIONS.	
6. ALL CONTROL WIRE AND CONDUIT SHALL COMPLY WITH THE NATIONAL ELECTRICAL CODE AND ELECTRICAL DIVISION OF THE SPECIFICATION.	
7. PROVIDE VIBRATION ISOLATION FOR ALL MECHANICAL EQUIPMENT TO PREVENT TRANSMISSION OF VIBRATION TO BUILDING STRUCTURE.	
8. LOCATE ALL TEMPERATURE AND FLOW MEASURING DEVICES IN ACCESSIBLE LOCATIONS WITH THE STRAIGHT SECTION OF PIPE OR DUCT UPSTREAM AND DOWNSTREAM AS RECOMMENDED BY THE MANUFACTURER FOR GOOD ACCURACY.	
9. PROVIDE ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS, WHERE REQUIRED, TO SERVICE DAMPERS, VALVES, SMOKE DETECTORS, AND OTHER CONCEALED MECHANICAL EQUIPMENT. ACCESS PANELS SHALL BE TURNED OVER TO THE GENERAL CONTRACTOR FOR INSTALLATION. ACCESS PANELS SHALL HAVE THE EQUIVALENT FIRE-RATED CAPACITY (1 HR, 2 HR, ETC.) AS THE WALL.	
10. ALL RTU AND AIR CONDITIONING CONDENSATE DRAIN LINES FROM EACH RTU AND AIR HANDLING UNIT SHALL BE PIPED FULL SIZE OF THE UNIT DRAIN OUTLET, WITH "P" TRAP, AND PIPED TO THE NEAREST APPROVED PLACE OF DISPOSAL. SEE THE DETAILS SHOWN IN THE DRAWINGS OR THE CONTRACT SPECIFICATIONS FOR THE DEPTH OF THE AIR CONDITIONING CONDENSATE TRAP.	
A. REFER TO TYPICAL DETAILS FOR DUCTWORK, PIPING, AND EQUIPMENT INSTALLATION.	
THERMOSTATIC CONTROLS (IECC 2020):	
C403.4.1 THERMOSTATIC CONTROLS (MANDATORY)	
THE SUPPLY OF HEATING AND COOLING ENERGY TO EACH ZONE SHALL BE CONTROLLED BY INDIVIDUAL THERMOSTATIC CONTROLS CAPABLE OF RESPONDING TO TEMPERATURE WITHIN THE ZONE, WHERE HUMIDIFICATION OR DEHUMIDIFICATION OR BOTH IS PROVIDED, NOT FEWER THAN ONE THERMOSTATIC CONTROL DEVICE SHALL BE PROVIDED FOR EACH HUMIDITY CONTROL SYSTEM.	
EXCEPTION: INDEPENDENT PERIMETER SYSTEMS THAT ARE DESIGNED TO OFFSET ONLY BOUNDARY ENVELOPE HEAT LOSSES, GAINS OR BOTH SERVING ONE OR MORE PERIMETER ZONES ALSO SERVED BY AN INTERIOR SYSTEM PROVIDED THAT BOTH OF THE FOLLOWING CONDITIONS ARE MET:	
1. THE PERIMETER SYSTEM INCLUDES NOT FEWER THAN ONE THERMOSTATIC CONTROL ZONE FOR EACH BUILDING EXPOSURE HAVING EXTERIOR WALLS FACING ONLY ONE ORIENTATION (WITHIN ± 45 DEGREES) (0.8 RAD) FOR MORE THAN 50 CONTIGUOUS FEET (15 240 MM).	
2. THE PERIMETER SYSTEM HEATING AND COOLING SUPPLY IS CONTROLLED BY THERMOSTATS LOCATED WITHIN THE ZONES SERVED BY THE SYSTEM.	
C403.4.1.2 DEADBAND (MANDATORY)	
WHERE USED TO CONTROL BOTH HEATING AND COOLING, ZONE THERMOSTATIC CONTROLS SHALL BE CONFIGURED TO PROVIDE A TEMPERATURE RANGE OR DEADBAND OF NOT LESS THAN 5°F (2.8°C) WITHIN WHICH THE SUPPLY OF HEATING AND COOLING ENERGY TO THE ZONE IS SHUT OFF OR REDUCED TO A MINIMUM.	
EXCEPTIONS:	
1. THERMOSTATS REQUIRING MANUAL CHANGE OVER BETWEEN HEATING AND COOLING MODES.	
2. OCCUPANCIES OR APPLICATIONS REQUIRING PRECISION IN INDOOR TEMPERATURE CONTROL AS APPROVED BY THE CODE OFFICIAL.	
C403.4.1.3 SETPOINT OVERLAP RESTRICTION (MANDATORY)	
WHERE A ZONE HAS A SEPARATE HEATING AND A SEPARATE COOLING THERMOSTATIC CONTROL LOCATED WITHIN THE ZONE, A LIMIT SWITCH, MECHANICAL STOP OR DIRECT DIGITAL CONTROL SYSTEM WITH SOFTWARE PROGRAMMING SHALL BE CONFIGURED TO PREVENT THE HEATING SETPOINT FROM EXCEEDING THE COOLING SETPOINT AND TO MAINTAIN A DEADBAND IN ACCORDANCE WITH SECTION C403.4.1.2.	
C403.4.2 OFF-HOUR CONTROLS (MANDATORY)	
EACH ZONE SHALL BE PROVIDED WITH THERMOSTATIC SETBACK CONTROLS THAT ARE CONTROLLED BY EITHER AN AUTOMATIC TIME CLOCK OR PROGRAMMABLE CONTROL SYSTEM.	
EXCEPTIONS:	
1. ZONES THAT WILL BE OPERATED CONTINUOUSLY.	
2. ZONES WITH A FULL HVAC LOAD DEMAND NOT EXCEEDING 6,800 BTU/H (2 KW) AND HAVING A MANUAL SHUTOFF SWITCH LOCATED WITH READY ACCESS.	
C403.4.2.1 THERMOSTATIC SETBACK (MANDATORY)	
THE THERMOSTATIC SETBACK CONTROLS SHALL BE CONFIGURED TO SET BACK OR TEMPORARILY OPERATE THE SYSTEM TO MAINTAIN ZONE TEMPERATURES DOWN TO 55°F (13°C) OR UP TO 85°F (29°C).	
C403.4.2.2 AUTOMATIC SETBACK AND SHUTDOWN (MANDATORY)	
AUTOMATIC TIME CLOCK OR PROGRAMMABLE CONTROLS SHALL BE CAPABLE OF STARTING AND STOPPING THE SYSTEM FOR SEVEN DIFFERENT DAILY SCHEDULES PER WEEK AND RETAINING THEIR PROGRAMMING AND TIME SETTING DURING A LOSS OF POWER FOR NOT FEWER THAN 10 HOURS. ADDITIONALLY, THE CONTROLS SHALL HAVE A MANUAL OVERRIDE THAT ALLOWS TEMPORARY OPERATION OF THE SYSTEM FOR UP TO 2 HOURS; A MANUALLY OPERATED TIMER CONFIGURED TO OPERATE THE SYSTEM FOR UP TO 2 HOURS, OR AN OCCUPANCY SENSOR.	
C403.4.2.3 AUTOMATIC START (MANDATORY)	
AUTOMATIC START CONTROLS	

HVAC DUCTWORK - SHEET METAL

1. PROVIDE VOLUME DAMPER AT EACH TAP TO MAIN DUCT AND WHERE NECESSARY TO PROPERLY BALANCE SYSTEM.

2. SUPPLY AND RETURN DUCTWORK 10' FROM ALL AC UNITS SHALL BE LINED WITH 1" ACOUSTICAL LINING.

3. SUPPLY AND INSTALL ALL NECESSARY SUPPLY DIFFUSERS AND RETURN AIR REGISTERS WHERE INDICATED ON THE DRAWING. COORDINATE LOCATION OF DIFFUSERS AND REGISTERS WITH REFLECTED CEILING PLAN.

4. UNLESS OTHERWISE SHOWN, LOCATE ALL ROOM THERMOSTATS 4'-0" (CENTER LINE) ABOVE THE FINISHED FLOOR. NOTIFY THE ENGINEER OF ANY ROOMS WHERE THE PRECEDING LOCATION CANNOT BE MAINTAINED OR WHERE THERE IS A QUESTION ON LOCATION.

5. ALL DUCTWORK DIMENSIONS, AS SHOWN ON THE DRAWINGS, ARE INTERNAL CLEAR DIMENSIONS, AND DUCT SIZE SHALL BE INCREASED TO COMPENSATE FOR DUCT LINING THICKNESS.

6. PROVIDE ALL 90-DEGREE SQUARE ELBOWS WITH DOUBLE RADIUS TURNING VANE. THESE, UNLESS OTHERWISE INDICATED, BOW IN KITCHEN EXHAUSTS SHALL BE OF UNVANED SMOOTH RADIUS CONSTRUCTION WITH A RADIUS EQUAL TO 1-1/2 TIMES THE WIDTH OF THE DUCT. PROVIDE ACCESS DOORS UPSTREAM OF ALL ELBOWS WITH TURNING VANES.

7. ALL RTU AND AIR HANDLING UNITS SHALL OPERATE WITHOUT MOISTURE CARRYOVER.

8. LOCATE ALL MECHANICAL EQUIPMENT FOR UNOBSTRUCTED ACCESS TO UNIT ACCESS PANELS, CONTROLS, AND VALVING.

9. PROVIDE FLEXIBLE CONNECTIONS IN ALL DUCTWORK SYSTEMS (SUPPLY, RETURN, AND EXHAUST) ATTACHED TO AIR HANDLING UNITS, FANS, AND OTHER EQUIPMENT THAT REQUIRE VIBRATION ISOLATION. FLEXIBLE CONNECTIONS SHALL BE PROVIDED AT THE POINT OF CONNECTION TO THE EQUIPMENT UNLESS OTHERWISE INDICATED.

10. UNLESS OTHERWISE NOTED, ALL DUCTWORK IS OVERHEAD, TIGHT TO THE UNDERSIDE OF THE STRUCTURE, WITH SPACE FOR INSULATION IF NEEDED.

11. PROVIDE ACCESS DOORS IN DUCTWORK TO PROVIDE ACCESS FOR ALL SMOKE DETECTORS, FIRE DAMPERS, SMOKE DAMPERS, VOLUME DAMPERS, COILS, AND OTHER ITEMS LOCATED IN THE DUCTWORK THAT REQUIRE SERVICE AND/OR INSPECTION.

12. PROVIDE ACCESS DOORS FOR THE OPERATION, ADJUSTMENT, AND MAINTENANCE OF ALL FANS, VALVES, AND MECHANICAL EQUIPMENT.

13. SEE SPECIFICATIONS FOR DUCTWORK GAUGES, BRACING, HANGERS, AND OTHER REQUIREMENTS.

SECTION 0101 - QUALITY OF WORK

1.1 CODE COMPLIANCE
A. ALL WORK SHALL MEET ALL STATE AND LOCAL CODES HAVING JURISDICTION.

END OF SECTION 0101

SECTION 230517 - SLEEVES AND SLEEVE SEALS FOR HVAC PIPING

1.1 SLEEVE-SEAL SYSTEMS
A. FIELD-ASSEMBLED, MODULAR SEALING-ELEMENT UNIT FOR FILLING ANNUAL SPACE BETWEEN PIPING AND SLEEVE.
1. SEALING ELEMENTS: EPDM RUBBER OR NBR.
2. PRESSURE PLATES: CARBON STEEL, PLASTIC, STAINLESS STEEL.
3. CONNECTING BOLTS AND NUTS: CARBON STEEL WITH CORROSION-RESISTANT COATING, STAINLESS STEEL.

B. MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, AVAILABLE MANUFACTURERS OFFERING PRODUCTS THAT MAY BE INCORPORATED INTO THE WORK, BUT ARE NOT LIMITED TO, THE FOLLOWING:
1. ADVANCE PRODUCTS & SYSTEMS, INC.
2. CALPCO, INC.
3. METRAFLEX COMPANY (THE).
4. PIPELINE SEAL AND INSULATOR, INC.
5. PROCO PRODUCTS, INC.

1.2 GROUT
A. NON-SHRINK, FACTORY-PACKAGED.

1.3 SLEEVE AND SLEEVE-SEAL SCHEDULE
A. USE SLEEVES AND SLEEVE SEALS FOR THE FOLLOWING PIPING-PENETRATION APPLICATIONS:
1. INTERIOR PARTITIONS:
A. PIPING SMALLER THAN NPS 6 (DN 150): GALVANIZED-STEEL PIPE SLEEVES, PVC PIPE SLEEVES.
B. PIPING NPS 6 (DN 150) AND LARGER: GALVANIZED-STEEL-SHEET SLEEVES.

END OF SECTION 230517

SECTION 230518 - ESCUTCHEONS FOR HVAC PIPING

PART 2 - PRODUCTS
2.1. ESCUTCHEONS
A. ONE-PIECE, CAST-BRASS TYPE: WITH POLISHED, CHROME-PLATED AND ROUGH-BRASS FINISH AND SETSCREW FASTENER.
B. ONE-PIECE, DEEP-PATTERN TYPE: DEEP-DRAWN, BOX-SHAPED BRASS WITH CHROME-PLATED FINISH AND SPRING-CLIP FASTENERS.
C. ONE-PIECE, STAMPED-STEEL TYPE: WITH CHROME-PLATED FINISH AND SPRING-CLIP FASTENERS.
2.2. FLOOR PLATES
A. ONE-PIECE FLOOR PLATES: CAST-IRON FLANGE WITH HOLES FOR FASTENERS.

PART 3 - EXECUTION
3.1. INSTALLATION
A. INSTALL ESCUTCHEONS FOR PIPING PENETRATIONS OF WALLS, CEILINGS, AND FINISHED FLOORS.
B. INSTALL ESCUTCHEONS WITH ID TO CLOSELY FIT AROUND PIPE, TUBE, AND INSULATION OF PIPING AND WITH OD THAT COMPLETELY COVERS OPENING.
1. ESCUTCHEONS FOR NEW PIPING:
a. PIPING WITH FITTING OR SLEEVE PROTRUDING FROM WALL: ONE-PIECE, DEEP-PATTERN TYPE.
b. INSULATED PIPING: ONE-PIECE, STAMPED-STEEL TYPE.
c. BARE PIPING AT WALL AND FLOOR PENETRATIONS IN FINISHED SPACES: ONE-PIECE, CAST-BRASS TYPE WITH POLISHED, CHROME-PLATED FINISH OR STAMPED-STEEL TYPE.
d. BARE PIPING AT CEILING PENETRATIONS IN FINISHED SPACES: ONE-PIECE, CAST-BRASS TYPE WITH POLISHED, CHROME-PLATED FINISH OR STAMPED-STEEL TYPE.

END OF SECTION 230518

SECTION 230529 - HANGERS AND SUPPORTS FOR HVAC PIPING AND EQUIPMENT

1.1 PERFORMANCE REQUIREMENTS
A. DELEGATED DESIGN: DESIGN TRAPEZE PIPE HANGERS AND EQUIPMENT SUPPORTS, INCLUDING COMPREHENSIVE ENGINEERING ANALYSIS BY A QUALIFIED PROFESSIONAL ENGINEER, USING PERFORMANCE REQUIREMENTS AND DESIGN CRITERIA INDICATED.
B. STANDARD PERFORMANCE: HANGERS AND SUPPORTS FOR HVAC PIPING AND EQUIPMENT SHALL WITHSTAND THE EFFECTS OF GRAVITY LOADS AND STRESSES WITHIN LIMITS AND UNDER CONDITIONS INDICATED ACCORDING TO ASCE/SEI 7-16. DESIGN SUPPORTS FOR MULTIPLE PIPES CAPABLE OF SUPPORTING COMBINED WEIGHT OF SUPPORTED SYSTEMS, SYSTEM CONTENTS, AND TEST WATER.
2. DESIGN EQUIPMENT SUPPORTS CAPABLE OF SUPPORTING COMBINED OPERATING WEIGHT OF SUPPORTED EQUIPMENT AND CONNECTED SYSTEMS.
3. DESIGN SEISMIC-RESTRAINT HANGERS AND SUPPORTS FOR PIPING AND EQUIPMENT AND OBTAIN APPROVAL FROM AUTHORITIES HAVING JURISDICTION.

1.2 COMPONENTS
A. METAL PIPE HANGERS AND SUPPORTS: CARBON OR STAINLESS STEEL.
B. TRAPEZE PIPE HANGERS: CARBON OR STAINLESS STEEL.
C. FIBERGLASS PIPE HANGERS: CLEVIS, CENTURY COMPOSITES, COOPER B-LINE.
D. METAL FRAMING SYSTEMS: MFMA MANUFACTURER.
E. FIBERGLASS STRUT SYSTEMS: COOPER B-LINE.
F. THERMAL-HANGER SHIELD INSERTS.
G. FASTENER SYSTEMS: POWDER-ACTUATED FASTENERS OR MECHANICAL-EXPANSION ANCHORS.
H. PIPE STANDS: COMPACT, LOW TYPE, SINGLE PIPE; HIGH TYPE, SINGLE PIPE; HIGH TYPE, MULTIPLE PIPES, CURB-MOUNTED TYPE.
I. EQUIPMENT SUPPORTS.

END OF SECTION 230529

SECTION 230593 - TESTING, ADJUSTING, AND BALANCING FOR HVAC

1.1 SUMMARY
A. TESTING, ADJUSTING, AND BALANCING FOR THE FOLLOWING:
1. AIR SYSTEMS: CONSTANT-VOLUME SYSTEMS.
2. EXISTING SYSTEMS.

1.2 QUALITY ASSURANCE

A. PROCURE THE SERVICES OF A TESTING, ADJUSTING AND BALANCING (TAB) SPECIALIST WHO SPECIALIZES IN HEATING, VENTILATION AND AIR CONDITIONING SYSTEMS. THE TAB AGENT SHALL HAVE THE FOLLOWING QUALIFICATIONS: AABC, NEBB, OR TABB CERTIFIED.

END OF SECTION 230593

1.3 EXECUTION

A. THE TAB SPECIALIST SHALL PERFORM FLOW MEASUREMENTS OF ALL EXISTING AIR AND HYDRONIC SYSTEMS THAT ARE TO REMAIN OR TO BE INCORPORATED INTO NEW WORK PRIOR TO THE START OF WORK IN THE PROJECT SCOPE. A REPORT OF THESE MEASUREMENTS, INDICATING ANY AND ALL DEFICIENCIES, SHALL BE SUBMITTED FOR OWNER REVIEW.
B. THE TAB SPECIALIST SHALL PERFORM FLOW MEASUREMENTS OF ALL NEW AIR AND HYDRONIC SYSTEMS AS LISTED ABOVE IN THE PROJECT SCOPE. A REPORT OF THESE MEASUREMENTS, INDICATING ANY AND ALL DEFICIENCIES, SHALL BE SUBMITTED FOR OWNER REVIEW.

C. THE REPORT SHALL INDICATE A SCHEMATIC DIAGRAM SHOWING THE LOCATIONS OF ALL EQUIPMENT TESTED AND MEASUREMENT LOCATIONS.

D. PRIOR TO THE FINAL INSPECTION OF THE WORK, THE TAB SPECIALIST SHALL BALANCE ALL SYSTEMS AS INDICATED ABOVE TO THE REQUIREMENTS OF THE DESIGN.

E. FURNISH AND INSTALL ALL ADDITIONAL BALANCING EQUIPMENT, PRESSURE TAPS, GAUGES, AND OTHER EQUIPMENT AS REQUIRED FOR A PROPERLY BALANCED SYSTEM AT NO ADDITIONAL COST TO THE OWNER. SUCH ADDITIONAL EQUIPMENT SHALL ADHERE STRICTLY TO THE RESPECTIVE EQUIPMENT MANUFACTURER'S RECOMMENDATIONS.

F. COORDINATE ALL WORK OF THIS SECTION WITH THE BUILDING MANAGER. BALANCING WORK SHALL NOT CONFLICT WITH OTHER WORK SO AS TO MAINTAIN COMPLETION WITHIN THE SPECIFIED TIME.

G. ALL INSTRUMENTS USED FOR TAB SHALL BE MAINTAINED IN GOOD WORKING CONDITION AND ACCURATELY CALIBRATED.

H. TOLERANCES: PLUS OR MINUS 5 PERCENT OF DESIGN VALUES.

I. INSPECTIONS: RANDOM CHECKS BY OWNER OR ARCHITECT TO VERIFY FINAL TESTING, ADJUSTING, AND BALANCING REPORT.

J. ADDITIONAL TESTS: RANDOM TESTS WITHIN 90 DAYS OF COMPLETING TAB TO VERIFY BALANCE CONDITIONS AND SEASONAL TESTS.

END OF SECTION 230593

SECTION 230713 - DUCT INSULATION

1.1 QUALITY ASSURANCE

SURFACE-BURNING CHARACTERISTICS: ALL INSULATION SHALL HAVE A COMPOSITE (INSULATION, FIBER OR FACING AND ADHESIVE USED TO ADHESIVE BONDING OR JACKET TO THE INSULATION) FLAME SPREAD INDEX OF 25 AND SMOKE-DEVELOPED INDEX OF 50 FOR INSULATION INSTALLED INDOORS, 75, AND SMOKE-DEVELOPED INDEX OF 150 FOR INSULATION INSTALLED OUTDOORS, ACCORDING TO ASTM E84.

1.2 FIELD QUALITY CONTROL

A. FIELD INSPECTIONS: BY OWNER-ENGAGED AGENCY.

1.3 INDOOR DUCT AND PLENUM INSULATION SCHEDULE:

A. CONCEALED, RECTANGULAR, ROUND, AND FLAT-oval SUPPLY RETURN, OUTDOOR, AND EXHAUST-AIR DUCT AND AIR PLENUM INSULATION.

B. FLEXIBLE ELASTOMERIC, MINERAL-FIBER BLANKET, MINERAL-FIBER BOARD, OR POLYOLEFIN WITH MINIMUM INSTALLED THERMAL RESISTANCE AS FOLLOWS:

• UNCONDITIONED SPACES WITHIN THE BUILDING: R-6
• WITHIN BUILDING ENVELOPE ASSEMBLY: R-12
• OUTSIDE OF BUILDING: R-12

1.4 ITEMS NOT INSULATED:

1. FIBROUS-GLASS DUCTS.
2. METAL DUCTS WITH DUCT LINER OR SUFFICIENT THICKNESS TO COMPLY WITH ENERGY CODE AND ASHRAE/IESNA 90.1.

3. FACTORY-INSULATED FLEXIBLE DUCTS.

4. FACTORY-INSULATED PLENUMS AND CASINGS.

5. FLEXIBLE CONNECTORS.

6. VIBRATION-CONTROL DEVICES.

7. FACTORY-INSULATED ACCESS PANELS AND DOORS.

8. DUCTS THAT HAVE INTERNAL ACOUSTICAL LINING.

1.5 PRODUCTS

A. THE FOLLOWING INSULATION MANUFACTURERS WILL BE ACCEPTABLE:

1. JOHNS-MANVILLE

2. OWENS-CORNING

1.6 ACOUSTICAL TREATMENT

WHERE SHOWN ON THE DRAWINGS, LOW-PRESSURE DUCTWORK SHALL BE LINED WITH 1/2" THICK R-11 INSULATION, FACTUMATE, 1-1/2 POUND MINIMUM INSULATION, AND FIBERGLASS FIBERGLASS FIBERGLASS LINER. LINING SHALL COMPLY WITH NFPA 30A AND SHALL HAVE A FLAME SPREAD CLASSIFICATION OF NOT MORE THAN 25 AND A SMOKE-DEVELOPED RATING NOT MORE THAN 50. DUCT SIZES WHERE LINING IS INDICATED ON PLANS ARE MINIMUM INSIDE CLEAR DIMENSIONS REQUIRED.

1.7 SEALANT MATERIALS

1. TWO-PART TAPE SEALING SYSTEM.
2. WATER-BASED JOINT AND SEAM SEALANT.
3. SOLVENT-BASED JOINT AND SEAM SEALANT.

4. FLANGED JOINT SEALANT.

5. FLANGE GASKETS.

END OF SECTION 230713

PIPING INSULATION

A. INSULATE ALL PIPING IN ACCORDANCE WITH INSULATION SCHEDULE EXCEPT AS OTHERWISE NOTED.

PIPING INSULATION SCHEDULE

SERVICE	SIZE (OPERATING TEMP.)	THICKNESS	FINISH
CONDENSATE PIPING (105-140°F)	<1.5"	1.0"	P-6

SECTION 23113 - METAL DUCTS

1.1 CONSTRUCTION

A. EACH DUCT SYSTEM SHALL BE CONSTRUCTED FOR THE SPECIFIC SMACNA Duct Pressure CLASSIFICATIONS SHOWN ON THE CONTRACT DRAWINGS. WHERE NO PRESSURE CLASSES ARE SPECIFIED BY THE DESIGNER, THE SMACNA 2-1/2 INCH WG PRESSURE CLASS IS THE BASIS OF COMPLIANCE WITH THESE STANDARDS, REGARDLESS OF THE VELOCITY IN THE DUCT.

B. ALL DUCTWORK SHALL BE CONSTRUCTED TO SMACNA 2" WG DESIGN AND NOT LESS THAN THE FOLLOWING STANDARDS:

1. DUCTWORK SHALL BE TRANSVERSELY JOINED BY CONNECTING SEAMS OF COMPANION ANGLES FORMED FROM 1-1/2" X 1-1/2" X 1/8" GALVANIZED ANGLES, TACK-WELDED OR RIVETED TO THE DUCT. THE ANGLE FRAME SHALL BE CONTINUOUSLY FLANGED UP INTO THE UPRIGHT OF THE ANGLE AND EACH CORNER SHALL BE FILLED IN AND GROUND SMOOTH. JOINTS SHALL BE GASKETED WITH 1/8" THICK REINFORCED GASKET, OVERLAPPED AT CORNERS, GASKET SIMILAR TO 3M-1202 OR APPROVED EQUAL.

2. RECTANGULAR FITTINGS AND ALL TRANSITION PIECES FROM RECTANGULAR TO ROUND SHALL BE NO. 16 GAUGE ALL-WELDED CONSTRUCTION.

3. HORIZONTAL DUCTS SHALL BE SUPPORTED ON NOT MORE THAN 6' CENTERS. VERTICAL RISERS SHALL BE SUPPORTED AT EACH FLOOR.

4. LONGITUDINAL SEAMS FOR RECTANGULAR DUCTWORK SHALL BE PITTSBURGH LOCK SEAMS WITH SEALING COMPOUND, EQUAL TO BENJAMIN FOSTER NO. 30-03 INSERTED INTO THE SEAM. ALL SEAMS SHALL BE BRUSHED WITH NO. 30-02 AND COVERED WITH APPROVED SEALING TAPE.

5. RECTANGULAR DUCTWORK 18 GAUGE AND HEAVIER, FILLER RODS SHALL BE IN ACCORDANCE WITH SPECIFICATIONS FOR IRON AND STEEL GAS WELDING RODS, ASTM 215; AVG A5.2.

6. ALL FITTINGS SUCH AS ELBOWS, TEES, ETC., SHALL BE NO. 20 GAUGE ZINC-COATED STEEL. ELBOWS SHALL BE OF FIVE (5) PIECE WELDED AIRTIGHT CONSTRUCTION.

7. WHERE LATEST EDITION OF SMACNA DOES NOT CLEARLY STATE GAUGES AND/OR STIFFENERS TO BE USED OR, WHERE SMACNA STANDARDS REQUIRE INTERPRETATION, THE FOLLOWING MINIMUM METAL GAUGES AND BRACING SHALL BE USED:

ERS SHALL HAVE AN OPPPOSED BLADE DAMPER UNLESS OTHERWISE NOTED.

USG	MAX. SIDE INCHES	TRANSVERSE JOINTS AND BRACING
22	UP TO 12	S-SLIP, DRIVE SLIP, ONE INCH POCKET LOCK ON 8-FOOT CENTERS
22	13 TO 24	1" X 1" X 1/8" ANGLES ON 4-FOOT CENTERS
20	25 TO 35	1" X 1" X 1/8" ANGLES ON 2-FOOT CENTERS

A. PROVIDE TAPPING IN DUCTS FOR THERMOMETERS WHERE SPECIFIED. IN ADDITION, PROVIDE AN AIRTIGHT PLUGGED TAPPING LOCATED AS FOLLOWS:

1. UPSTREAM OF EACH REHEATING COIL AND VAV BOX.
2. DOWNSTREAM OF EACH REHEATING COIL AND VAV BOX.

B. FLAT OVAL OR ROUND DUCTWORK MAY BE PROVIDED IN LIEU OF RECTANGULAR DUCTWORK, WITH THE REINFORCEMENT FOR FLAT SIDES THE SAME AS SPECIFIED FOR THE RECTANGULAR DUCTWORK, AND AS PER SMACNA FLAT OVAL DUCT CONSTRUCTION STANDARDS SHOWN IN FIG. 3-6 AND AS SHOWN IN FIG. 3-1 AND 3-2 FOR ROUND DUCTWORK.

C. ALL DUCTWORK SHALL BE SEALED TO CLASS "A" AND LEAK TESTED TO MEET SMACNA CLASS 6 FOR RECTANGULAR DUCTS AND CLASS 3 FOR ROUND DUCTS.



1.2 MATERIALS

A. SINGLE-WALL RECTANGULAR DUCTS AND FITTINGS.
B. SINGLE-WALL ROUND AND FLAT-oval DUCTS AND FITTINGS.
C. SHEET METAL MATERIALS:

1. GALVANIZED SHEET STEEL.
2. STAINLESS-STEEL SHEETS.
3. ALUMINUM SHEETS.
4. FACTORY-APPLIED ANTI-MICROBIAL COATING.

D. DUCT LINER:

1. FIBROUS GLASS, TYPE I, FLEXIBLE.
2. WITH ANTI-MICROBIAL EROSION-RESISTANT COATING.
2. FLEXIBLE ELASTOMERIC.
3. NATURAL FIBER.




MECHANICAL ROOF PLAN

2 1/4" = 1'-0"

MECHANICAL FLOOR PLAN KEY NOTES:

1. 6"Ø EXHAUST DUCT UP TO ROOF CAP.
2. 22"x12" SUPPLY AIR DUCT UP TO RTU-1 ON ROOF.
3. 26"x12" RETURN AIR DUCT UP TO RTU-1 ON ROOF.
4. FIELD COORDINATE THE EXACT LOCATION OF HVAC EQUIPMENT. MAINTAIN CODE REQUIRED, MANUFACTURER RECOMMENDED CLEARANCES AT HVAC EQUIPMENT.
5. 3"Ø SUPPLY AIR DUCT DN TO CRAWL SPACE. BALANCE FOR 30 CFM. PROVIDE W.M.S.
6. 3"Ø RELIEF AIR DUCT FROM CRAWL SPACE THROUGH ROOF CAP. PROVIDE W.M.S. AT DUCT END IN CRAWL SPACE.
7. TERMINATE THE CONDENSATE DRAIN PIPE INDIRECTLY TO THE NEAREST FLOOR SINK. THE CONTRACTOR IS REQUIRED TO VERIFY THE ROUTING AND TERMINATION IN THE FIELD.
8. ACOUSTICALLY LINE THE FIRST 10'-0" OF BOTH SUPPLY AND RETURN MAIN DUCTS.
9. PROVIDE NEW REMOTE TEMPERATURE/HUMIDITY SENSOR MOUNTED IN RETURN DUCT AND WIRE BACK TO T-STAT.
10. PROVIDE NEW 7-DAY PROGRAMMABLE THERMOSTAT. LOCATE THERMOSTAT 4' ABOVE FINISHED FLOOR. COORDINATE EXACT LOCATION WITH ARCHITECT AND OWNER PRIOR TO ROUGH-IN. PROVIDE LOCKABLE COVER.
11. FIELD VERIFY FIRE RATING OF ROOF & PROVIDE FIRE/SMOKE DAMPER AS IF REQUIRED.
12. INTERCONNECT EXHAUST FAN WITH RTU-1. FAN SHALL BE SUSPENDED FROM STRUCTURE ABOVE. VERIFY EXACT LOCATION OF STRUCTURAL MEMBERS PRIOR TO INSTALLATION.



BLACK ROCK COFFEE DRIVE THROUGH

NY ENGINEERS

NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH: 914.257.3455
WWW.NY-ENGINEERS.COM

CONTROL NO: #001


ISSUED FOR PERMIT (07-01-2025)

JOB NUMBER: 24-000325

DATE: 04-22-2025

CONTENTS: MECHANICAL FLOOR & ROOF PLAN

M1.0




BLACK ROCK COFFEE DRIVE THROUGH

NY ENGINEERS

NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY-ENGINEERS.COM

CONTROL NO: #001
ISSUED FOR PERMIT (07-01-2025)
JOB NUMBER: 24-000325
DATE: 04-22-2025
CONTENTS: MECHANICAL DETAILS (1 OF 2)



ELECTRIC HEAT ROOFTOP UNIT SCHEDULE																																	
TAG	QTY.	PROJECT ELEVATION (FT)	SERVICE	NOMINAL TONS	TOTAL CFM	O.A. CFM	SUPPLY FAN DATA			COOLING DATA						ELECTRIC HEATING DATA			ELECTRICAL DATA			WEIGHT (LBS)	DIMENSION (IN.) (L X W X H)	POWER EXHAUST	EFFICIENCY		MODEL	BASIS OF DESIGN	NOTES				
							FAN QTY.	E.S.P. (IN. W.C.)	BHP	MAX RPM	STAGE	TOTAL MBH	SENSIBLE MBH	EAT	LAT	STAGE	CAPACITY (kW)	MODEL	V/Ph/Hz	MCA	MCOP	DISCONNECT BY	TYPE										
RTU-1	1	5920	SEE PLAN	5.0	2000	160	1	1.20	1.44	2390	1	62.0	46.2	80	67	56.9	53.7	2	12 kW	CRHEATER328A00	208/3/60	55	60	MFR	NON-FUSE	830	74 3/8" X 46 5/8" X 33 3/8"	NO	14.0	11.4	50FE-B06A6M5-8A7C0 OR EQUAL	CARRIER OR EQUAL	1 TO 21

NOTES:

1. ALL EQUIPMENT MUST BE HIGH EFFICIENCY, MEETING OR EXCEEDING THE ENERGY CODE MINIMUM REQUIREMENTS.
2. ELECTRICAL CONNECTION TO BE SINGLE POINT AND TO BE THROUGH THE BOTTOM OF THE UNIT.
3. PROVIDE BAROMETRIC RELIEF DAMPER AND HOOD.
4. PROVIDE DIRTY FILTER STATUS SWITCH/ALARM.
5. PROVIDE 14" HIGH PRE-FAB INSULATED CURB WITH SEPARATE SUPPLY AND RETURN DUCT PENETRATIONS THROUGH THE ROOF WITHIN THE ROOF CURB.
6. PROVIDE A 7-DAY PROGRAMMABLE THERMOSTAT.
7. PROVIDE THERMOSTAT FOR FACTORY PROVIDED/INSTALLED BASED ON AVAILABILITY.
8. PROVIDE CONDENSER HAIL GUARDS.
9. PROVIDE FACTORY MOUNTED DISCONNECT SWITCH.
10. PROVIDE FACTORY MOUNT CONVENIENCE OUTLET.
11. THE FIRE ALARM CONTRACTOR SHALL INTERLOCK THE ROOFTOP UNIT WITH THE FIRE ALARM SYSTEM TO SHUT DOWN THE UNIT UPON DETECTION OF SMOKE.
12. PROVIDE ELECTRIC HEATER WITH SCR CONTROL.
13. PROVIDE A 5-YEAR EXTENDED WARRANTY ON NEW MECHANICAL EQUIPMENT.
14. ENTHALPY ECONOMIZER WITH BAROMETER RELIEF . PROVIDE FDD.
15. THE UNIT SHALL BE ANCHORED TO THE ROOF CURB.
16. ELECTRICAL CONNECTION TO BE SINGLE POINT AND TO BE THROUGH THE BOTTOM OF THE UNIT.
17. CABINET WITH 1/2" FIBERGLASS INSULATION.
18. PROVIDE 8-WIRE, 24 VAC, AUTOMATIC CHANGEOVER, 2-STAGE HEAT / COOL, REMOTELY PROGRAMMABLE THERMOSTAT.
19. REMOTE SENSORS SHALL BE PROVIDED IN RETURN AIR DUCT & WIRED BACK TO PROGRAMMABLE, 24 HOUR, 7 DAY, THERMOSTATS.
20. ANTI SHORT CYCLE TIMER.
21. VFD SUPPLY FAN.

CEILING EXHAUST FAN SCHEDULE													
SYMBOL	TYPE	QTY.	LOCATION	FAN DATA			PHYSICAL DATA			SOUND (Sones)	MODEL	BASIS OF DESIGN	
				AIR FLOW (CFM)	E.S.P. (IN. W.C.)	ELECTRICAL DATA	DIMENSION (IN.) (L X W X H)	NET WEIGHT (LBS)					
CEF-1	CEILING MOUNTED	1	REFER TO PLAN	70	0.5	115/1/60	1.9	15	14" X 12" X 11"	30	1.5	CSP-A390-VG OR EQUAL	GREENHECK OR EQUAL

NOTES:

1. TO AVOID MOTOR BEARING DAMAGE AND NOISY OR UNBALANCED IMPELLERS, KEEP DRYWALL SPRAY, CONSTRUCTION DUST, ETC. OFF POWER UNIT.
2. IT SHALL BE DUCTED TO A ROOF OR WALL CAP USING ROUND DUCTWORK.
3. THE BLOWER ASSEMBLY SHALL BE REMOVABLE, HAVE A CENTRIFUGAL TYPE BLOWER WHEEL, AND A PERMANENTLY LUBRICATED.
4. COORDINATE STARTERS AND DISCONNECTS WITH NEMA-1 ENCLOSURES FOR CEF-1, IF NOT FACTORY-PROVIDED. COORDINATE EXACT POWER REQUIREMENT WITH ELECTRICAL CONTRACTOR.
5. PROVIDE FAN WITH A BACKDRAFT DAMPER AND SPEED CONTROLLER FOR BALANCING PURPOSES.
6. ALL DIRECT-DRIVE FANS SHALL BE PROVIDED WITH ECM MOTORS.
7. PROVIDE FIRE BLANKET AND RADIATION DAMPER AS IF REQUIRED FOR FIRE RATED CEILING.

AIR CURTAIN SCHEDULE												
SYMBOL	TYPE	QTY.	LOCATION	FAN DATA			PHYSICAL DATA			SOUND (dBA)	MODEL	BASIS OF DESIGN
				AIR FLOW (CFM)	VELOCITY (FPM)	ELECTRICAL DATA	DIMENSION (IN.)	NET WEIGHT (LBS)				
AC-2-AC-3	WALL MOUNTED	2	REFER TO PLAN	625	1800	115/1/60	2.4	25" X 8"	20	49	LPV225-1U-OB	MARS
AC-1	WALL MOUNTED	1	REFER TO PLAN	900	1800	115/1/60	2.4	36" X 8"	32	49	LPV236-1U-OB	MARS

NOTES:

1. PROVIDE MANUFACTURER RECOMMENDED ACCESSORIES.
2. COORDINATE WITH ELECTRICAL CONTRACTOR FOR EXACT POWER REQUIREMENT.
3. COORDINATE COLOR CODE WITH CLIENT/ARCHITECT.
4. CONTRACTOR SHALL COORDINATE WITH ARCHITECT/OWNER FOR PROPER INTEGRATION OF AIR CURTAIN WITH DOOR SENSORS OR OTHER CONTROL MECHANISMS. CONTROL SHALL BE PROVIDED TO OPERATE THE AIR CURTAIN IN SYNCHRONIZATION WITH THE OPENING AND CLOSING OF THE DOOR.

VENTILATION SCHEDULE - 2018 INTERNATIONAL MECHANICAL CODE																
SR.NO	NAME	OCCUPANCY CLASSIFICATION	FLOOR AREA (S.F.)	OCCUPANTS PER 1000 SQ.FT.	OCCUPANTS (ACTUAL) Pz	REQUIRED OUTSIDE AND EXHAUST AIR						ACTUAL ROOM VENTILATION			EQUIPMENT	
						CFM/PERSON Rp	CFM/SQ.FT. Ra	TOTAL O.A. Vbz	ZONE AIR DISTRIBUTION EFFECTIVENESS Ez	ZONE OUTDOOR AIRFLOW Voz	TOTAL EXHAUST CFM	TOTAL	% O.A.	TOTAL O.A.	EXHAUST CFM	
1	KITCHEN AREA	COFFEE STATION	325	20	7	7.5	0.18	103	0.8	130	0	1950	-	160	0	RTU-1
2	STORAGE	STORAGE	175	0	1	0	0.12	21	0.8	27	0					CEF-1
2	RESTROOM	TOILET	55	0	0	0	0	0	0.8	0	70	50	0	0	0	EUH-1
3	RISER RM	-	30	0	0	0	0	0	0.8	0	0	0	0	0	0	-
	TOTAL		585	-	8	-	-	124	-	157	70	2000	-	160	70	-

NOTE:

1. COORDINATED WITH IMC 2018, TABLE 403.3.1.1.

AIR DEVICE SCHEDULE													
TYPE	SERVICE	SERVING	NECK SIZE	PANEL/FACE SIZE	MATERIAL	DESCRIPTION	MODEL NO.	BASIS OF DESIGN	EXAMPLE	REFERENCE IMAGE			
										NOMENCLATURE		U-CFM-T SIZE	
										CFM = AIR QUANTITY		CFM	T = TYPE OF AIR DEVICE
A	SUPPLY	REFER TO FLOOR PLAN	10"Ø,14"Ø	24" X 24"	ALUMINUM	SQUARE CEILING DIFFUSER	TDC	TIT					

ELECTRICAL LEGENDS

POWER	MISCELLANEOUS	ELECTRICAL ABBREVIATIONS
ABOVE COUNTER QUADPLEX RECEPTACLE	J (J)	JUNCTION BOX - CEILING/WALL MOUNTED
ABOVE COUNTER DUPLEX RECEPTACLE	PB	FULL BOX
QUADPLEX RECEPTACLE	(A)	CONDUIT CONCEALED IN WALL, CEILING OR UNDERGROUND. CENTER LINES DENOTE UNDERGROUND/FLOOR CONDUIT. DASHED LINES DENOTE DEMOLITION.
DUPLEX RECEPTACLE	(B)	ARROWHEAD DENOTES HOMERUN TO PANEL. SLASHED DENOTE QUANTITY OF CONDUCTORS.
SPECIAL RECEPTACLE	(C)	DOT DENOTES GROUND.
WEATHER PROOF/GFI DUPLEX RECEPTACLE	(D)	LONG SLASH DENOTES NEUTRAL CONDUCTOR. SHORT SLASH DENOTES PHASE CONDUCTOR, SWITCH LEG OR CONTROL.
D.GFI DEDICATED, GFI OUTLET	(E)	FLEXIBLE CONDUIT WHIP - MAX 6'-0" IN LENGTH
RECEPTACLE WITH ISOLATED GROUND	(F)	METER
CEILING DUPLEX RECEPTACLE	(G)	FUSED SWITCH
CEILING QUADPLEX RECEPTACLE	(H)	CIRCUIT BREAKER
CEILING SPECIAL RECEPTACLE	(I)	ENCLOSED CIRCUIT BREAKER
FLOOR QUADPLEX RECEPTACLE	(J)	FUSED SWITCH
FLOOR DUPLEX RECEPTACLE	(K)	DISCONNECT SWITCH
FLOOR SPECIAL RECEPTACLE	(L)	FUSED DISCONNECT SWITCH
GFI FLOOR QUADPLEX RECEPTACLE	(M)	COMBINATION STARTER DISCONNECT SWITCH W/H.O.A.
GFI FLOOR DUPLEX RECEPTACLE	(N)	MOTOR
LOW VOLTAGE		
VOICE/DATA OUTLET	(O)	FUSED SWITCH
ABOVE COUNTER VOICE/DATA OUTLET	(P)	DISCONNECT SWITCH
FLOOR / CEILING VOICE/DATA OUTLET	(Q)	FUSED DISCONNECT SWITCH
DATA OUTLET	(R)	COMBINATION STARTER DISCONNECT SWITCH W/H.O.A.
FLOOR / CEILING VOICE/DATA OUTLET	(S)	MOTOR
LIGHTING		
SWITCH	(T)	FUSED SWITCH
DIMMER SWITCH	(U)	DISCONNECT SWITCH
3 - WAY SWITCH	(V)	FUSED DISCONNECT SWITCH
4 - WAY SWITCH	(W)	COMBINATION STARTER DISCONNECT SWITCH W/H.O.A.
VACANCY SENSOR (WALL MOUNTED)	(X)	MOTOR
OCCUPANCY SENSOR (WALL MOUNTED)	(Y)	
LOW VOLTAGE MOMENTARY CONTACT SWITCH	(Z)	
TIME SWITCH OVER RIDE SWITCH	(AA)	
SINGLE POLE ROCKER SWITCH WITH WI-FI CONTROL AND BLUETOOTH REMOTE (#AWS04F OR EQUAL)	(BB)	
DIMMER WITH WALL MOUNTED OCCUPANCY SWITCH	(CC)	
VACANCY SENSOR (CEILING)	(DD)	
OCCUPANCY SENSOR (CEILING)	(EE)	
DAYLIGHT SENSOR (CEILING)	(FF)	
BATTERY EMERGENCY LIGHT (WALL MOUNTED)	(GG)	
BATTERY EMERGENCY LIGHT (CEILING MOUNTED)	(HH)	
EXIT SIGN	(II)	
UPPERCASE LETTER DENOTES FIXTURE TAG	(JJ)	
LOWERCASE LETTER DENOTES SWITCH DESIGNATION	(KK)	
TIME CLOCK	(LL)	
ANNOTATION		
KEY NOTE TAG	(MM)	
LINE WEIGHT LEGEND		
— NEW		
APPLICABLE CODES		
1. 2018 IDAHO BUILDING CODE WITH AMENDMENTS (IBC) 2. 2020 IDAHO ENERGY CONSERVATION CODE (IECC 2018) 3. 2018 IDAHO MECHANICAL CODE (IMC) 4. 2017 IDAHO PLUMBING CODE (ADOPTS WITH AMENDMENTS UPC 2015) 5. 2017 NATIONAL ELECTRICAL CODE		

POWER	MISCELLANEOUS	ELECTRICAL ABBREVIATIONS
ABOVE COUNTER QUADPLEX RECEPTACLE	J (J)	JUNCTION BOX - CEILING/WALL MOUNTED
ABOVE COUNTER DUPLEX RECEPTACLE	PB	FULL BOX
QUADPLEX RECEPTACLE	(A)	CONDUIT CONCEALED IN WALL, CEILING OR UNDERGROUND. CENTER LINES DENOTE UNDERGROUND/FLOOR CONDUIT. DASHED LINES DENOTE DEMOLITION.
DUPLEX RECEPTACLE	(B)	ARROWHEAD DENOTES HOMERUN TO PANEL. SLASHED DENOTE QUANTITY OF CONDUCTORS.
SPECIAL RECEPTACLE	(C)	DOT DENOTES GROUND.
WEATHER PROOF/GFI DUPLEX RECEPTACLE	(D)	LONG SLASH DENOTES NEUTRAL CONDUCTOR. SHORT SLASH DENOTES PHASE CONDUCTOR, SWITCH LEG OR CONTROL.
D.GFI DEDICATED, GFI OUTLET	(E)	FLEXIBLE CONDUIT WHIP - MAX 6'-0" IN LENGTH
RECEPTACLE WITH ISOLATED GROUND	(F)	METER
CEILING DUPLEX RECEPTACLE	(G)	FUSED SWITCH
CEILING QUADPLEX RECEPTACLE	(H)	CIRCUIT BREAKER
CEILING SPECIAL RECEPTACLE	(I)	ENCLOSED CIRCUIT BREAKER
FLOOR QUADPLEX RECEPTACLE	(J)	FUSED SWITCH
FLOOR DUPLEX RECEPTACLE	(K)	DISCONNECT SWITCH
FLOOR SPECIAL RECEPTACLE	(L)	FUSED DISCONNECT SWITCH
GFI FLOOR QUADPLEX RECEPTACLE	(M)	COMBINATION STARTER DISCONNECT SWITCH W/H.O.A.
GFI FLOOR DUPLEX RECEPTACLE	(N)	MOTOR
LOW VOLTAGE		
VOICE/DATA OUTLET	(O)	FUSED SWITCH
ABOVE COUNTER VOICE/DATA OUTLET	(P)	DISCONNECT SWITCH
FLOOR / CEILING VOICE/DATA OUTLET	(Q)	FUSED DISCONNECT SWITCH
DATA OUTLET	(R)	COMBINATION STARTER DISCONNECT SWITCH W/H.O.A.
FLOOR / CEILING VOICE/DATA OUTLET	(S)	MOTOR
LIGHTING		
SWITCH	(T)	FUSED SWITCH
DIMMER SWITCH	(U)	DISCONNECT SWITCH
3 - WAY SWITCH	(V)	FUSED DISCONNECT SWITCH
4 - WAY SWITCH	(W)	COMBINATION STARTER DISCONNECT SWITCH W/H.O.A.
VACANCY SENSOR (WALL MOUNTED)	(X)	MOTOR
OCCUPANCY SENSOR (WALL MOUNTED)	(Y)	
LOW VOLTAGE MOMENTARY CONTACT SWITCH	(Z)	
TIME SWITCH OVER RIDE SWITCH	(AA)	
SINGLE POLE ROCKER SWITCH WITH WI-FI CONTROL AND BLUETOOTH REMOTE (#AWS04F OR EQUAL)	(BB)	
DIMMER WITH WALL MOUNTED OCCUPANCY SWITCH	(CC)	
VACANCY SENSOR (CEILING)	(DD)	
OCCUPANCY SENSOR (CEILING)	(EE)	
DAYLIGHT SENSOR (CEILING)	(FF)	
BATTERY EMERGENCY LIGHT (WALL MOUNTED)	(GG)	
BATTERY EMERGENCY LIGHT (CEILING MOUNTED)	(HH)	
EXIT SIGN	(II)	
UPPERCASE LETTER DENOTES FIXTURE TAG	(JJ)	
LOWERCASE LETTER DENOTES SWITCH DESIGNATION	(KK)	
TIME CLOCK	(LL)	
ANNOTATION		
KEY NOTE TAG	(MM)	

ELECTRICAL SHEET INDEX

SHEET NUMBER	SHEET NAME
E0.1	ELECTRICAL SYMBOL LIST AND GENERAL NOTES
E1.0	LIGHTING PLAN
E2.0	POWER PLAN
E3.0	ELECTRICAL RISER DIAGRAM
E3.1	ELECTRICAL PANEL SCHEDULES

GENERAL NOTES:

1. ALL ELECTRICAL WORK SHALL BE IN ACCORDANCE WITH THE 2017 NATIONAL ELECTRICAL CODE AND ALL LOCAL CODE AMENDMENTS.

2. A COMPLETE GROUNDING SYSTEM SHALL BE PROVIDED AND INSTALLED IN ACCORDANCE WITH ARTICLE 250 OF THE NEC, AND AS SHOWN ON THE DRAWINGS.

3. CONDUCTORS SHALL BE COPPER RATED AT NOT LESS THAN 600 VOLTS. MINIMUM SIZE SHALL BE #12 AWG UNLESS OTHERWISE NOTED ON THE DRAWINGS. ALL WIRE #8 AWG AND LARGER SHALL BE STRANDED. ALL CONDUCTORS #10 AND SMALLER SHALL BE SOLID, UNLESS OTHERWISE NOTED.

4. BRANCH CIRCUIT CONDUCTORS SHALL BE TYPE THHN OR THWN AS REQUIRED.

5. PROVIDE A TYPED DIRECTORY IN ALL PANELBOARDS CLEARLY DESCRIBING THE LOCATION OF AND TYPE OF LOAD BEING SERVED FOR ALL CIRCUITS.

6. PHENOLIC NAMEPLATES FOR ALL PANELBOARDS AND DISCONNECT SWITCHES, BLACK LETTERS ON WHITE BACKGROUND.

7. VERIFY ALL REQUIREMENTS AND COORDINATE EXACT LOCATION OF INCOMING ELECTRICAL SERVICE WITH LOCAL POWER COMPANY PRIOR TO PROJECT START-UP. NOTIFY ENGINEER OF ANY CHANGES AS MAY BE REQUIRED.

ENERGY COMPLIANCE FOR OPTIONAL CANOPY:

COMcheck Software Version COMcheckWeb
Interior Lighting Compliance Certificate

Project Information

Energy Code: 2018 IECC
Project Title: New Construction
Project Type: Construction Site: Owner/Agent: Designer/Contractor:


Additional Efficiency Package(s)

Credits: 0.0 Required 0.0 Proposed
Allowed Interior Lighting Power


A	Floor Area (ft ²)	B	C	D	E
Area Category	Floor Area (ft ²)	Allowed Watts / ft ²	Allowed Watts	Tradable Watts / ft ²	Tradable Watts
1-Black Rock Coffe, Idaho Optional Canopy (Dining: Cafeteria/Fast Food)	752	0.79	594	0.11	36
Total Allowed Watts = 594					

Proposed Interior Lighting Power

A	Floor Area (ft ²)	B	C	D	E
Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	Lamps/ Fixture	# of	Fixture Watt.	Fixture Watt.</	



1 LIGHTING PLAN - STANDARD AWNING
1/4" = 1'-0"



2 LIGHTING PLAN - OPTIONAL CANOPY
1/4" = 1'-0"

LIGHTING KEY NOTES:

1. EXTERIOR MOUNTED PHOTOCELL. ROUTE ALL EXTERIOR LIGHTING CIRCUIT VIA PHOTOCELL AND LIGHTING CONTROL PANEL.
2. "EM" INDICATING EMERGENCY LIGHTING FIXTURE WITH 90 MINUTES BATTERY BACK. NIGHT LIGHTS SHALL BE CONNECTED TO THE NEAREST LIGHTING BRANCH CIRCUIT AHEAD OF ALL SWITCHING AND CONTROL FOR CONTINUOUS OPERATION.
3. NEW TIME CLOCK WITH MANUAL OVERRIDE SWITCH.
4. NEW LIGHTING CONTROL SWITCHBANK.
5. LIGHTING FIXTURES FURNISHED BY WALK-IN BOX VENDOR. ELECTRICAL CONTRACTOR TO INSTALL AND CONNECT FIXTURES, COORDINATING ALL ELECTRICAL REQUIREMENTS AND EXACT LOCATION WITH VENDOR PRIOR TO ROUGH-IN.
6. EXTERNAL LIGHTS CONTROLLED BY PHOTOCELL AND TIME CLOCK.

LIGHTING GENERAL NOTES:


1. REFER TO ARCHITECTURAL PLANS FOR MOUNTING HEIGHTS OF DEVICES.
2. REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT FIXTURE LOCATIONS FOR GENERAL LIGHTING.
3. ALL BRANCH CIRCUITS SHALL HAVE DEDICATED NEUTRAL CONDUCTOR AND FULLY SIZED INSULATED GROUNDING WIRE, INCLUDING IN MC CABLE. MULTIPLE CIRCUITS IN A COMMON RACEWAY MAY SHARE A COMMON GROUNDING WIRE.
4. ADJUST THE EMERGENCY AND EXIT LIGHTING QUANTITIES/LOCATION AS REQUIRED TO MEET THE LOCAL AHJ REQUIREMENTS. LOCATE EXIT SIGNS AND DOWNLIGHTS IN THE CENTER OF CEILING TILES WHERE POSSIBLE.
5. PROVIDE AN UN-SWITCH HOT LEG TO ALL EMERGENCY AND EXIT FIXTURES. BATTERY EMERGENCY LIGHTING SHALL BE CONNECTED TO THE ROOM LIGHTING CIRCUIT, AHEAD OF ANY SWITCH OR CONTROL FOR CONTINUOUS OPERATION. EXIT SIGNS SHALL BE CONNECTED TO A DEDICATED, LOCK ON CIRCUIT AND SHALL BE PROVIDED WITH A DEDICATED FEEDER AND HOMERUN.
6. MAXIMUM VOLTAGE DROP FOR FEEDER AND BRANCH CIRCUIT CONDUCTORS COMBINED, SHALL NOT EXCEED A 5% VOLTAGE DROP.
7. LIGHTING FIXTURES WHICH ARE CONTROLLED BY A DIMMER SWITCH SHALL BE WIRED TO A CIRCUIT HAVING DEDICATED NEUTRAL WIRE.

LIGHTING CONTROL SCHEDULE									
TAG	DESCRIPTION	MAKE/MODEL	WALL/CEILING	VOLTAGE	DEVICE DELAY SETTING	OPERATION	SENSING	RANGE (8' MOUNTING)	REMARKS
OS	OCCUPANCY MODE WALL MOUNT, DUAL TECHNOLOGY	SENSORSWITCH "WSX-PDT-SA"	WALL	120/277VAC	15 MIN	AUTO ON / AUTO OFF	INFRARED / MICROPHONICS	18' X 18'	SINGLE OUTPUT LOAD CONTROL, 120V, 800W MAX, 277V, 1200W MAX
NOTES:									
<ol style="list-style-type: none"> 1. CONTRACTOR SHALL INSTALL OCCUPANCY SENSOR DEVICES PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. 2. CONTRACTOR SHALL PROVIDE OWNER TRAINING ON THE OPERATION OF ALL LIGHTING CONTROL DEVICES PRIOR TO TURN-OVER. 3. CONTRACTOR SHALL RE-VISIT PROJECT SITE 30 DAYS POST-TURN OVER TO ADJUST CONTROL DEVICES WITH OWNER. 4. ENABLE WALK THRU MODE ON ALL SENSORS WHERE PROVIDED. 5. BASIS OF DESIGN IS SENSOR SWITCH. PROVIDE SENSOR SWITCH OR APPROVED EQUAL. 									

LUMINAIRE SCHEDULE		LUMINAIRE DESCRIPTION	LAMPS/LUMINAIRE		CONTROL TYPE	LUMINAIRE		MOUNTING	MANUFACTURER & CATALOG NUMBER
QTY	TYPE		MAX VA	VOLTS		MAX VA	VOLTS		
1	LED	0-10V	41.8	120	RECESSED	CPX 2X4 6000LM 80CRI 35K SWL MIN10 120			
1	LED	0-10V	41.8	120	RECESSED	CPX 2X4 6000LM 80CRI 35K SWL MIN10 120 E10WLCP			
1	LED	0-10V	22.5	120	RECESSED	LDN6 35/20 L06 AR LS 120 E210			
1	LED	0-10V	22.5	120	RECESSED	LDN6 35/20 L06 AR LS 120 E210 EL			
1	LED	0-10V	9	120	SURFACE	ALPHABET LIGHTING NU-QW-SW-10LM-27K-80-WW			
1	LED	SWITCHED	13	120	WALL/SURFACE	4428 IL-EXTERIOR SQUARE UP/DOWN LIGHT			
2	LED	-	24	120	WALL/SURFACE	PHILIPS CHLORIDE: CLU2-N-"COLOR"-REM"			
1	LED	-	5	120	WALL/SURFACE	LITHONIA LIGHTING: EDGC 1RW-EL			

NOTES:

1. COORDINATE WITH ARCHITECT FOR EXACT INFORMATION, INCLUDING MANUFACTURER, MODEL NUMBER, COLORS, FINISHES, TRIMS, LAMP COLOR TEMPERATURE, AND CEILING TYPES.
2. REFER TO ARCHITECTURAL SHEETS FOR WALL, COLUMN, AND PENDANT MOUNTING HEIGHTS UNLESS NOTED OTHERWISE.
3. E.C. SHALL COORDINATE VOLTAGES REQUIRED FOR FIXTURES PRIOR TO ORDERING.
4. ALL FIXTURES SHALL BE UL OR ETL LISTED.
5. ALL FIXTURES SHALL BEAR A MAXIMUM WATTAGE LABEL AS INDICATED ABOVE. THE DISTRIBUTOR SHALL AFFIX THE MAX WATTAGE LABEL PRIOR TO SHIPMENT WHERE A REDUCTION IN MAXIMUM WATTAGE IS REQUIRED FOR ENERGY CODE COMPLIANCE.



3 TIME CLOCK DIAGRAM
N.T.S.

GENERAL NOTES:

1. E.C. TO PROVIDE TIME CLOCK FOR THE CONTROL OF THE SIGNAGE AND INTERIOR LIGHTING. TIME CALL SHALL BE AN INTERMATIC, ET90815CR OR EQUAL, 120-277VAC 8 CKT, 100 HR. BATTERY BACKUP WITH LOCAL OVER RIDE SWITCH (MAX. 2HRS.) TIME CLOCK.

SWITCH BANK NOTES:

1. E.C. SHALL VERIFY EXACT CONFIGURATION REQUIRED WITH SPACE AVAILABLE.
2. PROVIDE LABELS AS DIRECTED BY OWNER.
3. SWITCHES SHALL NOT BE MOUNTED HIGHER THAN 48" A.F.F.
4. E.C. NEEDS TO COORDINATE EXACT LOCATION FOR THE SWITCH BANK AT SITE. ALL SWITCHES SHALL BE DIMMER SWITCHES COMPATIBLE WITH THE FIXTURES CONTROLLED. IT IS THE E.C.'S RESPONSIBILITY TO DETERMINE THAT ALL DIMMER SWITCHES ARE COMPATIBLE WITH THE FIXTURES CONTROLLED PRIOR TO ORDERING.

CONTROL NO: #001

ISSUED FOR PERMIT (07-01-2025)

JOB NUMBER: 24-000325

DATE: 04-22-2025

CONTENTS: LIGHTING PLAN

NY ENGINEERS

NEARBY ENGINEERS


382 NE 191ST STREET SUITE

49674, MIAMI, FL 33179




PH-914.257.3455

WWW.NY-ENGINEERS.COM

E1.0



BLACK ROCK COFFEE DRIVE THROUGH




BLACK ROCK COFFEE DRIVE THROUGH

NY ENGINEERS


NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY-ENGINEERS.COM

CONTROL NO: #001
ISSUED FOR PERMIT (07-01-2025)
JOB NUMBER: 24-000325
DATE: 04-22-2025
CONTENTS: POWER PLAN



ELECTRICAL ONE-LINE DIAGRAM NOTES:

- INFORMATION SHOWN IS DIAGRAMMATIC AND IS NOT INTENDED TO REPRESENT PHYSICAL ARRANGEMENTS, LOCATIONS, ROUTING OR CONNECTIONS. PHYSICAL LAYOUTS ARE TO BE PER FIELD CONDITIONS AND AS INDICATED ELSEWHERE IN THE ELECTRICAL PLANS.
- REFERENCE THE NOTES FOR ADDITIONAL REQUIREMENTS REGARDING EQUIPMENT AND INSTALLATION. NOT ALL INFORMATION SHOWN ON THIS DIAGRAM.
- LABEL ALL DISTRIBUTION EQUIPMENT.
- PROVIDE ARC-FLASH HAZARD WARNING FIELD LABELING TO ELECTRICAL EQUIPMENT IN ACCORDANCE WITH NEC 110.16.
- SERVICE EQUIPMENT SHALL BE MARKED TO INDICATE THE MAXIMUM AVAILABLE FAULT CURRENT AS REQUIRED BY 2017 NEC SECTION 110.24. THE FIELD MARKING(S) SHALL INCLUDE THE DATE THE FAULT CURRENT CALCULATION WAS PERFORMED AND BE OF SUFFICIENT DURABILITY TO WITHSTAND THE ENVIRONMENT INVOLVED. ELECTRICAL CONTRACTOR SHALL REQUEST A DATED LETTER WITH FAULT CURRENT INFORMATION FROM THE LOCAL UTILITY.
- ALL EXTERIOR ELECTRICAL EQUIPMENT SHALL BE PROVIDED WITH A NEMA-3R ENCLOSURE.
- ALL ELECTRICAL EQUIPMENT SHALL BE UL LISTED OR APPROVED BY CITY RECOGNIZED ELECTRICAL TESTING COMPANY.
- PROVIDE GROUNDING PER NEC FOR ALL EQUIPMENT AND DEVICES.
- CONFIRM COLD SEQUENCING/HOT SEQUENCING CONFIGURATION WITH LOCAL UTILITY COMPANY.
- SITE CONTRACTOR TO INSTALL UTILITY METER, CT CABINET AND MAINS DISCONNECT SWITCH AS PER LOCAL UTILITY APPROVED CONFIGURATION.



DISCONNECT AND STARTER SCHEDULE													
ITEM	DISCONNECT TYPE & RATING			VOLTAGE	POLES	NEMA ENCLOSURE	REMARKS	APPROVED MANUFACTURERS					
	HEAVY DUTY SWITCH		CIRCUIT BREAKER										
	FUSED	NON-FUSED											
DS-30			30	20A	120	1	1	SQUARE D EATON TYPE DH GENERAL ELECTRIC TYPE TH SIEMENS TYPE HNF					
DS-30R			30	20A	208	2	3R	SQUARE D EATON TYPE DH GENERAL ELECTRIC TYPE TH SIEMENS TYPE HNF					
DS-30R			30	20A	208	3	3R	SQUARE D EATON TYPE DH GENERAL ELECTRIC TYPE TH SIEMENS TYPE HNF					
DS-60			60	50A	208	2	1	SQUARE D EATON TYPE DH GENERAL ELECTRIC TYPE TH SIEMENS TYPE HNF					
DS-100R	100			60A	208	3	3R	SQUARE D EATON TYPE DH GENERAL ELECTRIC TYPE TH SIEMENS TYPE HNF					
DS-400R		400			208	3	3R	SQUARE D EATON TYPE DH GENERAL ELECTRIC TYPE TH SIEMENS TYPE HNF					



BLACK ROCK COFFEE DRIVE THROUGH

NY ENGINEERS

NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY-ENGINEERS.COM

CONTROL NO: #001
ISSUED FOR PERMIT (07-01-2025)
JOB NUMBER: 24-000325
DATE: 04-22-2025
CONTENTS: ELECTRICAL RISER DIAGRAM

PLUMBING LEGEND		PLUMBING ABBREVIATIONS		PLUMBING GENERAL NOTES	
SYMBOL	DESCRIPTION	AC	ACCESS DOOR	I.E.	INVERT ELEVATION
	DOMESTIC COLD WATER PIPING (CW)	AD	AREA DRAIN	IWH	INSTANTANEOUS WATER HEATER
	DOMESTIC HOT WATER PIPING (HW)	AAV	AIR ADMITTANCE VALVE	KS	KITCHEN SINK
	DOMESTIC HOT WATER RECIRCULATION (HWR)	ABV	ABOVE	L	LAVATORY
	DOMESTIC COLD WATER UNDERGROUND PIPING (CW)	AFF	ABOVE FINISHED FLOOR		
	DOMESTIC COLD WATER PIPING (CW)	A/E	ARCHITECT/ENGINEER		
	SANITARY PIPING (SAN)	AHJ	AUTHORITY HAVING JURISDICTION	M	METER
	VENT PIPING (V)	ADA	AMERICANS WITH DISABILITIES ACT	MB	MOP SINK
	SANITARY PIPING(UNDER GROUND)	ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS	MX	MIXING VALVE
GW	GREASE WASTE	ASTM	AMERICAN SOCIETY FOR TESTING & MATERIALS	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
GW	GREASE WASTE (UNDER GROUND)			N.T.S.	NOT TO SCALE
ST	STORM DRAIN	BHP	BRAKE HORSEPOWER	OW	OIL WASTE
OST	OVERFLOW STORM DRAIN	BT	BATH TUB	PD	PUMP DISCHARGE
G	GAS PIPING	BTU	BRITISH THERMAL UNIT	PDI	PLUMBING DRAINAGE INSTITUTE
DT	DRAIN TILE	BFP	BACK FLOW PREVENTER	PSIG	POUNDS PER SQUARE INCH GAUGE
	GAS PRESSURE REDUCING VALVE (GPR) WITH VENT	C/I	CONTRACTOR INSTALLED	RD	ROOF DRAIN
	ISOLATION VALVE	CD	CONDENSATE	OD	OVERFLOW ROOF DRAIN
	SOLENOID VALVE	CO	CLEAN OUT	RC	ROOF CONDUCTOR
	BALL VALVE (2-1/2" AND SMALLER)	CONN	CONNECTION	RM	ROOM
	GLOBE VALVE	CONT	CONTINUOUS		
	NORMALLY OPEN VALVE	CP	CIRCULATION PUMP	S	SINK
	NORMALLY CLOSED VALVE	CV	CHECK VALVE	SAN	SANITARY
	CHECK VALVE	CW	COLD WATER	SH	SHOWER
	BUTTERFLY VALVE (3" AND LARGER)	DF	DRINKING FOUNTAIN	TD	TRENCH DRAIN
	BALANCING VALVE (BV) / CIRCUIT SETTER	DFU	DRAINAGE FIXTURE UNIT	TPV	TEMPERATURE/PRESSURE
	TWO WAY CONTROL VALVE	DIA	DIAMETER	RELIEF VALVE	
	THREE WAY CONTROL VALVE	DN	DOWN	TP	TRAP PRIMER
	RELIEF(R), OR SAFETY(S) VALVE	DWG	DRAWING	TYP	TYPICAL
	PRESSURE REDUCING VALVE	"F	DEGREE FAHRENHEIT	TW	TEMPERED WATER
	THERMOSTAT MIXING VALVE	FCO	FLOOR CLEAN OUT	UB	UTILITY BOX
	STRAINER	FD	FLOOR DRAIN	U/G	UNDERGROUND
	BACKFLOW PREVENTER ASSEMBLY (BFP)	FFD	FLOOR FUNNEL DRAIN	UR	URINAL
	REDUCED PRESSURE ZONE ASSEMBLY (RPZ)	FFL	FINISH FLOOR LEVEL	V	VENT
	BALANCING VALVE ASSEMBLY / CIRCUIT SETTER ASSEMBLY	FS	FLOOR SINK	VTR	VENT THROUGH ROOF
	PRESSURE GAUGE - CLOSED (FURNISHED WITH VALVE)	GAL	GALLONS		
	HOSE BIBB	GD	GARBAGE DISPOSER		
	PUMP, IN SCHEMATIC PRESENTATION	GPM	GALLONS PER MINUTE		
	WATER METER	GPR	GAS PRESSURE REGULATOR		
	FLOOR DRAIN (FD)	GW	GREASE WASTE		
	FLOOR CLEANOUT (FCO)	GWH	GAS WATER HEATER		
	HALF-GRADE FLOOR SINK (FS)	GI	GREASE INTERCEPTOR		
	FULL-GRADE FLOOR SINK (FS)	HW	HOT WATER		
	REDUCER	HWR	HOT WATER RECIRCULATION		
	UNION	HB	HOSE BIB		
	PIPE DOWN				
	PIPE UP				
	WALL CLEANOUT (WCO) / CLEANOUT (CO)				
	DIRECTION OF FLOW				
	PIPE PITCH ARROW (DOWN IN ARROW DIRECTION)				
	TOP CONNECTION, 45 OR 90 DEGREES				
	BOTTOM CONNECTION, 45 OR 90 DEGREES				
	SIDE CONNECTION				
	CAPPED OUTLET				
	VALVE IN RISER				
	NEW CONNECTION				
	LIMIT OF DEMOLITION				
	SECTION TAKEN AT				



BLACK ROCK COFFEE

NY ENGINEERS

NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY.ENGINEERS.COM

WWW.NY-ENGINEERS.COM

ROL NO: #001

ED EOB PERMIT (07-01-2025)

NUMBER: 04-000305

NUMBER: 24-00325

DATE: 04-22-25


PLUMBING LEGENDS ABBREVIATIONS NO.

ABBREVIATIONS, NO. 1 SPECIFICATIONS

P0.1

11. *What is the primary purpose of the following statement?*

11. *What is the primary purpose of the following statement?*



1 SANITARY DRAINAGE AND VENT FLOOR PLAN
1/4" = 1'-0"

GENERAL NOTES:


- A. ALL SEWER LINES TO BE MADE UP IN FIELD AFTER BUILDING IS PLACED AND COORDINATED WITH CIVIL ENGINEER UTILITY PLAN.
- B. ALL THE SANITARY PIPING SHALL BE PROTECTED AGAINST FREEZING BY A HEAT TRACING SYSTEMS OR THERMAL INSULATION WITH VAPOR BARRIERS AS PER CODE.

SANITARY DRAINAGE AND VENT FLOOR PLAN KEYNOTES:

1. 2"Ø V PIPE DN.
2. 3"Ø VENT UP & 3"Ø VTR.
3. 4"Ø SAN PIPE UP TO WC-1.
4. 2"Ø SAN PIPE UP TO L-1.
5. 3"Ø SAN PIPE UP TO EQUIP. 32.0.
6. 3"Ø GW PIPE UP TO FS-1.
7. 4"Ø GW PIPE UP TO TD-1.
8. TERMINATE THE CONDENSATE DRAIN PIPE INDIRECTLY TO THE NEAREST FLOOR SINK. THE CONTRACTOR IS REQUIRED TO VERIFY THE ROUTING AND TERMINATION IN THE FIELD.
9. TERMINATE THE DRAIN PIPE FOR ESPRESSO MACHINE INDIRECTLY TO THE NEAREST FLOOR SINK. THE CONTRACTOR IS REQUIRED TO VERIFY THE ROUTING AND TERMINATION IN THE FIELD.
10. 3"Ø OST PIPE UP/DN.
11. 3"Ø ST PIPE UP/DN.
12. 4"Ø SAN PIPE UP TO FFD-1.
13. PROVIDE HEAT TRACING FOR ALL EXPOSED SANITARY PIPING IF REQUIRED.




BLACK ROCK COFFEE



2 SANITARY DRAINAGE UNDERGROUND PLAN
1/4" = 1'-0"

NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY-ENGINEERS.COM

CONTROL NO: #001
ISSUED FOR PERMIT (07-01-2025)
JOB NUMBER: 24-000325
DATE: 04-22-25
CONTENTS: SANITARY DRAINAGE AND VENT FLOOR PLAN




CONTINUATION
PROVIDED BY THE SITE
CONTRACTOR IN ACCORDANCE WITH
LOCAL AUTHORITY REQUIREMENTS

PLUMBING GENERAL NOTES:

- A. REFER TO THE PLUMBING FIXTURE SCHEDULES FOR THE SIZES OF BRANCH PIPES OF FIXTURES NOT SHOWN ON PLANS.
- B. REFERS TO FIXTURE & EQUIPMENT DESIGNATION. SEE CORRESPONDING SPECIFICATION AND EQUIPMENT SCHEDULE FOR FURTHER INFORMATION.
- C. ESPRESSO MACHINE, COFFEE BREWER, & COFFEE DISPENSER SHALL BE PROTECTED AGAINST BACKFLOW BY A BACKFLOW PREVENTER CONFORMING TO ASSE 1022 OR ASSE 1024, OR PROTECTED BY AN AIR GAP.
- D. ICE MACHINE SHALL BE PROTECTED AGAINST BACKFLOW BY BACKFLOW PREVENTERS AS PER CODE.
- E. PROVIDE ASSE1070 APPROVED THERMOSTATIC MIXING VALVE AT ALL LAVATORIES, HAND WASHING SINKS & DUMP SINK AT TEMP 110 DEG F.
- F. ALL THE WATER SUPPLY PIPING SHALL BE PROTECTED AGAINST FREEZING BY A HEAT TRACING SYSTEMS OR THERMAL INSULATION WITH VAPOR BARRIERS AS PER CODE.

⑥ DOMESTIC WATER FLOOR PLAN KEYNOTES:

1. 3/4"Ø CW PIPE DN TO WC-1.
2. 1/2"Ø CW, 1/2"Ø HW & 1/2"Ø HWC PIPE DN TO L-1.
3. 3/4"Ø CW & 3/4"Ø HW PIPE DN TO EQUIP-32.0.
4. 3/4"Ø CW & 3/4"Ø HW PIPE DN TO EQUIP-1.0.
5. 1/2"Ø CW, 1/2"Ø HW & 1/2"Ø HWC PIPE UP TO EQUIP-1.
6. 1/2"Ø CW & 1/2"Ø HW PIPE DN TO EQUIP-21.0.
7. 1/2"Ø FW PIPE DN TO EQUIP-7.0.
8. 1/2"Ø FW PIPE DN TO EQUIP-8.0.
9. 3/4"Ø CW, 3/4"Ø HW & 1/2"Ø HWC PIPE DN.
10. 1/2"Ø CW PIPE UP TO EQUIP-13.0.
11. 1/2"Ø FW PIPE UP TO EQUIP-20.0.
12. 1/2"Ø FW & 1/2"Ø HW PIPE DN.
13. 1/2"Ø FW PIPE DN TO EQUIP-27.0.




BLACK ROCK COFFEE

NY ENGINEERS

NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY.ENGINEERS.COM

CONTROL NO: #001
ISSUED FOR PERMIT (07-01-2025)
JOB NUMBER: 24-000325
DATE: 04-22-25
CONTENTS: DOMESTIC WAT

BLACK ROCK COFFEE




NY ENGINEERS

**NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY-ENGINEERS.COM**


CONTROL NO: #001
ISSUED FOR PERMIT (07-01-2025)
JOB NUMBER: 24-000325
DATE: 04-22-25
CONTENTS: PLUMBING RISER DIA

P3.0




1 SANITARY DRAINAGE RISER DIAGRAM

N.T.S SCALE




DOMESTIC WATER RISER DIAGRAM




1 PLUMBING VENT CONNECTION DETAIL
SCALE: N.T.S.

2 WATER HAMMER ARRESTOR DETAIL
SCALE: N.T.S.




# KEY NOTES:		
P.I.D.	SYMBOL	FIXTURE UNIT RATING
A	1-11	1 1/2"
B	12-32	3/4"
C	33-60	1"
D	61-113	1"

GENERAL NOTES:
1. WATER HAMMER ARRESTOR (WHA) INSTALLED AHEAD OF LAST FIXTURE SERVED BY BRANCH. (TYP)
2. CW PIPE.
3. HW PIPE.
4. CONNECT TO FIXTURE




3 LAVATORY AND HANDSINK TEMPERING VALVE DETAIL
SCALE: N.T.S.


NOTE:
1. PROVIDE TRAP AND SUPPLY INSULATION AS REQUIRED. SEE SPECIFICATIONS.
2. PROVIDE HOTWATER TEMPERING VALVE IF THE WATER TEMPERATURE IS MORE THAN 110 F.
3. TYPICAL AT ALL HAND SINKS AND LAVATORIES U.N.O.



4 HOT WATER RETURN & FLOW CONTROL DEVICE CONNECTION DETAIL
SCALE: N.T.S.




9 ABOVE MOP BASIN MOUNTED ELECTRIC WATER HEATER CONNECTION DETAIL
SCALE: N.T.S.




10 INLINE HOT WATER RECIRCULATION PUMP DETAIL
SCALE: N.T.S.


1 PLUMBING VENT CONNECTION DETAIL
SCALE: N.T.S.




5 VENT THROUGH ROOF (VTR) DETAIL
SCALE: N.T.S.



6 TYPICAL PIPE HANGER DETAIL
SCALE: N.T.S.



7 TYPICAL CLEANOUT TO FINISHED FLOOR
SCALE: N.T.S.



8 TYP. ROOF & OVERFLOW DRAIN
SCALE: N.T.S.



BLACK ROCK COFFEE

NY ENGINEERS

NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH-914.257.3455
WWW.NY-ENGINEERS.COM

CONTROL NO: #001
ISSUED FOR PERMIT (07-01-2025)
JOB NUMBER: 24-000325
DATE: 04-22-25
CONTENTS: PLUMBING DETAILS

PLUMBING FIXTURE SCHEDULE												
SYMBOL	MANUFACTURER	MODEL	Fixture	MOUNTING	HW	CW	WASTE	VENT	ACCESSORIES / REMARKS	IMAGES		
BALL VALVES	APOLLO / CONBRACO OR EQUAL	-	BALL VALVES	-	-	-	-	-	FULL PORT, BRASS BODY, 600 WOG			
ECO	ZURN OR EQUAL	Z1400	FLOOR CLEANOUT	FLOOR	-	-	REFER TO FLOOR PLAN	-	EXTRA HEAVY DUTY "LEVEL-TROL" ADJUSTABLE FLOOR CLEANOUT			
FCO	J.R. SMITH OR EQUAL	4020 SERIES	FLOOR CLEANOUT	FLOOR	-	-	REFER TO FLOOR PLAN	-	NO-HUB OUTLET, DUCO CAST IRON CLEANOUT WITH ROUND ADJUSTABLE SCORIATED NICKEL BRONZE ROUND TOP, VANDAL PROOF TOP.			
L-1	KOHLER OR EQUAL	K-2032	LAVATORY	WALL	1/2"	1/2"	2"	2"	WALL-MOUNT WITH OVERFLOW DRAIN, VITREOUS CHINA, LENGTH: 20-9/16" X WIDTH: 18-1/4" ASME A112.19.2, ADA, IAPMO/UPC, CSA B45 FAUCET: MOEN FINDLAYTM TWO-HANDLE CENTERSET, 1.2 GPM, WATERSENSE, ASME A112.18.1/CSA B125.1	 		
PIPE HANGERS	B-LINE OR EQUAL	B3170	PIPE HANGERS	-	-	-	-	-	PRE GALVANIZED, AVAILABLE IN STAINLESS STEEL MATERIAL, FACTORY MUTUAL ENGINEERING APPROVED.			
RPZ	-	-	REDUCED PRESSURE ZONE	-	-	-	-	-	MANUFACTURER AND MODEL NO AS APPROVED BY LOCAL DEPARTMENT OF WATER. PRESSURE DROP SHALL NOT BE EXCEED MORE THAN 7 PSI.			
WC-1	KOHLER OR EQUAL	K-31674	WATER CLOSET	FLOOR	-	3/4"	4"	2"	TWO PIECE DESIGN, 1.2 GPF, ASME A112.19.2/CSA B45.1, EPA WATER SENSE, ADA, GRAVITY TYPE FLOOR MOUNTED WATER CLOSET.			
FS-1	SIOUX CHIEF OR EQUAL	861-3-PI-D	FLOOR SINK	FLOOR	-	-	3"	2"	FLOOR SINK SHALL BE MODELED FROM IMPACT- MODIFIED PVC WITH SCH. 40 HUB CONNECTION, WHICH CONFORMS TO ASTM D2665 DESIGNED IN ACCORDANCE WITH ASME A112.6.7-01.			
TD-1	ULTIMATE RESTAURANT EQUIPMENT OR EQUAL	URE-1248 OR EQUAL	FLOOR TROUGH DRAIN	FLOOR	-	-	4"	2"	12"X48"X4" FLOOR TROUGH DRAIN 14 GAUGE, 304 GRADE STAINLESS STEEL CONSTRUCTION			
HB-1	WOODFORD	MODEL 17 OR EQUAL	HOSE BIBB	FLOOR	3/4"	-	-	-	FREEZELESS WALL HYDRANT, ANODIZED ALUMINUM BOX, ASSE STANDARD 1052 APPROVED NIDEL MODEL 50HA DOUBLE CHECK BACKFLOW PREVENTER.			
FFD	ZURN OR EQUAL	Z-1724	FLOOR FUNNEL DRAIN	FLOOR	-	-	4"	2"				

NOTE: 1. REFER TO ARCHITECTURE, OWNERSHIP OR INTERIOR DESIGNER FOR ALL FIXTURE SELECTION AND ACCESSORIES. ALL ARE SUBJECT TO CHANGE.

CIRCULATING PUMP SCHEDULE												
TAG	TYPE	QTY.	LOCATION	FLOW (GPM)	HEAD (FEET)	FLANGE SIZE NPT (IN)	ELECTRICAL DATA		WEIGHT (LBS)	MANUFACTURER	MODEL	
RCP-1	CIRCULATING PUMP	1	SEE PLAN	2	10	1/2"	83	115/160	8.0	ASTRO	230	

NOTES:
1. INSTALL AS PER THE MANUFACTURER'S INSTRUCTIONS.
2. THE PUMP SHALL BE CAPABLE OF TEMPERATURE-BASED CONTROLS.
3. PROVIDE TEMPERATURE SENSOR/THERMOSTAT ON RECYCLING WATER LINE AND CONNECT TO PUMP.

EXPANSION TANK SCHEDULE													
SYMBOL	QTY.	TANK VOLUME (GAL)	MAX. ACCEPTANCE FACTOR	MAX. ACCEPT. VOLUME (GAL)	TYPE	DIAPHRAGM MATERIAL	SHELL MATERIAL	MAX. OPERATING TEMPERATURE (°F)	MAX. WORKING PRESSURE (PSIG)	DIMENSION (IN.) (DIA. X H)	SHIPPING WEIGHT (LBS)	MANUFACTURER	MODEL
ET-1	1	2.0	0.45	0.9	REPLACEABLE BLADDER	HEAVY DUTY BUTYL	STEEL	200	150	8" Ø X 13"	5	AMTROL	ST-5

NOTES:
1. INSTALL AS PER THE MANUFACTURER'S INSTRUCTIONS.
2. PROVIDE WITH STANDARD SCHRAEDER TIRE VALVE CONNECTION.
3. ADJUST CHARGE PRESSURE IN FIELD.

STORAGE TANK ELECTRIC WATER HEATER SCHEDULE																	
TAG	TYPE	QTY.	LOCATION	TANK CAPACITY (GALLONS)	TEMPERATURE RISE (°F)	RECOVERY IN G.P.H. @ TEMP RISE	WATER CONNECTION SIZE (IN.)	ELECTRICAL DATA			WEIGHT (LBS)	DIMENSION (IN.) (DIA. X H)	MANUFACTURER	MODEL			
								OPERATION	PER ELEMENT WATTAGE (kW)	UPPER ELEMENT	LOWER ELEMENT	V/Ph/Hz	TOTAL WATTAGE (kW)				
EWH-1	ELECTRICAL	1	REFER TO PLAN	50	100	41	3/4" Ø	SIMULTANEOUS	4.0	1	1	208/1160	8.0	125	20-1/2" Ø X 59	AO SMITH	DEN-40

NOTES:
1. INSTALL AS PER THE MANUFACTURER'S INSTRUCTIONS.
2. TO REDUCE THE RISK OF EXCESSIVE PRESSURE AND TEMPERATURE IN THIS WATER HEATER INSTALL TEMPERATURE AND PRESSURE PROTECTIVE EQUIPMENT REQUIRED BY LOCAL CODES.
3. THE HEATER MAY NOT BE INSTALLED ON OR AGAINST COMBUSTIBLE SURFACE.
4. THE ELECTRICAL WATER HEATER STORAGE TANK SIZING IS CALCULATED BASED ON THE ASHRAE TABLE. UP-SIZING OF THE STORAGE TANK IS ALLOWED AS PER CLIENT REQUIREMENTS.
5. PROVIDE DRAIN PAN.

EQUIPMENT SCHEDULE												
TAG	QTY.	DESCRIPTION			MAKE AND MODEL			COLD (INCH)	HOT (INCH)	DIRECT WASTE (INCH)	INDIRECT WASTE (INCH)	REMARKS
1	1	3-COMPARTMENT SINK WITH DUAL DRAINBOARDS	REGENCY / 600S31718LFT		3/4"	3/4"		-	2"	75-1/2" X 44-3/4" W X 22-1/2" D		
4	1	HAND SINK WITH SIDE SPLASH	BK RESOURCES BK-DD-0090524-P-G		1/2"	1/2"		-	2"	11-1/8" L X 13-1/2" W X 5" D		
7	1	ICE MACHINE	MANITOWOC / IYT1900N WITH REMOTE CONDENSER & F-1300 BIN		1/2"	-		-	1/2"	-		
8	2	RANCILIO ESPRESSO MACHINE	RANCILIO CLASS 11-3 GOUPE ESPRESSO MACHINE		1/2"	-		-	1/2"	-		
20	1	COUNTERTOP NITRO BREW COFFEE DISPENSER	CORNELIUS NITRO PRO MINI / 621058753		1/2"	-		-	1/2"	-		
21	3	DUMP SINK WITH SIDE SPLASH	BK RESOURCES BK-DIS-1014-10-SS-P-G		1/2"	1/2"		-	2"	-		
27	1	HOT WATER DISPENSER	BUNN HX5 ELEMENT SST		1/2"	-		-	1/2"	-		
32	1	MOP SINK WITH TWO (2) DELTA 28T9 FAUCETS W/ HOOKS	FIAT TSB100 W/CAP ON TWO SIDES, CHROME PLATED DRAIN.		3/4"	3/4"		3"	-	24" H X 21.75" W X 12" D		

STORM CONDUCTOR PIPE SIZING						
ROOF	AREA	AREA (FT2)	WALL AREA (FT2)	TOTAL AREA (FT2)	RAINFALL INTENSITY (i) (INCH/HR)	RUN OFF COEFFICIENT®
DRAIN-1	A	545	672	1217	2	1
MAIN HEADER	-	545	672	1217	-	-

PLUMBING FIXTURE DEMAND TABULATION												
Fixture	DESCRIPTION	OCCUPANCY	QTY.	DRAINAGE FIXTURE UNITS	SUB-TOTAL	LOAD VALUES IN WATER (EACH)			LOAD			