

Plumbing Notes, Specifications, & Details												Sheet Number																																																																															
Gate Gourmet Seattle												P0																																																																															
<table border="1"> <tr> <td colspan="11" style="text-align: center;">GENERAL PLUMBING NOTES</td> <td colspan="1" rowspan="2" style="text-align: right;">ISSUED FOR</td> </tr> <tr> <td colspan="11"> <ol style="list-style-type: none"> DRAWINGS ARE DIAGRAMMATIC AND SHALL NOT BE SCALED. REFER TO DESIGN PLANS AND ELEVATIONS FOR EXACT LOCATION OF ALL PLUMBING FIXTURES, EQUIPMENT, ETC. PLUMBING CONTRACTOR SHALL FURNISH AND INSTALL ALL ITEMS REQUIRED FOR A COMPLETE AND ACCEPTABLE WORKING INSTALLATION. ALL WORK AND MATERIALS SHALL COMPLY WITH THE LATEST EDITION OF THE NATIONAL, STATE, AND ALL LOCAL CODES AND ORDINANCES HAVING JURISDICTION. THE PLUMBING CONTRACTOR SHALL VISIT THE SITE AND THOROUGHLY FAMILIARIZE HIMSELF WITH ALL EXISTING CONDITIONS. ALL EXECUTION AND BACKFILL AS REQUIRED FOR THIS PHASE OF CONSTRUCTION SHALL BE A PART OF THIS CONTRACT. ALL WORK SHALL BE PERFORMED BY A LICENSED PLUMBING CONTRACTOR IN A FIRST CLASS WORKMANLIKE MANNER. THE COMPLETED SYSTEM SHALL BE FULLY OPERATIVE AND ACCEPTED BY ENGINEER/DESIGNER. ALL REQUIRED INSURANCE SHALL BE PROVIDED FOR PROTECTION AGAINST PUBLIC LIABILITY OR PROPERTY DAMAGE FOR THE DURATION OF THE WORK. THE PLUMBING CONTRACTOR SHALL SECURE AND PAY ALL PERMIT FEES, INSPECTIONS, AND TESTS. TESTS SHALL COMPLY WITH ALL APPLICABLE REQUIREMENTS. ALL WORK SHALL BE COORDINATED WITH OTHER TRADES TO AVOID INTERFERENCE WITH THE PROGRESS OF CONSTRUCTION. THE PLUMBING CONTRACTOR SHALL GUARANTEE ALL MATERIALS AND WORKMANSHIP FREE FROM DEFECTS FOR A PERIOD OF NOT LESS THAN (1) ONE YEAR FROM DATE OF ACCEPTANCE. CORRECTION OF ANY DEFECTS SHALL BE COMPLETED WITHOUT ADDITIONAL CHARGE AND SHALL INCLUDE REPLACEMENT OR REPAIR OF ANY OTHER PHASE OF THE INSTALLATION WHICH MAY HAVE BEEN DAMAGED THEREBY. VERIFY LOCATION, SIZE AND INVERTS OF ALL EXISTING UTILITIES PRIOR TO START OF CONSTRUCTION. ADVISE ARCHITECT/ENGINEER OF ANY DISCREPANCIES. ALL FIXTURES SHALL BE PROVIDED WITH READILY ACCESSIBLE STOPS. PROVIDE SEISMIC SWAY BRACING FOR ALL SUSPENDED EQUIPMENT AND PIPING LARGER THAN 2" IN ACCORDANCE WITH SECTION WITH CURRENT CODES. </td> </tr> <tr> <td colspan="11" style="text-align: center;">GENERAL PLUMBING SPECIFICATIONS</td> <td colspan="1" rowspan="2" style="text-align: right;">DATE</td> </tr> <tr> <td colspan="11"> <p>GENERAL CONDITIONS</p> <ol style="list-style-type: none"> GENERAL AND SPECIAL CONDITIONS ARE HEREBY MADE A INTEGRAL PART OF THIS DIVISION OF THE SPECIFICATIONS IN THAT THEY ARE APPLICABLE TO THE WORK UNDER THIS DIVISION UNLESS OTHERWISE NOTED. PROVIDE ALL LABOR, MATERIAL AND EQUIPMENT REQUIRED FOR THE COMPLETION AND OPERATION OF ALL SYSTEMS IN THIS SECTION OF WORK IN ACCORDANCE WITH ALL APPLICABLE CODES. PERMITS: APPLY FOR AND PAY FOR ALL NECESSARY PERMITS, FEES, AND INSPECTIONS REQUIRED BY ANY PUBLIC AUTHORITY HAVING JURISDICTION. ACREAGE CHARGES, BOND PROPERTY ASSESSMENTS AND FACILITIES CHARGE ARE NOT TO BE CONSTRUED TO BE A PART OF THIS CONTRACT. WARRANTY: PROVIDE ALL MATERIALS AND EQUIPMENT UNDER THIS SECTION OF THE SPECIFICATIONS WITH A ONE YEAR WARRANTY FROM THE DATE OF ACCEPTANCE OF WORK BY THE OWNER. THE CONTRACTOR SHALL TIE INTO CIVIL PROVIDED TAP AS INDICATED ON PLANS. ALL COSTS FOR THIS SERVICE SHALL BE PART OF HIS BID CONTRACT PRICE. PROTECT COPPER PIPING AGAINST CONTACT WITH DISSIMILAR METALS. ALL HANGERS, SUPPORTS, ANCHORS, AND CLIPS SHALL BE COPPER OR COPPER PLATED. PROTECT COPPER PIPING AGAINST CONTACT WITH ALL MASONRY. WHERE COPPER IS SLEEVED THROUGH MASONRY, PROVIDE COPPER OR RED BRASS SLEEVES. MAKE SURE PROVISIONS ARE INSTALLED IN ALL PIPING SO NO STRAIN OR BREAKAGE RESULTS FROM EXPANSION OR CONTRACTION. PITCH ALL WATER PIPES SO THAT ALL PARTS MAY BE DRAINED. THE FORMATION OF SAGS AND TRAPS SHALL BE AVOIDED. <p>MATERIALS</p> <ol style="list-style-type: none"> ALL NEW WORK SHALL BE OF MATERIALS LISTED BELOW OR SHALL MATCH EXISTING. IF A CONFLICT EXISTS BETWEEN MATERIALS AND/OR EQUIPMENT, THE MORE STRINGENT SHALL APPLY AS ADJUDGED BY THE ARCHITECT/ENGINEER. THE CONTRACTOR SHALL VERIFY MATERIAL TYPE AND EQUIPMENT. SANITARY WASTE AND VENT PIPING: <ol style="list-style-type: none"> SANITARY WASTE AND VENT PIPING AND FITTINGS. SERVICE WEIGHT CAST IRON, HUB AND SPIGOT TYPE WITH COMPRESSION JOINTS (ASTM A 74) OR NO-HUB PIPING WITH COUPLINGS (CISPI 301). IF PERMITTED BY LOCAL CODES, SCHEDULE 40 PVC (ASTM D 2665) WITH SCHEDULE 40 SOCKET-TYPE PIPE FITTINGS (ASTM D 3311) MAY BE USED. EXCEPTIONS: DO NOT INSTALL PVC PIPING IN RETURN AIR PLENUMS OR WITHIN 10'-0" OF ANY LOCATION WHERE EQUIPMENT MAY DISCHARGE WATER IN EXCESS OF 140 DEGREES. SLOPE SANITARY WASTE PIPING 2.5' AND SMALLER AT 1/4" PER FOOT MIN. SLOPE SANITARY WASTE PIPING 3" AND LARGER AT 1/8" PER FOOT MINIMUM. WHERE WASTE PIPING IS EXPOSED IN REST ROOM AREAS, PROVIDE CHROME PLATED BRASS PIPING WITH MATCHING STOPS AND ESCUTCHEONS. PROVIDE REMOVABLE TRAPS WITH INTEGRAL CLEAN-OUT PLUG FOR ALL LAVATORIES. INSTALL CLEAN-OUTS IN A LOCATION THAT PERMITS ACCESS FOR SERVICE WITHOUT DAMAGE TO THE BUILDING OR FINISHED MATERIALS. SEWAGE EJECTOR PUMP <ol style="list-style-type: none"> SEWAGE EJECTOR PUMP WILL BE COMPLETELY SUBMERSIBLE, CAPABLE OF SELF-COMMUTING UNSCREENED SEWAGE, AUTOMATIC OPERATION, WITH ONE PIECE CAST IRON OR BRONZE NON-CLOG BALANCED IMPELLER. SEWAGE EJECTOR PUMP SHOULD HAVE HEAVY DUTY CAST IRON CASING, IMPELLER, AND MOTOR HOUSING. THE PUMP PIT/BASIN SHALL HAVE A STEEL COVER WITH REQUIRED OPENINGS FOR PUMPS, CONTROLS, AND VENT CONNECTIONS. COVER AND FRAME ARE TO BE OF GASTIGHT CONSTRUCTION AND SHALL BE TREATED WITH CORROSION RESISTANT COATING. EQUIP SUBMERSIBLE MOTOR WITH NATIONAL ELECTRICAL CODE CLASS 1, DIVISION 1 (EXPLOSION-PROOF) RATED SERVICE; UL LISTED FOR CLASS I, GROUP C AND D IN AIR OR SUBMERSIBLE IN SEWAGE SHAFTS SHOULD BE CARBON STEEL. DESIGN TO OPERATE ON A SINGLE PHASE, 60 HERTZ, 208/230 VOLT CIRCUIT (NEMA STANDARD MOTOR VOLTAGE 115 V). GUARANTEE THE CONTRACTOR SHALL GUARANTEE THE COMPLETE PLUMBING SYSTEM AGAINST DEFECTS DUE TO FAULTY MATERIALS, WORKMANSHIP OR FAILURE DUE TO NEGLIGENCE OF THE CONTRACTOR. THIS GUARANTEE SHALL EXTEND 12 MONTHS FROM DATE OF FINAL ACCEPTANCE. ALL SERVICE CALLS DURING THIS PERIOD SHALL BE PROVIDED BY THE CONTRACTOR. </td> </tr> <tr> <td colspan="11" style="text-align: center;">SEWAGE EJECTOR PUMP SCHEDULE</td> <td colspan="1" rowspan="2" style="text-align: right;">PROJECT NO:</td> </tr> <tr> <td>MARK</td> <td>QUANTITY</td> <td>DISCHARGE</td> <td>GPM</td> <td>TDH (FT)</td> <td>HP</td> <td>VOLTAGE</td> <td>PHASE</td> <td>MANUFACTURER & MODEL NO.</td> <td colspan="2">REMARKS</td> </tr> <tr> <td>SE-1 (DUPLEX)</td> <td>2</td> <td>2" NPT</td> <td>40</td> <td>18</td> <td>0.5</td> <td>208/230</td> <td>1</td> <td></td> <td colspan="2">DUPLEX SEWAGE SYSTEM DIMENSION 21.25'(H)X11.75'(W)X14.75'(L)</td> </tr> </table>												GENERAL PLUMBING NOTES											ISSUED FOR	<ol style="list-style-type: none"> DRAWINGS ARE DIAGRAMMATIC AND SHALL NOT BE SCALED. REFER TO DESIGN PLANS AND ELEVATIONS FOR EXACT LOCATION OF ALL PLUMBING FIXTURES, EQUIPMENT, ETC. PLUMBING CONTRACTOR SHALL FURNISH AND INSTALL ALL ITEMS REQUIRED FOR A COMPLETE AND ACCEPTABLE WORKING INSTALLATION. ALL WORK AND MATERIALS SHALL COMPLY WITH THE LATEST EDITION OF THE NATIONAL, STATE, AND ALL LOCAL CODES AND ORDINANCES HAVING JURISDICTION. THE PLUMBING CONTRACTOR SHALL VISIT THE SITE AND THOROUGHLY FAMILIARIZE HIMSELF WITH ALL EXISTING CONDITIONS. ALL EXECUTION AND BACKFILL AS REQUIRED FOR THIS PHASE OF CONSTRUCTION SHALL BE A PART OF THIS CONTRACT. ALL WORK SHALL BE PERFORMED BY A LICENSED PLUMBING CONTRACTOR IN A FIRST CLASS WORKMANLIKE MANNER. THE COMPLETED SYSTEM SHALL BE FULLY OPERATIVE AND ACCEPTED BY ENGINEER/DESIGNER. ALL REQUIRED INSURANCE SHALL BE PROVIDED FOR PROTECTION AGAINST PUBLIC LIABILITY OR PROPERTY DAMAGE FOR THE DURATION OF THE WORK. THE PLUMBING CONTRACTOR SHALL SECURE AND PAY ALL PERMIT FEES, INSPECTIONS, AND TESTS. TESTS SHALL COMPLY WITH ALL APPLICABLE REQUIREMENTS. ALL WORK SHALL BE COORDINATED WITH OTHER TRADES TO AVOID INTERFERENCE WITH THE PROGRESS OF CONSTRUCTION. THE PLUMBING CONTRACTOR SHALL GUARANTEE ALL MATERIALS AND WORKMANSHIP FREE FROM DEFECTS FOR A PERIOD OF NOT LESS THAN (1) ONE YEAR FROM DATE OF ACCEPTANCE. CORRECTION OF ANY DEFECTS SHALL BE COMPLETED WITHOUT ADDITIONAL CHARGE AND SHALL INCLUDE REPLACEMENT OR REPAIR OF ANY OTHER PHASE OF THE INSTALLATION WHICH MAY HAVE BEEN DAMAGED THEREBY. VERIFY LOCATION, SIZE AND INVERTS OF ALL EXISTING UTILITIES PRIOR TO START OF CONSTRUCTION. ADVISE ARCHITECT/ENGINEER OF ANY DISCREPANCIES. ALL FIXTURES SHALL BE PROVIDED WITH READILY ACCESSIBLE STOPS. PROVIDE SEISMIC SWAY BRACING FOR ALL SUSPENDED EQUIPMENT AND PIPING LARGER THAN 2" IN ACCORDANCE WITH SECTION WITH CURRENT CODES. 											GENERAL PLUMBING SPECIFICATIONS											DATE	<p>GENERAL CONDITIONS</p> <ol style="list-style-type: none"> GENERAL AND SPECIAL CONDITIONS ARE HEREBY MADE A INTEGRAL PART OF THIS DIVISION OF THE SPECIFICATIONS IN THAT THEY ARE APPLICABLE TO THE WORK UNDER THIS DIVISION UNLESS OTHERWISE NOTED. PROVIDE ALL LABOR, MATERIAL AND EQUIPMENT REQUIRED FOR THE COMPLETION AND OPERATION OF ALL SYSTEMS IN THIS SECTION OF WORK IN ACCORDANCE WITH ALL APPLICABLE CODES. PERMITS: APPLY FOR AND PAY FOR ALL NECESSARY PERMITS, FEES, AND INSPECTIONS REQUIRED BY ANY PUBLIC AUTHORITY HAVING JURISDICTION. ACREAGE CHARGES, BOND PROPERTY ASSESSMENTS AND FACILITIES CHARGE ARE NOT TO BE CONSTRUED TO BE A PART OF THIS CONTRACT. WARRANTY: PROVIDE ALL MATERIALS AND EQUIPMENT UNDER THIS SECTION OF THE SPECIFICATIONS WITH A ONE YEAR WARRANTY FROM THE DATE OF ACCEPTANCE OF WORK BY THE OWNER. THE CONTRACTOR SHALL TIE INTO CIVIL PROVIDED TAP AS INDICATED ON PLANS. ALL COSTS FOR THIS SERVICE SHALL BE PART OF HIS BID CONTRACT PRICE. PROTECT COPPER PIPING AGAINST CONTACT WITH DISSIMILAR METALS. ALL HANGERS, SUPPORTS, ANCHORS, AND CLIPS SHALL BE COPPER OR COPPER PLATED. PROTECT COPPER PIPING AGAINST CONTACT WITH ALL MASONRY. WHERE COPPER IS SLEEVED THROUGH MASONRY, PROVIDE COPPER OR RED BRASS SLEEVES. MAKE SURE PROVISIONS ARE INSTALLED IN ALL PIPING SO NO STRAIN OR BREAKAGE RESULTS FROM EXPANSION OR CONTRACTION. PITCH ALL WATER PIPES SO THAT ALL PARTS MAY BE DRAINED. THE FORMATION OF SAGS AND TRAPS SHALL BE AVOIDED. <p>MATERIALS</p> <ol style="list-style-type: none"> ALL NEW WORK SHALL BE OF MATERIALS LISTED BELOW OR SHALL MATCH EXISTING. IF A CONFLICT EXISTS BETWEEN MATERIALS AND/OR EQUIPMENT, THE MORE STRINGENT SHALL APPLY AS ADJUDGED BY THE ARCHITECT/ENGINEER. THE CONTRACTOR SHALL VERIFY MATERIAL TYPE AND EQUIPMENT. SANITARY WASTE AND VENT PIPING: <ol style="list-style-type: none"> SANITARY WASTE AND VENT PIPING AND FITTINGS. SERVICE WEIGHT CAST IRON, HUB AND SPIGOT TYPE WITH COMPRESSION JOINTS (ASTM A 74) OR NO-HUB PIPING WITH COUPLINGS (CISPI 301). IF PERMITTED BY LOCAL CODES, SCHEDULE 40 PVC (ASTM D 2665) WITH SCHEDULE 40 SOCKET-TYPE PIPE FITTINGS (ASTM D 3311) MAY BE USED. EXCEPTIONS: DO NOT INSTALL PVC PIPING IN RETURN AIR PLENUMS OR WITHIN 10'-0" OF ANY LOCATION WHERE EQUIPMENT MAY DISCHARGE WATER IN EXCESS OF 140 DEGREES. SLOPE SANITARY WASTE PIPING 2.5' AND SMALLER AT 1/4" PER FOOT MIN. SLOPE SANITARY WASTE PIPING 3" AND LARGER AT 1/8" PER FOOT MINIMUM. WHERE WASTE PIPING IS EXPOSED IN REST ROOM AREAS, PROVIDE CHROME PLATED BRASS PIPING WITH MATCHING STOPS AND ESCUTCHEONS. PROVIDE REMOVABLE TRAPS WITH INTEGRAL CLEAN-OUT PLUG FOR ALL LAVATORIES. INSTALL CLEAN-OUTS IN A LOCATION THAT PERMITS ACCESS FOR SERVICE WITHOUT DAMAGE TO THE BUILDING OR FINISHED MATERIALS. SEWAGE EJECTOR PUMP <ol style="list-style-type: none"> SEWAGE EJECTOR PUMP WILL BE COMPLETELY SUBMERSIBLE, CAPABLE OF SELF-COMMUTING UNSCREENED SEWAGE, AUTOMATIC OPERATION, WITH ONE PIECE CAST IRON OR BRONZE NON-CLOG BALANCED IMPELLER. SEWAGE EJECTOR PUMP SHOULD HAVE HEAVY DUTY CAST IRON CASING, IMPELLER, AND MOTOR HOUSING. THE PUMP PIT/BASIN SHALL HAVE A STEEL COVER WITH REQUIRED OPENINGS FOR PUMPS, CONTROLS, AND VENT CONNECTIONS. COVER AND FRAME ARE TO BE OF GASTIGHT CONSTRUCTION AND SHALL BE TREATED WITH CORROSION RESISTANT COATING. EQUIP SUBMERSIBLE MOTOR WITH NATIONAL ELECTRICAL CODE CLASS 1, DIVISION 1 (EXPLOSION-PROOF) RATED SERVICE; UL LISTED FOR CLASS I, GROUP C AND D IN AIR OR SUBMERSIBLE IN SEWAGE SHAFTS SHOULD BE CARBON STEEL. DESIGN TO OPERATE ON A SINGLE PHASE, 60 HERTZ, 208/230 VOLT CIRCUIT (NEMA STANDARD MOTOR VOLTAGE 115 V). GUARANTEE THE CONTRACTOR SHALL GUARANTEE THE COMPLETE PLUMBING SYSTEM AGAINST DEFECTS DUE TO FAULTY MATERIALS, WORKMANSHIP OR FAILURE DUE TO NEGLIGENCE OF THE CONTRACTOR. THIS GUARANTEE SHALL EXTEND 12 MONTHS FROM DATE OF FINAL ACCEPTANCE. ALL SERVICE CALLS DURING THIS PERIOD SHALL BE PROVIDED BY THE CONTRACTOR. 											SEWAGE EJECTOR PUMP SCHEDULE											PROJECT NO:	MARK	QUANTITY	DISCHARGE	GPM	TDH (FT)	HP	VOLTAGE	PHASE	MANUFACTURER & MODEL NO.	REMARKS		SE-1 (DUPLEX)	2	2" NPT	40	18	0.5	208/230	1		DUPLEX SEWAGE SYSTEM DIMENSION 21.25'(H)X11.75'(W)X14.75'(L)	
GENERAL PLUMBING NOTES											ISSUED FOR																																																																																
<ol style="list-style-type: none"> DRAWINGS ARE DIAGRAMMATIC AND SHALL NOT BE SCALED. REFER TO DESIGN PLANS AND ELEVATIONS FOR EXACT LOCATION OF ALL PLUMBING FIXTURES, EQUIPMENT, ETC. PLUMBING CONTRACTOR SHALL FURNISH AND INSTALL ALL ITEMS REQUIRED FOR A COMPLETE AND ACCEPTABLE WORKING INSTALLATION. ALL WORK AND MATERIALS SHALL COMPLY WITH THE LATEST EDITION OF THE NATIONAL, STATE, AND ALL LOCAL CODES AND ORDINANCES HAVING JURISDICTION. THE PLUMBING CONTRACTOR SHALL VISIT THE SITE AND THOROUGHLY FAMILIARIZE HIMSELF WITH ALL EXISTING CONDITIONS. ALL EXECUTION AND BACKFILL AS REQUIRED FOR THIS PHASE OF CONSTRUCTION SHALL BE A PART OF THIS CONTRACT. ALL WORK SHALL BE PERFORMED BY A LICENSED PLUMBING CONTRACTOR IN A FIRST CLASS WORKMANLIKE MANNER. THE COMPLETED SYSTEM SHALL BE FULLY OPERATIVE AND ACCEPTED BY ENGINEER/DESIGNER. ALL REQUIRED INSURANCE SHALL BE PROVIDED FOR PROTECTION AGAINST PUBLIC LIABILITY OR PROPERTY DAMAGE FOR THE DURATION OF THE WORK. THE PLUMBING CONTRACTOR SHALL SECURE AND PAY ALL PERMIT FEES, INSPECTIONS, AND TESTS. TESTS SHALL COMPLY WITH ALL APPLICABLE REQUIREMENTS. ALL WORK SHALL BE COORDINATED WITH OTHER TRADES TO AVOID INTERFERENCE WITH THE PROGRESS OF CONSTRUCTION. THE PLUMBING CONTRACTOR SHALL GUARANTEE ALL MATERIALS AND WORKMANSHIP FREE FROM DEFECTS FOR A PERIOD OF NOT LESS THAN (1) ONE YEAR FROM DATE OF ACCEPTANCE. CORRECTION OF ANY DEFECTS SHALL BE COMPLETED WITHOUT ADDITIONAL CHARGE AND SHALL INCLUDE REPLACEMENT OR REPAIR OF ANY OTHER PHASE OF THE INSTALLATION WHICH MAY HAVE BEEN DAMAGED THEREBY. VERIFY LOCATION, SIZE AND INVERTS OF ALL EXISTING UTILITIES PRIOR TO START OF CONSTRUCTION. ADVISE ARCHITECT/ENGINEER OF ANY DISCREPANCIES. ALL FIXTURES SHALL BE PROVIDED WITH READILY ACCESSIBLE STOPS. PROVIDE SEISMIC SWAY BRACING FOR ALL SUSPENDED EQUIPMENT AND PIPING LARGER THAN 2" IN ACCORDANCE WITH SECTION WITH CURRENT CODES. 																																																																																											
GENERAL PLUMBING SPECIFICATIONS											DATE																																																																																
<p>GENERAL CONDITIONS</p> <ol style="list-style-type: none"> GENERAL AND SPECIAL CONDITIONS ARE HEREBY MADE A INTEGRAL PART OF THIS DIVISION OF THE SPECIFICATIONS IN THAT THEY ARE APPLICABLE TO THE WORK UNDER THIS DIVISION UNLESS OTHERWISE NOTED. PROVIDE ALL LABOR, MATERIAL AND EQUIPMENT REQUIRED FOR THE COMPLETION AND OPERATION OF ALL SYSTEMS IN THIS SECTION OF WORK IN ACCORDANCE WITH ALL APPLICABLE CODES. PERMITS: APPLY FOR AND PAY FOR ALL NECESSARY PERMITS, FEES, AND INSPECTIONS REQUIRED BY ANY PUBLIC AUTHORITY HAVING JURISDICTION. ACREAGE CHARGES, BOND PROPERTY ASSESSMENTS AND FACILITIES CHARGE ARE NOT TO BE CONSTRUED TO BE A PART OF THIS CONTRACT. WARRANTY: PROVIDE ALL MATERIALS AND EQUIPMENT UNDER THIS SECTION OF THE SPECIFICATIONS WITH A ONE YEAR WARRANTY FROM THE DATE OF ACCEPTANCE OF WORK BY THE OWNER. THE CONTRACTOR SHALL TIE INTO CIVIL PROVIDED TAP AS INDICATED ON PLANS. ALL COSTS FOR THIS SERVICE SHALL BE PART OF HIS BID CONTRACT PRICE. PROTECT COPPER PIPING AGAINST CONTACT WITH DISSIMILAR METALS. ALL HANGERS, SUPPORTS, ANCHORS, AND CLIPS SHALL BE COPPER OR COPPER PLATED. PROTECT COPPER PIPING AGAINST CONTACT WITH ALL MASONRY. WHERE COPPER IS SLEEVED THROUGH MASONRY, PROVIDE COPPER OR RED BRASS SLEEVES. MAKE SURE PROVISIONS ARE INSTALLED IN ALL PIPING SO NO STRAIN OR BREAKAGE RESULTS FROM EXPANSION OR CONTRACTION. PITCH ALL WATER PIPES SO THAT ALL PARTS MAY BE DRAINED. THE FORMATION OF SAGS AND TRAPS SHALL BE AVOIDED. <p>MATERIALS</p> <ol style="list-style-type: none"> ALL NEW WORK SHALL BE OF MATERIALS LISTED BELOW OR SHALL MATCH EXISTING. IF A CONFLICT EXISTS BETWEEN MATERIALS AND/OR EQUIPMENT, THE MORE STRINGENT SHALL APPLY AS ADJUDGED BY THE ARCHITECT/ENGINEER. THE CONTRACTOR SHALL VERIFY MATERIAL TYPE AND EQUIPMENT. SANITARY WASTE AND VENT PIPING: <ol style="list-style-type: none"> SANITARY WASTE AND VENT PIPING AND FITTINGS. SERVICE WEIGHT CAST IRON, HUB AND SPIGOT TYPE WITH COMPRESSION JOINTS (ASTM A 74) OR NO-HUB PIPING WITH COUPLINGS (CISPI 301). IF PERMITTED BY LOCAL CODES, SCHEDULE 40 PVC (ASTM D 2665) WITH SCHEDULE 40 SOCKET-TYPE PIPE FITTINGS (ASTM D 3311) MAY BE USED. EXCEPTIONS: DO NOT INSTALL PVC PIPING IN RETURN AIR PLENUMS OR WITHIN 10'-0" OF ANY LOCATION WHERE EQUIPMENT MAY DISCHARGE WATER IN EXCESS OF 140 DEGREES. SLOPE SANITARY WASTE PIPING 2.5' AND SMALLER AT 1/4" PER FOOT MIN. SLOPE SANITARY WASTE PIPING 3" AND LARGER AT 1/8" PER FOOT MINIMUM. WHERE WASTE PIPING IS EXPOSED IN REST ROOM AREAS, PROVIDE CHROME PLATED BRASS PIPING WITH MATCHING STOPS AND ESCUTCHEONS. PROVIDE REMOVABLE TRAPS WITH INTEGRAL CLEAN-OUT PLUG FOR ALL LAVATORIES. INSTALL CLEAN-OUTS IN A LOCATION THAT PERMITS ACCESS FOR SERVICE WITHOUT DAMAGE TO THE BUILDING OR FINISHED MATERIALS. SEWAGE EJECTOR PUMP <ol style="list-style-type: none"> SEWAGE EJECTOR PUMP WILL BE COMPLETELY SUBMERSIBLE, CAPABLE OF SELF-COMMUTING UNSCREENED SEWAGE, AUTOMATIC OPERATION, WITH ONE PIECE CAST IRON OR BRONZE NON-CLOG BALANCED IMPELLER. SEWAGE EJECTOR PUMP SHOULD HAVE HEAVY DUTY CAST IRON CASING, IMPELLER, AND MOTOR HOUSING. THE PUMP PIT/BASIN SHALL HAVE A STEEL COVER WITH REQUIRED OPENINGS FOR PUMPS, CONTROLS, AND VENT CONNECTIONS. COVER AND FRAME ARE TO BE OF GASTIGHT CONSTRUCTION AND SHALL BE TREATED WITH CORROSION RESISTANT COATING. EQUIP SUBMERSIBLE MOTOR WITH NATIONAL ELECTRICAL CODE CLASS 1, DIVISION 1 (EXPLOSION-PROOF) RATED SERVICE; UL LISTED FOR CLASS I, GROUP C AND D IN AIR OR SUBMERSIBLE IN SEWAGE SHAFTS SHOULD BE CARBON STEEL. DESIGN TO OPERATE ON A SINGLE PHASE, 60 HERTZ, 208/230 VOLT CIRCUIT (NEMA STANDARD MOTOR VOLTAGE 115 V). GUARANTEE THE CONTRACTOR SHALL GUARANTEE THE COMPLETE PLUMBING SYSTEM AGAINST DEFECTS DUE TO FAULTY MATERIALS, WORKMANSHIP OR FAILURE DUE TO NEGLIGENCE OF THE CONTRACTOR. THIS GUARANTEE SHALL EXTEND 12 MONTHS FROM DATE OF FINAL ACCEPTANCE. ALL SERVICE CALLS DURING THIS PERIOD SHALL BE PROVIDED BY THE CONTRACTOR. 																																																																																											
SEWAGE EJECTOR PUMP SCHEDULE											PROJECT NO:																																																																																
MARK	QUANTITY	DISCHARGE	GPM	TDH (FT)	HP	VOLTAGE	PHASE	MANUFACTURER & MODEL NO.	REMARKS																																																																																		
SE-1 (DUPLEX)	2	2" NPT	40	18	0.5	208/230	1		DUPLEX SEWAGE SYSTEM DIMENSION 21.25'(H)X11.75'(W)X14.75'(L)																																																																																		

 Plumbing Notes, Specifications, & Details | || | | | | | | | | | | | | | |------------------------|--|--|--|--|--|--|--|--|--|--|--------------| | SEWAGE EJECTOR | | | | | | | | | | | DRAWN BY: | | <p>NO SCALE</p> | | | | | | | | | | | | | SECTION | | | | | | | | | | | CHECKED BY: | | | | | | | | | | | | | | | PLAN | | | | | | | | | | | SCALE: | | | | | | | | | | | | | | | ISSUE DATE: | | | | | | | | | | | Sheet Number | | | | | | | | | | | | | Plumbing Notes, Specifications, & Details | |

