

MECHANICAL SYMBOLS LIST

AC-1	EF-1	EQUIPMENT SYMBOL	MECHANICAL ABBREVIATIONS
		POINT OF NEW CONNECTION TO EXISTING	AFF ABOVE FINISHED FLOOR AL ACOUSTIC LINING BD BACKDRAFT DAMPER CDS CEILING DIFFUSER SUPPLY
AIR DEVICES			
		CEILING DIFFUSER SUPPLY	CDR CEILING DIFFUSER RETURN CFM CUBIC FEET OF AIR PER MINUTE
		CEILING DIFFUSER RETURN/EXHAUST	CP CONDENSATE PUMP
		SUPPLY GRILLE - SIDEWALL	CD CONDENSATE DRAIN PIPE EF EXHAUST FAN FC FLEXIBLE CONNECTION
		RETURN GRILLE - SIDEWALL	FD/AD FIRE DAMPER W/ACCESS DOOR FD FIRE DAMPER W/FUSIBLE LINK FSD FIRE SMOKE DAMPER
DUCT ACCESSORIES			
		BACKDRAFT DAMPER	MD MOTORIZED DAMPER OAI OUTSIDE AIR INTAKE T-X THERMOSTAT VD VOLUME DAMPER W.M.S. WIRE MESH SCREEN S.A.E SAME AS EXISTING V.I.F VERIFY IN FIELD RTU ROOF TOP UNIT

CONTROLS AND SENSORS	
	THERMOSTAT
	TEMPERATURE SENSOR
	DUCT SMOKE DETECTOR
DUCTWORK	
	AIR DUCT W/ 1.5" ACOUSTICAL LINING
	FLEXIBLE DUCT
	FLEXIBLE CONNECTION
	RECTANGULAR DUCT (WIDTH X DEPTH)
	ROUND DUCT (DIAMETER)
	ROUND DUCT CROSS SECTION
	SUPPLY AIR RECTANGULAR DUCT CROSS SECTION
	RETURN AIR RECTANGULAR DUCT CROSS SECTION

MECHANICAL DRAWING LIST	
M0.01	MECHANICAL GENERAL NOTES, SYMBOL LIST & ABBREVIATIONS
M0.02	MECHANICAL SPECIFICATIONS
M1.01	MECHANICAL FLOOR PLAN
M1.02	MECHANICAL ROOF PLAN
M5.01	MECHANICAL DETAILS
M6.01	MECHANICAL SCHEDULES

CODE COMPLIANCE	
ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTHING IN THESE DRAWINGS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:	
A.	2024 OHIO ENERGY CODE (BASE CODE - IECC 2021).
B.	2024 OHIO BUILDING CODE (BASE CODE - IBC 2021).
C.	2024 OHIO MECHANICAL CODE (BASE CODE - IMC 2021).
D.	2024 OHIO PLUMBING CODE (BASE CODE - IPC 2021).
E.	2021 OHIO FUEL GAS CODE (BASE CODE - IFGC 2021).

OHIO BUILDING DEPARTMENT NOTES

ALL WORK SHALL COMPLY WITH APPLICABLE SECTIONS OF OHIO BUILDING CODE 2024 (IBC 2021) AND ALL AMENDMENTS AND RULES AND REGULATIONS OF THE DEPARTMENT OF BUILDINGS TO DATE.

- THE CONTRACTOR SHALL ENGAGE THE SERVICES OF A PROFESSIONAL ENGINEER TO PROVIDE THE REQUIRED SPECIAL INSPECTIONS AND TESTS. TESTS WILL BE CONDUCTED UNDER DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT OR OTHER PERSON HAVING NOT LESS THAN FIVE (5) YEARS EXPERIENCE SUPERVISING THE INSTALLATION OF SUCH MECHANICAL SYSTEMS. THE TESTS WILL SHOW COMPLIANCE WITH OHIO BUILDING CODE 2024 (IBC 2021).
- THE LICENSED PROFESSIONAL ENGINEER, ARCHITECT OR OTHER PERSON HAVING NOT LESS THAN FIVE (5) YEARS EXPERIENCE SUPERVISING THE INSTALLATION OF SUCH MECHANICAL SYSTEMS AND CONDUCTING SUCH TESTS WILL FILE DOCUMENTATION AND REPORTS OF TESTS THAT THE SYSTEM COMPLIES WITH THE CONSTRUCTION DOCUMENTS AND APPLICABLE LAWS.
- TESTS OF MECHANICAL SYSTEMS SHALL BE PERFORMED IN ACCORDANCE WITH SECTION MC 107 AND THE FOLLOWING SECTIONS OF THE OHIO BUILDING CODE 2024 (IBC 2021).
- THE FOLLOWING WORK ITEMS, COMPONENTS, MATERIALS, CAPACITIES, ETC. SHALL COMPLY WITH THE REFERENCED CODE OR STANDARD:
 - STANDARDS OF HEATING - OHIO MECHANICAL CODE 2024 (IMC 2021) - SECTION 309.1.
 - DUCT CONSTRUCTION AND INSTALLATION - OHIO MECHANICAL CODE 2024 (IMC 2021) - SECTION 603.
 - AIR INTAKES, EXHAUSTS AND RELIEF - OHIO MECHANICAL CODE 2024 (IMC 2021) - SECTION 401.5
 - AIR FILTERS - OHIO MECHANICAL CODE 2024 (IMC 2021) - SECTION 605.
 - GAS FIRED EQUIPMENT - OHIO MECHANICAL CODE 2024 (IMC 2021) - SECTION 901.
- MINIMUM TEMPERATURE TO BE MAINTAINED IN OCCUPIED SPACES DURING HEATING SEASON: 68 DEG. FAHRENHEIT.
- VENTILATION FOR ALL AREA SHALL COMPLY WITH OHIO MECHANICAL CODE 2024 (IMC 2021) - SECTION 401.
- A STATEMENT SHALL BE FILED BY THE OWNER OR TENANT IN POSSESSION THAT THE VENTILATION SYSTEM WILL BE KEPT IN CONTINUOUS OPERATION AT ALL TIMES DURING THE NORMAL OCCUPANCY OF THE STRUCTURE AS REQUIRED BY OHIO MECHANICAL CODE 2024 (IMC 2021) - SECTION 403.
- REFER TO ARCHITECTURAL DRAWINGS FOR REQUIRED FIRE-RATED WALL AND SMOKE WALL CONSTRUCTION AND LOCATION.
- THESE PLANS ARE APPROVED ONLY FOR THE WORK INDICATED ON THE APPLICATION SPECIFICATION SHEET. ALL OTHER MATTERS SHOWN ARE NOT TO BE RELIED UPON OR TO BE CONSIDERED AS EITHER BEING APPROVED OR IN ACCORDANCE WITH APPLICABLE CODES.
- ALL HEATING AND COOLING LOADS CALCULATED PER ASHRAE/ACCA 183.
- SMOKE DETECTOR SHALL MEET UL268A.

FIELD VERIFY ALL CONDITION

DESIGN DRAWINGS ARE SCHEMATIC. THIS CONTRACTOR SHALL VISIT THE SITE PRIOR TO BID OR AWARD OF CONTRACT TO INSPECT EXISTING FIELD CONDITIONS. THIS CONTRACT SHALL INCLUDE ALL LABOR AND MATERIALS NECESSARY FOR FIELD MODIFICATIONS. DUE TO EXISTING CONDITIONS, THE CONTRACTOR SHALL CONTACT THE ARCHITECT, ENGINEER OR OWNER PRIOR TO BIDDING FOR INTERPRETATIONS AND CLARIFICATIONS OF THE DESIGN AND INCLUDE IN HIS BID ALL COSTS TO MEET THE DESIGN INTENT. CLARIFICATIONS MADE BY THE ARCHITECT, ENGINEER OR OWNER AFTER BIDDING WILL BE FINAL AND SHALL BE IMPLEMENTED AT CONTRACTORS COST. BIDDING CONTRACTORS SHALL HAVE A WORKING KNOWLEDGE OF LOCAL CODES AND ORDINANCES AND SHALL INCLUDE IN THEIR BIDS THE COSTS FOR ALL WORK INSTALLED IN STRICT ACCORDANCE WITH GOVERNING CODES, THE PLANS AND SPECIFICATIONS. NOT WITHSTANDING THE CONTRACTOR SHALL ALERT ARCHITECT, ENGINEER OR OWNER OF ANY APPARENT DISCREPANCIES BETWEEN GOVERNING CODES AND DESIGN INTENT.

SCOPE OF WORK

- THE WORK UNDER CONTRACT INCLUDES ALL LABOR, MATERIALS AND APPLIANCES NECESSARY FOR THE FURNISHING, INSTALLING AND TESTING, COMPLETE AND READY FOR SAFE OPERATION OF THE SYSTEMS AS DESCRIBED IN THE SPECIFICATIONS, FLOOR PLANS, DESIGN, DETAIL DRAWINGS, NOTES, RFS, ETC. FOR THIS PROJECT. WORK SHALL BE INSTALLED IN A NEAT, WORKMANLIKE MANNER.
- THE CONTRACTOR SHALL GIVE NECESSARY NOTICE, FILE DRAWINGS AND SPECIFICATIONS WITH THE DEPARTMENT HAVING JURISDICTION, OBTAIN PERMITS OR LICENSES NECESSARY TO CARRY OUT THIS WORK AND PAY ALL FEES THEREFORE. THE CONTRACTOR SHALL ARRANGE FOR INSPECTION AND TESTS OF ANY OR ALL PARTS OF THE WORK IF SO REQUIRED BY AUTHORITIES AND PAY ALL CHARGES FOR SAME. THE CONTRACTOR SHALL PAY ALL COSTS FOR, AND FURNISH TO THE OWNER BEFORE FINAL BILLING, ALL CERTIFICATES NECESSARY AS EVIDENCE THAT THE WORK INSTALLED CONFORMS WITH ALL REGULATIONS WHERE THEY APPLY TO THIS WORK.
- THE CONTRACTOR SHALL FURNISH A WRITTEN GUARANTEE TO REPLACE OR REPAIR PROMPTLY AND ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED FOR ANY WORKMANSHIP AND EQUIPMENT IN WHICH DEFECTS DEVELOP WITHIN ONE YEAR FROM THE DATE OF FINAL CERTIFICATE FOR PAYMENT AND/OR FROM DATE OR ACTUAL USE OF EQUIPMENT OR OCCUPANCY OF SPACES, BY OWNER, INCLUDED UNDER THE VARIOUS PARTS OF THE WORK, WHICHEVER DATE IS EARLIER. THIS WORK SHALL BE DONE AS DIRECTED BY THE OWNER. THIS GUARANTEE SHALL ALSO PROVIDE THAT WHERE DEFECTS OCCUR, THE CONTRACTOR WILL ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED IN REPAIRING AND REPLACING WORK OF OTHER TRADES AFFECTED BY DEFECTS, REPAIRS OR REPLACEMENTS IN EQUIPMENT SUPPLIED BY THE CONTRACTOR.

GENERAL NOTES

- CONTRACTOR SHALL SURVEY THE AREA OF THIS WORK BEFORE SUBMITTING A BID AND SHALL BE RESPONSIBLE FOR NOTIFYING THE ARCHITECT OF ANY CONDITIONS WHICH WOULD PREVENT THE INSTALLATION OF THE WORK AS SHOWN ON DRAWINGS.
- ALL APPLICABLE CODES, LAWS AND REGULATIONS GOVERNING OR RELATING TO ANY PORTION OF THIS WORK ARE HEREBY INCORPORATED INTO AND MADE A PART OF THESE SPECIFICATIONS, AND THEIR PROVISIONS SHALL BE CARRIED OUT BY THE CONTRACTOR WHO SHALL INFORM THE OWNER, PRIOR TO SUBMITTING A PROPOSAL, OF ANY WORK OR MATERIALS WHICH VIOLATE ANY OF THE ABOVE LAWS AND REGULATIONS. ANY WORK DONE BY THE CONTRACTOR CAUSING SUCH VIOLATION SHALL BE CORRECTED BY THE CONTRACTOR.
- BEFORE PROCEEDING WITH ANY WORK IN OCCUPIED OR USED AREAS, THE CONTRACTOR SHALL APPLY TO OWNER FOR PERMISSION TO ENTER SUCH AREAS. THE CONTRACTOR IS OBLIGED TO PERFORM HIS WORK ONLY AT THE TIMES DESIGNATED BY OWNER. THERE WILL BE NO ADDITIONAL COMPENSATION FOR THE WORK PERFORMED AFTER HOURS OR ON OFF-DAYS WITHOUT PRIOR WRITTEN APPROVAL.
- CONTRACTOR SHALL ASCERTAIN THE APPROPRIATE METHOD FOR BRINGING THE UNITS INTO AND THROUGH THE BUILDING TO POSITION UNIT IN LOCATION SHOWN ON THE PLANS. WHERE NECESSARY, EQUIPMENT SHALL BE SHIPPED FROM MANUFACTURER IN SECTIONS OF SIZE SUITABLE FOR MOVING THROUGH RESTRICTIVE SPACES. COORDINATE WITH BUILDING OWNER APPROPRIATE TIMES OF DAY SUCH EQUIPMENT MAY BE MOVED THROUGH ALL AREAS.
- DUCTWORK AND PIPING IS SHOWN DIAGRAMMATICALLY AND DOES NOT SHOW ALL OFFSETS, DROPS AND RISES OF RUNS. THE CONTRACTOR SHALL MAKE ALLOWANCE IN PRICING FOR ROUTING OF DUCTWORK AND PIPING TO AVOID OBSTRUCTIONS. EXACT LOCATIONS ARE SUBJECT TO APPROVAL OF ARCHITECT. COORDINATION WITH THE OTHER TRADES IS REQUIRED.
- SUPPORT ALL DUCTWORK AND PIPING FROM BUILDING STRUCTURE AND/OR FRAMING IN AN APPROVED MANNER. WHERE OVERHEAD CONSTRUCTION DOES NOT PERMIT FASTENING OR SUPPORTS FOR EQUIPMENT, FURNISH ADDITIONAL FRAMING. INSERTS SHALL BE STEEL, SLOTTED TYPE AND FACTORY PAINTED. MAXIMUM LOADING INCLUDING PIPES, DUCTWORK CONTENTS AND COVERING SHALL NOT EXCEED 75% OF RATED INSERT CAPABILITY. WHEN SUPPORTING FROM BUILDING USE BEAM CLAMPS IN APPROVED MANNER.
- PROVIDE ALL NECESSARY FLASHING AND COUNTER FLASHING TO MAINTAIN THE WATERPROOFING INTEGRITY OF THIS BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF PIPES, DUCTS, LOUVERS, CONDUIT, AND EQUIPMENT. PROVIDE EQUIPMENT CURBS AND DUNNAGE STEEL AS REQUIRED.
- SEAL OPENINGS AROUND DUCTS AND PIPING THROUGH PARTITIONS, WALLS AND FLOORS (NOT IN SHAFTS) WITH MINERAL WOOL OR OTHER NONCOMBUSTIBLE MATERIAL (FIBERGLASS INSULATION IS NOT ACCEPTABLE).
- WHERE PENETRATIONS THROUGH FIRE RATED WALLS ARE NOT FIRE PROOFED THIS CONTRACTOR SHALL BE RESPONSIBLE TO SEAL SAME TO MAINTAIN THE RATED INTEGRITY.
- INSTALL WORK SO AS TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE AND REPAIR. MINOR DEVIATIONS FROM DRAWINGS MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST SHALL NOT BE MADE WITHOUT APPROVAL.
- ACCESS DOORS ARE REQUIRED FOR ALL BUILDING SERVICE VALUES THAT RUN THROUGH THE SPACE, AND ACCESS DOOR SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL. COORDINATE ALL LOCATIONS OF ACCESS DOORS WITH THE ARCHITECT.
- REMOVABLE ACCESS TILE AND/OR ACCESS DOOR ARE REQUIRED IN HUNG CEILINGS, SHAFTS AND WALLS FOR ALL VOLUME AND FIRE DAMPERS, AUTOMATIC DAMPERS AND ALL OTHER MECHANICAL EQUIPMENT AND DEVICES. HVAC CONTRACTOR TO FURNISH ACCESS LOCATION REQUIREMENTS TO GENERAL CONTRACTOR. ACCESS TILE IDENTIFICATION: PROVIDE BUTTONS, TABS, AND MARKERS TO IDENTIFY LOCATION OF CONCEALED VALVES, DAMPERS AND EQUIPMENT.
- THE CONTRACTOR SHALL KEEP ALL EQUIPMENT AND MATERIALS, AND ALL PARTS OF THE BUILDING, EXTERIOR SPACES AND ADJACENT STREETS, SIDEWALKS AND PAVEMENTS, FREE FROM MATERIAL AND DEBRIS RESULTING FROM THE EXECUTION OF THIS WORK. EXCESS MATERIALS WILL NOT BE PERMITTED TO ACCUMULATE EITHER ON THE INTERIOR OR THE EXTERIOR.
- MATERIALS AND WORKMANSHIP, UNLESS OTHERWISE NOTED, SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- ALL EQUIPMENT SHALL BE PROVIDED WITH ONE YEAR WARRANTY PARTS AND LABOR AND FIVE YEARS ON COMPRESSORS. WARRANTY PERIOD BEGINS UPON PROJECT ACCEPTANCE.
- ALL MATERIAL AND EQUIPMENT TO BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR HIS WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF THE SAME WHICH MAY BE DAMAGED, LOST, OR STOLEN WITHOUT ADDITIONAL COST TO THE OWNER.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FAILURE OF ANY DUCTWORK SYSTEM OR EQUIPMENT TO FUNCTION PROPERLY UPON COMPLETION OF HIS WORK UPON SAID SYSTEM OR EQUIPMENT.
- SUBMIT SHOP DRAWING OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES.
- INSURANCE: IN ACCORDANCE WITH BUILDING REQUIREMENTS THE CONTRACTOR SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND ENGINEER.
- THE FINAL ACCEPTANCE WILL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, BALANCED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATES OF INSPECTION AND APPROVAL.
- WHERE A CONFLICT EXISTS BETWEEN THE DRAWINGS, THE SPECIFICATIONS OR ANY OTHER CONSTRUCTION DOCUMENT, THE ONE WITH THE MOST STRINGENT REQUIREMENT(S) SHALL APPLY.
- SPECIFICATIONS ARE OF SIMPLIFIED FORM AND INCLUDE INCOMPLETE SENTENCES, WORDS OR PHRASES SUCH AS "THE CONTRACTOR SHALL," "SHALL BE," "FURNISH," "PROVIDE," "A," "THE," AND "ALL" HAVE BEEN OMITTED FOR BREVITY.

DEFINITIONS:

- "PROVIDE": TO SUPPLY, INSTALL AND CONNECT UP COMPLETE AND READY FOR SAFE AND REGULAR OPERATION THE PARTICULAR WORK REFERRED TO UNLESS SPECIFICALLY OTHERWISE NOTED.
- "INSTALL": TO ERECT, MOUNT AND CONNECT COMPLETE WITH RELATED ACCESSORIES.
- "FURNISH" OR "SUPPLY": TO PURCHASE, PROCURE, ACQUIRE AND DELIVER COMPLETE WITH RELATED ACCESSORIES.

GENERAL HVAC NOTES

- PROVIDE ALL MATERIAL AND EQUIPMENT AND PERFORM ALL LABOR REQUIRED TO INSTALL COMPLETE AND OPERABLE MECHANICAL SYSTEMS AS INDICATED ON THE DRAWINGS, AS SPECIFIED AND AS REQUIRED BY CODE.
- CONTRACT DOCUMENT DRAWINGS FOR MECHANICAL WORK (HVAC, PLUMBING, AND FIRE PROTECTION) ARE DIAGRAMMATIC AND ARE INTENDED TO CONVEY SCOPE AND GENERAL ARRANGEMENT ONLY.
- THE LOCATIONS OF ALL ITEMS SHOWN ON THE DRAWINGS OR CALLED FOR IN THE SPECIFICATIONS THAT ARE NOT FIXED BY DIMENSIONS ARE APPROXIMATE ONLY. THE EXACT LOCATIONS NECESSARY TO SECURE THE BEST CONDITIONS AND RESULTS MUST BE DETERMINED BY THE PROJECT SITE CONDITIONS AND SHALL HAVE THE APPROVAL OF THE ENGINEER BEFORE BEING INSTALLED. DO NOT SCALE DRAWINGS.
- WHEN MECHANICAL WORK (HVAC, PLUMBING, SHEET METAL, FIRE PROTECTION, ETC.) IS SUBCONTRACTED, IT SHALL BE THE MECHANICAL CONTRACTOR'S RESPONSIBILITY TO COORDINATE SUBCONTRACTORS AND THE ASSOCIATED CONTRACTS. WHEN DISCREPANCIES ARISE PERTAINING TO WHICH CONTRACTOR PROVIDES A PARTICULAR ITEM OF THE MECHANICAL CONTRACT OR WHICH CONTRACTOR PROVIDES FINAL CONNECTIONS FOR A PARTICULAR ITEM OF THE MECHANICAL CONTRACT, IT SHALL BE BROUGHT TO THE ATTENTION OF THE MECHANICAL CONTRACTOR, WHOSE DECISION SHALL BE FINAL.
- COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, ELECTRICAL WORK, ETC., SHOWN ON OTHER CONTRACT DOCUMENT DRAWINGS.
- INSTALL ALL MECHANICAL EQUIPMENT AND APPURTENANCES IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, CONTRACT DOCUMENTS, AND APPLICABLE CODES AND REGULATIONS.
- WHERE TWO OR MORE ITEMS OF THE SAME TYPE OF EQUIPMENT ARE REQUIRED, THE PRODUCT OF ONE MANUFACTURER SHALL BE USED.
- COORDINATE ALL EQUIPMENT CONNECTIONS WITH MANUFACTURERS' CERTIFIED DRAWINGS. COORDINATE AND PROVIDE ALL DUCT AND PIPING TRANSITIONS REQUIRED FOR FINAL EQUIPMENT CONNECTIONS TO FURNISHED EQUIPMENT. FIELD VERIFY AND COORDINATE ALL DUCT AND PIPING DIMENSIONS BEFORE FABRICATION.
- ALL CONTROL WIRE AND CONDUIT SHALL COMPLY WITH THE NATIONAL ELECTRIC CODE AND ELECTRICAL DIVISION OF THE SPECIFICATION.
- PROVIDE VIBRATION ISOLATION FOR ALL MECHANICAL EQUIPMENT TO PREVENT TRANSMISSION OF VIBRATION TO BUILDING STRUCTURE.
- PROVIDE VIBRATION ISOLATORS FOR ALL PIPING SUPPORTS CONNECTED TO, AND WITHIN 50 FT. OF, ISOLATED EQUIPMENT (EXCEPT AT BASE ELBOW SUPPORTS AND ANCHOR POINTS).
- LOCATE ALL TEMPERATURE, PRESSURE, AND FLOW MEASURING DEVICES IN ACCESSIBLE LOCATIONS WITH THE STRAIGHT SECTION OF PIPE OR DUCT UP- AND DOWNSTREAM AS RECOMMENDED BY THE MANUFACTURER FOR GOOD ACCURACY.
- WHERE BEAMS ARE INDICATED TO BE PENETRATED WITH DUCTWORK OR PIPING, COORDINATE DUCTWORK AND PIPING LAYOUT WITH BEAM OPENING SIZE AND OPENING LOCATIONS. COORDINATION SHALL BE DONE PRIOR TO THE FABRICATION OF DUCTWORK, CUTTING OF PIPING, OR FABRICATION OF BEAMS.
- ALL MISCELLANEOUS STEEL REQUIRED TO ENSURE PROPER INSTALLATION AND AS SHOWN IN THE DETAILS FOR PIPING, DUCTWORK, AND EQUIPMENT (UNLESS OTHERWISE NOTED) SHALL BE FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR.
- PROVIDE ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS, WHERE REQUIRED, TO SERVICE DAMPERS, VALVES, SMOKE DETECTORS, AND OTHER CONCEALED MECHANICAL EQUIPMENT. ACCESS PANELS SHALL BE TURNED OVER TO THE GENERAL CONTRACTOR FOR INSTALLATION. ACCESS PANELS SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL.
- MECHANICAL EQUIPMENT, DUCTWORK, AND PIPING SHALL NOT BE SUPPORTED FROM A METAL DECK.
- ALL EQUIPMENT, PIPING, DUCTWORK, ETC., SHALL BE SUPPORTED AS DETAILED, SPECIFIED AND REQUIRED TO PROVIDE A VIBRATION-FREE INSTALLATION.
- ALL DUCTWORK, PIPING, AND EQUIPMENT SUPPORTED FROM STRUCTURAL STEEL SHALL BE COORDINATED WITH THE GENERAL CONTRACTOR. ALL ATTACHMENTS TO STEEL BAR JOISTS, TRUSSES, OR JOIERS GIRDERS SHALL AT PANEL LEVELS PROVIDE BEAM CLAMPS MEETING MSS STANDARDS. WELDING TO STRUCTURAL MEMBERS SHALL NOT BE PERMITTED. THE USE OF C-CLAMPS SHALL NOT BE PERMITTED.
- ALL ROOF-MOUNTED EQUIPMENT CURBS/STEEL RAILS FOR EQUIPMENT PROVIDED BY THE MECHANICAL CONTRACTOR SHALL BE FURNISHED BY THE MECHANICAL CONTRACTOR AND INSTALLED BY THE GENERAL CONTRACTOR.
- LOCATIONS AND SIZES OF ALL FLOOR, WALL, AND ROOF OPENINGS SHALL BE COORDINATED WITH ALL OTHER TRADES INVOLVED.
- ALL OPENINGS IN FIRE WALLS DUE TO DUCTWORK, PIPING, CONDUIT, ETC., SHALL BE FIRE STOPPED WITH A PRODUCT SIMILAR TO 3M OR APPROVED EQUAL.
- ALL AIR CONDITIONING CONDENSATE DRAIN LINES FROM EACH AIR HANDLING UNIT SHALL BE PIPED FULL SIZE OF THE UNIT DRAIN OUTLET, WITH "P" TRAP, AND PIPED TO THE NEAREST DRAIN. SEE THE DETAILS SHOWN IN THE DRAWINGS OR THE CONTRACT SPECIFICATIONS FOR THE DEPTH OF THE AIR CONDITIONING CONDENSATE TRAP.
- REFER TO TYPICAL DETAILS FOR DUCTWORK, PIPING, AND EQUIPMENT INSTALLATION.

ISSUANCE NAME: DATE
CD SET: 07-28-25
1 LL COMMENTS: 08-13-25

PROJECT NUMBER: 2

SPECIFICATIONS

SECTION 0001 - NOTICE TO BIDDERS

1.1 BIDDERS REPRESENTATIONS

- A. THE BIDDER BY MAKING A BID REPRESENTS THAT:
THE BIDDER HAS READ AND UNDERSTANDS THE BIDDING DOCUMENTS, TO THE EXTENT THAT SUCH DOCUMENTATION RELATES TO THE WORK FOR WHICH THE BID IS SUBMITTED, AND FOR OTHER PORTIONS OF THE PROJECT, IF ANY, BEING BID CONCURRENTLY OR PRESENTLY UNDER CONSTRUCTION.
- B. THE BID IS MADE IN COMPLIANCE WITH THE BIDDING DOCUMENTS.
- C. THE SPECIFICATIONS AND DRAWINGS ARE INTENDED TO SERVE JOINTLY AS A BASIS FOR THE BIDDER TO SUBMIT A CONTRACT PRICE FOR THE MATERIAL AND LABOR.
- D. SHOULD CONFLICTS OR DISCREPANCIES OCCUR WITHIN THE BIDDING DOCUMENTS, THE ITEM OR ITEMS IN DISPUTE THAT REPRESENT THE GREATER COST SHALL PREVAIL IN THE FINAL BID.
- E. THE BID IS BASED UPON THE MATERIALS, EQUIPMENT AND SYSTEMS REQUIRED BY THE BIDDING DOCUMENTS WITHOUT EXCEPTION.

1.2 EXISTING CONDITIONS AND COORDINATION

- A. THE BIDDER HAS VISITED THE SITE, BECOME FAMILIAR WITH LOCAL CONDITIONS UNDER WHICH THE WORK IS TO BE PERFORMED AND HAS CORRELATED THE BIDDER'S PERSONAL OBSERVATIONS WITH THE REQUIREMENTS OF THE PROPOSED BIDDING DOCUMENTS.
- B. THE BIDDER SHALL PROPOSE COORDINATION OF WORK SUCH THAT CONFLICTS WITH OTHER TRADES AND SPACE ALLOCATIONS ARE AVOIDED.

1.3 RESPONSIBILITIES

- A. THE BIDDER UNDERSTANDS THAT ANY CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR THE TIMELY COMPLETION AND ACCEPTANCE OF THEIR WORK AND THAT ANY ITEMS DAMAGED, LOST OR STOLEN DURING TIME OF CONSTRUCTION SHALL BE REPAIRED OR REPLACED WITHOUT ANY ADDITIONAL COST TO THE OWNER.
- B. THE BIDDER UNDERSTANDS THAT ANY PROPOSED WORK IN OCCUPIED TENANT SPACES SHALL BE PERFORMED DURING TIMES OF NON-TENANT OCCUPANCY OR AS SCHEDULED OR DIRECTED BY THE BUILDING MANAGER.
- C. THE BIDDER UNDERSTANDS THAT ANY PROPOSED SHUT-DOWN OF EXISTING SYSTEMS DURING CONSTRUCTION SHALL BE PRE-ARRANGED WITH THE BUILDING MANAGER AND THAT SUCH SHUT-DOWNS ARE TO BE KEPT TO A MINIMUM.

END OF SECTION 0001

SECTION 0101 - QUALITY OF WORK

1.1 WORKMANSHIP

- A. ALL WORK SHALL BE FREE FROM DEFECTS IN MATERIALS AND WORKMANSHIP FOR A PERIOD OF ONE YEAR FROM DATE OF FINAL ACCEPTANCE.
- B. ALL DEFECTS WHICH DEVELOP OR ARE DISCOVERED WITHIN THIS PERIOD SHALL BE REPAIRED BY THE CONTRACTOR TO THE SATISFACTION OF THE ARCHITECT OR BUILDING MANAGER AT NO ADDITIONAL COST TO THE OWNER.
- C. UPON COMPLETION OF THE WORK THE CONTRACTOR SHALL REMOVE FROM THE SITE, ALL TOOLS, DEMOLISHED APPLIANCES AND ANY SURPLUS MATERIAL.

1.2 CODE COMPLIANCE

- A. ALL WORK SHALL MEET ALL STATE AND LOCAL CODES HAVING JURISDICTION.

END OF SECTION 0101

SECTION 0102 - REQUIRED DOCUMENTS

1.1 SHOP DRAWINGS

- A. A SET OF PRINTS FOR ANY MECHANICAL WORK INCLUDING BUT NOT LIMITED TO, DUCTWORK AND PIPING LAYOUT SHALL BE SUBMITTED FOR APPROVAL TO THE ENGINEER PRIOR TO CONSTRUCTION OR PURCHASE OF MATERIALS.

1.2 SUBmittALS

- A. EQUIPMENT SUBmittALS OF ALL PROPOSED MECHANICAL AND ANCILLARY EQUIPMENT INCLUDING ALL ACCESSORIES SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW. ALL PERTINENT MODELS, SIZES, ACCESSORIES AND CHOICES SHALL BE CLEARLY CHECKED, PRINTED OR OTHERWISE INDICATED ON THE SUBmittALS.

1.3 RECORD DRAWINGS

- A. UPON COMPLETION OF THE WORK, A RECORD DRAWING SHALL BE SUBMITTED TO THE OWNER DEPICTING ALL SUBSEQUENT CHANGES, ADDITIONS AND OR CORRECTIONS TO THE CONTRACT DRAWINGS AND OR CONTRACT SCOPE MADE DURING CONSTRUCTION. THIS DRAWING SHALL REPRESENT A COMPLETE RECORD OF THE WORK INSTALLED.

1.4 EQUIPMENT OPERATING INSTRUCTIONS

- A. ON COMPLETION AND ACCEPTANCE OF WORK, THIS CONTRACTOR SHALL FURNISH WRITTEN INSTRUCTIONS, EQUIPMENT MANUALS AND DEMONSTRATE TO THE OWNER THE PROPER OPERATION AND MAINTENANCE OF ALL EQUIPMENT AND APPARATUS FURNISHED UNDER THIS CONTRACT.
- B. THESE INSTRUCTIONS SHALL BE TYPED ON 8-1/2 IN. X 11 IN. PAPER AND BOUND IN THREE-RING BINDERS WITH CLEAR ACETATE COVERS. THE CONTRACTOR SHALL GIVE THREE COPIES OF THE INSTRUCTIONS TO THE OWNER AND ONE ELECTRONIC COPY TO THE ENGINEER.
- C. THE INSTRUCTION BOOKLET SHALL BE ORGANIZED IN SECTIONS, WITH ONE SECTION PER SYSTEM. THE COVER OF THE INSTRUCTION BOOKLET SHALL BEAR THE NAME, ADDRESS AND PHONE NUMBER OF THE PROJECT, ARCHITECT, ENGINEER, MECHANICAL CONTRACTOR AND SUBCONTRACTORS.

END OF SECTION 0102

SECTION 078413 - PENETRATION FIRE-STOPPING

1.1 QUALITY ASSURANCE

- A. INSTALLER QUALIFICATIONS: AN FM GLOBAL-APPROVED FIRE-STOP CONTRACTOR OR A UL-QUALIFIED FIRE-STOP CONTRACTOR.
- B. FIRE-TEST-RESPONSE CHARACTERISTICS: UL, INTERTEK ETL SEMKO OR FM GLOBAL
- C. PENETRATION FIRESTOPPING
- D. PENETRATIONS IN FIRE-RESISTANCE-RATED WALLS: F-RATINGS PER ASTM E 814 OR UL 1479.
- E. PENETRATIONS IN HORIZONTAL ASSEMBLIES: F- AND T-RATINGS PER ASTM E 814 OR UL 1479.
- F. PENETRATIONS IN SMOKE BARRIERS: L-RATINGS PER UL 1479.
- G. W-RATINGS: PER UL 1479.

1.2 INSTALLATION

A. IDENTIFICATION: PREPRINTED METAL OR PLASTIC LABELS.

B. FIELD QUALITY CONTROL

- A. INSPECTION OF INSTALLED FIRE-STOPPING: BY OWNER-ENGAGED AGENCY ACCORDING TO ASTM E 2174.

1.5 THROUGH-PENETRATION FIRESTOP SYSTEM SCHEDULE

WHERE UL-CERTIFIED SYSTEMS ARE INDICATED, THEY REFER TO SYSTEM NUMBERS IN UL'S "FIRE RESISTANCE DIRECTORY" UNDER PRODUCT CATEGORY XHEZ.

FOR THE FOLLOWING SYSTEMS:

METALLIC AND NON-METALLIC PIPES, CONDUIT, OR TUBING, ELECTRICAL CABLES, CABLE TRAYS WITH ELECTRIC CABLES, MISCELLANEOUS ELECTRICAL PENETRANTS, INSULATED PIPES, GROUPINGS OF PENETRANTS, USE ONE OR MORE OF THE FOLLOWING MATERIALS:

- A. LATEX SEALANT
- B. SILICONE SEALANT
- C. INTUMESCENT PUTTY
- D. MORTAR
- E. SILICONE FOAM
- F. PILLOWS/BAGS
- G. INTUMESCENT WRAP STRIPS
- H. INTUMESCENT COMPOSITE SHEET

1.6 MANUFACTURERS

- A. HILTI CONSTRUCTION CHEMICAL, INC
- B. TREMCO INC.
- C. 3M FIRE PROTECTION PRODUCTS

END OF SECTION 078413

SECTION 230593 - TESTING, ADJUSTING, AND BALANCING FOR HVAC

1.1 SUMMARY

- A. TESTING, ADJUSTING, AND BALANCING FOR THE FOLLOWING:
 - 1. MOTORS.
 - 2. CONDENSING UNITS.
 - 3. AIR SYSTEM: CONSTANT VOLUME

1.2 QUALITY ASSURANCE

- A. THE CONTRACTOR SHALL PROCURE THE SERVICES OF A TESTING, ADJUSTING AND BALANCING (TAB) SPECIALIST WHO SPECIALIZES IN HEATING, VENTILATION AND AIR CONDITIONING SYSTEMS. THE TAB AGENT SHALL HAVE THE FOLLOWING QUALIFICATIONS: AABC, NEBB OR TABB CERTIFIED.

1.3 EXECUTION

- A. THE TAB SPECIALIST SHALL PERFORM FLOW MEASUREMENTS OF ALL EXISTING AIR AND HYDROSTATIC SYSTEMS THAT ARE TO REMAIN OR TO BE INCORPORATED INTO NEW WORK PRIOR TO THE STARTING OF WORK IN THE PROJECT SCOPE. A REPORT OF THESE MEASUREMENTS, INDICATING ANY AND ALL DEFICIENCIES SHALL BE SUBMITTED FOR OWNER REVIEW.

- C. THE REPORT SHALL INDICATE A SCHEMATIC DIAGRAM INDICATING LOCATIONS OF ALL EQUIPMENT TESTED AND MEASUREMENT LOCATIONS.

- D. PRIOR TO FINAL INSPECTION OF THE WORK, THE TAB SPECIALIST SHALL BALANCE ALL SYSTEMS AS INDICATED ABOVE TO THE REQUIREMENTS OF THE DESIGN.

- E. THE CONTRACTOR SHALL HAVE FURNISH AND INSTALL ALL ADDITIONAL BALANCING EQUIPMENT, PRESSURE TAPS, GAUGES AND OTHER EQUIPMENT AS REQUIRED FOR A PROPERLY BALANCED SYSTEM AT NO ADDITIONAL COST TO THE OWNER. SUCH ADDITIONAL EQUIPMENT SHALL ADHERE IN STRICT ACCORDANCE WITH THE RESPECTIVE EQUIPMENT MANUFACTURER'S RECOMMENDATIONS.

- F. THE CONTRACTOR SHALL HAVE THE TESTING AND BALANCING SPECIALIST COORDINATE ALL WORK OF THIS SECTION WITH THE BUILDING MANAGER. BALANCING WORK SHALL NOT CONFLICT WITH OTHER WORK SO AS TO MAINTAIN COMPLETION WITHIN THE SPECIFIED TIME.

- G. ALL INSTRUMENTS USED FOR TAB SHALL BE MAINTAINED IN GOOD WORKING CONDITION AND ACCURATELY CALIBRATED.

- H. TOLERANCES: PLUS OR MINUS 5 PERCENT OF DESIGN VALUES.

- I. INSPECTIONS: RANDOM CHECKS BY OWNER OR ARCHITECT TO VERIFY FINAL TESTING, ADJUSTING, AND BALANCING REPORT.

- J. ADDITIONAL TESTS: RANDOM TESTS WITHIN 90 DAYS OF COMPLETING TAB TO VERIFY BALANCE CONDITIONS AND SEASONAL TESTS.

END OF SECTION 230593

END OF SECTION 233713

SECTION 230518 - ESCUTCHEONS FOR HVAC PIPING

PART 1 - PRODUCTS

1.1 ESCUTCHEONS

- A. ONE-PIECE, CAST-BRASS TYPE: WITH POLISHED, CHROME-PLATED AND ROUGH-BRASS FINISH AND SETSCREW FASTENER.
- B. ONE-PIECE, DEEP-PATTERN TYPE: DEEP-DRAWN, BOX-SHAPED BRASS WITH CHROME-PLATED FINISH AND SPRING-CLIP FASTENERS.
- C. ONE-PIECE, STAMPED-STEEL TYPE: WITH CHROME-PLATED FINISH AND SPRING-CLIP FASTENERS.

1.2 FLOOR PLATES

- A. ONE-PIECE FLOOR PLATES: CAST-IRON FLANGE WITH HOLES FOR FASTENERS.

PART 2 - EXECUTION

2.1 INSTALLATION

- A. INSTALL ESCUTCHEONS FOR PIPING PENETRATIONS OF WALLS, CEILINGS, AND FINISHED FLOORS.

- B. INSTALL ESCUTCHEONS WITH ID TO CLOSELY FIT AROUND PIPE, TUBE, AND INSULATION OF PIPING AND WITH OD THAT COMPLETELY COVERS OPENING.

2.2 FIELD QUALITY CONTROL

- A. REPLACE BROKEN AND DAMAGED ESCUTCHEONS AND FLOOR PLATES USING NEW MATERIALS.

END OF SECTION 230518

SECTION 230529 - HANGERS AND SUPPORTS FOR HVAC PIPING AND EQUIPMENT

1.1 PERFORMANCE REQUIREMENTS

- A. DELEGATED DESIGN: DESIGN TRAPEZE PIPE HANGERS AND EQUIPMENT SUPPORTS, INCLUDING COMPREHENSIVE ENGINEERING ANALYSIS BY A QUALIFIED PROFESSIONAL ENGINEER, USING PERFORMANCE REQUIREMENTS AND DESIGN CRITERIA INDICATED.

- B. STRUCTURAL PERFORMANCE: HANGERS AND SUPPORTS FOR HVAC PIPING AND EQUIPMENT SHALL WITHSTAND THE EFFECTS OF GRAVITY LOADS AND STRESSES WITHIN LIMITS AND UNDER CONDITIONS INDICATED ACCORDING TO ASCE/SEI 7.

- 1. DESIGN SUPPORTS FOR MULTIPLE PIPES CAPABLE OF SUPPORTING COMBINED WEIGHT OF SUPPORTED SYSTEMS, SYSTEM CONTENTS, AND TEST WATER.

- 2. DESIGN EQUIPMENT SUPPORTS CAPABLE OF SUPPORTING COMBINED OPERATING WEIGHT OF SUPPORTED EQUIPMENT AND CONNECTED SYSTEMS AND

- 3. DESIGN SEISMIC-RESTRAINT HANGERS AND SUPPORTS FOR PIPING AND EQUIPMENT AND OBTAIN APPROVAL FROM AUTHORITIES HAVING JURISDICTION.

1.2 SUBMITTALS

A. SHOP DRAWINGS: SIGNED AND SEALED BY A PROFESSIONAL ENGINEER

1.3 QUALITY ASSURANCE

A. AWS D1.1/D1.1M, "STRUCTURAL WELDING CODE - STEEL."

1.4 COMPONENTS

A. METAL PIPE HANGERS AND SUPPORTS: CARBON OR STAINLESS STEEL

B. FIBERGLASS PIPE HANGERS: CLEVIS, CENTURY COMPOSITES, COOPER B-LINE

C. METAL FRAMING SYSTEMS: MFMA MANUFACTURER

D. FIBERGLASS STRUT SYSTEMS: COOPER B-LINE

E. THERMAL-HANGER SHIELD INSERTS

F. FASTENER SYSTEMS: POWDER-ACTUATED FASTENERS OR MECHANICAL-EXPANSION ANCHORS

G. PIPE STANDS: COMPACT, LOW TYPE, SINGLE PIPE, HIGH TYPE, SINGLE PIPE, HIGH TYPE, MULTIPLE PIPES, CURB-MOUNTED TYPE

I. EQUIPMENT SUPPORTS

END OF SECTION 230529

SECTION 233713 - DIFFUSERS, REGISTERS, AND GRILLES

1.1 PRODUCTS

- A. DIFFUSERS, REGISTERS AND GRILLES SHALL BE FURNISHED AND INSTALLED FOR CAPACITIES AND IN LOCATIONS INDICATED ON DRAWINGS. ALL REGISTERS AND DIFFUSERS SHALL BE PRIME COATED STEEL OR EXTRUDED ALUMINUM FINISHED UNLESS OTHERWISE NOTED IN BAKED WHITE ENAMEL.

B. MANUFACTURERS: TITUS

- 1. SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCT BY ONE OF THE FOLLOWING:

a. METALAIRE, INC.

b. RUSKIN

- C. ALL DIFFUSERS SHALL HAVE CONTROLLING/EQUALIZING GRID AND OPPOSED BLADE DAMPER UNLESS OTHERWISE NOTED.

- D. ALL DUCTED RETURN REGISTERS SHALL HAVE AN OPPOSED BLADE DAMPER UNLESS OTHERWISE NOTED.

END OF SECTION 230593

END OF SECTION 233713


SECTION 230548 - VIBRATION CONTROLS FOR PIPING AND HVAC EQUIPMENT

PART 1 - GENERAL

1.1 PERFORMANCE REQUIREMENTS

A. SEISMIC-RESTRAINT LOADING:

- 1. SITE CLASS AS DEFINED IN THE IBC: A, B
- 2. ASSIGNED SEISMIC USE GROUP OR BUILDING CATEGORY AS DEFINED IN THE IBC: I, II, III
- a. COMPONENT IMPORTANCE FACTOR: 1.0
- b. COMPONENT RESPONSE MODIFICATION FACTOR: 2.5
- c. COMPONENT AMPLIFICATION FACTOR: 2.5
- 3. DESIGN SPECTRAL RESPONSE ACCELERATION AT SHORT PERIODS (0.2 SECOND): 18%
- 4. DESIGN SPECTRAL RESPONSE ACCELERATION AT 1-SECOND PERIOD: 8%



JOYBIRD

CONSULTANTS
(MEP ENGINEER):
NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

MECHANICAL FLOOR PLAN 1

3/16" = 1'-0"

FIELD VERIFY ALL CONDITIONS	
A. DESIGN DRAWINGS ARE SCHEMATIC AND ARE BASED ON AS-BUILT/RECORD DRAWINGS PROVIDED BY OWNER. THE CONTRACTOR SHALL VISIT PRIOR TO BIDDING OR AWARD OF CONTRACT TO INSPECT EXISTING FIELD CONDITIONS. THIS CONTRACT SHALL INCLUDE ALL LABOR AND MATERIAL NECESSARY FOR FIELD MODIFICATIONS DUE TO EXISTING CONDITION.	

MECHANICAL GENERAL NOTES	
A. REFER TO THE ARCHITECTURAL DRAWING FOR THE EXACT LOCATION AND MOUNTING HEIGHT OF VARIOUS EQUIPMENT. ALL SUCH EQUIPMENT AND EQUIPMENT COLORS AND FINISH SHALL BE COORDINATED WITH THE ARCHITECT. MOUNTING HEIGHT SHALL BE APPROVED BY THE ARCHITECT.	


MECHANICAL FLOOR PLAN KEY NOTES:	
1	EXTEND FULL SIZE SUPPLY & RETURN DUCTWORK FROM EXISTING ROOF TOP UNIT TO SPACE EXTEND AS SHOWN. TRANSITION DUCT AS NECESSARY TO MAKE CONNECTION. ACOUSTICALLY LINE THE FIRST 10'-0" OF BOTH SUPPLY AND RETURN MAIN DUCTS.
2	RELOCATE AND REUSE EXISTING THERMOSTAT. IF EXISTING THERMOSTAT IS NOT IN GOOD CONDITION TO REUSE, THEN INSTALL AND WIRE NEW 7-DAY PROGRAMMABLE THERMOSTAT. COORDINATE EXACT LOCATION WITH ARCHITECT AND OWNER PRIOR TO ROUGH-IN.
3	REUSE EXISTING REMOTE TEMP. SENSOR MOUNTED IN RETURN AIR DUCT/SPACE. PROVIDE NEW IF EXISTING TEMP. SENSORS ARE DAMAGED OR NOT WORKING PROPERLY. CONTRACTOR TO VERIFY IN FIELD PRIOR TO BID.
4	REUSE EXISTING SMOKE DETECTOR. IF EXISTING SMOKE DETECTOR IS NOT IN CONDITION TO REUSE, THEN INSTALL NEW ONE. SMOKE DETECTOR SHALL BE FURNISHED/INSTALLED BY MECHANICAL CONTRACTOR AND WIRED BY ELECTRICAL CONTRACTOR TO SHUT DOWN CORRESPONDING RTU UNDER ALARM CONDITIONS. ALL WIRING SHALL BE IN CONDUIT PER NEC. SMOKE DETECTOR SHALL BE SYSTEM SENSOR MODEL DH100ACDCLP OR EQUAL.
5	8'X8"(E) EXHAUST DUCT UP THRU ROOF TO EF-1(E).
6	EXISTING ELECTRIC UNIT HEATER TO REMAIN & TO BE REUSED. CONTRACTOR TO FIELD VERIFY EXACT LOCATION AND WORKING CONDITION PRIOR TO BID.
7	EXISTING SUPPLY, RETURN & EXHAUST AIR DUCTWORK TO REMAIN & TO BE REUSED. CONTRACTOR SHALL CLEAN AND REFURISH TO "LIKE NEW" CONDITION. CONTRACTOR TO FIELD VERIFY EXACT SIZE AND LOCATION OF EXISTING DUCTWORK. EXTEND/MODIFY DUCTWORK AS/IF REQUIRED. REPLACE WITH SIMILAR KIND IF BEYOND REPAIR/CLEAN. CONTRACTOR TO VERIFY IN FIELD PRIOR TO BID.

△ ISSUANCE NAME DATE
CD SET 07-28-25
1 LL COMMENTS 08-13-25

PROJECT NUMBER: 24-343

MECHANICAL
FLOOR PLAN

M1.01



MECHANICAL ROOF PLAN | 2

3/16" = 1'-0"

MECHANICAL GENERAL NOTES	
A. THE CONTRACTOR SHALL VERIFY EXACT LOCATION OF TRUSSES AND MODIFY DUCTWORK ACCORDINGLY. B. G.C. TO PATCH & REPAIR EXTRA PENETRATION ON ROOF TO MATCH EXISTING IN ALL ASPECTS. C. ALL ITEMS TO BE REUSED OR RELOCATED SHALL BE CLEANED, REPAIRED, AND RESTORED TO LIKE NEW CONDITION PRIOR TO REUSE. D. ALL SOURCE OF MECHANICAL INTAKE SHALL MAINTAIN 10 LINEAR FEET SEPARATION BETWEEN ANY SOURCE OF EXHAUST. CONTRACTOR IS RESPONSIBLE TO ADJUST DUCT LENGTH AS NEEDED. E. EXISTING ROOF CURBS TO BE REUSED WHEREVER POSSIBLE. CONTRACTOR TO FIELD VERIFY THE CONDITION OF EXISTING CURBS. REPLACE EXISTING CURBS IF NOT IN A GOOD CONDITION. F. IF EXISTING ROOF CURBS ARE DAMAGED OR NOT REUSABLE, REPLACE WITH NEW ROOF CURB REQUIRED AND REDO ROOFING. COORDINATE WITH ROOFING CONTRACTOR.	

MECHANICAL FLOOR PLAN KEY NOTES:	
	CONTRACTOR TO FIELD VERIFY THAT THE LOCATION OF ANY EXHAUST SOURCE SHOULD BE AT LEAST 10'-0" AWAY FROM THE OUTSIDE AIR INTAKE OPENING OF RTU.
	EXISTING CONDENSATE DRAIN FROM RTU-1(E) TO REMAIN AS IT IS. CONTRACTOR TO FLUSH THE EXISTING DRAIN LINES. REPLACE AS/IF REQUIRED.
	EXISTING RTU TO REMAIN AS IS AND TO BE REUSED WITH ALL ITS EXISTING ACCESSORIES & ROOF CURB. CONTRACTOR TO FIELD VERIFY EXACT LOCATION AND CONFIGURATION ON SITE. CLEAN AND REFURBISH TO "LIKE NEW" CONDITION. REPAIR / REPLACE ANY ACCESSORIES AS/IF REQUIRED TO PROVIDE A FULLY FUNCTIONING UNIT. INFORM TO ARCHITECT IF ANY ACCESSORIES NOT WORKING OR NOT IN GOOD CONDITION.
	EXISTING ROOF MOUNTED EXHAUST FAN TO REMAIN & TO BE REUSED WITH ALL ITS EXISTING ACCESSORIES AND ROOF CURB. CONTRACTOR TO MAKE SURE THE MAINTAINS A MINIMUM 10'-0" FROM ALL OUTSIDE AIR INTAKES & A MINIMUM 40" ABOVE ROOF. CONTRACTOR TO VERIFY EXACT LOCATION ON SITE. CLEAN AND REFURBISH TO "LIKE NEW" CONDITION. REPAIR / REPLACE ANY ACCESSORIES AS/IF REQUIRED TO PROVIDE A FULLY FUNCTIONING UNIT. INFORM TO ARCHITECT IF ANY ACCESSORIES NOT WORKING OR NOT IN GOOD CONDITION.


ISSUANCE NAME: DATE: 07-28-25
CD SET: 07-28-25
1 LL COMMENTS: 08-13-25

PROJECT NUMBER: 24-343
MECHANICAL
ROOF PLAN

M1.02

CONSULTANTS
(MEP ENGINEER):
NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

JOYBIRD



EXISTING ROOF TOP UNIT (GAS HEAT) SCHEDULE																		
UNIT ID	MANUFACTURER	STATUS	MODEL	AREA SERVED	NOMINAL TONS	SUPPLY FAN		HEATING CAPACITY (MBH)		COOLING CAPACITY		ELECTRICAL DATA				AFUE (%)	SEER/EER	MAX OPERATING WEIGHT (LBS.)
						SUPPLY AIR (CFM)	OUTSIDE AIR (CFM)	MAX. ESP (IN. OF W.G.)	INPUT (MBH)	OUTPUT (MBH)	TOTAL (MBH)	SENSIBLE (MBH)	VOLTS/PH/HZ	MCA (A)	MOCP (A)			
RTU-1(E)	DAIKIN (V.I.F)	EXISTING	S.A.E	SEE PLAN	35 (V.I.F)	10000 (V.I.F)	1920	S.A.E	600 (V.I.F)	S.A.E	S.A.E	S.A.E	480/3/60 (V.I.F)	277 (V.I.F)	300 (V.I.F)	S.A.E	S.A.E	S.A.E
NOTES / ACCESSORIES FOR RTU-1(E):																		
1) S.A.E - SAME AS EXISTING, V.I.F - VERIFY IN FIELD.																		
2) EXISTING RTU WITH ALL ACCESSORIES TO REMAIN SAME AND TO BE REUSED.																		
3) CONTRACTOR TO CONFIRM IF EXISTING RTU IS WORKING AT ITS 100% RATED CAPACITY.																		
4) CONTRACTOR TO FIELD VERIFY EXACT LOCATION AND CONFIGURATION OF RTU ON SITE.																		
5) CONTRACTOR TO RE-BALANCE OUTSIDE AIR & RETURN AIR DAMPERS ON EXISTING RTU TO MATCH VALUES MENTIONED IN ABOVE TABLE.																		
6) REPLACE ALL AIR FILTERS WITH NEW MERV-13 FILTERS BEFORE HANDLING OVER THE SPACE TO THE OWNER / TENANT.																		

EXISTING EXHAUST FAN SCHEDULE												
TAG	QUANTITY	FLOW RATE	STATIC PRESSURE	ELECTRIC DATA			MAXIMUM LOUDNESS	BASIS OF DESIGN			MAX WEIGHT (LBS)	
				EXTERNAL CFM	IN W.G.	SPEED RPM		V/PH/HZ	MCA (A)	MOCP (A)		
EF-1(E)	1	150 (V.I.F)	S.A.E	S.A.E	230/60/1 (V.I.F)	S.A.E	S.A.E	S.A.E	S.A.E	S.A.E	90C15DH (V.I.F)	S.A.E
NOTES:												
1. S.A.E: SAME AS EXISTING, V.I.F: VERIFY IN FIELD.												
2. EXISTING FAN WITH ALL ACCESSORIES TO REMAIN & TO BE REUSED.												
3. CONTRACTOR TO CONFIRM IF EXISTING FAN IS WORKING AT 100% RATED CAPACITY, REPAIR/REPLACE WITH SIMILAR KIND IF NEEDED.												

EXISTING ELECTRIC UNIT HEATER SCHEDULE									
UNIT TAG	LOCATION	QTY	TYPE	ELECTRICAL DATA (HEATING ELEMENT)		MOTOR DATA		MODEL	NOTES
				kW	V/PH/HZ	V/PH/HZ	V/PH/HZ		
EUH-1(E)	SEE PLAN	1	HORIZONTAL DISCHARGE (V.I.F)	3 (V.I.F)	208/1/60 (V.I.F)	208/1/60 (V.I.F)	208/1/60 (V.I.F)	UHEC (V.I.F)	1,2
EUH-2(E)	SEE PLAN	1	CEILING MOUNTED (V.I.F)	5 (V.I.F)	208/1/60 (V.I.F)	277/1/60 (V.I.F)	277/1/60 (V.I.F)	QMARK CDF-557 (V.I.F)	1,2
NOTES:									
1. S.A.E: SAME AS EXISTING, V.I.F: VERIFY IN FIELD.									
2. EXISTING ELECTRIC UNIT HEATERS WITH ALL ACCESSORIES TO REMAIN & TO BE REUSED.									

MECHANICAL AIR TERMINAL DEVICES SCHEDULE								
TAG	DESCRIPTION	MOUNT	SIZE	BASIS OF DESIGN		NOTES		
				MANUFACTURER	MODEL			
SG-1(E)	DOUBLE DEFECTION GRILLE (V.I.F)	SURFACE	S.A.E	S.A.E	300RL (V.I.F)	1		
CDS-1(E)	SQUARE PLAQUE DIFFUSER (V.I.F)	LAY-IN	S.A.E	S.A.E	OMNI (V.I.F)	1		
RG-1(E)	SINGLE DEFLECTION GRILLE (V.I.F)	SURFACE	S.A.E	S.A.E	350RL (V.I.F)	1		
CDE-1(E)	EGGCRATE RETURN (V.I.F)	LAY-IN	S.A.E	S.A.E	50F (V.I.F)	1		
NOTES:								
1. S.A.E: SAME AS EXISTING, V.I.F: VERIFY IN FIELD.								

VENTILATION CALCULATION												
ROOM NAME	AREA (SQ.FT.)	NUMBER OF PEOPLE/1000 SQFT AS PER 2024 OHIO MECHANICAL CODE	NUMBER OF PEOPLE AS PER 2024 OHIO MECHANICAL CODE	FINAL PEOPLE NO.	MIN OUTSIDE AIR AS PER 2024 OHIO MECHANICAL CODE		REQ. OA (CFM)	PROVIDED OA (CFM)	PROVIDED OA (CFM)	EXHAUST AIRFLOW RATE (CFM/SQ.FT OR /FIXT.)	TOTAL EXHAUST (CFM)	PROVIDED EXHAUST (CFM)
					CFM/PEOPLE	CFM/SQ.FT						
101 ENTRY VESTIBULE	135	10	2	3	3	0.06	25	30	0	0	140	150
102 RETAIL AREA	7377	15	111	125	125	0.12	1825	1830	0	0	140	150
103 CIRCULATION	177	0	0	3	3	0.06	15					

ELECTRICAL LEGENDS

NOTES:	
• ALL MOUNTING HEIGHTS GIVEN ARE TO CENTERLINE OF DEVICE UNLESS OTHERWISE NOTED.	
• ALL SYMBOL MAY NOT BE USED.	
SYMBOL	DESCRIPTION
\$ _a	SINGLE POLE TOGGLE SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ ₃	THREE WAY TOGGLE SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ ₄	FOUR WAY TOGGLE SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _K	SINGLE POLE KEYED TOGGLE SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _{3K}	THREE WAY KEYED TOGGLE SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _{4K}	FOUR WAY KEYED TOGGLE SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _{DM}	DIMMER SWITCH WITH MOMENTARY ON/OFF BUTTON - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _M	MOMENTARY ON/OFF SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _{LV}	LOW VOLTAGE ON/OFF SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _{LV}	LOW VOLTAGE ON/OFF/DIMMING SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _{VS}	WALL MOUNTED DUAL TECHNOLOGY VACANCY SENSOR SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
\$ _{SO}	WALL MOUNTED DUAL TECHNOLOGY OCCUPANCY SENSOR SWITCH - MOUNT AT 48" A.F.F. SUB-SMALL LETTER INDICATED SWITCH LEG.
ST	TERMAL OVERLOAD SWITCH - MOUNT AT FRACTIONAL HP MOTOR
_a	CEILING MOUNTED OCCUPANCY SENSOR - DUAL TECHNOLOGY SUB-SMALL LETTER INDICATED SWITCH LEG.
_a	CEILING MOUNTED VACANCY SENSOR - DUAL TECHNOLOGY SUB-SMALL LETTER INDICATED SWITCH LEG.
PC	PHOTOCELL
□□	INVERTER WITH INTEGRAL BACK-UP BATTERY
□□	POWER PACK. SUB-SMALL LETTER INDICATED SWITCH LEG.
□□	GROUNDED DUPLEX RECEPTACLE (NEMA5-20R) - MOUNT AT 15" A.F.F. U.N.O.
□□A	GROUNDED DUPLEX RECEPTACLE (NEMA5-20R) - MOUNT ABOVE COUNTER BACKSPLASH OR 42" A.F.F.
□□C	GROUNDED DUPLEX RECEPTACLE (NEMA5-20R) - MOUNT AT CEILING
□□GFI	GROUNDED DUPLEX RECEPTACLE (NEMA5-20R) - GFI TYPE - MOUNT AT 18" A.F.F. U.N.O.
□□WP	GROUNDED DUPLEX GFI RECEPTACLE (NEMA5-20R) W/ "WEATHERPROOF WHILE IN USE" COVER
□□	GROUNDED DUPLEX RECEPTACLE (NEMA5-20R) WITH TOP RECEPTACLE CONTROLLER BY SWITCH/SENSOR AND BOTTOM RECEPTACLE SHALL NOT BE CONTROLLED BY SWITCH/SENSOR. CONTROLLER RECEPTACLE SHALL BE PERMANENTLY MARKED AS PER NEC 406.3 (E) AND PROVIDED IN GREEN COLOR.
□□U	GROUNDED DUPLEX RECEPTACLE WITH INTEGRAL USB-A & USB-C CHARGING PORTS (EQUAL TO HUBBELL #USB20AC5) - MOUNT AT 15" A.F.F. U.N.O.
□□C1	CEILING MOUNTED RECEPTICAL (20A)
□□	GROUNDED DOUBLE DUPLEX RECEPTACLE (NEMA5-20R) - MOUNT AT 15" A.F.F. U.N.O.
□□	GROUNDED DOUBLE DUPLEX RECEPTACLE (NEMA5-20R) WITH TOP RECEPTACLE CONTROLLER BY SWITCH/SENSOR AND BOTTOM RECEPTACLE SHALL NOT BE CONTROLLED BY SWITCH/SENSOR. CONTROLLER RECEPTACLE SHALL BE PERMANENTLY MARKED AS PER NEC 406.3 (E) AND PROVIDED IN GREEN COLOR.
X	DATA OUTLET W/ JACKS, BACK BOX, 1" CONDUIT TILL CEILING SPACE WITH PULL STRING, ONE 90° ELBOW AND PLASTIC BUSHING AT BOTH ENDS AND CAT6 PLUMED RATED CABLES TO IT RACK - MOUNT AT 15" A.F.F. U.N.O.
D-xx	1: ONE DATA. 2: TWO DATA. 3: THREE DATA. 4: FOUR DATA. "D-xx" INDICATE OUTLET ID
▼	TELEPHONE OUTLET
▼	DATA OUTLET
■■	FLUSH MOUNTED FLOOR BOX WITH RECEPTACLE/DATA DEVICES AS LISTED ABOVE
□	JUNCTION BOX
□	MOTORIZED DAMPER
○	MOTOR
□□	EMERGENCY SWITCH - MOUNT AT 48" A.F.F. M - MASTER, S = SLAVE
□□	NON-FUSED SAFETY DISCONNECT SWITCH - MOUNT TOP AT 75" A.F.F. U.N.O.
□□	FUSED SAFETY DISCONNECT SWITCH - MOUNT TOP AT 75" A.F.F. U.N.O.
□□	PUSH BUTTON
□□	BUZZER SYSTEM
□□	STEP DOWN TRANSFORMER
■■■	SURFACE MOUNTED ELECTRIC PANEL - REFER TO PANEL SCHEDULES & POWER RISER DIAGRAM FOR VOLTAGE, RATING AND FEEDER SIZE.
■■■■	RECESSED MOUNTED ELECTRIC PANEL - REFER TO PANEL SCHEDULES & POWER RISER DIAGRAM FOR VOLTAGE, RATING AND FEEDER SIZE.
■■■■■	TRANSFORMER
□□	LIGHTING CONTROL RELAY PANEL
□□	TIMECLOCK
□□	CEILING MOUNTED SPEAKER. PROVIDE JUNCTION BOX AND 1" CONDUIT TILL CEILING SPACE WITH PULL STRING, ONE 90° ELBOW AND PLASTIC BUSHING AT BOTH ENDS. COORDINATE WIRING'S REQUIREMENT WITH SOUND SYSTEM'S VENDOR.
□□	WALL MOUNTED SPEAKER. PROVIDE JUNCTION BOX AND 1" CONDUIT TILL CEILING SPACE WITH PULL STRING, ONE 90° ELBOW AND PLASTIC BUSHING AT BOTH ENDS. COORDINATE WIRING'S REQUIREMENT WITH SOUND SYSTEM'S VENDOR.
□□	VOLUME CONTROL. PROVIDE JUNCTION BOX AND 1" CONDUIT WITH PULL STRING TO A/V RACK. COORDINATE WIRING'S REQUIREMENT WITH SOUND SYSTEM'S VENDOR.
□□	BRANCH CIRCUIT WIRING
□□	BRANCH CIRCUIT FEEDER
□□	UNSWITCHED BRANCH CIRCUIT WIRING
□□	ELECTRICAL GROUND
APPLICABLE CODES	
A	2023 NATIONAL ELECTRICAL CODE, NFPA 70
B	2021 INTERNATIONAL ENERGY CONSERVATION CODE

ABBREVIATION	
SYMBOL	DESCRIPTION
A	AMPERE
A.F.F.	ABOVE FINISH FLOOR
APS	AUXILIARY POWER SUPPLY
C	CONDUIT
CKT	CIRCUIT
CU	CONDENSING UNIT
DE	DEMOLITION
DF	DESTRATIFICATION FAN
DWCP	DOMESTIC WATER CIRCULATING PUMP
E.C.	ELECTRICAL CONTRACTOR
EF	EXHAUST FAN
EM	ITEM PROVIDED WITH OR CONNECTED TO EMERGENCY POWER
EMT	ELECTRICAL METAL TUBING
ER	EXISTING TO REMAIN
ETP	ELECTRONIC TRAP PRIMER
ETR	EXISTING TO REMAIN
EV	EVAPORATOR UNIT
EWC	ELECTRIC WATER COOLER
EWH	ELECTRIC WATER HEATER
EX	EXISTING TO REMAIN
FACP	FIRE ALARM CONTROL PANEL
FATC	FIRE ALARM TERMINAL CABINET
G.C.	GENERAL CONTRACTOR
GFI	GROUND FAULT INTERRUPTER
HT	HEAT TRACE
HVAC	HEATING VENTILATION AIR CONDITIONING
IG	ISOLATED GROUND
J	JUNCTION BOX
KEF	KITCHEN EXHAUST FAN
LCP	LIGHTING CONTROL PANEL
LTG	LIGHTING
LV	LOW VOLTAGE
MCB	MAIN CIRCUIT BREAKER
MD	MOTORIZED DAMPER
MDP	MAIN DISTRIBUTION PANEL
MH	MOUNTING HEIGHT
MLO	MAIN LUGS ONLY
N	NEW
NL	NIGHT LIGHT
P	POLE
PE	PRIMARY ELECTRIC SERVICE
PP	POWER PANEL
PVC	POLYVINYL CHLORIDE CONDUIT
RE	RELOCATE
RGS	RIGID GALVANIZED STEEL CONDUIT
RTU	ROOF TOP UNIT
SF	SAFETY SWITCH
SW	SWITCHBOARD
T.B.D.	TO BE DETERMINED
TR	TAMPER RESISTANT
TV	TELEVISION
TX	TRANSFORMER
U.N.O.	UNLESS NOTED OTHERWISE
WH	WATER HEATER
WP	WEATHER PROOF
ZD	ZONE DAMPER

ELECTRICAL GENERAL NOTES	
1. ALL WORK SHALL BE PERFORMED IN COMPLIANCE WITH CURRENT APPLICABLE CODES, ORDINANCES, THE REGULATORY AGENCIES HAVING JURISDICTION AND THE SPECIFICATIONS. THE SPECIFICATIONS MAY EXCEED THE REQUIREMENTS OF THE CODE, THE MOST STRINGENT CONDITION WILL APPLY.	45. ALL WIRING SHALL BE IN CONDUIT, UNLESS OTHERWISE INDICATED. CONDUITS SHALL BE RUN CONCEALED IN NEW AND ABOVE CEILINGS.
2. THE INTENT OF THESE DOCUMENTS IS FOR THE MEP TRADES TO FURNISH AND INSTALL COMPLETE MECHANICAL AND ELECTRICAL SYSTEMS. THE SPECIFIED ELECTRICAL SYSTEM SHALL BE COMPLETE IN ALL RESPECTS; OPERATIONAL, TESTED, ADJUSTED, APPROVED BY THE AUTHORITIES HAVING JURISDICTION AND READY FOR BENEFICIAL USE BY THE OWNER.	46. ALL EXPOSED WIRING IN CEILING OR INTERIOR WALLS MUST BE IN EMT.
3. THE TRADES SHALL OBTAIN AND REVIEW ALL CONTRACT DOCUMENTS BEFORE SUBMITTING A BID. INFORMATION IS PROVIDED ON THE VARIOUS DRAWINGS, SCHEDULES, SPECIFICATIONS AND ALL OF THE VARIOUS DOCUMENTS IN THE BIDDING PACKAGE. THE CONTRACT DOCUMENTS ARE COMPLEMENTARY AND FORM A TOTAL PROJECT DESIGN AND INFORMATION SOURCE FOR CONSTRUCTION PURPOSES.	47. METAL CLAD CABLE "MC" MAY BE USED ABOVE ACCESSIBLE CEILINGS AND IN DRYWALL. FOR RECEPTACLES AND LIGHTING FIXTURES ONLY, MC CABLE IS LIMITED TO BRANCH CIRCUITS NOT EXCEEDING 30AMP. HOME RUN FROM FIRST RECEPTACLE/LIGHT FIXTURE TO PANEL BOARD SHALL BE IN CONDUIT.
4. THE DRAWINGS ARE DIAGRAMMATIC AND INDICATE THE GENERAL ARRANGEMENT OF SYSTEMS AND WORK INCLUDED IN THE CONTRACT, COORDINATE LOCATIONS OF EQUIPMENT WITH OTHER TRADES BEFORE AND DURING CONSTRUCTION. ANY MODIFICATION TO THE EQUIPMENT LAYOUT, REQUIRED FOR INSTALLATION, IS TO BE PERFORMED UNDER THE CONTRACT AGREEMENT, AT NO ADDITIONAL COST. REFER TO DETAILS, SCHEDULES AND SPECIFICATIONS FOR ADDITIONAL INFORMATION.	48. ALL HOME RUNS FROM FIRST RECEPTACLE/LIGHT FIXTURE/KITCHEN EQUIPMENT/HVAC EQUIPMENT...ETC TO PANEL BOARD SHALL BE IN CONDUIT.
5. THE CONTRACTOR SHALL BECOME THOROUGHLY FAMILIAR WITH THE PROJECT DOCUMENTS OF ALL TRADES. THE DRAWINGS ARE DIAGRAMMATIC AND SHOW THE GENERAL ARRANGEMENT OF EQUIPMENT AND CONDUITS. THE CONTRACTOR SHALL COORDINATE THE EXACT LOCATION OF EQUIPMENT AND CONDUITS, INSTALLATION WITH ALL THE TRADES BEFORE COMMENCING WORK.	49. NO "MC" CABLE IS ALLOWED IN DEMISING WALLS.
6. EQUIPMENT SHALL BE INSTALLED IN ACCESSIBLE LOCATIONS. WHEN EQUIPMENT MUST BE LOCATED ABOVE AN INACCESSIBLE CEILING (GYP BOARD OR EQUIVALENT), OR BEHIND A WALL, AN APPROPRIATE ACCESS DOOR SHALL BE PROVIDED. IF AN ACCESS DOOR IS REQUIRED, IT SHALL BE OF A RATING APPROPRIATE FOR THE WALL/CEILING IN WHICH IT IS TO BE INSTALLED. THE CONTRACTOR SHALL COORDINATE LOCATIONS OF ACCESS PANELS FOR ALL DEVICES, REQUIRING ACCESS, WITH THE ARCHITECT, PRIOR TO INSTALLATION OF SUCH DEVICES OR OTHER APPURTENANCES.	50. CABLES TYPES NM, NMC, NMS AND ROMEX IS NOT PERMITTED.
7. WHERE A CONFLICT OCCURS BETWEEN THE DOCUMENTS, IT SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT. CARRY AS PART OF THE BID THE LARGER QUANTITY AND/OR MORE EXPENSIVE ITEMS.	51. FLEXIBLE CONDUIT MAY BE USED ONLY FOR FINAL CONNECTIONS FROM OUTLET/JUNCTION BOXES TO LIGHT FIXTURES, MOTORS, APPLIANCES, ETC. LENGTH OF FLEXIBLE CONDUITS SHALL NOT EXCEED 6'.
8. THIS CONTRACT SHALL INCLUDE ALL THE NECESSARY CONDUITS, FITTINGS, TRANSITIONS ETC. AS REQUIRED TO INSTALL CONDUITS AND EQUIPMENT, AND TO AVOID ANY CONFLICTS WITH OTHER TRADES AND THE BUILDING STRUCTURE. THE CONTRACTOR SHALL BE HELD RESPONSIBLE FOR ANY ASSUMPTIONS, OMISSIONS OR ERRORS HE MAKES AS A RESULT OF HIS FAILURE TO COORDINATE WITH OTHER TRADES OR BECOME FULLY FAMILIAR WITH THE PROJECT DOCUMENTS OF ALL TRADES.	52. ALL EXPOSED CABLES OF ANY TYPE IN PLENUM CEILING SPACE SHALL BE PLENUM RATED.
9. DO NOT INSTALL ANY ELECTRICAL PANELS, TRANSFORMERS, SPECIAL EQUIPMENT, BELOW PIPING OR THROUGH MECHANICAL ROOMS, THAT ARE NOT ASSOCIATED WITH OR SERVE THE RESPECTIVE ROOMS. COORDINATE THE LOCATION OF MECHANICAL EQUIPMENT IN THE FIELD AND ADJUST AS NECESSARY.	53. NO MORE THAN FOUR (4) 90 DEGREE BENDS IN ONE RUN FOR ELECTRICAL POWER SYSTEM.
10. CONTRACTOR TO FOLLOW EXISTING BASE BUILDING PHASING COLOR CODE. IF BASE BUILDING PHASING COLOR CODE IS UNKNOWN, FOLLOW COLOR CODE AS MENTIONED IN SPECIFICATION.	54. ALL EMPTY CONDUITS SHALL HAVE A FULL STRING WITH A MINIMUM 10' OF SLACK ON BOTH END.
11. FIELD VERIFY WITH MANUFACTURER'S PROVIDED EXACT ELECTRICAL CHARACTERISTICS AND CONNECTION REQUIREMENTS OF ALL OPERATIONAL EQUIPMENT PRIOR TO MAKING ELECTRICAL POWER CONNECTION. FURNISH AND INSTALL SAFETY DISCONNECT AS REQUIRED BY NEC.	55. CONTRACTOR TO INSTALL EXPOSED CONDUIT IN NEAT AND ORGANIZED WAY IN STRAIGHT LINES AND PARALLEL OR IN RIGHT ANGLES TO THE BUILDING STRUCTURE. DO NOT LOOP EXCESS FLEXIBLE CONDUIT IN CEILING SPACE OR WALL CAVITY.
12. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE OWNER, ALL LOCATIONS OF EQUIPMENT BEING FURNISHED BY THE OWNER PRIOR TO ROUGHING OR INSTALLING OUTLETS.	56. CONTRACTOR TO PROVIDE RIGHT ANGLES TURNS USING FITTINGS OR SYMMETRICAL BENDS.
13. REFER TO ARCHITECTURAL DRAWINGS FOR ELEVATIONS AND EXACT LOCATION OF DEVICES PRIOR TO ROUGHING OR INSTALLATION OF OUTLETS.	57. CONTRACTOR TO PAINT ALL EXPOSED CONDUITS.
14. REFER TO ARCHITECT'S REFLECTED CEILING PLAN FOR EXACT LOCATIONS OF CEILING MOUNTED DEVICES.	58. NO CONDUIT TO BE SUPPORTED FROM THE DECK.
15. CONTRACTOR SHALL PROVIDE ALL NECESSARY MISCELLANEOUS STEEL FOR THE SUPPORT OF ALL EQUIPMENT, PIPING, CONDUIT AND DUCTWORK SUSPENDED FROM SLAB, STEEL, WALL OR TRUSSWORK.	59. CONTRACTOR TO RUN CONDUITS ABOVE SUSPENDED CEILING AND UP-HIGH AS POSSIBLE IN AREAS WITH NO SUSPENDED CEILING.
16. ELECTRICAL CONTRACTOR SHALL SEAL ALL CONDUITS PENETRATING EXTERIOR WALLS WITH FIRE STOPPING MATERIAL.	60. CONDUITS INSTALLED ON ROOF SHALL HAVE A MINIMUM DISTANCE OF 7/8" BETWEEN BOTTOM OF CONDUIT AND TOP OF ROOF.
17. ALL PENETRATIONS OF FLOORS AND WALLS (WHETHER OR NOT FIRE RESISTANCE RATED) SHALL BE PROVIDED WITH A THROUGH PENETRATION PROTECTION SYSTEM (FIRESTOPPING), EACH THROUGH - PENETRATION PROTECTION SYSTEM SHALL BE TESTED IN ACCORDANCE WITH ASTM E814 AND BE LISTED FOR THE TYPE OF FLOOR OR WALL ASSEMBLY PENETRATED AND THE TYPE OF PROTECTION SYSTEM.	61. OTHERWISE CONTRACTOR TO USE "XHHW-2" INSULATED CONDUCTOR AS PER NFPA 310.15(B)(3)(c)."
18. IT IS NOT THE INTENTION TO SHOW EVERY FITTING, HANGER, WIRE OR DEVICE, ALL SUCH ITEMS SHALL BE FURNISHED AND INSTALLED AS NECESSARY FOR A COMPLETE SYSTEM.	62. NO MORE THAN THREE (3) CURRENT CARRYING CONDUCTORS TO BE INSTALLED IN ONE CONDUIT. IF MORE THAN THREE (3) CURRENT CARRYING CONDUCTORS INSTALLED IN ONE CONDUIT, CONTRACTOR TO ADJUST THE SIZE WIRING AS PER TABLE 310.15(B)(3)(c), NEC 2017.
19. SEE SPECIFICATION SECTION "ELECTRICAL IDENTIFICATION" FOR PROPERLY LABELING EQUIPMENT WIRING, PANELS, SWITCHBOARD, DISCONNECT SWITCHES, BOXES, CONDUITS, ETC.	63. ALL EQUIPMENT, DEVICES AND FIXTURES SHALL BE GROUNDED IN COMPLIANCE WITH NEC & UL REQUIREMENT.
20. CONTRACTOR SHALL DETERMINE THE QUANTITY OF CONDUCTORS REQUIRED FOR PROPER OPERATION OF ALL SWITCHING SCHEMES.	64. VERIFY EXACT LOCATION AND ELECTRICAL REQUIREMENT OF ALL HVAC EQUIPMENT WITH MECHANICAL DRAWINGS PRIOR TO ANY WORK AND MODIFICATIONS AS NEEDED.
21. SEISMICALLY SUPPORT THE EQUIPMENT AS REQUIRED BY CODE, THE AUTHORITY HAVING JURISDICTION, AND/OR AS SPECIFIED. SUBMIT ENGINEERED INSTALLATION DETAILS PER THE SPECIFICATIONS. THE CONTRACTOR'S SEISMIC ENGINEER SHALL REVIEW THE INSTALLATION AND PROVIDE A DETAILED REPORT FOR THE RECORD.	65. VERIFY EXACT LOCATION AND ELECTRICAL REQUIREMENT OF ELECTRIC WATER HEATER WITH PLUMBING DRAWINGS PRIOR TO ANY WORK AND MODIFICATIONS AS NEEDED.
22. PROVIDE ALL BONDING AND GROUNDED REQUIRED BY THE NATIONAL ELECTRIC CODE, NFPA 70 AND AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.	66. COORDINATE ALL FLOOR CUT MEANS (TRENCHING/CORING) OF EXISTING FLOOR SLAB WITH LANDLORD PRIOR TO ANY WORK.
23. ALL REQUIRED BONDING CONDUCTORS SHALL BE MINIMUM #8 SOLID INSULATED COPPER, PROVIDE ALL NECESSARY FITTINGS, JUNCTION BOXES, END FITTINGS, ETC, FOR A COMPLETE, CONTINUOUS INSTALLATIONS.	67. FLOOR OUTLETS SHALL BE FED FROM THE NEAREST AVAILABLE FULL HEIGHT WALL. CONTRACTOR TO COORDINATE CONDUIT ROUTING AND TRENCHING OF EXISTING FLOOR SLAB WITH LANDLORD AND EXISTING CONDITION IN THE FIELD PRIOR TO ANY WORK. SEAL ALL PENETRATION WITH FIRE STOPPING MATERIAL AS NEEDED.
24. ALL BONDING/GROUNDING CONNECTIONS SHALL BE MADE BY LISTED CLAMP OR CONNECTORS AS REQUIRED BY ARTICLE 250 OF NFPA 70, THE NATIONAL ELECTRIC CODE (CURRENT ADOTTED EDITION).	68. NOTHING SHALL BE ATTACHED TO, SUSPENDED FROM, OR PENETRATE LANDLORD'S STRUCTURE, FLOOR, DECK OR ROOF. TENANT'S TENANT'S CONTRACTOR MAY ATTACH NON-DESTRUCTIVELY, TO OR SUSPEND FROM THE TOP CHORD OF THE JOIST OR THE STRUCTURE STEEL WHICH EXISTS ABOVE TENANT'S SPACE, WHEN ATTACHING TO LANDLORD'S STRUCTURE, DO NOT DRILL, WELD, SCREW OR SHOT BLAST INTO STRUCTURE. ALTERNATIVE METHODS OF ATTACHMENT ONLY, NOTHING TO DAMAGE LANDLORD'S BASE BUILDING STRUCTURE. TENANT'S CONTRACTOR SHALL PROVIDE SIGNED AND SEALED STRUCTURAL DRAWINGS BY A STRUCTURAL ENGINEER WITH LEGALLY ACTIVE REGISTRATION AS INDICATED BY ALL JURISDICTIONAL REQUIREMENTS, FOR ALL ELECTRICAL INSTALLATION AND ALL STRUCTURE MODIFICATIONS FOR LANDLORD RECORDS.
25. AN INSULATED (GREEN) EQUIPMENT GROUND WIRES SHALL BE PROVIDED WITH ALL FEEDERS AND BRANCH CIRCUITS.	69. SLAB ON GRADE:
26. AN EXTRA SEPARATE ISOLATED GROUND CONDUCTOR SHALL BE PROVIDED FOR EACH ISOLATED GROUND RECEPTACLE IN ADDITION TO THE REGULAR GROUND CONDUCTOR. THIS EXTRA SEPARATE ISOLATED GROUND CONDUCTOR SHALL BE TERMINATED AT THE GROUND BAR OF THE MAIN PANEL BOARD AND IS NOT ALLOWED TO GROUND RACEWAYS, BOXES, ETC.	70. TENANT'S GENERAL CONTRACTOR SHALL ADVISE THE OPERATION TEAM PRIOR TO ANY SLAB MODIFICATION OR REMOVAL. IF ANY ELEVATED SLAB IS TO BE MODIFIED IN ANYWAY (DRILLED, CORED OR PENETRATED), TENANT'S GENERAL CONTRACTOR SHALL PROVIDE STABILIZED AND CENTERED DRAWINGS. LISTED FIRESTOPPING MATERIALS AND METHODS OF PENETRATION SHALL BE USED. PENETRATIONS SHALL BE SEALED, FIRE STOPPED AND WATERPROOFED. THE PENETRATION SLEEVE SHALL EXTEND A MINIMUM OF 4" ON EITHER SIDE OF THE SLAB AND BE LABELED WITH THE REQUIRED NFPA RATING. TENANT'S GENERAL CONTRACTOR SHALL VERIFY THAT WORK SHALL NOT CONFLICT WITH ANY EXISTING STRUCTURE, UTILITY OR OTHER UNDER-SLAB CONDITION. NON-DESTRUCTIVE VERIFICATION MAY BE REQUIRED. ANY DAMAGE OR DOWNTIME CAUSED BY TENANT'S GENERAL CONTRACTOR WORK SHALL BE REPAIRED AND REIMBURSED AT TENANT'S GENERAL CONTRACTOR EXPENSES.
27	

GENERAL

1. REQUIREMENTS SPECIFIED ON COVER SHEET, ALONG WITH ELECTRICAL SPECIFICATIONS AND ALL ITS SECTIONS, COMPRIZE THE CONTRACT DOCUMENTS FOR THE ELECTRICAL CONTRACT. DRAWINGS AND ALL THEIR REVISIONS UP TO THE BID SUBMISSION DATE BECOME A PART OF THE CONTRACT, ALONG WITH THESE SPECIFICATIONS. THIS CONTRACTOR SHALL, AND AGREES, THAT BY THE SPECIFICATIONS SHALL BE INTERPRETED AS ALSO IMPLIED BY THE DRAWINGS AND SPECIFICATIONS, PROVIDED NECESSARY ITEMS FOR A COMPLETE INSTALLATION OF ALL ELECTRICALLY OPERATED EQUIPMENT LISTED IN THE SPECIFICATIONS OR SHOWN ON THE CONTRACT DRAWINGS.
2. THE ARCHITECTURAL, STRUCTURAL, MECHANICAL, PLUMBING AND EQUIPMENT DRAWINGS AND SPECIFICATIONS ARE INCORPORATED INTO, AND BECOME A PART OF, THIS DRAWING. THIS CONTRACTOR SHALL EXAMINE ALL SUCH DRAWINGS AND SPECIFICATIONS AND BECOME THOROUGHLY FAMILIAR WITH THE PROVISIONS CONTAINED THEREIN. THE SUBMISSION OF HIS BID SHALL INDICATE SUCH KNOWLEDGE.
3. ELECTRICAL DRAWINGS ARE DIAGRAMMATIC. THEY ARE INTENDED TO SHOW THE APPROXIMATE LOCATIONS OF EQUIPMENT AND CONDUIT DIMENSIONS GIVEN ON THE PLANS. IN FIGURES, SHALL TAKE PRIORITY OVER SCALED DIMENSIONS AND SHOULD BE READ IN CONJUNCTION WITH THE CONTRACT DRAWINGS. ALL EQUIPMENT ROOMS TO MAKE SURE THE EQUIPMENT, AS PURCHASED, FITS IN THE ROOM OR SPACE SHOWN. EXACT LOCATION OF ALL EQUIPMENT SHALL BE VERIFIED IN THE FIELD AND ROUTINE CONDUITS SHALL SUIT FIELD CONDITIONS.
4. UNTIL THE TIME OF INSTALLATION, THE ARCHITECT RESERVES THE RIGHT TO MAKE MINOR CHANGES IN THE LOCATION OF CONDUIT AND EQUIPMENT WITHOUT ADDITIONAL CHARGE TO THE CONTRACTOR.
5. THE ELECTRICAL DRAWINGS AND SPECIFICATIONS ARE INTENDED TO SUPPLEMENT EACH OTHER. MATERIAL AND LABOR NECESSARY TO THE PROJECT SHALL BE FURNISHED AND INSTALLED EVEN THOUGH NOT SPECIFICALLY MENTIONED IN BOTH. LABOR AND/OR MATERIALS NEITHER SHOWN NOR SPECIFIED, BUT OBVIOUSLY NECESSARY FOR THE COMPLETION AND PROPER FUNCTIONING OF THE SYSTEM, SHALL BE FURNISHED AND INSTALLED BY THE ELECTRICAL CONTRACTOR AT NO ADDITIONAL COST.
6. ARRANGE ALL EQUIPMENT SUBSTANTIALLY AS SHOWN ON THE DRAWINGS, MAKE DEVIATIONS ONLY WHERE NECESSARY TO AVOID INTERFERENCE. CHECK ALL EQUIPMENT SIZES AGAINST AVAILABLE SPACE PRIOR TO SHIPMENT TO AVOID INTERFERENCE.
7. EXAMINE THE WORK OF OTHER TRADES INSOFAR AS THEIR WORK COMES IN CONTACT WITH OR IS COVERED BY THIS WORK. IN NO CASE ATTACH TO, OR FINISH AGAINST ANY DEFECTIVE WORK OR INSTALL WORK IN A MANNER WHICH WILL PREVENT PROPER INSTALLATION OF THE WORK OF OTHER TRADES.
8. ELECTRICAL CONTRACTOR SHALL VERTIFY WITH OTHER TRADES ALL ELECTRICAL DRAWINGS AND SPECIFICATIONS. ALL EQUIPMENT CONNECTIONS CONTRACTOR SHALL VERIFY VOLTAGE, PHASE AND HORSEPOWER AND SHALL NOTIFY ENGINEER OF ANY DISCREPANCIES PRIOR TO START OF WORK. ELECTRICAL CONTRACTOR SHALL PROVIDE DISCONNECTING MEANS AND OVERLOAD PROTECTION FOR ALL EQUIPMENT, UNLESS FURNISHED INTEGRAL WITH EQUIPMENT PACKAGE.
9. IT IS THE INTENT OF THESE DRAWINGS THAT THIS BE A COMPLETE ELECTRICAL JOB. ANY ERRORS OR OMISSIONS SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO BIDDING THE JOB.

VISIT TO THE SITE

1. THE CONTRACTOR SHALL VISIT THE SITE OF THE WORK AND FAMILIARIZE HIMSELF WITH ALL CONDITIONS AFFECTING HIS WORK. THE SUBMISSION OF HIS PROPOSAL SHALL INDICATE SUCH KNOWLEDGE. NO ADDITIONAL PAYMENT SHALL BE MADE ON CLAIMS THAT ARISE FROM A LACK OF KNOWLEDGE OF THE EXISTING CONDITIONS.
- CODE AND PERMITS
1. INSTALLATION SHALL BE IN FULL ACCORDANCE WITH ALL CODES, RULES AND REGULATIONS OF MUNICIPAL, CITY, COUNTY, STATE AND PUBLIC UTILITIES AND ALL OTHER AUTHORITIES HAVING JURISDICTION OVER THE PREMISES.
2. COMPLY WITH ANY SPECIFIC REQUIREMENTS THAT ARE IN EXCESS BUT NOT IN CONFLICT WITH CODE REQUIREMENTS.
3. THE CONTRACTOR SHALL SECURE AND PAY FOR ALL PERMITS, PLAN REVIEWS AND CERTIFICATES OF INSPECTION IN CONNECTION WITH HIS WORK, REQUIRED BY THE FOREGOING AUTHORITIES. BEFORE PAYMENT OF THE CONTRACT IS ALLOWED, ALL CERTIFICATES SHALL BE DELIVERED TO THE ARCHITECT IN DUPLICATE.
4. ELECTRICAL MATERIAL AND EQUIPMENT SHALL BEAR THE UL LABEL EXCEPT WHERE UL DOES NOT LABEL SUCH TYPES OF MATERIAL AND EQUIPMENT.

SHOP DRAWINGS SUBMITTALS

1. THE ELECTRICAL CONTRACTOR SHALL SUBMIT FIVE (5) SETS OF SHOP DRAWINGS. THE SHOP DRAWINGS OF THE FOLLOWING EQUIPMENT USING THE INDICATED NUMBERING SYSTEM AND TITLES, SHALL BE SUBMITTED THROUGH THE ARCHITECT TO THE ENGINEER AND THEN RESUBMITTED FOR FINAL APPROVAL, IF NECESSARY. SHOP DRAWINGS SHALL BE SUBMITTED FOR THE FOLLOWING ITEMS:
 - A. WIRING DEVICES
 - B. FUSES AND SAFETY SWITCHES INCLUDING FAULT CURRENT STUDY BASED ON EQUIPMENT BEING SUPPLIED.
 - C. CONTACTORS, TIME SWITCHES AND PHOTOCELL
 - D. LIGHTING FIXTURES
 - E. SUPERVISORY ALARM SYSTEM
2. ALL SUBMITTED SHOP DRAWINGS (MANUFACTURERS "EQUIPMENT DESCRIPTIVE SHEETS OR VENDORS" PREPARED DRAWINGS) SHALL HAVE THE GENERAL CONTRACTOR'S OR SUBCONTRACTOR'S "STAMP OF APPROVAL" INDICATING THAT THE ITEM SUBMITTED IS AS CALLED FOR ON THE PLANS AND SPECIFICATIONS, IS APPROVED FOR USE IN THE PROJECT AND IS IN CONFORMITY WITH THE DATE OF APPROVAL AND INITIALED BY THE PERSON APPROVING THE SUBMITTAL AND THE NAME OF THE COMPANY SUBMITTING SAID EQUIPMENT FOR APPROVAL.
3. SUBMIT BOUND BROCHURES COMPLETE WITH A TABLE OF CONTENTS. LOOSE OR STAPLED TOGETHER SHEETS ARE NOT ACCEPTABLE. ANY SUBMITTALS NOT IN BROCHURE FORM OR NOT AS SPECIFIED SHALL BE RETURNED AT THE CONTRACTOR'S EXPENSE FOR RESUBMITTAL.
4. ALL DESCRIPTIVE LITERATURE SHALL BE SUBMITTED IN A THREE (3) HOLE BROCHURE WITH A COVER IDENTIFYING THE FOLLOWING:
 - A. NAME OF THE JOB.
 - B. LOCATION OF THE JOB, ADDRESS, CITY AND STATE.
 - C. NAME AND ADDRESS OF THE COMPANY SUBMITTING THE BROCHURES.
 - D. DATE OF THE SUBMITTAL.
5. EVERY EFFORT SHALL BE MADE, IN CHECKING THE SHOP DRAWINGS, TO DETECT AND CORRECT ALL ERRORS, OMISSIONS AND INACCURACIES. FAILURE TO DO THIS WILL NOT RELIEVE THE ELECTRICAL CONTRACTOR OF THE RESPONSIBILITY FOR THE PROPER AND COMPLETE INSTALLATION IN ACCORDANCE WITH THE CONTRACT.

RECORD DRAWINGS

1. SUBMIT TO THE ARCHITECT ONE SET OF REPRODUCIBLE (MYLARS) ELECTRICAL DRAWINGS SHOWING THE RECORD CONDITIONS.

STANDARDS AND SUBSTITUTIONS

1. WHEREVER THE WORDS "APPROVED BY", "APPROVED EQUAL", "AS DIRECTED" OR SIMILAR PHRASES ARE USED IN THE FOLLOWING SPECIFICATIONS, THEY SHALL BE UNDERSTOOD TO REFER TO THE OWNER AS THE APPROVING AGENCY. THE NAME OF THE APPROVING ENGINEER OR MANUFACTURER OF THE EQUIPMENT (WHETHER OR NOT THE WORDS "APPROVED EQUAL" ARE USED) SHALL BE KNOWN AS THE "STANDARD".

GENERAL NOTES

1. E.C TO MAKE A FIELD SURVEY OF THE EXISTING ELECTRICAL SERVICE TO ENSURE THAT THE TOTAL CONNECTED LOAD DOES NOT EXCEED THE ELECTRICAL SERVICE. ANY ADDITIONAL EQUIPMENT OR EQUIPMENT NOT LISTED ON THE CONTRACT DRAWINGS, WILL BE COMPLETED BY TENANT'S TENANT'S GC, AT TENANT'S SOLE EXPENSE.
2. EMT (ELECTRIC METALLIC TUBING) SHALL BE USED IN ALL DEMISING WALLS, HOME RUNS, AND BETWEEN J-BOXES AND PULL BOXES. MC CABLE MAY BE USED IN OTHER APPLICATION AS ALLOWED BY THE AUTHORITY HAVING JURISDICTION (A.H.J.). ALL EXPOSED CONDUIT, RIGID OR MC CABLE, SHALL BE INSTALLED IN TIGHT, STRAIGHT LINES, PARALLEL OR IN RIGHT ANGLES TO THE BUILDING STRUCTURE. DO NOT LOOP EXCESS MC CABLE IN CEILING SPACE OR WALL CAVITY.
3. 7 DAY, 24 HOUR TIME CLOCK IS REQUIRED TO CONTROL STOREFRONT ENTRY LIGHTS, SHOW WINDOW LIGHTS, AND OTHER RECEPTACLES. STAFFING SIGNAGE, ILLUMINATED STOREFRONT SIGNS MUST REMAIN LIT DURING THE MALL BUSINESS HOURS.
4. ALL PENETRATIONS SHALL BE CORE BORED ONLY, SAW CUTTING, JACK HAMMERING, AND TRENCHING IS STRICTLY PROHIBITED. ALL PENETRATIONS SHALL BE SLEVED, SEALED, FIRE STOPPED, AND WATERPROOFED. THE PENETRATION SLEEVE SHALL EXTEND A MINIMUM OF 4' ON EITHER SIDE OF THE SLAB AND BE LABELED WITH THE REQUIRED NFPA.
5. EC SHALL VERIFY THAT WORK SHALL NOT CONFLICT WITH ANY EXISTING STRUCTURAL, UTILITY, OR OTHER UNDER-SLAB CONDITION. (NONDESTRUCTIVE VERIFICATION MAYBE REQUIRED) ANY DAMAGE OR DOWNTIME CAUSED BY TENANT'S WORK SHALL BE REPAIRED AND REIMBURSED AT TENANT'S EXPENSE.
6. EC TO USE OF ENERGY STAR PRODUCTS AND/OR EQUIPMENT WHENEVER POSSIBLE DURING TENANT BUILD OUT, WHICH CAN REDUCE ENERGY CONSUMPTION.

MATERIALS AND WORKMANSHIP

1. THESE SPECIFICATIONS ESTABLISH QUALITY STANDARD OF MATERIALS AND EQUIPMENT TO BE PROVIDED. SPECIFIC ITEMS ARE IDENTIFIED BY MANUFACTURER, TRADES, OR CONTRACTOR. THIS CONTRACTOR SHALL SUBMIT HIS BASE BID PRICED UPON STANDARD SECURED EQUIPMENT DESCRIBED HEREIN AND AS DETAILED ON DRAWINGS AND ASSOCIATED CONTRACT.
2. THESE SPECIFICATIONS ARE NOT THE CONTRACT, AND ANYTHING NOT BY THE SPECIFICATIONS SHALL BE INTERPRETED AS ALSO IMPLIED BY THE DRAWINGS AND SPECIFICATIONS. PROVIDE NECESSARY ITEMS FOR A COMPLETE INSTALLATION OF ALL ELECTRICALLY OPERATED EQUIPMENT LISTED IN THE SPECIFICATIONS OR SHOWN ON THE CONTRACT DRAWINGS.
3. ELECTRICAL DRAWINGS ARE DIAGRAMMATIC. THEY ARE INTENDED TO SHOW THE APPROXIMATE LOCATIONS OF EQUIPMENT AND CONDUIT DIMENSIONS GIVEN ON THE PLANS. IN FIGURES, SHALL TAKE PRIORITY OVER SCALED DIMENSIONS AND SHOULD BE READ IN CONJUNCTION WITH THE CONTRACT DRAWINGS. ALL EQUIPMENT ROOMS TO MAKE SURE THE EQUIPMENT, AS PURCHASED, FITS IN THE ROOM OR SPACE SHOWN. EXACT LOCATION OF ALL EQUIPMENT SHALL BE VERIFIED IN THE FIELD AND ROUTINE CONDUITS SHALL SUIT FIELD CONDITIONS.
4. UNTIL THE TIME OF INSTALLATION, THE ARCHITECT RESERVES THE RIGHT TO MAKE MINOR CHANGES IN THE LOCATION OF CONDUIT AND EQUIPMENT WITHOUT ADDITIONAL CHARGE TO THE CONTRACTOR.
5. THE ELECTRICAL DRAWINGS AND SPECIFICATIONS ARE INTENDED TO SUPPLEMENT EACH OTHER. MATERIAL AND LABOR NECESSARY TO THE PROJECT SHALL BE FURNISHED AND INSTALLED EVEN THOUGH NOT SPECIFICALLY MENTIONED IN BOTH. LABOR AND/OR MATERIALS NEITHER SHOWN NOR SPECIFIED, BUT OBVIOUSLY NECESSARY FOR THE COMPLETION AND PROPER FUNCTIONING OF THE SYSTEM, SHALL BE FURNISHED AND INSTALLED BY THE ELECTRICAL CONTRACTOR AT NO ADDITIONAL COST.
6. ARRANGE ALL EQUIPMENT SUBSTANTIALLY AS SHOWN ON THE DRAWINGS, MAKE DEVIATIONS ONLY WHERE NECESSARY TO AVOID INTERFERENCE. CHECK ALL EQUIPMENT SIZES AGAINST AVAILABLE SPACE PRIOR TO SHIPMENT TO AVOID INTERFERENCE.
7. EXAMINE THE WORK OF OTHER TRADES INSOFAR AS THEIR WORK COMES IN CONTACT WITH OR IS COVERED BY THIS WORK. IN NO CASE ATTACH TO, OR FINISH AGAINST ANY DEFECTIVE WORK OR INSTALL WORK IN A MANNER WHICH WILL PREVENT PROPER INSTALLATION OF THE WORK OF OTHER TRADES.
8. ELECTRICAL CONTRACTOR SHALL VERTIFY WITH OTHER TRADES ALL ELECTRICAL DRAWINGS AND SPECIFICATIONS. ALL EQUIPMENT CONNECTIONS CONTRACTOR SHALL VERIFY VOLTAGE, PHASE AND HORSEPOWER AND SHALL NOTIFY ENGINEER OF ANY DISCREPANCIES PRIOR TO START OF WORK. ELECTRICAL CONTRACTOR SHALL PROVIDE DISCONNECTING MEANS AND OVERLOAD PROTECTION FOR ALL EQUIPMENT, UNLESS FURNISHED INTEGRAL WITH EQUIPMENT PACKAGE.
9. IT IS THE INTENT OF THESE DRAWINGS THAT THIS BE A COMPLETE ELECTRICAL JOB. ANY ERRORS OR OMISSIONS SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO BIDDING THE JOB.

SCOPE OF WORK

1. THE ELECTRICAL CONTRACTOR SHALL PROVIDE ALL LABOR, MATERIAL, STORAGE, UNPACKING AND PLACEMENT; TO INCLUDE BUT NOT BE LIMITED TO, THE FOLLOWING ITEMS:
 - A. COMPLETE POWER AND LIGHTING DISTRIBUTION SYSTEM.
 - B. COMPLETE BRANCH CIRCUIT WIRING SYSTEM.
 - C. COMPLETE AIR CONDITIONING, REFRIGERATION, AND VENTILATION EQUIPMENT.
 - D. LIGHTING FIXTURE INSTALLATION.
 - E. COMPLETE TELEPHONE AND COMMUNICATION CONDUIT SYSTEM INCLUDING PULL BOXES, OUTLET BOXES AND CONDUIT AS SPECIFIED, SHOWN ON THE DRAWINGS AND REQUIRED BY THE LOCAL TELEPHONE COMPANY AND/OR OWNER. FROM EACH OUTLET PROVIDE A 1' EMPTY EMT CONDUIT ROUTED INTO THE CEILING CAPABLE TO THE OUTLET. THIS CONDUIT IS TO BE LOCATED IN A CLOSET. PROVIDE A DIA LINE IN EACH RUN AND TERMINATE IN A BUSBAR ELBOW.
 - F. TEMPORARY ELECTRICAL POWER AND LIGHTING AS REQUIRED FOR CONSTRUCTION.
 - G. TESTING OF ALL CABLES AND CIRCUIT WIRING AFTER INSTALLATION.
 - H. EXIT LIGHT SYSTEM.
 - I. WIRING DEVICES.
 - J. LIGHTING CONTROLS.
 - K. GROUNDING OF THE ELECTRICAL SYSTEM.
 - L. IDENTIFY RACEWAYS AND CABLES WITH COLOR BANDING AS FOLLOWS:
2. COLORS:
 - A. FIRE ALARM SYSTEM: RED
 - B. SECURITY SYSTEM: BLUE AND YELLOW
 - C. TELECOMMUNICATION SYSTEM: GREEN AND YELLOW

GROUNDING AND BONDING

1. GROUND ALL EQUIPMENT PER N.E.C.
2. ALL CONDUITS SHALL CONTAIN A CODE-SIZED GROUND WIRE SIZED PER NEC IN ADDITION TO THE CONDUCTORS SHOWN ON THE PLANS. WHERE CIRCUIT CONDUCTORS ARE INCREASED IN SIZE FOR VOLTAGE DROP, THE GROUND WIRE SIZE SHALL BE INCREASED PROPORTIONATELY.
3. AFTER INSTALLING GROUNDING SYSTEM BUT BEFORE PERMANENT ELECTRICAL CIRCUITY HAS BEEN TESTED, TEST FOR COMPLIANCE WITH REQUIREMENTS.

WIRE AND CABLE

1. COLOR CODE CONDUCTORS (EXCEPT CONTROL AND INSTRUMENTATION CONDUCTORS) AS FOLLOWS:
 - A. PHASE A BLACK;
 - B. PHASE B RED;
 - C. PHASE C BLUE;
 - D. NEUTRAL WHITE;
 - E. GROUND GREEN.
2. #12 AND #10 CONDUCTORS SHALL HAVE CONTINUOUS INSULATION COLOR, AS LISTED ABOVE.
3. COLOR CODE CONDUCTORS LARGER THAN ABOVE, WHICH DO NOT HAVE CONTINUOUS INSULATION COLOR BY APPLICATION OF AT LEAST TWO LAPS OF COLORED TAPE ON EACH CONDUCTOR AT ALL POINTS OF ACCESS INDICATED ON THE DRAWINGS. COLOR TAPE SHALL BE EQUAL OF 3M PRODUC. SCOTCH #35.
4. CONDUCTORS SHALL BE SOFT ANNEALED COPPER INSULATED FOR 400 VOLTS UNLESS SPECIFICALLY INDICATED OTHERWISE. ALUMINUM AND IRON/ROMEX CONDUCTORS ARE NOT ALLOWED ON THIS PROJECT.

NAMEPLATES

1. FURNISH AND MOUNT ON EACH PANELBOARD, SWITCHBOARD (INCLUDING BRANCH SWITCHES), LARGE JUNCTION BOX, SAFETY SWITCH, STARTER, REMOTE CONTROL, PUSH BUTTON STATION, AND ALL SIMILAR CONTROLS, A NAMEPLATE DESCRIPTIVE OF THE EQUIPMENT OR EQUIPMENT CONTROLLED.
2. PROVIDE BLACK AND WHITE NAMEPLATES CONSTRUCTED FROM LAMINATED PHENOLIC WITH A WHITE CENTER CORE. LETTERS SHALL BE ENGRAVED IN THE PHENOLIC TO FORM WHITE LETTERS 3/8" HIGH. FASTEN THE NAMEPLATES WITH SCREWS AND AN ADHESIVE TYPE FASTENER.

MOUNTING ACCESSORIES

1. THIS CONTRACTOR SHALL FURNISH AND INSTALL ALL ANGLE IRON, CHANNEL IRON, RODS, SUPPORTS, HANGERS, CONCRETE OR PLYWOOD REQUIRED TO INSTALL, MOUNT AND SUPPORT ELECTRICAL EQUIPMENT OR DEVICE CALLER FOR ON THE PLANS.
2. SUPPORTING MATERIAL SHALL BE COMPLETE WITH HANGERS, CONNECTORS, BOLT CLOMPS AND NECESSARY ACCESSORIES TO MAKE A COMPLETE INSTALLATION. SUPPORTING MATERIAL SHALL BE GALVANIZED, PAINTED OR OTHERWISE SUITABLY FINISHED PRODUCTS BY BRINKLEY, STEEL CITY OR RACO WILL BE ACCEPTABLE.
3. ALL SURFACE-MOUNTED EQUIPMENT ON BLOCK WALLS SHALL BE MOUNTED ON 3/4" PLYWOOD BACKBOARD. ALL FLOOR-MOUNTED EQUIPMENT SHALL BE INSTALLED ON A 4" HIGH CONCRETE HOUSEKEEPING PAD.

EXECUTION

1. THE ELECTRICAL WORK FOR CONSTRUCTION PROPOSED SHALL CONFORM TO ALL FEDERAL (OSHA) STATE, ALL SPECIFIC SAFETY REQUIREMENTS AND THE REQUIREMENTS OF THE CURRENT EDITION OF THE NEC.
2. CHECK THE HVAC AND PLUMBING SPECIFICATIONS FOR ELECTRICAL REQUIREMENTS AND INCLUDE THE SAME IN THE CONTRACT COST.
3. EQUIPMENT CONNECTIONS, STARTERS, DISCONNECT SWITCHES, CONTROL TRANSFORMERS AND PUSHBUTTON STATION FOR THE EQUIPMENT FURNISHED BY THE OWNER OR UNDER A SEPARATE CONTRACT SHALL BE INSTALLED AND CONNECTED UNDER THIS DRAWING AS INDICATED ON THE CONTRACT DRAWINGS.
4. ALL CONDUIT, PIPING, EXHAUST, BATH, AND CONCRETE CONSTRUCTION RELATED TO THE CONTRACTOR'S WORK WILL BE THE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR. THIS CONTRACTOR SHALL ASSUME THE RESPONSIBILITY OF PROVIDING THE SLEEVES, CHASES AND OPENINGS NECESSARY FOR THE ELECTRICAL INSTALLATION AND FOR THEIR REPAIR IN AN ACCEPTABLE MANNER, AS DETERMINED BY THE ARCHITECT. ALL HOLES SHALL BE CORE DRILLED. PROVIDE FIRE STOP IN ALL OPENINGS CREATED THROUGH FIRE-RATED WALLS, FLOORS OR CEILINGS.
5. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ALL REQUIRED ACCESS PANELS NECESSARY FOR HIS WORK, COORDINATE WITH ARCHITECT PRIOR TO INSTALLATION.

RACEWAYS

1. ALL WIRE SHALL BE RUN IN ACCORDANCE WITH CODE IN CORROSION RESISTANT, RIGID, THREADED, METAL CONDUIT OR ELECTRICAL METALLIC TUBING (E.M.T.) UNLESS OTHERWISE SPECIFICALLY STATED HEREIN.
2. ALL MATERIALS SHALL BE NEW AND FREE FROM DEFECTS AND SHALL BE THE BEST OF THEIR SEVERAL KINDS UNLESS SPECIFIED OR INDICATED ON THE DRAWINGS TO THE CONTRARY.
3. DURING EACH PHASE AND AT THE COMPLETION OF THE CONSTRUCTION, THIS CONTRACTOR SHALL REMOVE ALL DEBRIS AND EXCESS MATERIALS CAUSED BY HIS WORK. HE SHALL LEAVE THE AREA OF OPERATION BROOM CLEAN.
4. ALL ELECTRICAL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OR ETY LABEL.
5. THIS CONTRACTOR SHALL GUARANTEE HIS WORKMANSHIP AND MATERIAL, LAMPS EXCEPT FOR A PERIOD OF ONE YEAR FROM THE DATE OF BUILDING OPENING AND LEAVE HIS WORK IN PERFECT ORDER AT THE COMPLETION. SHOULD DEFECTS DEVELOP WITHIN THE GUARANTEE PERIOD, THE CONTRACTOR SHALL, UPON NOTICE OF THE SAME, REMEDY THE DEFECTS AND HAVE ALL DAMAGES TO OTHER WORK OR FURNISHINGS CAUSED BY THE REPAIRS CORRECTED AT HIS EXPENSE TO THE CONDITION BEFORE SUCH DAMAGE.

OUTLETS

1. THE CONTRACTOR SHALL PROVIDE ALL OUTLET PLATES FOR OUTLET BOXES AS FOLLOWS:
 - A. FINISHED AREAS: STAINLESS STEEL.
 - B. UNFINISHED AREAS: ZINC COATED SHEET METAL, ALUMINUM, OR CAST METAL, AS APPROPRIATE FOR THE TYPE OF BOX.
 - C. EXTERIOR AREAS: COATED STEEL WITH GRAY, POWDER EPOXY, PRIMER OR OTHER WEATHERPROOF. TELEPHONE, COMMUNICATION AND SIGNAL OUTLET PLATES, SHALL MATCH THOSE USED FOR RECEPTACLES AND SWITCHES. ALL OUTLET AND/JUNCTION BOXES SHALL BE COMPLETE WITH A COVER PLATE BY THIS CONTRACTOR.

2. WHERE DEVICES ARE GANGED, THEY SHALL BE INSTALLED UNDER A COMMON COVER PLATE.

3. LOCATE OUTLETS APPROXIMATELY 4'-0" ABOVE THE FINISHED FLOOR ELEVATION OR NEAREST BLOCK COURSE (WITHIN A.D.A. REQUIREMENTS), UNLESS OTHERWISE INDICATED. THE LONG DIMENSION OF THE SWITCHES SHALL BE VERTICAL.

4. LOCATE RECEPTACLES APPROXIMATELY 1'-6" ABOVE THE FINISHED FLOOR ELEVATION OR NEAREST BLOCK COURSE (WITHIN A.D.A. REQUIREMENTS), UNLESS NOTED OTHERWISE. THE LONG DIMENSION OF RECEPTACLES SHALL BE VERTICAL.

5. SAFETY SWITCHES SHALL BE THE ENCLOSED HEAVY-DUTY TYPE (TYPE HD) WITH QUICK-MAKE, QUICK-BREAK MECHANISM AND EXTERNAL PAD LOCKABLE OPERATING HANDLE.

6. SAFETY SWITCHES SHALL BE RATED FOR 240 OR 400 VOLTS AS APPLICABLE. THEY SHALL BE HORSEPOWER RATED WHEN USED IN MOTOR CIRCUITS.

7. SAFETY SWITCHES SHALL BE FUSIBLE OR NON-FUSIBLE, 2, 3, OR 4 POLE AS INDICATED ON THE DRAWINGS.

8. SAFETY SWITCHES SHALL BE SINGLE THROW UNLESS OTHERWISE INDICATED ON THE DRAWINGS.

9. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

10. MANUFACTURER SHALL BE SQUARE D, SIEMENS, OR CUTLER-HAMMER. ALL SAFETY SWITCHES SHALL BE BY ONE MANUFACTURER.

11. MOUNTING CASE CIRCUIT BREAKERS SHALL BE AS SCHEDULED ON THE DRAWINGS AND AS INDICATED ON THE DRAWINGS.

12. MOUNTING CASE CIRCUIT BREAKERS SHALL BE AS SCHEDULED ON THE DRAWINGS AND AS INDICATED ON THE DRAWINGS.

13. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

14. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

15. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

16. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

17. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.


18. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

19. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

20. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

21. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.

22. ENCLOSURES SHALL BE NEMA 1 INDOORS AND NEMA 3R OUTDOORS UNLESS OTHERWISE INDICATED ON DRAWINGS.



JOYBIRD

CONSULTANTS
(MEP ENGINEER):
NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

ELECTRICAL LIGHTING PLAN

3/16" = 1'-0"

ELECTRICAL LIGHTING PLAN GENERAL NOTES:	
A.	THE TIME CLOCK (MIN. 2 CHANNEL) SHALL BE SET AS PER THE REQUIREMENT OF THE PROJECT SPACE.
B.	E.C. TO VERIFY THAT ALL EXISTING EMERGENCY LIGHT & EXIT SIGNS HAVE BEEN PROVIDED IN ACCORDANCE WITH THE APPLICABLE ENERGY CODE. REPLACE IF EXISTING IS FOUND INOPERABLE, PROVIDE NEW IF REQUIRED.
C.	E.C. TO FIELD VERIFY THE OPERABLE CONDITION OF ALL EXISTING LIGHTING FIXTURE. RELAMP OR REWIRE AS REQUIRED.
D.	ALL THE EMERGENCY LIGHTS, EXIT SIGNS AND NIGHT LAMPS SHALL BE CONNECTED TO THE NEAREST LIGHTING CIRCUIT AHEAD OF SWITCHING FOR CONTINUOUS OPERATIONS.
E.	E.C. TO FIELD VERIFY WHETHER EXISTING HALF-SHADED LIGHT FIXTURES ARE EQUIPPED WITH EMERGENCY BATTERY BACKUP. IF NOT, PROVIDE CODE-COMPLIANT EMERGENCY LIGHTING BY ALTERNATE MEANS.
F.	THE MANUAL OVERRIDE SWITCH SHALL TURN OFF THE INTENDED LIGHTING (TIME CLOCK AND CONTACTORS) BEFORE 2 HOURS. WHEN IT IS INITIATED, COORDINATE EXACT LOCATION IN THE FIELD.
G.	LIGHT FIXTURES MARKED "E" AND "ETR" (EXISTING TO BE RELOCATED) ARE EXISTING TO REMAIN. FIELD VERIFY OPERATIONAL CONDITION; PROVIDE NEW FIXTURES IF FOUND INOPERABLE. FIELD VERIFY AVAILABILITY OF BATTERY BACKUP WHERE APPLICABLE AND PROVIDE AS REQUIRED TO MEET CODE COMPLIANCE.
H.	E.C. TO VERIFY AND ENSURE COMPLIANCE WITH CODE-REQUIRED EMERGENCY ILLUMINANCE LEVELS. E.C. SHALL REARRANGE (IF REQUIRED) THE EMERGENCY FIXTURES AND BATTERY BACKED FIXTURES TO PROVIDE INITIAL ILLUMINATION THAT IS NOT LESS THAN AN AVERAGE OF 1 FOOTCANDLE (111 LUX) AND A MINIMUM AT ANY POINT OF 0.1 FOOTCANDLE (1 LUX) MEASURED ALONG THE PATH OF EGRESS AT FLOOR LEVEL. ILLUMINATION LEVELS SHALL BE PERMITTED TO DECLINE TO 0.4 FOOTCANDLE (6 LUX) AVERAGE AND A MINIMUM AT ANY POINT OF 0.06 FOOTCANDLE (0.6 LUX) AT THE END OF THE EMERGENCY LIGHTING TIME DURATION. A MAXIMUM-TO-MINIMUM ILLUMINATION UNIFORMITY RATIO OF 40 TO 1 SHALL NOT BE EXCEEDED.
ELECTRICAL LIGHTING PLAN KEY NOTES: #	
1.	E.C. TO COORDINATE THE EXACT LOCATION OF THE TIMECLOCK(TC) AND LIGHTING CONTACTOR(LC) WITH THE ARCHITECT. REUSE EXISTING TIMECLOCK IF AVAILABLE AFTER FIELD VERIFYING THE OPERABLE CONDITION.
2.	SWITCH BANK FOR LIGHTING CONTROL. COORDINATE EXACT LOCATION WITH ARCHITECT/OWNER. COORDINATE FOR THE EXACT NUMBER OF SWITCHES WITH THE ARCHITECT/OWNER/LIGHTING VENDOR.
3.	PROVIDE TWO (2) 10A CURRENT LIMITERS PER TWO-CIRCUIT TRACK, INSTALLED ON EACH HOT CONDUCTOR AND CLEARLY LABELED. EACH TRACK SHALL HAVE TWO (2) SEPARATE CIRCUITS, EACH CONTROLLED BY ITS OWN SWITCH OR DIMMER TO ALLOW MINIMUM 50% SEPARATE CONTROL PER IEC REQUIREMENTS. FIELD VERIFY THE NUMBER OF SWITCHES OR DIMMERS REQUIRED BASED ON FINAL LOAD DISTRIBUTION AND CONTROL ZONING. COORDINATE WITH LIGHTING VENDOR FOR WIRING, CURRENT LIMITER COMPATIBILITY, AND SWITCHING REQUIREMENTS.
4.	CONNECT THE SIGNAGE TO THE EXISTING/SPECIFIED SIGNAGE CIRCUIT THROUGH THE TIMER CONTROLLED LIGHTING CONTACTOR (LC). COORDINATE WITH THE OWNER OR LANDLORD TO DETERMINE THE EXACT LOCATION AND SCHEDULE FOR THE TIME CLOCK. COORDINATE POWER REQUIREMENTS WITH THE SIGN VENDOR.
5.	E.C. TO ENSURE THAT THE PHOTOCELL IS CONCEALED FROM PUBLIC VIEW.
6.	JUNCTION BOX FOR INTERIOR SIGNAGE, CONTROL VIA TIMECLOCK. E.C. TO FIELD VERIFY THE EXACT LOCATION WITH THE ARCHITECT AND SIGNAGE VENDOR.
7.	COORDINATE WITH LIGHTING VENDOR TO PROVIDE EMERGENCY BATTERY BACKUP POWER TO DESIGNATED TRACK HEADS TO SERVE AS EMERGENCY LIGHTING. EMERGENCY HEADS SHALL BE CLEARLY IDENTIFIED AND CIRCUITED TO ENSURE OPERATION IN COMPLIANCE WITH CODE-REQUIRED EMERGENCY ILLUMINANCE LEVELS.


TYPE	DESCRIPTION	QTY	LUMINAIRE SPECIFICATION	INPUT WATTS	DIMMING LOAD TYPE	LUMINAIRE NOTES
EL-03A	EXISTING TRACK HEAD	303	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-03B	EXISTING LIGHT TRACK	40	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-04	EXISTING LIGHT PENDANT	2	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-01	RELOCATED EXISTING 4" LED TROFFER LIGHT	2	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE/RELOCATE AS NEEDED.
LT-02	4" DIA. RECESSED ADJUSTABLE DOWNLIGHT	6	LUCIER LIGHTING: FAR-FAS-1-PR-PR-7C12A-30-85	14W	0-10V	FLANGE AND BAFFLE TO MATCH CEILING FINISH
LT-03A	BLACK LED TRACK HEAD	121	JUNO LIGHTING: R610-30K-90CRI-P	21W	WLV,MLV	ORDER ACCESSORIES AS NEEDED - QUANTITY OF TRACK HEADS MAY INCREASE PER OWNER'S REQUIREMENTS FOR DISPLAY LIGHTING
LT-03B	BLACK TWO-CIRCUIT TRACK	1	-	-	-	JUNO LIGHTING: TEK-[LENGTH]-BL, ORDER LENGTH ACCESSORIES AS NEEDED
LT-04	LINEAR LED WALL SCONCE	9	TECH LIGHTING KLE 30 WALL: BLACK FINISH	14W	0-10V	FLANGE AND BAFFLE TO MATCH CEILING FINISH
LT-07	INDOOR LED STRIP	2	CORE ARCHITECTURAL LIGHTING: L5M55-30K-[LENGTH], (PROFILE: ALU-CN); (TRANSFORMER: PSDL-192W-24V)	5.5W/FT	0-10V	INSTALL AT FABRIC DISPLAY MILLWORK - ORDER LENGTHS AS NEEDED
LT-08	LOW VOLTAGE LED TAPELIGHT IN CHANNEL	1	OCL LIGHTING: WP1-P1AA-18-FR-BKP-LED2-30K-UNV	25W	0-10V	ORDER ACCESSORIES AS NEEDED
EL-05	EXISTING TOFFER LIGHT	3	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-06	EXISTING DOWNLIGHT	3	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-07	EXISTING EXTERIOR WALL SCONCE	2	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-08	EXISTING EXTERIOR WALL SCONCE WITH BATTERY BACKUP	1	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EX	WALL MOUNTED EXIT SIGNAGE	PER PLAN	TBD	TBD		

LIGHTING FIXTURE GENERAL NOTES:	
A.	VERIFY ALL LUMINAIRE COLORS, TRIMS, LENGTHS, ETC. WITH THE ARCHITECT PRIOR TO PLACING FINAL PURCHASE ORDERS. SUBMISSION OF SHOP DRAWINGS WILL BE INTERPRETED AS HAVING BEEN COORDINATED WITH THE ARCHITECTURAL DRAWINGS.
B.	PROVIDE ALL LENGTHS, FEEDS, ACCESSORIES, CONNECTORS, WIRING, POWER SUPPLIES, DRIVERS ETC. FOR A COMPLETE INSTALLATION. THE E.C. SHALL VERIFY THE COMPLETE BILL OF MATERIAL WITH MANUFACTURER'S REPRESENTATIVE AND ENSURE ALL EQUIPMENT ARE INCLUDED IN BID PRICE. COORDINATE INSTALLATION WITH ARCHITECTURAL DETAILS.
C.	ALL FIXTURES INDICATED AS EMERGENCY SHALL BE PROVIDED WITH 90-MINUTE BATTERY PACK AND ALL FLORENT FIXTURES INDICATED AS EMERGENCY SHALL BE PROVIDED WITH 1300LUMENS, 90MINUTE BATTERY PACK.

△ ISSUANCE NAME DATE
CD SET 07-28-25
1 LL COMMENTS 08-13-25

PROJECT NUMBER: 24-343
ELECTRICAL
LIGHTING PLAN

E1.01



ELECTRICAL EMERGENCY LIGHTING PLAN | 1

3/16" = 1'-0"

ELECTRICAL LIGHTING PLAN GENERAL NOTES:						
A. THE TIME CLOCK (MIN. 2 CHANNEL) SHALL BE SET AS PER THE REQUIREMENT OF THE PROJECT SPACE.						
B. E.C. TO VERIFY THAT ALL EXISTING EMERGENCY LIGHT & EXIT SIGNS HAVE BEEN PROVIDED IN ACCORDANCE WITH THE APPLICABLE ENERGY CODE. REPLACE IF EXISTING IS FOUND INOPERABLE, PROVIDE NEW IF REQUIRED.						
C. E.C. TO FIELD VERIFY THE OPERABLE CONDITION OF ALL EXISTING LIGHTING FIXTURE. RELAMP OR REWIRE AS REQUIRED.						
D. ALL THE EMERGENCY LIGHTS, EXIT SIGNS AND NIGHT LAMPS SHALL BE CONNECTED TO THE NEAREST LIGHTING CIRCUIT AHEAD OF SWITCHING FOR CONTINUOUS OPERATIONS.						
E. E.C. TO FIELD VERIFY WHETHER EXISTING HALF-SHADED LIGHT FIXTURES ARE EQUIPPED WITH EMERGENCY BATTERY BACKUP. IF NOT, PROVIDE CODE-COMPLIANT EMERGENCY LIGHTING BY ALTERNATE MEANS.						
F. THE MANUAL OVERRIDE SWITCH SHALL TURN OFF THE INTENDED LIGHTING (TIME CLOCK AND CONTACTORS) BEFORE 2 HOURS. WHEN IT IS INITIATED, COORDINATE EXACT LOCATION IN THE FIELD.						
G. LIGHT FIXTURES MARKED "E" AND "ETR" (EXISTING TO BE RELOCATED) ARE EXISTING TO REMAIN. FIELD VERIFY OPERATIONAL CONDITION; PROVIDE NEW FIXTURES IF FOUND INOPERABLE. FIELD VERIFY AVAILABILITY OF BATTERY BACKUP WHERE APPLICABLE AND PROVIDE AS REQUIRED TO MEET CODE COMPLIANCE.						
H. E.C. TO VERIFY AND ENSURE COMPLIANCE WITH CODE-REQUIRED EMERGENCY ILLUMINANCE LEVELS. E.C. SHALL REARRANGE (IF REQUIRED) THE EMERGENCY FIXTURES AND BATTERY BACKED FIXTURES TO PROVIDE INITIAL ILLUMINATION THAT IS NOT LESS THAN AN AVERAGE OF 1 FOOTCANDLE (111 LUX) AND A MINIMUM AT ANY POINT OF 0.1 FOOTCANDLE (1 LUX) MEASURED ALONG THE PATH OF EGRESS AT FLOOR LEVEL. ILLUMINATION LEVELS SHALL BE PERMITTED TO DECLINE TO 0.4 FOOTCANDLE (6 LUX) AVERAGE AND A MINIMUM AT ANY POINT OF 0.06 FOOTCANDLE (0.6 LUX) AT THE END OF THE EMERGENCY LIGHTING TIME DURATION. A MAXIMUM-TO-MINIMUM ILLUMINATION UNIFORMITY RATIO OF 40 TO 1 SHALL NOT BE EXCEEDED.						
ELECTRICAL LIGHTING PLAN KEY NOTES: #						
1. E.C. TO COORDINATE THE EXACT LOCATION OF THE TIMECLOCK(TC) AND LIGHTING CONTACTOR(LC) WITH THE ARCHITECT. REUSE EXISTING TIMECLOCK IF AVAILABLE AFTER FIELD VERIFYING THE OPERABLE CONDITION.						
2. SWITCH BANK FOR LIGHTING CONTROL. COORDINATE EXACT LOCATION WITH ARCHITECT/OWNER. COORDINATE FOR THE EXACT NUMBER OF SWITCHES WITH THE ARCHITECT/OWNER/LIGHTING VENDOR.						
3. PROVIDE TWO (2) 10A CURRENT LIMITERS PER TWO-CIRCUIT TRACK, INSTALLED ON EACH HOT CONDUCTOR AND CLEARLY LABELED. EACH TRACK SHALL HAVE TWO (2) SEPARATE CIRCUITS, EACH CONTROLLED BY ITS OWN SWITCH OR DIMMER TO ALLOW MINIMUM 50% SEPARATE CONTROL PER IEC REQUIREMENTS. FIELD VERIFY THE NUMBER OF SWITCHES OR DIMMERS REQUIRED BASED ON FINAL LOAD DISTRIBUTION AND CONTROL ZONING. COORDINATE WITH LIGHTING VENDOR FOR WIRING, CURRENT LIMITER COMPATIBILITY, AND SWITCHING REQUIREMENTS.						
4. CONNECT THE SIGNAGE TO THE EXISTING/SPECIFIED SIGNAGE CIRCUIT THROUGH THE TIMER CONTROLLED LIGHTING CONTACTOR (LC). COORDINATE WITH THE OWNER OR LANDLORD TO DETERMINE THE EXACT LOCATION AND SCHEDULE FOR THE TIME CLOCK. COORDINATE POWER REQUIREMENTS WITH THE SIGN VENDOR.						
5. E.C. TO ENSURE THAT THE PHOTOCELL IS CONCEALED FROM PUBLIC VIEW.						
6. JUNCTION BOX FOR INTERIOR SIGNAGE, CONTROL VIA TIMECLOCK, E.C. TO FIELD VERIFY THE EXACT LOCATION WITH THE ARCHITECT AND SIGNAGE VENDOR.						
7. COORDINATE WITH LIGHTING VENDOR TO PROVIDE EMERGENCY BATTERY BACKUP POWER TO DESIGNATED TRACK HEADS TO SERVE AS EMERGENCY LIGHTING. EMERGENCY HEADS SHALL BE CLEARLY IDENTIFIED AND CIRCUITED TO ENSURE OPERATION IN COMPLIANCE WITH CODE-REQUIRED EMERGENCY ILLUMINANCE LEVELS.						

TYPE	DESCRIPTION	QTY	LUMINAIRE SPECIFICATION	INPUT WATTS	DIMMING LOAD TYPE	LUMINAIRE NOTES
EL-03A	EXISTING TRACK HEAD	303	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-03B	EXISTING LIGHT TRACK	40	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-04	EXISTING LIGHT PENDANT	2	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-01	RELOCATED EXISTING 4' LED TROFFER LIGHT	2	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE/RELOCATE AS NEEDED.
LT-02	4" DIA. RECESSED ADJUSTABLE DOWNLIGHT	6	LUCIER LIGHTING: FAR-FAS-1-PR-PR-27C12A-30-85	14W	0-10V	FLANGE AND BAFFLE TO MATCH CEILING FINISH
LT-03A	BLACK LED TRACK HEAD	121	JUNO LIGHTING: R610L-30K-90CRI-P	21W	WLV,MLV	ORDER ACCESSORIES AS NEEDED - QUANTITY OF TRACK HEADS MAY INCREASE PER OWNER'S REQUIREMENTS FOR DISPLAY LIGHTING
LT-03B	BLACK TWO-CIRCUIT TRACK	1	-	-	-	JUNO LIGHTING: TEK-[LENGTH]-BL, ORDER LENGTH ACCESSORIES AS NEEDED
LT-04	LINEAR LED WALL SCONCE	9	TECH LIGHTING KLE 30 WALL: BLACK FINISH	14W	0-10V	FLANGE AND BAFFLE TO MATCH CEILING FINISH
LT-07	INDOOR LED STRIP	2	CORE ARCHITECTURAL LIGHTING: L5M55-30K-[LENGTH], (PROFILE: ALU-CN); (TRANSFORMER: PSDL-192W-24V)	5.5W/FT	0-10V	INSTALL AT FABRIC DISPLAY MILLWORK - ORDER LENGTHS AS NEEDED
LT-08	LOW VOLTAGE LED TAPELIGHT IN CHANNEL	1	OCL LIGHTING: WP1-1TAA-18-FR-BKP-LED2-30K-UNV	25W	0-10V	ORDER ACCESSORIES AS NEEDED
EL-05	EXISTING TOFFER LIGHT	3	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-06	EXISTING DOWNLIGHT	3	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-07	EXISTING EXTERIOR WALL SCONCE	2	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EL-08	EXISTING EXTERIOR WALL SCONCE WITH BATTERY BACKUP	1	EXISTING		EXISTING	GC TO CONFIRM LIGHTS ARE IN WORKING ORDER AND REPLACE AS NEEDED.
EX	WALL MOUNTED EXIT SIGNAGE	PER PLAN	TBD	TBD		

LIGHTING FIXTURE GENERAL NOTES:	
A. VERIFY ALL LUMINAIRE COLORS, TRIMS, LENGTHS, ETC. WITH THE ARCHITECT PRIOR TO PLACING FINAL PURCHASE ORDERS. SUBMISSION OF SHOP DRAWINGS WILL BE INTERPRETED AS HAVING BEEN COORDINATED WITH THE ARCHITECTURAL DRAWINGS.	
B. PROVIDE ALL LENGTHS, FEEDS, ACCESSORIES, CONNECTORS, WIRING, POWER SUPPLIES, DRIVERS ETC. FOR A COMPLETE INSTALLATION. THE E.C. SHALL VERIFY THE COMPLETE BILL OF MATERIAL WITH MANUFACTURER'S REPRESENTATIVE AND ENSURE ALL EQUIPMENT ARE INCLUDED IN BID PRICE. COORDINATE INSTALLATION WITH ARCHITECTURAL DETAILS.	
C. ALL FIXTURES INDICATED AS EMERGENCY SHALL BE PROVIDED WITH 90-MINUTE BATTERY PACK AND ALL FLORENT FIXTURES INDICATED AS EMERGENCY SHALL BE PROVIDED WITH 1300LUMENS, 90MINUTE BATTERY PACK.	


PROJECT NUMBER: 24-343
ELECTRICAL
EMERGENCY
LIGHTING PLAN

JOYBIRD

CONSULTANTS
(MEP ENGINEER):
NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

△ ISSUANCE NAME DATE
CD SET 07-28-25
1 LL COMMENTS 08-13-25

E1.02



ELECTRICAL POWER PLAN GENERAL NOTES:

- A. ALL CONDUCTORS SHALL BE COPPER UNLESS OTHERWISE INDICATED. ABOVE FINISHED FLOOR TO CENTER OF THE COVER
- B. MOUNT ALL RECEPTACLES AT +18" PLATE UNLESS OTHERWISE INDICATED.
- C. FOR OUTLETS REQUIRING GFCI PROTECTION WHERE THE RECEPTACLE IS CONCEALED SUCH AS IN THE CASE OF A WATER FOUNTAIN OR VENDING MACHINE INSTALLATION, THE CONTRACTOR SHALL PROVIDE A STANDARD RECEPTACLE WITH GFCI CIRCUIT BREAKER IN THE ASSOCIATED PANEL. BLANK FACE GFCI TEST/RESET BUTTONS ARE NOT PERMITTED UNLESS EXPLICITLY LOCATED ON THESE DRAWINGS.
- D. FURNISH AND INSTALL ALL EXTERIOR RECEPTACLES WITH WEATHERPROOF COVERS. EXTERIOR RECEPTACLES SHALL BE GFCI TYPE.
- E. FOR ALL EXTERIOR ELECTRICAL EQUIPMENT, FURNISH AND INSTALL WITH NEMA 3R ENCLOSURES MINIMUM. IN THE EVENT THAT THERE IS A DISCREPANCY BETWEEN THIS REQUIREMENT AND INFORMATION LOCATED ELSEWHERE IN THE ELECTRICAL DOCUMENTS, THE CONTRACTOR SHALL BID ACCORDING TO THE MOST STRINGENT REQUIREMENT.
- F. IN BREAK ROOMS AND SIMILAR SPACES, THE CONTRACTOR SHALL REFER TO ARCHITECTURAL DOCUMENTS AND LOCATE ELECTRICAL DEVICES AT LOCATIONS AND ELEVATIONS TO BEST SERVE EACH DEDICATED APPLIANCE.
- G. COORDINATE WITH OTHER DISCIPLINES IN THE FIELD TO ENSURE THAT THE INTEGRITY OF FIRE RATED CONSTRUCTION IS PRESERVED WHERE PENETRATING RATED WALLS AND FLOORS.
- H. THE CONTRACTOR SHALL ROUTE ALL EXPOSED CONDUIT NEATLY AND TIGHT TO SUPPORTING SURFACES. IN THE EVENT THAT THE OWNER IS NOT SATISFIED WITH WORKMANSHIP, THE CONTRACTOR SHALL MAKE CORRECTIONS AT NO ADDITIONAL COST TO THE OWNER. MC CABLE IS NOT PERMITTED IN EXPOSED AREAS.
- I. FOR ALL CIRCUIT RUNS SHOWN ON ELECTRICAL DRAWINGS, THE ROUTING IS APPROXIMATE. THE CONTRACTOR SHALL MAKE ROUTING ADJUSTMENTS AS REQUIRED BASED ON FIELD CONDITIONS AND COORDINATION WITH OTHER DISCIPLINES.
- J. IN THE EVENT THAT THERE IS A DISCREPANCY IN THE MINIMUM CIRCUIT AMPACITY (MCA) AND/OR THE MAXIMUM OVERCURRENT PROTECTION (MOP), THE CONTRACTOR SHALL BID ACCORDING TO THE MORE STRINGENT REQUIREMENTS.
- K. MECHANICAL, PLUMBING, AND OTHER EQUIPMENT FURNISHED AND INSTALLED BY OTHER DIVISIONS IS SHOWN ON ELECTRICAL DRAWINGS FOR CIRCUITING PURPOSES ONLY. THE CONTRACTOR SHALL REFER TO OTHER DISCIPLINE CONSTRUCTION DOCUMENTS FOR EXACT LOCATIONS OF EQUIPMENT PRIOR TO ROUGH-IN OF THE ASSOCIATED ELECTRICAL CIRCUITS, DISCONNECTING MEANS, OUTLETS, ETC. AND ADJUST ROUTING AND LOCATIONS ACCORDINGLY.
- L. THE RECEPTACLES MARKED AS "GFI" ON THE FLOOR PLAN INDICATES THAT THE RECEPTACLE SHALL BE GFI PROTECTED. E.C. SHALL PROVIDE GFI BREAKER IN PANEL IF GFI RECEPTACLE IS NOT READILY ACCESSIBLE OR FOR THE RECEPTACLES OTHER THAN 20A.
- M. TAMPER RESISTANT "TR" RECEPTACLES SHALL BE PROVIDED AS PER ARTICLE 406.12 OF NEC WHERE EVER REQUIRED.
- N. ALL THE RECEPTACLES SHALL BE GFI PROTECTED EITHER AT RECEPTACLE OR AT ELECTRICAL PANEL AS SPECIFIED IN 210.8(B)
- O. ELECTRICAL CONTRACTOR SHALL VERIFY AND PROVIDE THE EXACT ELECTRICAL REQUIREMENT INCLUDING RECEPTACLE, PLUG, CORD, CIRCUIT BREAKER AND CABLES FOR ALL THE EQUIPMENT IN COORDINATION WITH THE EQUIPMENT SUPPLIER/MANUFACTURER IN THE FIELD. BASE BID ACCORDINGLY.
- P. COORDINATE EXACT LOCATION AND ELECTRICAL CONNECTION REQUIREMENTS OF THE DUCT SMOKE DETECTOR, MOTORIZED DAMPERS, AND THERMOSTATS IN THE FIELD WITH THE MECHANICAL DRAWING. PROVIDE WIRING AS REQUIRED.
- Q. E.C. SHALL REUSE EXISTING RECEPTACLES AND FLOOR BOXES WHEREVER POSSIBLE.
- R. RECEPTACLES MARKED "(E)" ARE EXISTING TO REMAIN. WHERE FEASIBLE, EXISTING CIRCUITS MAY BE EXTENDED OR REUSED; FIELD VERIFY CIRCUIT CONDITIONS AND COORDINATE FINAL CONNECTIONS WITH ELECTRICAL CONTRACTOR. ADJUST AND REARRANGE PANEL SCHEDULES AS REQUIRED TO REFLECT FINAL CIRCUIT CONFIGURATION.


ELECTRICAL FLOOR POWER PLAN KEYED NOTES:

1. CLEAR WORKING & DEDICATED SPACE SHALL BE PROVIDED FOR THE ELECTRICAL PANELS AS PER NEC 110.26.
2. EXISTING FLOOR BOX TO REMAIN. E.C. TO PROTECT DURING CONSTRUCTION AND REUSE EXISTING CIRCUIT. E.C. SHALL VERIFY OPERABLE CONDITION AND CONTROL IN THE FIELD. IF NOT FOUND OR FOUND INOPERABLE, REPLACE WITH NEW.
3. PLYWOOD WALL MOUNTED BOARD 3'X3' FOR DATA RACK, COORDINATE EXACT PLACEMENT WITH THE CLIENT/LV VENDOR.
4. E.C. SHALL REUSE EXISTING FLOOR BOX AND PROVIDE ONE ADDITIONAL FLOOR BOX TO FEED COUNTERTOP RECEPTACLES. USE FLEX CONDUIT WHIPS AS REQUIRED. COORDINATE EXACT LOCATIONS WITH MILLWORK DRAWINGS, ARCHITECT, AND LANDLORD PRIOR TO INSTALLATION.
5. NEW POS DESK - DETAILS BY MILL WORKER.
6. EXISTING MECHANICAL EQUIPMENT SHALL REMAIN CONNECTED TO THE EXISTING CIRCUIT. E.C. SHALL VERIFY THE OPERABLE CONDITION OF THE ELECTRICAL CIRCUIT AND CONTROL IN THE FIELD. REPLACE IF FOUND INOPERABLE. BASE BID ACCORDINGLY.
7. SINGLE GANG BOX MOUNTED ON CEILING. PROVIDE RECEPTACLE AND DATA POINT OUTLET AS REQUIRED. COORDINATE WITH THE LOW VOLTAGE VENDOR.
8. EXISTING PLUMBING EQUIPMENT SHALL REMAIN CONNECTED TO THE EXISTING CIRCUIT. E.C. SHALL VERIFY THE OPERABLE CONDITION OF THE ELECTRICAL CIRCUIT AND CONTROL IN THE FIELD. REPLACE IF FOUND INOPERABLE. BASE BID ACCORDINGLY.
9. EXISTING ROLL DOWN GATE TO REMAIN ALONG WITH EXISTING CIRCUIT AND CONTROL. E.C. TO FIELD VERIFY THE OPERABLE CONDITION OF CIRCUIT AND CONTROL, PROVIDE NEW IF FOUND INOPERABLE.
10. REUSE EXISTING CIRCUIT AT COLUMN WRAP FOR POWER. ROUTE VIA FLEXIBLE CONDUIT WHIPS TO RECEPTACLES MOUNTED INSIDE CABINETS AS SHOWN. COORDINATE EXACT LOCATIONS WITH ARCHITECTURAL DRAWINGS.
11. COUNTERTOP OUTLETS, COORDINATE EXACT LOCATION AND MOUNTING HEIGHT WITH MILLWORK DRAWINGS, ARCHITECT, AND LANDLORD PRIOR TO BID.

ELECTRICAL/LV PLAN LEGEND	
SYMBOL	DESCRIPTION
	SINGLE GANG BOX MOUNTED ON CEILING
	CONDUIT PATHWAY TO MDF
W.A.P.	WIRELESS ACCESS POINT
(E)	EXISTING TO REMAIN RECEPTACLES

ISSUANCE NAME: DATE: 07-28-25
CD SET: 08-13-25
1 LL COMMENTS: 08-13-25

PROJECT NUMBER: 24-343
ELECTRICAL FLOOR POWER & LV PLAN



ELECTRICAL ROOF POWER PLAN | 1
3/16" = 1'-0"

ELECTRICAL ROOF POWER PLAN KEYED NOTES: (E)	
1. EXISTING (E) MECHANICAL UNITS SHALL REMAIN CONNECTED TO THE EXISTING CIRCUIT. E.C. TO VERIFY THE OPERABLE CONDITION OF THE ELECTRICAL CIRCUIT AND CONTROLS IN THE FIELD. REPLACE IF FOUND INOPERABLE. BASE BID ACCORDINGLY.	
2. E.C. TO FIELD VERIFY FOR THE AVAILABILITY AND OPERABLE CONDITION OF THE EXISTING SERVICE RECEPTACLE. PROVIDE NEW IF FOUND INOPERABLE OR UNAVAILABLE.	

ELECTRICAL ROOF POWER PLAN GENERAL NOTES:	
A. ALL THE ELECTRICAL ELEMENTS, VIZ., CONDUITS, WIRING, AND DISCONNECT SWITCHES, SHALL BE RATED FOR EXTERIOR USE.	
B. THE DISCONNECT SWITCHES FOR THE BRANCH CIRCUIT SHOWN ON THE PLAN SHALL BE RATED EQUAL TO OR HIGHER THAN THE BREAKER RATING. REFER TO BREAKER RATING IN THE PANEL SCHEDULE AND PROVIDE DISCONNECT AS NEEDED.	
C. GFI MARKED ON THE PLAN INDICATES THAT THE CIRCUIT SHALL BE GFI PROTECTED. E.C. SHALL PROVIDE A GFI BREAKER IN THE PANEL FOR THE INDICATED CIRCUIT IF EITHER THE RECEPTACLE IS NOT AVAILABLE OR NOT ACCESSIBLE.	
D. A 125-VOLT, SINGLE-PHASE, 15-OR 20-AMPERE-RATED RECEPTACLE OUTLET SHALL BE INSTALLED AT AN ACCESSIBLE LOCATION WITHIN 7.5 M (25 FT) OF THE EQUIPMENT AS SPECIFIED IN 210.63(A) AND (B) AS PER NEC 210.63.	




△ ISSUANCE NAME	DATE
CD SET	07-28-25
1 LL COMMENTS	08-13-25

PROJECT NUMBER: 24-343

ELECTRICAL ROOF
POWER PLAN


E2.02

CONSULTANTS
(MEP ENGINEER):
NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM



PANEL:	E110H	(EXISTING)	-										MOUNTING:	SURFACE	
480Y/277	VOLTS		3	PHASE	-	-				DEMAND LOAD (in kVA)	106.71		PANEL LOCATION:	BOH	
200	AMPS	MCB - MAIN CIRCUIT BREAKER	4	WIRE	-	-				DEMAND CURRENT (in Amps)	128.50		FED FROM:	ELEC. METER	
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	NOTES	PER PHASE (KVA)			NOTES	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.	
1	90/3P	RTU	H	19.90		A	B	C							
3			H	19.90	ETR, VIF	32.57			ETR, VIF	12.67	X	TRANSFORMER E110L	100/3P	2	
5			H	19.90			32.57			12.67	X			4	
7	25/1P	EWH-1	O	4.00		9.00			ETR, VIF	5.00	H	EUH-2(E)	20/1P	6	
9	20/1P	SPARE					0.00					SPARE	20/1P	8	
11	20/1P	SPARE						0.00				SPARE	20/1P	10	
13		SPACE				0.00						SPACE		12	
15		SPACE					0.00					SPACE		14	
17		SPACE						0.00				SPACE		16	
19		SPACE				0.00						SPACE		18	
21		SPACE					0.00					SPACE		20	
23		SPACE						0.00				SPACE		22	
25		SPACE				0.00						SPACE		24	
27		SPACE					0.00					SPACE		26	
29		SPACE						0.00				SPACE		28	
31		SPACE				0.00						SPACE		30	
33		SPACE					0.00					SPACE		32	
35		SPACE						0.00				SPACE		34	
37		SPACE				0.00						SPACE		36	
39		SPACE					0.00					SPACE		38	
41		SPACE						0.00				SPACE		40	

PANEL:	E110L	(EXISTING)	-										MOUNTING:	SURFACE	
208Y/120	VOLTS		3	PHASE	-	-	-	DEMAND LOAD (in kVA)	38.01				PANEL LOCATION:	BOH	
150	AMPS	MCB - MAIN CIRCUIT BREAKER	4	WIRE	-	-	-	DEMAND CURRENT (in Amps)	105.62				FED FROM:	PANEL E110H, VIA X'MER	
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	NOTES	PER PHASE (KVA)			NOTES		LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.
1	20/1P	NORTH FLOOR RECEPT.	R	0.72	ETR, VIF	1.26			RWC		0.54	R	CEILING RECEPT.	20/1P	2
3	20/1P	NORTH FLOOR RECEPT. (POS)	R	0.72	ETR, VIF		1.08		RWC		0.36	R	GENERAL RECEPT.	20/1P	4
5	20/1P	CENTER FLOOR RECEPT.	R	0.90	ETR, VIF			1.40	RWC		0.50	O	REF. BREAK ROOM	20/1P	6
7	20/1P	CENTER FLOOR RECEPT.	R	0.72	ETR, VIF	1.92			RWC		1.20	L	INTERIOR SIGNAGE	20/1P	8
9	20/1P	SOUTH FLOOR RECEPT.	R	0.90	ETR, VIF		2.10		RWC		1.20	L	INTERIOR SIGNAGE	20/1P	10
11	20/1P	SOUTH FLOOR RECEPT.	R	0.90	ETR, VIF			2.10	RWC		1.20	L	TRACK LIGHTING-7	20/1P	12
13	20/1P	SOUTH FLOOR RECEPT. (POS)	R	0.72	ETR, VIF	1.92			RWC		1.20	L	TRACK LIGHTING-8	20/1P	14
15	20/1P	CENTER WALL RECEPT.	R	0.36	RWC		0.86		ETR, VIF		0.50	M	GARAGE DOOR	20/1P	16
17	20/1P	STORE FRONT RECEPT.	R	0.36	RWC			0.56	RWC		0.20	O	TIME CLOCK	20/1P	18
19	20/1P	WEST WALL RECEPT.	R	1.08	RWC	2.28			RWC		1.20	L	REAR SIGNAGE	20/1P	20
21	20/1P	NORTH WEST RECEPT.	R	0.90	RWC		2.10		RWC		1.20	L	TRACK LIGHTING-1	20/1P	22
23	20/1P	SOUTH WEST RECEPT.	R	0.36	RWC			1.56	RWC		1.20	L	TRACK LIGHTING-2	20/1P	24
25	20/1P	SOUTH EAST RECEPT.	R	1.08	RWC	2.28			RWC		1.20	L	TRACK LIGHTING-3	20/1P	26
27	20/1P	NORTH EAST WALL RECEPT.	R	1.08	RWC		2.28		RWC		1.20	L	TRACK LIGHTING-4	20/1P	28
29	20/1P	EAST WALL RECEPT.	R	1.08	RWC			2.28	RWC		1.20	L	TRACK LIGHTING-5	20/1P	30
31	20/1P	MANAGER'S OFFICE RECEPT.	R	0.72	RWC	1.92			RWC		1.20	L	TRACK LIGHTING-6	20/1P	32
33	20/1P	SHOW WINDOW RECEPT.	R	1.60	RWC		2.80		ETR, VIF		1.20	L	SIGNAGE	20/1P	34
35	20/1P	RTU RECEPT.	R	0.18	ETR, VIF			1.68	ETR, VIF		1.50	H	EUH-1(E)	20/2P	36
37	20/1P	BREAK ROOM RECEPT.	R	0.54	RWC	2.04					1.50	H			38
39	20/1P	RESTROOM RECEPT.	R	0.36	RWC		1.36		ETR, VIF		1.00	M	EF-1(E)	20/2P	40
41	20/1P	WATER FOUNTAIN	R	0.18	RWC			1.18			1.00	M			42



CONSULTANTS (MEP ENGINEER):

NEARBY ENGINEERS
82 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NEARBY-ENGINEERS.COM

82 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (305) 837-9217

PTI - (646) 837-5217
WWW.NY-ENGINEERS.COM

JOYBIRD

PROJECT NUMBER: 24-343

**ELECTRICAL
ANEL SCHEDULE
RISER DIAGRAM**

PLUMBING SYMBOLS LIST

— SAN —	SANITARY SEWER (UNDERFLOOR)
— SAN —	SANITARY SEWER (ABOVE FLOOR)
— — —	VENT PIPING
— — —	COLD WATER PIPING
— — —	HOT WATER PIPING
— — —	HOT WATER RETURN PIPING
— G —	GAS PIPING
— — — O	P-TRAP
— — — O	PIPE UP
— — — O	PIPE DROP
— — — O	CLEANOUT
— — — II	PLUGGED OUTLET/CLEANOUT
— — — O	POINT OF CONNECTION

PLUMBING ABBREVIATIONS

CO	CLEANOUT
CW	COLD WATER
HW	HOT WATER
HWR	HOT WATER RETURN
SAN	SANITARY
V	VENT
W	WASTE
LAV	LAVATORY
WC	WATER CLOSET
TYP.	TYPICAL
DN	DOWN
AFF	ABOVE FINISH FLOOR
FD	FLOOR DRAIN
BFP	BACK FLOW PREVENTER
WH	WATER HEATER
EX.	EXISTING
ET	EXPANSION TANK

PLUMBING DRAWING LIST

P0.01	PLUMBING NOTES, SYMBOLS, ABBREVIATIONS & SPECIFICATIONS
P1.01	PLUMBING SANITARY AND VENT FLOOR PLAN
P1.02	PLUMBING WATER FLOOR PLAN
P2.01	PLUMBING DETAILS
P3.01	PLUMBING SCHEDULES & RISERS

BUILDING DEPARTMENT PLUMBING NOTES

- ALL PLUMBING SYSTEMS (SANITARY, WASTE, VENT, WATER) AND ASSOCIATED EQUIPMENT SHALL BE INSTALLED, OPERATED AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF 2024 OHIO PLUMBING CODE.
- INSTALLATION OF UNDERGROUND PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 701
- PROTECTION OF PIPING AND PLUMBING SYSTEM COMPONENTS AS PER SECTION PC 312.
- TRENCHING, EXCAVATION AND BACKFILL AS PER SECTION PC 314.
- RODENT PROOFING AS PER PC 312.12
- MATERIALS USED IN PLUMBING SYSTEMS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 312, PC 604, PC 701, PC 903, PC 1102.
- EQUIPMENT CONNECTIONS AND JOINING OF PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTERS 4, 5, 6, 7 AND 9.
- DEEP SEAL TRAPS FOR FLOOR DRAINS SHALL BE PROVIDED AS PER PC 1002, AND CLEAN-OUTS SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 708
- DRAINAGE PIPE CLEANOUTS AS PER SECTION PC 719.
- VERTICAL AND HORIZONTAL PIPING SHALL BE SUPPORTED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 313
- WATER SUPPLY SYSTEMS SHALL BE INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 6 SECTION PC 601-603, 604, 606, 607, 608, 610
- THE SANITARY DRAINAGE SYSTEM SHALL BE SIZED AND INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 7 SECTION PC 701, 704, 705, 706, 707, 708, 711.
- VENT PIPING FOR THE SANITARY DRAINAGE SYSTEM SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 9 SECTIONS PC 901 THROUGH PC 912 THROUGH PC 917 1A. INSPECTION AND TESTING OF PLUMBING SYSTEMS SHALL BE IN ACCORDANCE WITH SECTION PC 107.

PLUMBING SPECIFICATIONS

- BASIC PLUMBING REQUIREMENTS, MATERIALS AND METHODS
 - SCOPE
 - PROVIDE ALL MATERIAL, TOOLS, SUPERVISION AND LABOR INCLUDING ALL MISCELLANEOUS AND INCIDENTAL ITEMS REQUIRED FOR COMPLETE AND OPERABLE PLUMBING INSTALLATIONS AS SHOWN OR DESCRIBED ON THE DRAWINGS AND IN THESE SPECIFICATIONS.
 - THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING AND NEW CONDITIONS AND MATERIALS WITHIN THE CONSTRUCTION AREA. ANY DAMAGE CAUSED BY THE CONTRACTOR SHALL BE REPAIRED TO THE OWNER'S SATISFACTION.
 - OBTAIN ALL PERMITS, PAY ALL PERMIT FEES AND SCHEDULE ALL REQUIRED INSPECTIONS. COPIES OF ALL PERMITS AND INSPECTION CERTIFICATES SHALL BE FORWARDED TO THE OWNER FOR RECORD.
 - THE GENERAL CONDITIONS OF THE CONTRACT AND ALL DIVISION 1 REQUIREMENTS APPLY TO THE WORK OF THIS SECTION.
 - THE CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID TO DETERMINE CONDITIONS AND THE EXTENT OF THE WORK. BY COMMENCING WORK, THE CONTRACTOR ACKNOWLEDGES HIS CONFIRMATION OF ALL CONDITIONS AS ACCEPTABLE WITH REFERENCE TO HIS CONTRACT, SCOPE OF WORK AND BID PRICE SUCH THAT NO ADDITIONAL COMPENSATION SHALL BE FORTHCOMING FOR UNFORESEEN EXISTING CONDITIONS.
 - IN ALL AREAS SUBJECT TO FREEZING CONDITIONS, THE CONTRACTOR SHALL PROVIDE FREEZE PROTECTION FOR ALL DOMESTIC WATER PIPING INSTALLED UNDER HIS CONTRACT.
 - ALL ELECTRICAL REQUIREMENTS SHALL BE COORDINATED WITH THE CONTRACTOR FOR ELECTRICAL WORK. THIS CONTRACTOR IS RESPONSIBLE FOR ALL LOW VOLTAGE WIRING FOR EQUIPMENT INSTALLED UNDER HIS CONTRACT. THE CONTRACTOR FOR ELECTRICAL WORK IS RESPONSIBLE FOR LINE VOLTAGE POWER WIRING ONLY.
 - COLOR AND FINISH SELECTIONS FOR ALL MATERIALS, INCLUDING PAINTING OF PIPING, SHALL BE AS DIRECTED AND/OR APPROVED BY THE ARCHITECT.
 - MINOR DETAILS NOT SHOWN OR SPECIFIED, BUT NECESSARY FOR THE PROPER AND ACCEPTABLE CONSTRUCTION, INSTALLATION OR OPERATION OF ANY PART OF THE WORK AS DETERMINED BY THE ENGINEER SHALL BE INCLUDED AS IF SPECIFIED OR INDICATED ON THE DRAWINGS.
 - THIS CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL REQUIREMENTS FOR THE INSTALLATION, CONNECTION, EXTENSION OR MODIFICATION TO ALL UTILITY SERVICES WITH RESPECTIVE PROVIDERS INCLUDING PAYMENT OF ALL ASSOCIATED FEES.

1.01 SCOPE

1.02 SUBMITTALS

1.03 SUBSTITUTIONS

1.04 DEFINITIONS

- FURNISH: TO PURCHASE, PROCURE, ACQUIRE AND DELIVER, COMPLETE WITH RELATED ACCESSORIES.
- INSTALL: TO ERECT, MOUNT AND CONNECT, COMPLETE WITH RELATED ACCESSORIES.
- PROVIDE: TO FURNISH AND INSTALL.
- PLUMBING CONTRACTOR: THE CONTRACTOR, THIS CONTRACTOR: THE CONTRACTOR FOR PLUMBING WORK WHICH IS SPECIFIED HEREIN AND SHOWN ON THESE DRAWINGS.
- THE DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED TO ILLUSTRATE THE GENERAL ARRANGEMENT AND ROUTING OF PIPING AND GENERAL LOCATIONS OF EQUIPMENT. PRECISE LOCATIONS OF EQUIPMENT, RISERS AND STACKS, AND ROUTING AND ELEVATION OF ALL PIPING SYSTEMS SHALL BE COORDINATED IN THE FIELD WITH THE ARCHITECT, ARCHITECTURAL DRAWINGS, THE WORK OF OTHER TRADES, EXISTING AND NEW BUILDING CONDITIONS, AND/OR THE PREFERENCES OF THE OWNER/TENANT AS CONSTRUCTION PROCEEDS. ALL PIPING SHALL BE INSTALLED CONCEALED IN FINISHED SPACES, UNLESS NOTED OTHERWISE.
- PROVIDE ALL NECESSARY INCIDENTAL MATERIALS AND ACCESSORIES REQUIRED TO MAKE THE WORK COMPLETE IN ALL RESPECTS, EVEN IF NOT PARTICULARLY SHOWN OR SPECIFIED.
- REFER TO PLUMBING EQUIPMENT/FIXTURE SCHEDULE ON THE DRAWINGS FOR ALL FIXTURE AND EQUIPMENT SPECIFICATIONS.
- REFER TO FIXTURE CONNECTION SIZE SCHEDULE FOR ALL FIXTURE ROUGHING SIZE REQUIREMENTS.
- VERIFY ALL INDICATED CONDITIONS BEFORE STARTING WORK AND REPORT ANY DISCREPANCIES. THE DRAWINGS REFLECT CONDITIONS WHICH CAN BE REASONABLY INTERPRETED FROM THE EXISTING VISIBLE CONDITIONS OR FROM DRAWINGS AND INFORMATION FURNISHED BY THE OWNER.
- LOCATE ALL FIXTURES AND EQUIPMENT AS PER THE FINAL ARCHITECTURAL DRAWINGS.
- PRODUCTS
- SANITARY AND VENT PIPING:
 - ABOVE GRADE PIPING SHALL BE HUBLESS CAST IRON PIPE WITH STAINLESS STEEL COUPLINGS AND ELASTOMERIC GASKETS WITH A MINIMUM 4 BANDS PER COUPLING.
 - SLOPE OF DRAINAGE SYSTEM SHALL BE 1/8" PER FOOT OF RUN FOR PIPE OVER 3" (I.D.) AND 1/4" PER FOOT OF RUN FOR PIPE 3" AND SMALLER (I.D.). VENT PIPING SHALL BE PITCHED TO DRAIN.
 - ALL CAST IRON SOIL PIPE AND FITTINGS SHALL BE MARKED WITH THE COLLECTIVE TRADEMARK OF THE CAST IRON SOIL PIPE INSTITUTE (CISPI) AND BE LISTED BY NSF INTERNATIONAL.
- DOMESTIC WATER PIPING:
 - ABOVE GRADE WATER PIPING SHALL BE TYPE 'L' HARD-DRAWN COPPER TUBE.
 - FITTINGS IN DOMESTIC WATER PIPING SHALL BE WROUGHT COPPER OR CAST BRASS.
 - JOINTS SHALL BE MADE WITH LEAD-FREE SOLDER.
 - THE ENTIRE DOMESTIC WATER DISTRIBUTION SYSTEM SHALL BE INSULATED INCLUDING ALL VALVES, FITTINGS, ETC.
 - COMPLY WITH NSF 61 FOR MATERIALS FOR WATER-SERVICE PIPING AND SPECIALTIES FOR DOMESTIC WATER.
 - ALL DOMESTIC WATER PIPING ABOVE GRADE SHALL BE INSULATED WITH FIRE-RETARDANT, FACTORY APPLIED JACKET. PROVIDE COLD WATER PIPING WITH FACTORY APPLIED VAPOR BARRIER INSULATION. REQUIREMENT SHOULD COMPLY WITH 2021 INTERNATIONAL ENERGY CONSERVATION CODE.
 - AS PER 2021 INTERNATIONAL ENERGY CONSERVATION CODE, SERVICE WATER EQUIPMENT SHALL BE EQUIPPED WITH AUTOMATIC TEMPERATURE CONTROLS CAPABLE OF ADJUSTING FROM THE LOWEST TO THE HIGHEST ACCEPTABLE TEMPERATURE SETTING FOR THE INTENDED USE AS PER THE 2024 OHIO PLUMBING CODE.
 - AS PER 2021 INTERNATIONAL ENERGY CONSERVATION CODE, SYSTEMS DESIGNED TO MAINTAIN USAGE TEMPERATURES IN HOT WATER PIPES, SUCH AS RECYCLING HOT WATER SYSTEM SHALL BE EQUIPPED WITH AUTOMATIC TIME SWITCHES OR OTHER CONTROLS THAT CAN BE SET TO SWITCH THE USAGE TEMPERATURE MAINTENANCE SYSTEM DURING EXTENDED PERIOD WHEN HOT WATER IS NOT REQUIRED.
 - AS PER 2021 INTERNATIONAL ENERGY CONSERVATION CODE, AUTOMATICALLY REGULATE THE TEMPERATURE OF HOT WATER DELIVERED TO PLUMBING FIXTURE TO A RANGE OF 105°F (41°C) MINIMUM TO 120°F (49°C) MAXIMUM.
 - INSULATION REQUIREMENT SHOULD COMPLY WITH 2021 INTERNATIONAL ENERGY CONSERVATION CODE. REFER BELOW TABLE FOR MINIMUM PIPE INSULATION THICKNESS ACC. TO 2024 OHIO PLUMBING CODE, 2021 INTERNATIONAL ENERGY CONSERVATION CODE.
- SUBSTITUTIONS
 - ALL EQUIPMENT SHALL BE PRODUCTS OF THE SPECIFIED MANUFACTURER OR MANUFACTURERS. ALL BIDS SHALL BE BASED ON THE SPECIFIED MANUFACTURER OR MANUFACTURER'S EQUIPMENT. FOR SUBSTITUTIONS OF OTHER MANUFACTURER'S EQUIPMENT TO BE CONSIDERED, THE SUBSTITUTION MUST BE INDICATED PRIOR TO BIDDING WITH THE REASON FOR THE PROPOSED SUBSTITUTION IDENTIFIED, AND THE PROPOSED CREDIT TO THE OWNER INDICATED. THE ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF ANY PROPOSED SUBSTITUTIONS.
 - THE CONTRACTOR ASSUMES ALL RESPONSIBILITY FOR COORDINATING THE WORK OF OTHER TRADES WHICH MAY BE AFFECTED BY SUBSTITUTIONS, INCLUDING ALL RELATED COSTS.
- SEAL ALL JOINTS BETWEEN SEGMENTS OF INSULATION.
- PROVIDE SHIELDS BETWEEN HANGERS AND INSULATION.

MINIMUM PIPE INSULATION THICKNESS

FLUID OPERATING TEMPERATURE RANGE AND USAGE (°F)	INSULATION CONDUCTIVITY	NOMINAL PIPE OR TUBE SIZE (INCHES)		
CONDUCTIVITY BTU IN/ (H· FT² °F)	MEAN RATING °F	<1	1 to < 1½	
141-200	0.25-0.29	125	1.5	1.5
105-140	0.22-0.28	100	1.0	1.5

J. OR TO DISCONNECTING AND CONNECTING NEW WORK TO EXISTING SYSTEMS, THE PLUMBING CONTRACTOR SHALL NOTIFY THE PROPERTY OWNER AND OFFER A PROPOSED SCHEDULE OF WORK. ESB WILL AUTHORIZE CONNECTIONS AND COORDINATE NECESSARY SHUT DOWNS AND DRAIN DOWNS AS REQUIRED. SHUT DOWNS AND DRAIN DOWNS MAY BE PERFORMED BY THE PLUMBING CONTRACTOR ONLY AFTER RECEIVING ESB AUTHORIZATION, AND SHOULD BE PERFORMED UNDER SUPERVISION OF ESB PERSONNEL. THREE (3) DAYS ADVANCE NOTICE TO THE PROPERTY OWNER IS REQUIRED.

K. PLUMBING CONTRACTOR IS ADVISED THAT DUE TO THE NATURE OF THE OPERATIONS AND TENANT REQUIREMENTS, CONNECTIONS TO EXISTING SYSTEMS MAY HAVE TO BE MADE AFTER REGULAR WORKING HOURS. THE PROPERTY OWNER WILL ADVISE THE PLUMBING CONTRACTOR OF THE TIME CONSTRAINTS UPON RECEIPT AND APPROVAL OF THE PLUMBING CONTRACTOR'S REQUEST FOR SHUT DOWN AND CONNECTION TO EXISTING SYSTEMS.

L. IN CONNECTING TO EXISTING STACKS AND RISERS, PROVISION IS TO BE MADE FOR FUTURE CONNECTIONS BY PROVIDING CAPPED AND VALVED OUTLETS ON DOMESTIC WATER RISERS AND PLUGGED OUTLETS ON THE SANITARY AND VENT STACKS.

2.02 ABOVE GRADE

A. INSTALL PLUMBING PIPING IN ACCORDANCE WITH RECOGNIZED INDUSTRY PRACTICES TO ENSURE THAT PIPING COMPLIES WITH REQUIREMENTS AND SERVES INTENDED PURPOSES.

B. ROUTE PIPING IN AN ORDERLY MANNER, PLUMB AND PARALLEL TO BUILDING STRUCTURE. MAINTAIN GRADIENT, SLOPE PIPING AND ARRANGE SYSTEMS TO DRAIN. IN DOMESTIC WATER SYSTEMS, PROVIDE DRAIN VALVES AT MAIN SHUT-OFF VALVES AND ALL LOW POINTS IN PIPING.

C. USE EXISTING CONNECTIONS AT MAINS WHERE AVAILABLE FOR NEW BRANCH PIPING. LOCATE ALL RISERS AND PIPING BEFORE CONSTRUCTION COMMENCES AND TAKE CARE NOT TO DAMAGE SAME. ANY DAMAGE OCCURRING TO THE EXISTING PIPING WILL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

3. TESTING

A. AT THE COMPLETION OF THE PLUMBING WORK, COMPLETELY TEST THE ENTIRE INSTALLATION OF ALL SYSTEMS FOR PROPER OPERATION AND COMPLIANCE WITH APPLICABLE CODES AND LOCAL REQUIREMENTS. CORRECT ALL DEFICIENCIES FOUND.

B. TESTING OF THE INSTALLED SYSTEMS SHALL BE MADE BY THE CONTRACTOR IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER.

C. THE CONTRACTOR SHALL NOT COVER UP OR PERMANENTLY CONCEAL PIPING DEVICES OR ANY PORTION OF NEWLY CONSTRUCTED PLUMBING SYSTEMS UNTIL SUCH SYSTEM, OR PORTION OF THE SYSTEM, HAS BEEN TESTED IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER AND INSPECTED BY THE LOCAL INSPECTOR AND APPROVED IN WRITING, EXCEPT PIPING PASSING THROUGH FLOORS, WALLS, PARTITIONS, OR BEAMS, FOR DISTANCES EQUAL TO THE THICKNESS OF SUCH FLOOR, WALL, PARTITION OR BEAM.

D. THIS CONTRACTOR SHALL NOTIFY THE VARIOUS DEPARTMENTS, BUREAUS AND INDIVIDUALS AT LEAST TWO WEEKS IN ADVANCE OF THE TIME THAT THE TESTS ARE TO BE CONDUCTED.

E. ALL DEFECTIVE PARTS SHALL BE REPLACED OR CORRECTED BY THIS CONTRACTOR AND AN EXTRA TEST OR TESTS SHALL BE MADE UNTIL THE OPERATION IS SATISFACTORY. ALL ARRANGEMENTS AND EXPENSES NECESSARY TO CONDUCT ALL TESTS REQUIRED BY THESE SPECIFICATIONS AND THE VARIOUS AGENCIES HAVING JURISDICTION OVER THE WORK INSTALLED UNDER THIS CONTRACT SHALL BE MADE BY THIS CONTRACTOR. NO EXTRA COMPENSATION WILL BE ALLOWED FOR THESE TESTS, THE COST THEREOF BEING INCLUDED IN THE LUMP SUM BID FOR THIS CONTRACT.

F. WHERE ANY EVIDENCE OF STOPPAGE IS FOUND IN PIPING OR EQUIPMENT, THIS CONTRACTOR SHALL DISCONNECT, CLEAN, REPAIR AND RECONNECT ALL OBSTRUCTED PIPING OR EQUIPMENT AND SHALL ALSO PAY FOR ALL NECESSARY CUTTING AND REPAIRS TO ADJOINING WORK.

G. ALL PIPING AND EQUIPMENT SHALL BE THOROUGHLY CLEANED INSIDE AND OUT, OF DIRT, CUTTINGS, OILS AND OTHER FOREIGN SUBSTANCES AND SHALL BE LEFT CLEAN.

H. ALL REQUIRED TESTS SHALL BE WITNESSED BY LOCAL AUTHORITIES AND THE OWNER'S REPRESENTATIVE.

I. ALL EQUIPMENT WILL BE FACTORY TESTED.

J. CONTRACTOR SHALL IDENTIFY TO THE OWNER'S REPRESENTATIVE ANY LEAKS OR DAMAGE THAT OCCURS AS A RESULT OF SYSTEM TESTING. CONTRACTOR SHALL TAKE NECESSARY PRECAUTIONS TO LIMIT ANY POTENTIAL DAMAGE. CORRECTIVE ACTION REQUIRED AS A RESULT OF TESTING SHALL BE PERFORMED IMMEDIATELY AND AT THE CONTRACTOR'S EXPENSE.

K. REPORT IN WRITING TO AUTHORITIES HAVING JURISDICTION, THE ARCHITECT AND THE OWNER THE RESULTS OF ALL TESTING.

L. TESTING REQUIREMENTS

- TEST ALL DOMESTIC WATER PIPING HYDROSTATICALLY TO 125 PSIG.
- HYDROSTATIC TEST PRESSURES SHALL REMAIN CONSTANT WITH NO VARIATION FOR 120 MINUTES.
- TESTS SHALL BE WITNESSED BY THE BUILDING ENGINEER.

M. THE PLUMBING CONTRACTOR WILL BE HELD RESPONSIBLE FOR ALL DAMAGE DUE TO TEST FAILURES AND LEAKAGE IN THE TEST AREA AND ADJACENT TENANT OR ESB SPACES.

N. THOROUGHLY FLUSH PIPING SYSTEM WITH FRESH WATER IMMEDIATELY PRIOR TO FINAL ACCEPTANCE.

O. WARRANTY

- EQUIPMENT, MATERIALS AND WORKMANSHIP FURNISHED UNDER THIS CONTRACT SHALL BE GUARANTEED BY THE CONTRACTOR FOR A PERIOD OF ONE YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THE WORK BY THE OWNER. THE CONTRACTOR SHALL KEEP THE WORK IN GOOD REPAIR FOR ONE YEAR AFTER THE DATE OF FINAL APPROVAL. THE CONTRACTOR SHALL, AT HIS OWN EXPENSE, PROMPTLY CORRECT AND REPAIR ANY AND ALL BREAKS, FAILURES OR WEAR DUE TO FAULTY MATERIALS, WORKMANSHIP OR EQUIPMENT. ALL SETTLEMENTS OF SURFACES THAT MAY OCCUR WITHIN THAT PERIOD SHALL ALSO BE PROMPTLY REPAIRED.

JOYBIRD


CONSULTANTS
(MEP ENGINEER):

NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE 49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

ISSUANCE NAME DATE
CD SET 07-28-25
1 LL COMMENTS 08-13-25



PROJECT NUMBER: 24-343
PLUMBING
NOTES, SYMBOLS,
ABBREVIATIONS &
SPECIFICATIONS

P0.01



PLUMBING SANITARY AND VENT PLAN | 1

△ ISSUANCE NAME: DATE: 07-28-25
CD SET: 07-13-25
1 LL COMMENTS: 08-13-25





PROJECT NUMBER: 24-343
PLUMBING SANITARY AND VENT FLOOR PLAN

P1.01

CONSULTANTS (MEP ENGINEER):
NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE 49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

JOYBIRD



PLUMBING WATER FLOOR PLAN | 1
3/16" = 1'-0"

GENERAL NOTES:	
1.	CW/HW PIPING TO BE PROVIDED WITH INSULATION AS PER 2021 INTERNATIONAL ENERGY CONSERVATION CODE (REFER SHEET P.01)
2.	PROVIDE BRANCH PRV IF PRESSURE EXCEEDS 80 PSI.
3.	CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SLAB PENETRATION AS PER STRUCTURAL REQUIREMENT.
4.	PROVIDE ACCESS PANELS FOR WATER HAMMER ARRESTOR, CLEANOUTS & SHUT-OFF VALVES AS REQUIRED.
5.	REFER RISER DIAGRAMS FOR ALL PIPE SIZES.
6.	PROVIDE TRAP PRIMER/SEAL ON FLOOR DRAIN AS PER LOCAL JURISDICTION.

DOMESTIC WATER KEYED NOTES:	
1	EXISTING WATER CLOSET WITH EXISTING WATER PIPING WITH ASSOCIATED ACCESSORIES AND FITTINGS TO REMAIN. CONTRACTOR TO FIELD VERIFY EXISTING CONDITION OF PIPING AND FIXTURE, REPLACE IF REQUIRED.
2	EXISTING LAVATORY WITH EXISTING WATER PIPING WITH ASSOCIATED ACCESSORIES AND FITTINGS TO REMAIN. CONTRACTOR TO FIELD VERIFY EXISTING CONDITION OF PIPING AND FIXTURE, REPLACE IF REQUIRED.
3	EXISTING MOP SINK TO BE REPLACED WITH NEW MOP SINK AT SAME PLACE. CONTRACTOR TO FIELD VERIFY THE EXISTING WATER PIPING AND REUSE, PLACED IF REQUIRED.
4	EXISTING WATER HEATER WITH EXISTING WATER PIPING WITH ASSOCIATED ACCESSORIES AND FITTINGS TO REMAIN. CONTRACTOR TO FIELD VERIFY EXISTING WATER HEATER CONDITION, LOCATION AND CAPACITY. UPGRADE OR REPLACE IF REQUIRED.
5	EXTEND AND CONNECT NEW 1/2" CW PIPING TO EXISTING CW PIPE IN SPACE. CONTRACTOR TO FIELD VERIFY SIZE AND LOCATION OF EXISTING CW LINE. UPGRADE IF REQUIRED.
6	EXTEND AND CONNECT NEW 1/2" HW PIPING TO EXISTING HW PIPE IN SPACE. CONTRACTOR TO FIELD VERIFY SIZE AND LOCATION OF EXISTING HW LINE. UPGRADE IF REQUIRED.
7	PROVIDE THERMOSTATIC MIXING VALVE. SET MAXIMUM TEMPERATURE TO 110° F

CONSULTANTS
(MEP ENGINEER):
NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM


JOYBIRD

ISSUANCE NAME: DATE:
CD SET: 07-28-25
1 LL COMMENTS: 08-13-25


PROJECT NUMBER: 24-343

PLUMBING WATER
FLOOR PLAN


P1.02



1 P2.01 N.T.S PIPE SLEEVE THRU WALL SECTION



2 P2.01 N.T.S FLOOR DRAIN DETAIL




PC TO PROVIDE WATER HAMMER ARRESTERS BY SIOUX CHIEF, PRECISION PLUMBING PRODUCTS, WATTS OR APPROVED EQUIVALENT WITH PISTON AND O-RING CONSTRUCTION, HAVING PDI #WH-201, ASSE #1010 AND ANSI #A112.26.1M CERTIFICATION. INSTALL IN HORIZONTAL OR VERTICAL POSITION, BUT NEVER UPSIDE DOWN. INSTALL IN LINE WITH WATER FLOW DIRECTION IF POSSIBLE. SIZE THE UNITS AS SHOWN ON THE DRAWINGS AND/OR PER THE TABLES SHOWN ABOVE


NOTE:

1. PROVIDE ASSE 1010 APPROVED WATER HAMMER ARRESTOR FOR FIXTURES WITH QUICK CLOSING VALVE.

NOTE:



4 P2.01 N.T.S HANGER DETAIL



5 P2.01 N.T.S INSULATION OF PIPING, VALVES AND FITTINGS FOR EXPOSED AND CONCEALED LOCATIONS

CONSULTANTS
(MEP ENGINEER):

NY ENGINEERS

NEARBY ENGINEERS

382 NE 191ST STREET SUITE
49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

JOYBIRD

ISSUANCE NAME DATE
CD SET 07-28-25
1 LL COMMENTS 08-13-25


PROJECT NUMBER: 24-343

PLUMBING
DETAILS


P2.01

PLUMBING FIXTURE SCHEDULE								
LEGEND	PLUMBING FIXTURE	CONNECTION SIZE - INCHES						
		TRAP	SOIL/WASTE	VENT	COLD WATER	HOT WATER	THERMOSTATIC MIXING VALVE	
EX.WC	EXISTING WATER CLOSET	E	E	E	E	-	-	EXISTING TO REMAIN
EX.LAV	EXISTING LAVATORY	E	E	E	E	E	E	EXISTING TO REMAIN
P-03	BREAK ROOM SINK	1½"	2"	1½"	½"	½"	-	ELKEY SINK: LRAD1517551 FAUCET: LKAV4032
(P-0)	MOP SINK	2"	3"	2"	¾"	¾"	-	SB-902 STERN WILLIAMS, FAUCET: FIAT 830-AA OR EQUIVANT
DF-1	DRINKING FOUNTAIN	1½"	2"	1½"	½"	-	-	P-TRAP

NOTE: CONTRACTOR TO COORDINATE WITH ARCHITECTURAL DRAWINGS FOR ALL PLUMBING FIXTURES SPECIFICATIONS AND MOUNTING HEIGHT INSTALLATION.



1 SANITARY AND VENT RISER



2 DOMESTIC WATER RISER

ISSUANCE NAME: DATE: 07-28-25
CD SET: 07-13-25
1 LL COMMENTS: 08-13-25

PROJECT NUMBER: 24-343
PLUMBING SCHEDULE & RISERS

CONSULTANTS (MEP ENGINEER):

NY ENGINEERS
NEARBY ENGINEERS
382 NE 191ST STREET SUITE 49674, MIAMI, FL 33179
PH - (646) 837-9217
WWW.NY-ENGINEERS.COM

JOYBIRD