


MECHANICAL SYMBOLS LIST		ARKANSAS BUILDING DEPARTMENT MECHANICAL NOTES		NOTE TO CONTRACTOR		
  EQUIPMENT SYMBOL		ALL WORK SHALL COMPLY WITH APPLICABLE SECTIONS OF 2021-IBC AND RULES AND REGULATIONS OF THE ARKANSAS DEPARTMENT OF BUILDINGS TO DATE.		1. PLAN INSTALLATION OF NEW WORK AND CONNECTIONS TO EXISTING WORK TO INSURE MINIMUM INTERFERENCE WITH REGULAR OPERATION OF EXISTING FACILITIES. ALL SYSTEM SHUTDOWNS AFFECTING OTHER AREAS SHALL BE COORDINATED WITH BUILDING OWNER. INSTALL ISOLATION VALVES AT POINT OF CONNECTION TO THE EXISTING PIPING. PROVIDE TEMPORARY DUCT CAPS AND/OR CONNECTIONS TO MINIMIZE SHUTDOWN TIME.		
AIR DEVICES		11. SUPPORT ALL DUCTWORK AND PIPING FROM BUILDING STRUCTURE AND/OR FRAMING IN AN APPROVED MANNER WHERE OVERHEAD CONSTRUCTION DOES NOT PERMIT FASTENING OR SUPPORTS FOR EQUIPMENT, FURNISH ADDITIONAL FRAMING INSERTS SHALL BE STEEL, SLOTTED TYPE AND FACTORY PAINTED. MULTI-ROD SHALL BE SIMILAR TO FEE & MASON SERIES 9000 WITH END CAPS AND CLOSURE STRIPS. MAXIMUM LOADING INCLUDING PIPES, DUCTWORK CONTENTS AND COVERING SHALL NOT EXCEED 75% OF RATED INSERT CAPABILITY. WHEN SUPPORTING FROM BUILDING USE BEAM CLAMPS IN APPROVED MANNER.		18. LOCATIONS AND SIZES OF ALL FLOOR, WALL, AND ROOF OPENINGS SHALL BE COORDINATED WITH ALL OTHER TRADES INVOLVED.		
 CEILING DIFFUSER SUPPLY		12. PROVIDE ALL NECESSARY FLASHING AND COUNTER FLASHING TO MAINTAIN THE WATERPROOFING INTEGRITY OF THIS BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF PIPES, DUCTS, LOUVERS, CONDUIT, AND EQUIPMENT. PROVIDE EQUIPMENT CURBS AND DUNNAGE STEEL AS REQUIRED.		19. ALL OPENINGS IN FIRE WALLS DUE TO DUCTWORK, PIPING, CONDUIT, ETC., SHALL BE FIRE STOPPED WITH A PRODUCT SIMILAR TO 3M OR APPROVED EQUAL.		
 CEILING DIFFUSER RETURN		13. SEAL OPENINGS AROUND DUCTS AND PIPING THROUGH PARTITIONS, WALLS AND FLOORS WITH MINERAL WOOL OR OTHER NONCOMBUSTIBLE MATERIAL (FIBERGLASS INSULATION IS NOT ACCEPTABLE).		20. ALL DCONDENSATE DRAIN LINES FROM EACH ROOF TOP UNIT SHALL BE PIPED FULL SIZE OF THE UNIT DRAIN OUTLET, WITH "P" TRAP, AND PIPED TO THE NEAREST DRAIN. SEE THE DETAILS SHOWN IN THE DRAWINGS OR THE CONTRACT SPECIFICATIONS FOR THE DEPTH OF THE AIR CONDITIONING CONDENSATE TRAP.		
 CEILING DIFFUSER EXHAUST		14. INSTALL WORK SO AS TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE AND REPAIR. MINOR DEVIATIONS FROM DRAWINGS MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST SHALL NOT BE MADE WITHOUT APPROVAL.		21. REFER TO TYPICAL DETAILS FOR DUCTWORK, PIPING, AND EQUIPMENT INSTALLATION.		
 SIDEWALL/DUCT MOUNTED GRILLE-SUPPLY		15. ACCESS DOORS ARE REQUIRED FOR ALL BUILDING SERVICE VALVES THAT RUN THROUGH THE SPACE, AND ACCESS DOOR SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL. COORDINATE ALL LOCATIONS OF ACCESS DOORS WITH THE ARCHITECT.		22. ALL TESTS SHALL BE COMPLETED BEFORE ANY MECHANICAL EQUIPMENT OR PIPING INSULATION IS APPLIED.		
 SIDEWALL/DUCT MOUNTED GRILLE-RETURN		16. REMOVABLE ACCESS TILE AND/OR ACCESS DOOR ARE REQUIRED IN HUNG CEILINGS, SHAFTS AND WALLS FOR ALL VOLUME AND FIRE DAMPERS, AUTOMATIC DAMPERS AND ALL OTHER MECHANICAL EQUIPMENT AND DAMPERS. HVAC CONTRACTOR TO FURNISH ACCESS LOCATION REQUIREMENTS TO GENERAL CONTRACTOR. ACCESS TILE IDENTIFICATION: PROVIDE BUTTONS, TABS, AND MARKERS TO IDENTIFY LOCATION OF CONCEALED VALVES, DAMPERS AND EQUIPMENT.		23. TESTING, ADJUSTING, AND BALANCING AGENCY SHALL BE A MEMBER OF THE ASSOCIATED AIR BALANCE COUNCIL (AABC) OR THE NATIONAL ENVIRONMENTAL BALANCING BUREAU (NEBB). TESTING, ADJUSTING, AND BALANCING SHALL BE PERFORMED IN ACCORDANCE WITH THE AABC STANDARDS.		
DUCT ACCESSORIES		17. THE CONTRACTOR SHALL KEEP ALL EQUIPMENT AND MATERIALS, AND ALL PARTS OF THE BUILDING, EXTERIOR SPACES AND ADJACENT STREETS, SIDEWALKS AND PAVEMENTS, FREE FROM MATERIAL AND DEBRIS RESULTING FROM THE EXECUTION OF THIS WORK. EXCESS MATERIALS WILL NOT BE PERMITTED TO ACCUMULATE EITHER ON THE INTERIOR OR THE EXTERIOR.		HVAC DUCTWORK – SHEET METAL		
 VOLUME DAMPER W/ ACCESS DOOR		18. UNLESS OTHERWISE SPECIFICALLY SPECIFIED, INCLUDE ALL CUTTING AND PATCHING OF EXISTING FLOORS, WALLS, PARTITIONS AND OTHER MATERIALS IN THE EXISTING BUILDING. THE CONTRACTOR SHALL RESTORE THESE AREAS TO ORIGINAL CONDITION.		1. CERTAIN ITEMS SUCH AS RISES AND DROPS IN DUCTWORK ACCESS DOORS, VOLUME DAMPERS, ETC., ARE INDICATED ON THE CONTRACT DOCUMENT DRAWINGS FOR CLARITY FOR A SPECIFIC LOCATION REQUIREMENT AND SHALL NOT BE INTERPRETED AS THE EXTENT OF THE REQUIREMENTS FOR THESE ITEMS.		
 FIRE DAMPER W/ ACCESS DOOR		19. MATERIALS AND WORKMANSHIP, UNLESS OTHERWISE NOTED, SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.		2. CONTRACTOR TO CHECK AND CORRECT ANY AND ALL DEFICIENCIES IN EXISTING DUCTS. ALL NEW DUCTWORK WILL COMPLY WITH THE LATEST SMACNA GUIDELINES AND CONFORM WITH REQUIREMENTS OF THE LATEST HANDBOOKS PUBLISHED BY ASHRAE.		
 MOTORIZED DAMPER W/ ACCESS DOOR		20. ALL EQUIPMENT SHALL BE PROVIDED WITH ONE YEAR WARRANTY PARTS AND LABOR AND FIVE YEARS ON COMPRESSORS. WARRANTY PERIOD BEGINS UPON PROJECT ACCEPTANCE.		3. PROVIDE VOLUME DAMPER AT EACH TAP TO MAIN DUCT AND WHERE NECESSARY TO PROPERLY BALANCE SYSTEM.		
CONTROLS & SENSORS		21. ALL MATERIAL AND EQUIPMENT TO BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.		4. SUPPLY AND RETURN DUCTWORK 10' FROM ALL HVAC UNITS SHALL BE LINED WITH 1.5" ACOUSTICAL LINING.		
 CEILING DIFFUSER SUPPLY		22. THE CONTRACTOR SHALL BE RESPONSIBLE FOR HIS WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF THE SAME WHICH MAY BE DAMAGED, LOST, OR STOLEN WITHOUT ADDITIONAL COST TO THE OWNER.		5. RE-INSULATE ALL DUCTWORK AND PIPING IN WHICH INSULATION HAS BEEN REMOVED OR DAMAGED WITH INSULATION EQUAL TO THE EXISTING INSULATION.		
 MANUAL ON/OFF SWITCH		23. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FAILURE OF ANY DUCTWORK SYSTEM OR EQUIPMENT TO FUNCTION PROPERLY UPON COMPLETION OF HIS WORK UPON SAID SYSTEM OR EQUIPMENT.		6. CONTRACTOR SHALL SUPPLY AND INSTALL ALL NECESSARY SUPPLY DIFFUSERS AND RETURN AIR REGISTERS WHERE INDICATED ON THE DRAWING. COORDINATE LOCATION OF DIFFUSERS AND REGISTERS WITH REFLECTED CEILING PLAN.		
 DUCT SMOKE DETECTOR		24. SUBMIT SHOP DRAWING OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES.		7. IN CORRIDORS WHERE CEILING SPEAKERS AND AIR DIFFUSERS ARE INDICATED BETWEEN THE SAME LIGHT FIXTURES, INSTALL BOTH DEVICES AT THE QUARTER POINTS BETWEEN THE FIXTURES.		
 CO2 DETECTOR		25. ALL MATERIAL AND EQUIPMENT TO BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.		8. UNLESS OTHERWISE SHOWN, LOCATE ALL ROOM THERMOSTATS 4'-0" (CENTER LINE) ABOVE THE FINISHED FLOOR. NOTIFY THE ENGINEER OF ANY ROOMS WHERE THE PRECEDING LOCATION CANNOT BE MAINTAINED OR WHERE THERE IS A QUESTION ON LOCATION.		
 TEMPERATURE SENSOR		26. SUBMISSION OF A PROPOSAL SHALL BE CONSTRUED AS EVIDENCE THAT A CAREFUL EXAMINATION OF THE PORTIONS OF THE EXISTING BUILDING, EQUIPMENT, ETC., WHICH AFFECT THIS WORK, AND THE ACCESS TO SUCH SPACES, HAS BEEN MADE AND THAT THE CONTRACTOR IS FAMILIAR WITH EXISTING CONDITIONS AND DIFFICULTIES THAT MAY AFFECT THE EXECUTION OF THE WORK. LATER CLAIMS SHALL NOT BE MADE FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WHICH COULD HAVE BEEN FORESEEN DURING SUCH AN EXAMINATION. THE ON-SITE INSPECTION SHALL VERIFY EXISTING DUCTWORK, PIPING (SIZES, CLEARANCES, ETC) AND CONDITIONS.		9. ALL CONTROL WIRE AND CONDUIT SHALL COMPLY WITH THE NATIONAL ELECTRIC CODE AND ELECTRICAL DIVISION OF THE SPECIFICATION.		
DUCTWORK		27. INSURANCE: IN ACCORDANCE WITH BUILDING REQUIREMENTS THE CONTRACTOR SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND ENGINEER.		10. PROVIDE VIBRATION ISOLATION FOR ALL MECHANICAL EQUIPMENT TO PREVENT TRANSMISSION OF VIBRATION TO BUILDING STRUCTURE.		
 AIR DUCT W/ 1.5" ACOUSTICAL LINING		28. THE FINAL ACCEPTANCE WILL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, BALANCED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATES OF INSPECTION AND APPROVAL.		11. LOCATE ALL TEMPERATURE AND FLOW MEASURING DEVICES IN ACCESSIBLE LOCATIONS WITH THE STRAIGHT SECTION OF PIPE OR DUCT UP AND DOWNSTREAM AS RECOMMENDED BY THE MANUFACTURER FOR GOOD ACCURACY.		
 FLEXIBLE DUCT		29. SPECIFICATIONS ARE OF SIMPLIFIED FORM AND INCLUDE INCOMPLETE SENTENCES. WORDS OR PHRASES SUCH AS "THE CONTRACTOR SHALL," "SHALL BE," "FURNISH," "PROVIDE," "A," "THE," AND "ALL" HAVE BEEN OMITTED FOR BREVITY.		12. WHERE BEAMS ARE INDICATED TO BE PENETRATED WITH DUCTWORK OR PIPING, COORDINATE DUCTWORK AND PIPING LAYOUT WITH BEAM OPENING SIZE AND OPENING LOCATIONS. COORDINATION SHALL BE DONE PRIOR TO THE FABRICATION OF DUCTWORK, CUTTING OF PIPING, OR FABRICATION OF BEAMS.		
 FLEXIBLE CONNECTION		30. WHERE A CONFLICT EXISTS BETWEEN THE DRAWINGS, THE SPECIFICATIONS OR ANY OTHER CONSTRUCTION DOCUMENT, THE ONE WITH THE MOST STRINGENT REQUIREMENT(S) SHALL APPLY.		13. ALL MISCELLANEOUS STEEL REQUIRED TO ENSURE PROPER INSTALLATION AND AS SHOWN IN THE DETAILS FOR DUCTWORK, AND EQUIPMENT (UNLESS OTHERWISE NOTED) SHALL BE FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR.		
 24X12 RECTANGULAR DUCT (WIDTH X DEPTH)				14. PROVIDE ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS, WHERE REQUIRED, TO SERVICE DAMPERS, VALVES, SMOKE DETECTORS, AND OTHER CONCEALED MECHANICAL EQUIPMENT. ACCESS PANELS SHALL BE TURNED OVER TO THE GENERAL CONTRACTOR FOR INSTALLATION. ACCESS PANELS SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL.		
 Ø12 ROUND DUCT (DIAMETER)				15. MECHANICAL EQUIPMENT, DUCTWORK, AND PIPING SHALL NOT BE SUPPORTED FROM A METAL DECK.		
 ROUND DUCT CROSS SECTION				16. ALL EQUIPMENT, PIPING, DUCTWORK, ETC., SHALL BE SUPPORTED AS DETAILED, SPECIFIED AND REQUIRED TO PROVIDE A VIBRATION-FREE INSTALLATION.		
 SUPPLY AIR RECTANGULAR DUCT CROSS SECTION				17. RUNS OF FLEXIBLE DUCT SHALL NOT EXCEED 5 FT.		
 RETURN AIR RECTANGULAR DUCT CROSS SECTION				18. ALL DUCTWORK SHALL BE COORDINATED WITH ALL TRADES INVOLVED. OFFSETS IN DUCTS, INCLUDING DIVIDED DUCTS AND TRANSITIONS AROUND OBSTRUCTIONS, SHALL BE PROVIDED AT NO ADDITIONAL COST TO THE OWNER.		
MECHANICAL ABBREVIATIONS				19. PROVIDE ACCESS DOORS IN DUCTWORK TO PROVIDE ACCESS FOR ALL SMOKE DETECTORS, FIRE DAMPERS, SMOKE DAMPERS, VOLUME DAMPERS, COILS, AND OTHER ITEMS LOCATED IN THE DUCTWORK THAT REQUIRE SERVICE AND/OR INSPECTION.		
AL	ACOUSTIC LINING			20. PROVIDE ACCESS DOORS IN DUCTWORK FOR THE OPERATION, ADJUSTMENT, AND MAINTENANCE OF ALL FANS, VALVES, AND MECHANICAL EQUIPMENT.		
CDS	CEILING DIFFUSER SUPPLY			21. ALL DUCTS SHALL BE GROUNDED ACROSS FLEXIBLE CONNECTIONS WITH FLEXIBLE COPPER GROUNDING STRAPS. GROUNDING STRAPS SHALL BE BOLTED OR SOLDERED TO BOTH THE EQUIPMENT AND THE DUCT.		
CDR	CEILING DIFFUSER RETURN			22. SMOKE DETECTORS SHALL BE FURNISHED AND WIRED BY THE ELECTRICAL CONTRACTOR. THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR MOUNTING THE SMOKE DETECTOR IN DUCTWORK AS SHOWN ON THE DRAWINGS AND IN ACCORDANCE WITH THE MANUFACTURER'S PRINTED INSTRUCTIONS.		
CFM	CUBIC FEET OF AIR PER MINUTE			23. SEE SPECIFICATIONS FOR DUCTWORK GAUGES, BRACING, HANGERS, AND OTHER REQUIREMENTS.		
COD	CORD OPERATED DAMPER			CODE COMPLIANCE		
DN	DOWN			ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTHING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECTS:		
EA	EXHAUST AIR			a. INTERNATIONAL BUILDING CODE 2021		
EDH	ELECTRIC DUCT HEATER			b. ARKANSAS MECHANICAL CODE 2021		
EF	EXHAUST FAN			c. ARKANSAS PLUMBING CODE 2018		
FD/AD	FIRE DAMPER W/ACCESS DOOR			d. ARKANSAS FUEL GAS CODE 2018		
EG	EXHAUST GRILLE			e. INTERNATIONAL ENERGY CONSERVATION CODE 2009		
MD	MOTORIZED DAMPER			f. NATIONAL ELECTRICAL CODE 2020		
RTU	ROOF TOP UNIT			GRAPHIC SCALE		
RG	RETURN GRILLE			SEAL PROJECT NO. _____		
RA	RETURN AIR			SCALE AS NOTED		
SEER	SEASONAL ENERGY EFFICIENCY RATIO			DRAWN BY NYE		
SG	SUPPLY GRILL			CHECKED BY NYE		
SA	SUPPLY AIR			DATE 06/04/2025		
VD	VOLUME DAMPER			SHEET NUMBER M0.1		
TEF	TOILET EXHAUST FAN					
MECHANICAL DRAWING LIST						
MO.1	MECHANICAL GENERAL NOTES, ABBREVIATIONS & SYMBOLS LIST					
MO.2	MECHANICAL SPECIFICATIONS (1 OF 2)					
MO.3	MECHANICAL SPECIFICATIONS (2 OF 2)					
M1.1	MECHANICAL FLOOR PLAN					
M3.1	MECHANICAL ROOF PLAN					
M4.1	MECHANICAL DETAILS					
M5.1	MECHANICAL SCHEDULES					
M6.1	MECHANICAL HOOD DATA					

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

MECHANICAL GENERAL NOTES, ABBREVIATIONS & SYMBOLS LIST

PHYSICAL LOCATION

PROJECT NAME

DRAWING TITLE

GRAPHIC SCALE

SEAL

PROJECT NO. _____

SCALE

AS NOTED

DRAWN BY

NYE

CHECKED BY

NYE

DATE

06/04/2025

SHEET NUMBER

M0.1

||
||
||

1.2 MATERIALS

- A. SINGLE-WALL RECTANGULAR DUCTS AND FITTINGS.
- B. SINGLE-WALL ROUND AND FLAT-oval DUCTS AND FITTINGS.
- C. SHEET METAL MATERIALS:

- 1. GALVANIZED SHEET STEEL.
- 2. STAINLESS-STEEL SHEETS.
- 3. ALUMINUM SHEETS.
- 4. FACTORY-APPLIED ANTI-MICROBIAL COATING.

D. DUCT LINER:

- 1. FIBROUS GLASS, TYPE I, FLEXIBLE.
- 2. FLEXIBLE ELASTOMERIC.
- 3. NATURAL FIBER.

E. SEALANT MATERIALS:

- 1. TWO-PART TAPE SEALING SYSTEM.
- 2. WATER-BASED JOINT AND SEAM SEALANT.
- 3. SOLVENT-BASED JOINT AND SEAM SEALANT.
- 4. FLANGED JOINT SEALANT.
- 5. FLANGE GASKETS.
- 6. ROUND DUCT JOINT O-RING SEALS.

1.3 DUCT CLEANING

- A. CLEAN EXISTING DUCT SYSTEM(S) BEFORE TESTING, ADJUSTING, AND BALANCING.

B. CLEAN THE FOLLOWING ITEMS:

- 1. AIR OUTLETS AND INLETS.
- 2. SUPPLY, RETURN, AND EXHAUST FANS.
- 3. AIR-HANDLING UNITS.
- 4. COILS AND RELATED COMPONENTS.
- 5. RETURN-AIR DUCTS, DAMPERS, ACTUATORS, AND TURNING VANES.
- 6. SUPPLY-AIR DUCTS, DAMPERS, ACTUATORS, AND TURNING VANES.
- 7. DEDICATED EXHAUST AND VENTILATION COMPONENTS AND MAKEUP AIR SYSTEMS.

1.4 DUCT SCHEDULE

- A. ALL DUCTS SHALL BE GALVANIZED STEEL EXCEPT AS FOLLOWS:

- 8. MOIST ENVIRONMENT DUCT MATERIAL: ALUMINUM.

KITCHEN EXHAUST DUCTWORK:

- A. ALL HORIZONTAL AND VERTICAL KITCHEN EXHAUST DUCTWORK SHALL BE CONSTRUCTED OF 16 GAUGE MINIMUM BLACK IRON OR PREFABRICATED DOUBLE WALL GREASE DUCTWORK APPROVED FOR KITCHEN EXHAUST APPLICATION WITH ETL LISTED TO UL 1978 AND UL 2221 SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER INSTALLATION INSTRUCTIONS AND LOCAL CODES SHALL SEAMS AND JOINTS SHALL HAVE A LIQUID TIGHT CONTINUOUS EXTERNAL WELD AS PER NFPA 96 FOR BLACK IRON DUCTWORK. THE EXTERIOR OF ALL KITCHEN RANGE BLACK IRON EXHAUST DUCTS SHALL HAVE 1-1/2" X 1-1/2" X 1-1/8" WELDED ANGLES, PUNCHED FOR SECURING BLOCK INSULATION. WHERE KITCHEN RANGE BLACK IRON EXHAUST DUCT RISER PASSED VERTICALLY THROUGH FLOORS OF THE BUILDING, PROVIDE ANGLE CLIPS WELDED TO THE DUCT OF REQUIRED SIZES TO SUPPORT THE WEIGHT OF THE RISER SECTIONS ON THE BUILDING STRUCTURE AT EACH OF THE FLOOR LEVELS. PROVIDE AND INSTALL ALL SUPPLEMENTARY STRUCTURAL STEEL IN SHAFTS TO PROPERLY SUPPORT EXHAUST DUCTWORK FROM BUILDING CONSTRUCTION. PROVIDE MINIMUM 12"X12" ACCESS DOOR ON SIDE OF HORIZONTAL DUCTS AT 12' SPACING. ACCESS DOORS SHALL BE SIMILAR TO DESCRIPTION IN "ACCESS DOORS IN SHEET METAL WORK WORK" EXCEPT THAT DOOR GAUGE SHALL BE THE SAME AS DUCT GAUGE. ALL HORIZONTAL DUCTS SHALL BE PITCHED BACK TO HOODS 1/4" PER FOOT OR MAXIMUM PITCH ATTAINABLE. THIS TRADE SHALL DRILL OR CUT ALL REQUIRED OPENING AS REQUIRED BY THE DUCTS EXTINGUISHING SYSTEM AND AS COORDINATED WITH THE TRADE SUPPLYING THE EXTINGUISHING SPRAY HEADS. MAINTAIN 6" CLEARANCE BETWEEN SHEET METAL DUCT AND ANY SURFACE SUCH AS SLAB, BEAM OR SHAFT ENCLOSURE.

- B. ALL HORIZONTAL AND VERTICAL KITCHEN RANGE BLACK IRON EXHAUST DUCTWORK GAUGES SHALL BE AS FOLLOWS.

SIZE	GAUGE BLACK IRON
------	------------------

LESS THAN 155 SQIN	16
155-200 SQIN	14
201-255 SQIN	12

- C. ALL EXHAUST DUCT WORK FROM DISHWASHERS, POT SINKS, OVENS, OR OTHER KITCHEN APPARATUS EMITTING HEAT OR VAPOR (OTHER THAN RANGE HOOD EXHAUST) SHALL BE CONSTRUCTED OF ALUMINUM WITH WELDED JOINTS (USING SMACNA STANDARDS) AND MADE WATERTIGHT. THIS INCLUDES ALL DUCTWORK FROM THE EQUIPMENTS TO THE EXHAUST FAN AND FROM THE EXHAUST FAN TO THE DISCHARGE AIR LOUVERS. THE DUCTS SHALL PITCH BACK TO THE DISHWASHER FROM THE VERTICAL RISER OR WHERE THE RUN OF DUCT IS TOO LONG SHALL CHANGE PITCH TO DRAIN TO

THE BOTTOM OF THE RISER, WHERE DUCTS LEAVE SHAFT TO ENTER THE EXHAUST FAN THEY SHALL ALSO BE PITCHED TO A LOW POINT AWAY FROM THE WELD 3/4" DRAINS AT ALL LOW POINTS AND RUN TO THE NEAREST DRAIN. THIS TRADE SHALL BE HELD RESPONSIBLE TO PROVIDE A WATERTIGHT AND DRAINED SYSTEM. REGARDLESS OF THE QUANTITY OF STEAM OR WATER VAPOR LEAVING THE EQUIPMENTS.

END OF SECTION 233113

02	06/04/2025	PERMIT SET
01	05/06/2025	REVISED CHECK SET
00	04/29/2025	CHECK SET
NO.	DATE	ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

PROJECT NAME

PHYSICAL LOCATION

DRAWING TITLE

**MECHANICAL
SPECIFICATIONS
(2 OF 2)**

GRAPHIC SCALE

SEAL

PROJECT NO.

SCALE

AS NOTED

DRAWN BY

NYE

CHECKED BY

NYE


DATE

06/04/2025

SHEET NUMBER

M0.3

Property of NY Engineers



MECHANICAL FLOOR PLAN KEY NOTES

1. 1" CONDENSATE DRAIN PIPE WITH CONDENSATE DRAIN PUMP TO LAVATORY WASTE W/AIR GAP FITTING. COORDINATE W/ PLUMBING CONTRACTOR IN FIELD.
2. CONTRACTOR SHALL PROVIDE FIELD MANUFACTURED FILTER RACK AT THE UNIT INLET. COORDINATE WITH ARCHITECT FOR ACCESS DOOR FOR FILTER.
3. INSTALL REFRIGERANT PIPING BETWEEN INDOOR AND OUTDOOR UNITS AS PER MANUFACTURERS RECOMMENDATIONS. PROVIDE INSULATION TO REFRIGERANT PIPING AS PER 2009 IECC. COORDINATE PIPE ROUTING WITH ARCHITECT/OWNER.
4. THE AC-3(N) AND AC-4(N) SHALL BE INTERLOCKED WITH THE KITCHEN EXHAUST HOOD SYSTEM AND ENSURE THAT THE AC-3(N) AND AC-4(N) ONLY OPERATES WHEN THE EXHAUST FAN IS WORKING.
5. LOCATION OF DIGITAL THERMOSTAT CONTROL. INSTALL AND WIRE NEW 7-DAY PROGRAMMABLE THERMOSTAT. COORDINATE EXACT LOCATION WITH ARCHITECT AND OWNER PRIOR TO ROUGH-IN.
6. PROVIDE AND INSTALL Ø3"/Ø5" CONCENTRIC VENT LINE FOR EXHAUST /COMBUSTION AIR INTAKE FROM WATER HEATER AND TERMINATE THROUGH SIDE WALL. PVC/CPVC APPROVED POLYPROPYLENE AND STAINLESS STEEL MATERIAL WITH TERMINATION KIT SHALL BE PROVIDED. INSTALL AS PER MANUFACTURERS INSTRUCTION.
7. ROUTE 8"Ø TOILET EXHAUST DUCT TERMINATED TOWARDS THE EXTERIOR WALL AND MAINTAIN 3 FEET FROM OPERABLE OPENINGS INTO BUILDINGS AND 10 FEET FROM MECHANICAL AIR INTAKES.
8. ROUTE 6"Ø EXHAUST DUCT TO SIDE EXTERIOR WALL AND MAINTAIN A MINIMUM MAINTAIN 3 FEET FROM OPERABLE OPENINGS INTO BUILDINGS AND 10 FEET FROM MECHANICAL AIR INTAKES.
9. CONTRACTOR TO FIELD VERIFY & INSTALL THE HOOD AS PER MANUFACTURER RECOMMENDATION.
10. GREASE DUCT TO BE PROVIDED WITH KITCHEN EQUIPMENT AND INSTALLED BY MECHANICAL CONTRACTOR. INSTALL AS PER MANUFACTURER'S INSTRUCTIONS. INSTALL OWNER FURNISHED UL-2221 LISTED DOUBLE-WALL GREASE DUCT EQUAL TO CAPTIVEAIRE SYSTEMS MODEL DW-2R ROUND 20 GAUGE 430 STAINLESS STEEL INNER DUCT INSULATED WITH A 24 GAUGE OUTER SHELL FROM HOOD COLLAR TO EXHAUST FAN ON ROOF. INSTALL EXHAUST DUCT AS PER MANUFACTURER'S INSTRUCTIONS. PROVIDE CLEANOUTS AT EVERY CHANGE OF DIRECTION IN THE DUCT AND EVERY 10 FEET WITH MINIMUM OF 3 FEET OF CLEARANCE IN FRONT OF CLEAN-OUT. COORDINATE EXACT DUCT LENGTHS REQUIRED BASED ON FIELD CONDITIONS WITH MANUFACTURER.
11. 16"Ø GREASE EXHAUST DUCT FROM HOOD-1(N) UPTO ROOF LEVEL AND CONNECT WITH KEF-1(N). GREASE DUCT CONSTRUCTION SHALL BE STEEL HAVING A MINIMUM THICKNESS OF 0.0575 INCH (1.463 MM) (NO. 16 GAGE). BLACK IRON WELDED LIQUID TIGHT. PROVIDE TRANSITION AT HOOD COLLAR.
12. PROVIDE AND INSTALL EMERGENCY MANUAL SHUTDOWN PUSH BUTTON FOR HOOD-1(N). PUSH BUTTON SHALL BE IN THE PATH OF EGRESS, A MINIMUM OF 10 FT. AWAY FROM THE HOOD AND A MAXIMUM OF 20 FT.

06/04/2025	PERMIT SET
05/06/2025	REVISED CHECK SET
04/29/2025	CHECK SET
DATE	ISSUE DESCRIPTION

382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

GENERAL NOTES:

1. ALL WORK SHALL COMPLY WITH ALL LOCAL AND STATE CODES AND AUTHORITIES HAVING JURISDICTION.
2. THE CONTRACTOR SHALL SECURE AND PAY FOR ALL REQUIRED PERMITS AND ARRANGE ALL REQUIRED INSPECTIONS.
3. THE CONTRACTOR SHALL COORDINATE HIS WORK WITH OTHER CONTRACTORS AND TRADES.
4. THESE DRAWINGS, AS PREPARED, ARE DIAGRAMMATIC BUT SHALL BE FOLLOWED AS CLOSELY AS CONSTRUCTION OF THE PROJECT AND THE WORK OF THE TRADES WILL PERMIT. EQUIPMENT LOCATIONS INDICATED ARE APPROXIMATE. COORDINATE EXACT LOCATIONS AND REQUIRED CLEARANCES WITH EQUIPMENT SUPPLIER AND ALL TRADES PRIOR TO INSTALLATION.
5. THE CONTRACTOR SHALL FURNISH AND INSTALL ALL THE EQUIPMENT INDICATED WITHIN THE MECHANICAL DRAWINGS UNLESS OTHERWISE NOTED. ALL EQUIPMENT SHALL BE UL LISTED. VERIFY LOCATION AND DIMENSIONS IN THE FIELD PRIOR TO FABRICATION AND / OR INSTALLATION.
6. DUCT SIZES SHOWN ON DRAWINGS ARE CLEAR INSIDE DIMENSIONS.
7. PROVIDE MINIMUM R-5 INSULATION (INTERNAL FOR EXPOSED DUCTS AND EXTERNAL FOR CONCEALED DUCTS) FOR SUPPLY & RETURN AIR DUCTS. PROVIDE ACOUSTIC INSULATION ON MAIN SUPPLY AND RETURN DUCTS UP TO 10 FT. FROM HVAC UNIT.
8. ALL DUCTWORK SHALL BE FABRICATED, INSTALLED, SEALED, AND INSULATED PER THE LATEST ISSUE OF SMACNA LOW-VELOCITY DUCT MANUAL.
9. ALL SUPPLY, RETURN, EXHAUST GRILLES ON THE ABOVE FLOOR. EXACT LOCATION TO VERIFY WITH ARCHITECTURE.
10. THE CONTRACTOR IS TO MAKE ALL LOW-VOLTAGE WIRING CONNECTIONS FOR ALL HVAC EQUIPMENT INCLUDING TEMPERATURE CONTROLS, ROOF TOP UNITS, SMOKE DETECTORS AND CONTRACTOR PANEL.
11. PROVIDE FIRE OR FIRE+SMOKE DAMPER WHEREVER DUCTS ARE CROSSING FIRE/SMOKE RATED WALLS/ BARRIERS AS PER LOCAL CODE. COORDINATE WITH ARCHITECTURAL DRAWING FOR FIRE RATING OF THE WALLS.

PROJECT NAME

Digitized by srujanika@gmail.com


ING TITLE

MECHANICAL FLOOR

MIC. SCALE

PROJECT NO.	-
SCALE	AS NO
DRAWN BY	NYE
CHECKED BY	NYE

SHEET NUMBER
M1.1



1 MECHANICAL ROOF PLAN

MECHANICAL ROOF PLAN KEY NOTES

1. CONTRACTOR TO FURNISH AND INSTALL THE CONDENSING UNIT MOUNTING ON STEEL RAILS AS PER MANUFACTURER'S RECOMMENDATIONS. CONTRACTOR TO COORDINATE FINAL LOCATION WITH CLIENT AND ARCHITECT.
2. INSTALL NEW REFRIGERANT PIPING BETWEEN INDOOR AND OUTDOOR UNIT AS PER MANUFACTURER'S RECOMMENDATIONS. PROVIDE WEATHER PROOF COATING FOR EXPOSED PIPING. PROVIDE INSULATION TO REFRIGERANT PIPING AS PER 2009 INTERNATIONAL ENERGY CONSERVATION CODE.
3. COORDINATE THE FINAL LOCATION OF THE MECHANICAL EQUIPMENT WITH THE STRUCTURAL DRAWINGS.
4. KITCHEN EXHAUST FAN KEF-1(N) DISCHARGE SHALL BE LOCATED NOT LESS THAN 10 FEET HORIZONTALLY FROM OR NOT LESS THAN 3 FEET ABOVE AIR INTAKE OPENINGS INTO ANY BUILDING. EXHAUST AIR DISCHARGE OPENING LOCATED 40 INCHES ABOVE THE ROOF SURFACE.
5. CONTRACTOR TO PROVIDE 6" HIGH CONCRETE PADS AND VIBRATION ISOLATORS FOR INSTALLING THE NEW FANS.
6. MECHANICAL OUTSIDE AIR INTAKE OPENING SHALL BE MAINTAINED 3 FEET BELOW CONTAMINANT SOURCE AND 10 FEET HORIZONTALLY FROM ANY HAZARDOUS CONTAMINANT SOURCE.

GENERAL NOTES


- A. ALL ROOF PENETRATIONS AND REPAIRS SHALL BE BY THE GENERAL CONTRACTOR.
- B. ROOFING WORK SHALL BE PERFORMED BY THE ROOFING CONTRACTOR.
- C. PROVIDE FIRE OR FIRE+SMOKE DAMPER WHEREVER DUCTS ARE CROSSING FIRE/SMOKE RATED WALLS/ BARRIERS. COORDINATE WITH ARCHITECTURAL DRAWING FOR FIRE RATING OF THE WALLS.
- D. PROVIDE WEATHER PROOF COATING FOR EXPOSE DUCTWORK AND PIPING.
- E. COORDINATE ALL MD AND FSD WITH ELECTRICAL CONTRACTOR FOR POWER REQUIREMENT.

02	06/04/2025	PERMIT SET
01	05/06/2025	REVISED CHECK SET
00	04/29/2025	CHECK SET
NO.	DATE	ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

PROJECT NAME		
PHYSICAL LOCATION		
DRAWING TITLE		
MECHANICAL ROOF PLAN		
GRAPHIC SCALE	PROJECT NO.	
SEAL	SCALE	AS NOTED
	DRAWN BY	NYE
	CHECKED BY	NYE
	DATE	06/04/2025
	SHEET NUMBER	M3.1

Property of NY Engineers



INDOOR UNITS SCHEDULE															MAKE:	LG OR EQUIVALENT		
UNIT TAG	LOCATION	TYPE	CAP. (TON)	COOLING (MBH)	HEATING (MBH)	OA CFM	TOTAL CFM	MAX RATED ESP. (IN. W.G)	MAX. SOUND PRESS. (DBA)	ELECTRICAL DATA		DIMENSIONS (HXWXD) (IN.)		PIPE SIZE		WEIGHT (LBS.)	MODEL NO.	
AC-1(N)	SEE PLAN	R32 MULTI V™ MID STATIC DUCTED	4	48.1	54.2	300	1480	0.79	42	2.5	208-230 / 60 / 1	14"x27"x51"	3/8"	5/8"	1"	94	ZRNU483M3AA	
AC-2(N)	SEE PLAN	R32 MULTI V™ MID STATIC DUCTED	4	48.1	54.2	310	1480	0.79	42	2.5	208-230 / 60 / 1	14"x27"x51"	3/8"	5/8"	1"	94	ZRNU483M3AA	
NOTES:															1. SUPPLY AIR CFM BASED ON HIGH SPEED. 2. REFRIGERANT R32 SHALL BE PROVIDED. 3. PROVIDE ALL MOUNTING BRACKET AND ALL ASSOCIATED ACCESSORIES. 4. ALL REFRIGERANT PIPING SHALL BE SIZED AS PER MANUFACTURERS RECOMMENDATIONS. 5. PROVIDE FILTER ON ALL RETURNS TO UNIT. 6. SEE FLOOR PLAN FOR QUANTITIES. 7. INDOOR UNIT ACCESS PANEL FILED-PROVIDED. 8. CONTRACTOR SHALL PROVIDE A LONG LINE SET FOR REFRIGERANT PIPING IN THE EVENT THAT TOTAL REFRIGERANT LENGTH EXCEED THE MANUFACTURER'S STANDARD RECOMMENDED LENGTH. 9. PROVIDE ELECTRICAL POWER TO THE INDOOR UNIT FROM THE OUTDOOR UNIT AS PER MANUFACTURER RECOMMENDATIONS.			

OUTDOOR UNITS SCHEDULE															MAKE: LG OR EQUIVALENT				
UNIT TAG	NUMBER OF MODULES	LOCATION	INDOOR UNIT SERVED	CAP.TR	COOLING MBH	HEATING MBH	COMPRESSOR TYPE		UNIT DIMENSIONS IN.(HXWXD)	WEIGHT (LBS)	PIPING DIMENSION		ELECTRICAL		DUCTED		MODEL NO.		
ACCU-1(N)	1	SEE PLAN	AC-1(N)	4	48	54	HERMETICALLY SEALED SCROLL		54"x13"x37"	257	3/8"	5/8"	208-230V/60/1	31	40	54	12.2	17	ZRUM048GSS0
ACCU-2(N)	1	SEE PLAN	AC-2(N)	4	48	54	HERMETICALLY SEALED SCROLL		54"x13"x37"	257	3/8"	5/8"	208-230V/60/1	31	40	54	12.2	17	ZRUM048GSS0
NOTES:															1. UNIT SHALL HAVE 10 YEAR EXTENDED WARRANTY FOR COMPRESSOR PARTS. 2. PROVIDE LOW AMBIENT CONTROL FOR CONDENSING UNIT OPERATION DOWN TO MINUS 10 DEG.F. 3. PROVIDE COMPRESSOR CYCLE PROTECTOR. 4. PROVIDE STEEL RAILS FOR CONDENSER MOUNTING. 5. STEEL RAILS TO BE PROVIDED BY MECH CONTRACTOR. 6. CONTACT SHALL PROVIDE A LONG LINE SET FOR A REFRIGERANT PIPING IN THE EVENT THAT THE TOTAL REFRIGERANT LENGTH EXCEEDS THE MANUFACTURER STANDARDS RECOMMENDED LENGTH. 7. AIR CONDITIONER UNIT SHALL PROCESS PRODUCE NOISE LEVELS IN EXCESS OF 42dB FOR SINGLE AIR CIRCULATING DEVICE AND 45 DECIBELS FOR THE CUMULATIVE NOISE LEVEL OF MULTIPLE AIR CIRCULATING DEVICES AS MEASURED THREE FEET FROM THE NOISE SOURCE AT AN OPEN DOOR WINDOW OF THE NEARBY RESIDENCE.				

100% OA SPLIT HEAT PUMP TYPE CONDENSING UNITS SCHEDULE															MAKE: TRANE MITSUBISHI OR EQUIVALENT				
UNIT TAG	NUMBER OF MODULES	LOCATION	INDOOR UNITS SERVED	CAP.TR	COOLING MBH	HEATING MBH	COMPRESSOR TYPE	UNIT DIMENSIONS IN.(HXWXD)	WEIGHT (LBS)	PIPING DIMENSION		ELECTRICAL		SOUND LEVEL (dBA)	EER	IEER	COP	MODEL NO.	
ACCU-3 (N)	1	SEE PLANS	AC-3 (N)	8	96	108	INVERTER SCROLL HERMATIC	72X50X30	688	3/8"	7/8"	460/60/3	29	45	56	12.3	21	4	TUHYH0964AN41AN
ACCU-4 (N)	1	SEE PLANS	AC-4 (N)	8	96	108	INVERTER SCROLL HERMATIC	72X50X30	688	3/8"	7/8"	460/60/3	29	45	56	12.3	21	4	TUHYH0964AN41AN
NOTES:															1. UNIT SHALL HAVE TEN YEAR EXTENDED WARRANTY FOR COMPRESSORS/PARTS. 2. PROVIDE LOW AMBIENT CONTROL FOR CONDENSING UNIT OPERATION DOWN TO -10°F. 3. PROVIDE COMPRESSOR CYCLE PROTECTOR. 4. PROVIDE STEEL RAILS AND VIBRATION ISOLATORS FOR MOUNTING THE UNIT. 5. CONTRACTOR SHALL PROVIDE A LONG LINE SET FOR REFRIGERANT PIPING IN THE EVENT THAT TOTAL REFRIGERANT LENGTH EXCEED THE MANUFACTURER'S STANDARD RECOMMENDED LENGTH. 6. AIR CONDITIONER UNIT SHALL NOT PRODUCE NOISE LEVELS IN EXCESS OF 42 dB FOR A SINGLE AIR CIRCULATING DEVICE AND 45 DECIBELS FOR THE CUMULATIVE NOISE LEVEL OF MULTIPLE AIR CIRCULATING DEVICES AS MEASURED 3 FEET FROM THE NOISE SOURCE AT AN OPEN DOOR OR WINDOW OF A NEARBY RESIDENCE.				

100% OA SPLIT SYSTEM INDOOR SCHEDULE															MAKE: TRANE MITSUBISHI OR EQUIVALENT				
UNIT TAG	LOCATION	UNIT TYPE	CAP. (TON)	COOLING MBH	HEATING MBH	TOTAL CFM (MAX.)	OA CFM (IN. W.G)	MAX. ESP. (SOUND)	MAX. (MOP)	ELECTRICAL DATA		DIMENSIONS (HXWXD) (IN.)		PIPE SIZE		WEIGHT (LBS.)	MODEL NO.	REMARKS	
AC-3 (N)	SEE PLANS	DUCTED FCU FOR 100% OA APPLICATIONS	8.0	96.0	57.0	1200	1100	0.8	41	208-230/1/60	4.80	15	18X49X44	3/8"	7/8"	1-1/4"	177	TPEFYP0960A140A	-
AC-4 (N)	SEE PLANS	DUCTED FCU FOR 100% OA APPLICATIONS	8.0	96.0	57.0	1200	1100	0.8	41	208-230/1/60	4.80	15	18X49X44	3/8"	7/8"	1-1/4"	177	TPEFYP0960A140A	-
NOTES:															1. SUPPLY AIR CFM BASED ON HIGH SPEED. 2. REFRIGERANT R410A SHALL BE PROVIDED. 3. PROVIDE MOUNTING BRACKETS AND ALL ASSOCIATED ACCESSORIES. 4. ALL REFRIGERANT PIPING TO BE SIZED PER MANUFACTURERS RECOMMENDATIONS. 5. PROVIDE FACTORY SPECIFIED FILTER ON ALL RETURNS TO UNIT. 6. INDOOR UNIT ACCESS PANEL FIELD-PROVIDED. 7. CONTRACTOR SHALL PROVIDE A LONG LINE SET FOR REFRIGERANT PIPING IN THE EVENT THAT TOTAL REFRIGERANT LENGTH EXCEEDS THE MANUFACTURER'S STANDARD RECOMMENDED LENGTH. 8. PROVIDE ELECTRICAL POWER TO THE INDOOR UNIT FROM THE OUTDOOR UNIT AS PER MANUFACTURER RECOMMENDATIONS.				

EXHAUST FAN SCHEDULE															AIR TERMINALS SCHEDULE						
MARK	MANUFACTURER	MODEL	TYPE	AREA SERVED	FAN				ELECTRICAL				APPROXIMATE WEIGHT	ACCESSORIES	NOTES	AIR TERMINALS SCHEDULE					
					EXHAUST AIRFLOW (CFM)	EXTERNAL STATIC (IN. W.G.)	DRIVE TYPE	MOTOR HP	VOLTAGE	PHASE	MCA	MOPC				FLA	CORE VEL. FPM	N.C. LEVEL	NECK SIZE	FACE SIZE	DESCRIPTION
KEF-1 (N)	CAPTIVEAIRE	DU85HFA	ROOF MOUNTED	HOOD-1	2500	0.909	DIRECT	1.00	115	1	15	25	11.6	94	RC, FSC, GDC, WP	1,2					
EF-1 (N)	GREENHECK	SP-LP0511-1	CEILING	MEN'S RESTROOM	70	0.5	DIRECT	0.01	115	1	0.4	15	0.29	8	BD, DP, FSC, VI	3,4					
EF-2 (N)	GREENHECK	SP-LP0511-1	CEILING	WOMEN'S RESTROOM	70	0.5	DIRECT	0.01	115	1	0.4	15	0.29	8	BD, DP, FSC, VI	3,4					
EF-3 (N)	GREENHECK	SP-LP0511-1	CEILING	MOP SINK	70	0.5	DIRECT	0.01	115	1	0.4	15	0.29	8	BD, DP, FSC, VI	3,4					
OAF-1 (N)	GREENHECK	USF-08-B7	ROOF MOUNTED	SEE PLAN	610	0.8	DIRECT	0.13	460	3	1.4	15	1.1	148	MD	1,3,4					
MAF-1 (N)	GREENHECK	USF-15-B7	ROOF MOUNTED	SEE PLAN	2200	0.8	DIRECT	0.5	460	3	3.8	15	3	174	MD	1,3,4					
NOTES / ACCESSORIES:															1. PROVIDE MANUFACTURER RECOMMENDED ACCESSORIES & INSTALL AS PER MANUFACTURER'S RECOMMENDATION. 2. REFER MECHANICAL HOOD DATA ON M6.1 SHEET FOR FURTHER DETAILS.						

VENTILATION CALCULATION															AIR CURTAIN SCHEDULE						
ROOM NAME	AREA (SQ.FT.)	NUMBER OF PEOPLE/1000sq.ft AS PER IMC 2021	NUMBER OF PEOPLE AS PER IMC 2021	NUMBER OF PEOPLE AS PER ARCH LAYOUT	FINAL PEOPLE NO.	CFM/PEOPLE	CFM/SQ.FT	MIN OUTSIDE AIR AS PER REQ. OSA	PROVIDED OSA	EXHAUST AIRFLOW RATE (CFM)/(CFM/SQ.FT)		PROVIDED EXHAUST AIR CFM	AIRFLOW CFM		ELECTRICAL DATA		MOTOR QUANTITY	Motor HP	AMPS	FINISH	NOTES
										100 DINING AREA	924		70	65	37	37					
101 SERVING LINE	171	15	3	0	3	7.5	0.12	45	50	0	0	900	115	1	60	1	1/6	2.4	OBSIDIAN BLACK	1,2,3	
102 SERVING LINE	246	15	4	0	3	0	0	0	0	0	0	900	115	1	60	1	1/6	2.4	OBSIDIAN BLACK	1,2,3	
103 MEN RESTROOM	51	0	0	0	0	0	0	0	0	0	0	900	70								
104 WOMEN RESTROOM	51	0	0	0	0	0	0	0	0	0	0	900	70								
105 KITCHEN / MOP SINK	650	20	13	0	4	7.5	0.12	110	110	0	0	900	70								
TOTAL	2093				47				610		210		210								

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

02 06/04/2025 PERMIT SET
01 05/06/2025 REVISED CHECK SET
00 04/29/2025 CHECK SET
NO. DATE ISSUE DESCRIPTION

PROJECT NAME: PHYSICAL LOCATION
DRAWING TITLE: MECHANICAL SCHEDULES
GRAPHIC SCALE: M5.1

SEAL: PROJECT NO. -
SCALE: AS NOTED
DRAWN BY: NYE
CHECKED BY: NYE
DATE: 06/04/2025
SHEET NUMBER: M5.1

PLUMBING LEGEND		BUILDING DEPARTMENT PLUMBING NOTES																	
SYMBOL	DESCRIPTION	<p>B. SUBMITTALS FROM SUPPLIERS OR MANUFACTURERS WHICH DO NOT BEAR THE STAMP OF THE SUBMITTING CONTRACTOR INDICATING THAT THE CONTRACTOR HAS REVIEWED THE SUBMITTAL FOR CONFORMANCE WITH THE PROJECT REQUIREMENTS WILL BE RETURNED REJECTED.</p> <p>C. THE ENGINEER'S REVIEW OF SUBMITTALS IS A COURTESY WHICH DOES NOT RELIEVE THE CONTRACTOR FROM CONFORMING WITH THE CONSTRUCTION DOCUMENTS, REGARDLESS OF THE ACTION INDICATED BY THE SHOP DRAWINGS STAMP.</p> <p>D. REVIEW OF SHOP DRAWINGS BY THE ENGINEER SHALL BE LIMITED TO THE INITIAL REVIEW AND A SECOND REVIEW OF ANY REQUIRED RESUBMITTED DATA. IF THE ENGINEER IS REQUIRED TO REVIEW SHOP DRAWINGS FOR A THIRD (OR MORE) SUBMISSION OF THE SAME ITEM, THE CONTRACTOR SHALL BE LIABLE FOR COMPENSATING THE ENGINEER FOR THESE SUBSEQUENT REVIEWS AS PER THE ENGINEER'S CURRENT HOURLY RATE SCHEDULE.</p> <p>E. SUBMIT PROOF OF APPROVAL AND/OR CONFIRMATION OF SATISFACTORY TEST RESULTS TO THE OWNER AND THE ARCHITECT.</p> <p>F. SUBMIT TO THE OWNER'S MAINTENANCE PERSONNEL OPERATION AND MAINTENANCE DATA FOR ALL SYSTEM COMPONENTS, SERVICING REQUIREMENTS, INSPECTION DATA, REPLACEMENT PART NUMBERS AND AVAILABILITY AND CONTACT INFORMATION FOR SERVICE/SUPPLY COMPANY.</p> <p>G. FOR ALL BELOW GRADE PIPING WHERE ACTUAL INSTALLATION DEVIATES FROM CONSTRUCTION DRAWINGS, THE CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS INDICATING BELOW GRADE PIPE LOCATIONS DIMENSIONED TO NEAREST COLUMN LINES.</p> <p>H. RECORD AS-BUILT DRAWINGS SHALL BE SUPPLIED TO THE OWNER/TENANT AFTER COMPLETION OF THE WORK SHOWING ANY ALTERATIONS, ADDITIONS AND/OR DELETIONS TO THE SYSTEM(S) INSTALLED.</p> <p>1.03 SUBSTITUTIONS</p> <p>A. ALL EQUIPMENT SHALL BE PRODUCTS OF THE SPECIFIED MANUFACTURER OR MANUFACTURERS. ALL BIDS SHALL BE BASED ON THE SPECIFIED MANUFACTURER OR MANUFACTURER'S EQUIPMENT. FOR SUBSTITUTIONS OF OTHER MANUFACTURER'S EQUIPMENT TO BE CONSIDERED, THE SUBSTITUTION MUST BE INDICATED PRIOR TO BIDDING WITH THE REASON FOR THE PROPOSED SUBSTITUTION IDENTIFIED, AND THE PROPOSED CREDIT TO THE OWNER INDICATED. THE ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF ANY PROPOSED SUBSTITUTIONS.</p> <p>B. THE CONTRACTOR ASSUMES ALL RESPONSIBILITY FOR COORDINATING THE WORK OF OTHER TRADES WHICH MAY BE AFFECTED BY SUBSTITUTIONS, INCLUDING ALL RELATED COSTS.</p> <p>1.05 DEFINITIONS</p> <p>A. FURNISH: TO PURCHASE, PROCURE, ACQUIRE AND DELIVER, COMPLETE WITH RELATED ACCESSORIES.</p> <p>B. INSTALL: TO ERECT, MOUNT AND CONNECT, COMPLETE WITH RELATED ACCESSORIES.</p> <p>C. PROVIDE: TO FURNISH AND INSTALL.</p> <p>D. PLUMBING CONTRACTOR, THE CONTRACTOR, THIS CONTRACTOR: THE CONTRACTOR FOR PLUMBING WORK WHICH IS SPECIFIED HEREIN AND SHOWN ON THESE DRAWINGS.</p> <p>1.06 DRAWINGS</p> <p>A. THE DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED TO ILLUSTRATE THE GENERAL ARRANGEMENT AND ROUTING OF PIPING AND GENERAL LOCATIONS OF EQUIPMENT, PRECISE LOCATIONS OF EQUIPMENT, RISERS AND STACKS, AND ROUTING AND ELEVATION OF ALL PIPING SYSTEMS SHALL BE COORDINATED IN THE FIELD WITH THE ARCHITECT, ARCHITECTURAL DRAWINGS, THE WORK OF OTHER TRADES, EXISTING AND NEW BUILDING CONDITIONS AND/OR THE PREFERENCES OF THE OWNER/TENANT AS CONSTRUCTION PROCEEDS. ALL PIPING SHALL BE INSTALLED CONCEALED IN FINISHED SPACES, UNLESS NOTED OTHERWISE.</p> <p>B. PROVIDE ALL NECESSARY INCIDENTAL MATERIALS AND ACCESSORIES REQUIRED TO MAKE THE WORK COMPLETE IN ALL RESPECTS, EVEN IF NOT PARTICULARLY SHOWN OR SPECIFIED.</p> <p>F. IN ALL AREAS SUBJECT TO FREEZING CONDITIONS, THE CONTRACTOR SHALL PROVIDE FREEZE PROTECTION FOR ALL DOMESTIC WATER PIPING INSTALLED UNDER HIS CONTRACT.</p> <p>G. ALL ELECTRICAL REQUIREMENTS SHALL BE COORDINATED WITH THE CONTRACTOR FOR ELECTRICAL WORK. THIS CONTRACTOR IS RESPONSIBLE FOR ALL LOW VOLTAGE WIRING FOR EQUIPMENT INSTALLED UNDER HIS CONTRACT. THE CONTRACTOR FOR ELECTRICAL WORK IS RESPONSIBLE FOR LINE VOLTAGE POWER WIRING ONLY.</p> <p>H. COLOR AND FINISH SELECTIONS FOR ALL MATERIALS, INCLUDING PAINTING OF PIPING, SHALL BE AS DIRECTED AND/OR APPROVED BY THE ARCHITECT.</p> <p>I. MINOR DETAILS NOT SHOWN OR SPECIFIED, BUT NECESSARY FOR THE PROPER AND ACCEPTABLE CONSTRUCTION, INSTALLATION OR OPERATION OF ANY PART OF THE WORK AS DETERMINED BY THE ENGINEER SHALL BE INCLUDED AS IF SPECIFIED OR INDICATED ON THE DRAWINGS.</p> <p>J. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL REQUIREMENTS FOR THE INSTALLATION CONNECTION, EXTENSION OR MODIFICATION TO ALL UTILITY SERVICES WITH RESPECTIVE PROVIDERS INCLUDING PAYMENT OF ALL ASSOCIATED FEES.</p> <p>K. THE CONTRACTOR IS RESPONSIBLE FOR ALL PAINTING ASSOCIATED WITH CUTTING AND PATCHING ALL PAINTING IN AREAS WITH COMPLETE FINISH. RENOVATIONS SHALL BE PROVIDED BY THE GENERAL CONTRACTOR.</p> <p>1.02 SUBMITTALS</p> <p>A. SUBMITTAL REQUIREMENTS SHALL BE COORDINATED WITH THE ARCHITECT AND AUTHORITIES HAVING JURISDICTION, UNLESS OTHERWISE DIRECTED, CONTRACTOR SHALL PROVIDE SUBMITTALS AS LISTED BELOW.</p> <p>1. PIPE AND FITTINGS</p> <p>2. VALVES</p> <p>3. HANGERS AND SUPPORTS</p> <p>4. PLUMBING PIPING LAYOUT</p> <p>5. TESTS</p> <p>6. PLUMBING FIXTURES</p> <p>7. WATER HEATERS & ACCESSORIES</p> <p>8. MIXING VALVES</p> <p>9. ALL SCHEDULED PLUMBING EQUIPMENT</p> <p>5. COMPLY WITH NSF 61 FOR MATERIALS FOR WATER-SERVICE PIPING AND SPECIALTIES FOR DOMESTIC WATER.</p> <p>6. AS PER IECC 2009 EDITION, SECTION 504.2, WATER HEATING EQUIPMENT AND HOT WATER STORAGE TANKS SHALL MEET THE REQUIREMENTS OF TABLE 504.2, THE EFFICIENCY SHALL BE VERIFIED THROUGH DATA FURNISHED BY THE MANUFACTURER OR THROUGH CERTIFICATION UNDER AN APPROVED CERTIFICATION PROGRAM.</p> <p>7. AS PER IECC 2009 EDITION, SECTION 503.2.8, ALL PIPING SERVING AS PART OF A HEATING SYSTEM SHALL BE THERMALLY INSULATED IN ACCORDANCE WITH TABLE 503.2.8</p> <p style="text-align: center;">MINIMUM PIPE INSULATION (THICKNESS IN INCHES)</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th rowspan="2">FLUID</th> <th colspan="2">NOMINAL PIPE DIAMETER</th> </tr> <tr> <th><=1.5"</th> <th>>1.5"</th> </tr> </thead> <tbody> <tr> <td>HOT WATER</td> <td>1-1/2</td> <td>2</td> </tr> </tbody> </table> <p>F. HANGERS AND SUPPORTS:</p> <p>1. HANGERS SHALL BE STANDARD STEEL, MALLEABLE OR WROUGHT IRON, AS MANUFACTURED BY GRINNELL OR APPROVED EQUAL, SUITABLE FOR THE TYPE OF CONSTRUCTION. PIPING SHALL NOT BE HUNG FROM OTHER PIPE.</p> <p>2. SECTIONS OF INDIVIDUAL PIPE RUNS SHALL BE SUPPORTED BY CLEVIS HANGERS.</p> <p>3. ALL EQUIPMENT SHALL BE PROVIDED WITH APPROVED SUPPORTS.</p> <p>4. PROVIDE SEISMIC RESTRAINTS IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES AND STANDARDS AND THE REQUIREMENTS OF AUTHORITIES HAVING JURISDICTION.</p> <p>5. SUPPORTS SHALL BE PROVIDED IN STRICT ACCORDANCE WITH THE RECOMMENDATIONS OF THE PIPING MANUFACTURER.</p> <p>D. VALVES:</p> <p>1. PROVIDE GATE VALVES, BUTTERFLY OR BALL VALVES FOR SHUT-OFF DUTY ON MAIN AND BRANCH SUPPLY LINES, FOR ALL PIPE RUNS 2" AND SMALLER, PROVIDE BALL FOR ALL PIPE RUNS LARGER THAN 2" AND SMALLER THAN 4", PROVIDE GATE VALVES. PIPING 4" AND LARGER, PROVIDE BUTTERFLY VALVES FOR SHUT-OFF DUTY.</p> <p>C. WATER HEATER</p> <p>C.1 WATER HEATER (GAS FIRED)</p> <p>1. NEW TANKLESS GAS FIRED WATER HEATERS PROPOSED, PLEASE REFER WATER HEATER SCHEDULES FOR DETAILS.</p> <p>2. BURNER SHALL BE ALUMINIZED STEEL OR CAST IRON, ADJUSTABLE, OR SELF-ADJUSTING AIR-GAS MIXTURE CONTROL.</p> <p>3. INSTALL THE WORK OF THIS SECTION IN ACCORDANCE WITH INTERNATIONAL ENERGY CONSERVATION CODE 2009 AND THE MANUFACTURER'S PRINTED INSTALLATION INSTRUCTIONS, UNLESS OTHERWISE SPECIFIED.</p> <p>4. THE OUTER JACKET SHALL BE STEEL WITH BAKED ENAMEL/ACRYLIC FINISH AND SHALL BE PROVIDED WITH ACCESS DOOR FOR SERVICING CONTROLS AND BURNER.</p> <p>5. 5. THE DRAIN VALVE SHALL BE LOCATED IN THE FRONT FOR EASE OF SERVICING.</p> <p>G. 6. PROVIDE GLOBE VALVES FOR THROTTLING/BALANCING OF THE HOT WATER CIRCULATING SYSTEM.</p> <p>H. INSTALL PIPING TO CONSERVE BUILDING SPACE, DO NOT INTERFERE WITH USE OF BUILDING SPACE AND THE WORK OF OTHER TRADES, ALL PIPING RUN IN CEILING SHALL BE INSTALLED TIGHT TO THE STRUCTURE ABOVE.</p> <p>I. INSTALL PIPING TO ALLOW FOR EXPANSION AND CONTRACTION WITHOUT STRESSING PIPE JOINTS OR CONNECTED EQUIPMENT. PROVIDE PIPE ANCHORS, GUIDES AND EXPANSION JOINTS OR LOOPS IN ALL HOT WATER AND HOT WATER CIRCULATING MAIN SUPPLY PIPING AND SEGMENTS OF SUCH PIPE THAT EXCEED 30'-0" IN LENGTH.</p> <p>J. IN ALL AREAS WITH FINISHED SURFACES, SYSTEM PIPING AND COMPONENTS SHALL BE CONCEALED ABOVE OR WITHIN FINISHED SURFACES.</p> <p>K. REDUCIONS IN PIPE SIZES SHALL BE MADE WITH ONE-PIECE REDUCING FITTINGS. BUSHINGS ARE NOT ACCEPTABLE. USE FLANGED FITTINGS AT THE BASE OF RISERS.</p> <p>L. VENT PENETRATIONS THROUGH THE ROOF SHALL BE FLASHED.</p> <p>M. IF WATER PRESSURE EXCEEDS 80 PSI, A WATER PRESSURE REDUCING VALVE SHALL BE INSTALLED IN WATER PIPING AT CONNECTION TO MAIN.</p> <p>N. PROVIDE DIELECTRIC FITTINGS BETWEEN DISSIMILAR METALS.</p> <p>O. PIPE BACKFLOW PREVENTER DRAINS TO FLOOR DRAIN OR OTHER APPROVED INDIRECT WASTE SOURCE.</p> <p>P. PROVIDE ACCESS DOORS/PANELS FOR SERVICE AND ACCESS TO ALL VALVES AND OTHER SYSTEM COMPONENTS ENCLOSED IN WALLS AND CEILINGS. ACCESS DOORS SHALL BE FURNISHED BY THIS CONTRACTOR, INSTALLED BY THE GENERAL CONTRACTOR.</p> <p>Q. ALL FIXTURES REQUIRING VACUUM BREAKERS SHALL BE EQUIPPED WITH INTEGRAL VACUUM BREAKERS.</p> <p>R. ANY PENETRATIONS THROUGH FIRE RATED PARTITIONS, FLOORS, OR CEILINGS SHALL BE STEEL SLEVED AND SEALED WITH 3M BRAND UL RATED FIRE BARRIER CAULK OR APPROVED EQUAL. WHEN THE WATER PIPING SYSTEM IS COMPLETE, THOROUGHLY FLUSH ALL DIRT, SEDIMENT, SOLDER, ETC., OUT OF THE SYSTEM, REMOVING ALL STRAINERS, VALVE STEM SEATS, ETC., REQUIRED TO ACCOMPLISH THE FLUSHING.</p> <p>T. AT ALL INDIRECT WASTE DRAINS, MAINTAIN AIR GAP AS REQUIRED BY CODE.</p> <p>INSTALL SLEEVES FOR ALL PIPES WHICH PASS THROUGH WALLS, FLOORS, AND CEILINGS, WHERE PIPES ARE TO BE INSULATED, THE SLEEVE SHALL BE LARGE ENOUGH TO ACCOMMODATE INSULATION. SLEEVES SHALL BE FLUSH WITH FINISHED SURFACES AT BOTH ENDS. ON FINISHED SURFACES IN EXPOSED AREAS PROVIDE ESCUTCHEONS COMPATIBLE WITH FINISH.</p>										FLUID	NOMINAL PIPE DIAMETER		<=1.5"	>1.5"	HOT WATER	1-1/2	2
FLUID	NOMINAL PIPE DIAMETER																		
	<=1.5"	>1.5"																	
HOT WATER	1-1/2	2																	
PLUMBING ABBREVIATIONS		<p>02 06/04/2025 PERMIT SET</p> <p>01 05/06/2025 REVISED CHECK SET</p> <p>00 04/29/2025 CHECK SET</p> <p>NO. DATE ISSUE DESCRIPTION</p>																	
<p>NY ENGINEERS 382 NE 191ST STREET SUITE 49674, MIAMI, FL 33179</p>																			
<p>PROJECT NAME PHYSICAL LOCATION DRAWING TITLE GRAPHIC SCALE SEAL PROJECT NO. SCALE DRAWN BY CHECKED BY DATE SHEET NUMBER</p>																			
<p>PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:</p> <p>a. ARKANSAS BUILDING CODE 2021</p> <p>b. ARKANSAS MECHANICAL CODE 2021</p> <p>c. ARKANSAS PLUMBING CODE 2018</p> <p>d. ARKANSAS FUEL GAS CODE 2018</p> <p>e. INTERNATIONAL ENERGY CONSERVATION CODE 2009</p> <p>f. INTERNATIONAL ELECTRICAL CODE 2020</p> <p>P0.1 PLUMBING SYMBOLS, ABBREVIATION, NOTES & SPECIFICATION</p> <p>P0.2 PLUMBING SPECIFICATION</p> <p>P1.1 PLUMBING SANITARY & VENT PLAN</p> <p>P1.2 PLUMBING WATER SUPPLY & GAS PLAN</p> <p>P4.1 PLUMBING DETAILS (1 OF 2)</p> <p>P4.2 PLUMBING DETAILS (2 OF 2)</p> <p>P5.1 PLUMBING SANITARY RISER AND SCHEDULES</p> <p>P5.2 PLUMBING WATER SUPPLY, GAS RISER AND SCHEDULES</p> <p>CODE COMPLIANCE</p> <p>ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADO</p>																			

2. INSTALLATION

2.01 GENERAL

A. ALL WORK WHICH REQUIRES DISRUPTION OF THE ROOFING SHALL BE DONE BY A CONTRACTOR CERTIFIED BY THE ROOFING MANUFACTURER AS REQUIRED TO MAINTAIN ANY EXISTING ROOF WARRANTIES.

B. EXTERIOR INSTALLATIONS TO BE WEATHER PROOF IN ALL RESPECTS.

C. EXTERIOR MATERIALS AND EQUIPMENT SHALL BE PAINTED TO PREVENT CORROSION, COLOR PER ARCHITECT.

D. COORDINATE THE PLUMBING WORK WITH ALL OTHER AFFECTED WORK AND THE CONSTRUCTION SCHEDULE.

E. REAM PIPE AND TUBE ENDS, REMOVE BURRS, BEVEL PLAIN AND FERROUS END PIPE.

F. REMOVE SCALE AND FOREIGN MATERIAL, FROM INSIDE AND OUTSIDE, BEFORE ASSEMBLY.

G. PREPARE PIPING CONNECTIONS TO EQUIPMENT WITH FLANGES AND UNIONS.

H. COORDINATION WITH THE WORK OF OTHER TRADES IS REQUIRED. PROVIDE OFFSETS IN PIPING SYSTEMS OR MINOR DEVIATIONS TO THE INDICATED PIPE ROUTING IN ORDER TO COORDINATE THE PLUMBING WORK WITH THE WORK OF ALL OTHER TRADES AND THE GENERAL BUILDING CONDITIONS.

I. NO DOMESTIC WATER PIPING SHALL BE INSTALLED IN UNHEATED SPACES.

J. PRIOR TO DISCONNECTING AND CONNECTING NEW WORK TO EXISTING SYSTEMS, THE PLUMBING CONTRACTOR SHALL NOTIFY THE PROPERTY MANAGER AND OFFER A PROPOSED SCHEDULE OF WORK. ESB WILL AUTHORIZE CONNECTIONS AND COORDINATE NECESSARY SHUT DOWNS AND DRAIN DOWNS AS REQUIRED. SHUT DOWNS AND DRAIN DOWNS MAY BE PERFORMED BY THE PLUMBING CONTRACTOR ONLY AFTER RECEIVING ESB AUTHORIZATION, AND SHOULD BE PERFORMED UNDER SUPERVISION OF ESB PERSONNEL. THREE (3) DAYS ADVANCE NOTICE TO THE PROPERTY MANAGER IS REQUIRED.

K. THE PLUMBING CONTRACTOR IS ADVISED THAT DUE TO THE NATURE OF THE OPERATIONS AND TENANT REQUIREMENTS, CONNECTIONS TO EXISTING SYSTEMS MAY HAVE TO BE MADE AFTER REGULAR WORKING HOURS. THE PROPERTY MANAGER WILL ADVISE THE PLUMBING CONTRACTOR OF THE TIME CONSTRAINTS UPON RECEIPT AND APPROVAL OF THE PLUMBING CONTRACTOR'S REQUEST FOR SHUT DOWN AND CONNECTION TO EXISTING SYSTEMS.

L. WHEN CONNECTING TO EXISTING STACKS AND RISERS, PROVISION IS TO BE MADE FOR FUTURE CONNECTIONS BY PROVIDING CAPPED AND VALVED OUTLETS ON DOMESTIC WATER RISERS AND PLUGGED OUTLETS ON THE SANITARY AND VENT STACKS.

2.02 ABOVE GRADE

A. INSTALL PLUMBING PIPING IN ACCORDANCE WITH RECOGNIZED INDUSTRY PRACTICES TO ENSURE THAT PIPING COMPLIES WITH REQUIREMENTS AND SERVES INTENDED PURPOSES.

B. ROUTE PIPING IN AN ORDERLY MANNER, PLUMB AND PARALLEL TO BUILDING STRUCTURE. MAINTAIN GRADIENT, SLOPE PIPING AND ARRANGE SYSTEMS TO DRAIN. IN DOMESTIC WATER SYSTEMS, PROVIDE DRAIN VALVES AT MAIN SHUT-OFF VALVES AND ALL LOW POINTS IN PIPING.

C. USE EXISTING CONNECTIONS AT MAINS WHERE AVAILABLE FOR NEW BRANCH PIPING, LOCATE ALL RISERS AND PIPING BEFORE CONSTRUCTION COMMENCES AND TAKE CARE NOT TO DAMAGE SAME. ANY DAMAGE OCCURRING TO THE EXISTING PIPING WILL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

3. TESTING

A. AT THE COMPLETION OF THE PLUMBING WORK, COMPLETELY TEST THE ENTIRE INSTALLATION OF ALL SYSTEMS FOR PROPER OPERATION AND COMPLIANCE WITH APPLICABLE CODES AND LOCAL REQUIREMENTS. CORRECT ALL DEFICIENCIES FOUND.

B. TESTING OF THE INSTALLED SYSTEMS SHALL BE MADE BY THE CONTRACTOR IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER.

C. THE CONTRACTOR SHALL NOT COVER UP OR PERMANENTLY CONCEAL PIPING, DEVICES OR ANY PORTION OF NEWLY CONSTRUCTED PLUMBING SYSTEM(S) UNTIL SUCH SYSTEM, OR PORTION OF THE SYSTEM, HAS BEEN TESTED IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER AND INSPECTED BY THE LOCAL INSPECTOR AND APPROVED IN WRITING, EXCEPT PIPING PASSING THROUGH FLOORS, WALLS, PARTITIONS, OR BEAMS, FOR DISTANCES EQUAL TO THE THICKNESS OF SUCH FLOOR, WALL, PARTITION OR BEAM.

D. THIS CONTRACTOR SHALL NOTIFY THE VARIOUS DEPARTMENTS, BUREAUS AND INDIVIDUALS AT LEAST TWO WEEKS IN ADVANCE OF THE TIME THAT THE TESTS ARE TO BE CONDUCTED.

E. ALL DEFECTIVE PARTS SHALL BE REPLACED OR CORRECTED BY THIS CONTRACTOR AND AN EXTRA TEST OR TESTS SHALL BE MADE UNTIL THE OPERATION IS SATISFACTORY. ALL ARRANGEMENTS AND EXPENSES NECESSARY TO CONDUCT ALL TESTS REQUIRED BY THESE SPECIFICATIONS AND THE VARIOUS AGENCIES HAVING JURISDICTION OVER THE WORK INSTALLED UNDER THIS CONTRACT SHALL BE MADE BY THIS CONTRACTOR. NO EXTRA COMPENSATION WILL BE ALLOWED FOR THESE TESTS, THE COST THEREOF BEING INCLUDED IN THE LUMP SUM BID FOR THIS CONTRACT.

F. WHERE ANY EVIDENCE OF STOPPAGE IS FOUND IN PIPING OR EQUIPMENT, THIS CONTRACTOR SHALL DISCONNECT, CLEAN, REPAIR AND RECONNECT ALL OBSTRUCTED PIPING OR EQUIPMENT AND SHALL ALSO PAY FOR ALL NECESSARY CUTTING AND REPAIRS TO ADJOINING WORK.

G. ALL PIPING AND EQUIPMENT SHALL BE THOROUGHLY CLEANED INSIDE AND OUT, OF DIRT, CUTTINGS, OILS AND OTHER FOREIGN SUBSTANCES AND SHALL BE LEFT CLEAN.

H. ALL REQUIRED TESTS SHALL BE WITNESSED BY LOCAL AUTHORITIES AND THE OWNER'S REPRESENTATIVE.

I. ALL EQUIPMENT WILL BE FACTORY TESTED.

J. CONTRACTOR SHALL IDENTIFY TO THE OWNER'S REPRESENTATIVE ANY LEAKS OR DAMAGE THAT OCCURS AS A RESULT OF SYSTEM TESTING. CONTRACTOR SHALL TAKE NECESSARY PRECAUTIONS TO LIMIT ANY POTENTIAL DAMAGE. CORRECTIVE ACTION REQUIRED AS A RESULT OF TESTING SHALL BE PERFORMED IMMEDIATELY AND AT THE CONTRACTOR'S EXPENSE.

K. REPORT IN WRITING TO AUTHORITIES HAVING JURISDICTION, THE ARCHITECT AND THE OWNER THE RESULTS OF ALL TESTING.

L. TESTING REQUIREMENTS

a. UPON COMPLETION OF SECTION OF OR THE ENTIRE SYSTEM, THE SYSTEM, OR THE PORTION COMPLETED, SHALL BE TESTED AND PROVED TIGHT UNDER WATER PRESSURE NO LESS THAN THE WORKING PRESSURE OF THE SYSTEM.

b. TESTS SHALL BE WITNESSED BY THE BUILDING ENGINEER.

c. THE PLUMBING CONTRACTOR WILL BE HELD RESPONSIBLE FOR ALL DAMAGE DUE TO TEST FAILURES AND LEAKAGE IN THE TEST AREA AND ADJACENT TENANT OR ESB SPACES.

M. REFILL ENTIRE POTABLE HOT AND COLD WATER SUPPLY SYSTEM WITH CHLORINE SOLUTION (HTH OLIN CHEMICAL CORP.) AT A STRENGTH TO MEET STANDARDS OF THE DEPARTMENT OF HEALTH, AND FOR A PERIOD OF RETENTION AS STIPULATED.

N. THOROUGHLY FLUSH PIPING SYSTEM WITH FRESH WATER IMMEDIATELY PRIOR TO FINAL ACCEPTANCE.


4. WARRANTY

A. EQUIPMENT, MATERIALS AND WORKMANSHIP FURNISHED UNDER THIS CONTRACT SHALL BE GUARANTEED BY THE CONTRACTOR FOR A PERIOD OF ONE YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THE WORK BY THE OWNER. THE CONTRACTOR SHALL KEEP THE WORK IN GOOD REPAIR FOR ONE YEAR AFTER THE DATE OF FINAL APPROVAL. THE CONTRACTOR SHALL, AT HIS OWN EXPENSE, PROMPTLY CORRECT AND REPAIR ANY AND ALL BREAKS, FAILURES OR WEAR DUE TO FAULTY MATERIALS, WORKMANSHIP OR EQUIPMENT. ALL SETTLEMENTS OF SURFACES THAT MAY OCCUR WITHIN THAT PERIOD SHALL ALSO BE PROMPTLY REPAIRED.

02	06/04/2025	PERMIT SET
01	05/06/2025	REVISED CHECK SET
00	04/29/2025	CHECK SET
NO.	DATE	ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

PROJECT NAME		
PHYSICAL LOCATION		
DRAWING TITLE		
PLUMBING SPECIFICATION		
GRAPHIC SCALE		
SEAL	PROJECT NO.	
	SCALE	AS NOTED
	DRAWN BY	NYE
	CHECKED BY	NYE
	DATE	06/04/2025
	SHEET NUMBER	P0.2



SANITARY GENERAL NOTES:

1. UNLESS OTHERWISE NOTED, SLOPE OF DRAINAGE SYSTEM TO BE $1/8$ " PER FOOT OF RUN FOR PIPE 3" OR LARGER AND $1/4$ " PER FOOT FOR PIPE $2\frac{1}{2}$ " OR SMALLER.
2. CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SLAB PENETRATION AS PER STRUCTURAL REQUIREMENT.
3. ALL MATERIAL INDICATED AND IMPLIED ON THESE DRAWINGS SHALL BE NEW UNLESS OTHERWISE NOTED.
4. ALL CLEANOUTS TO BE ACCESSIBLE.
5. ANY ROOF PENETRATION SHALL BE PERFORMED BY LANDLORD'S ROOFERS AT LANDLORD OPTION, A BONDED ROOFER APPROVED IN ADVANCE BY LANDLORD.
6. PROVIDE TRAP PRIMER/ SEAL ON FLOOR DRAIN AS PER LOCAL JURISDICTION.


PLUMBING SANITARY KEYED NOTES:

1. CONNECT NEW 4" SANITARY LINE TO EXISTING 4" SANITARY WASTE LINE IN SPACE. CONTRACTOR TO FIELD VERIFY EXISTING SANITARY LINE SIZE, LOCATION AND INVERT. RE-ROUTE PIPING AS PER SITE CONDITION IF REQUIRED. BASE BID ACCORDINGLY.
2. CONNECT NEW 4" GREASE WASTE LINE TO EXISTING 4" GREASE WASTE STUB IN SPACE. CONTRACTOR TO FIELD VERIFY EXISTING GREASE LINE SIZE, LOCATION AND INVERT. RE-ROUTE PIPING AS PER SITE CONDITION IF REQUIRED. BASE BID ACCORDINGLY.
3. ROUTE INDIRECT WASTE FROM DROP-IN REFRIGERATED WELL TO FLOOR SINK WITH APPROVED AIR GAP.
4. ROUTE INDIRECT WASTE FROM ESPRESSO MACHINE TO FLOOR SINK WITH APPROVED AIR GAP.
5. ROUTE INDIRECT WASTE FROM ICE-CREAM FREEZER TO FLOOR SINK WITH APPROVED AIR GAP.
6. ROUTE INDIRECT WASTE FROM ICE DISPENSER & BEVERAGE DISPENSER TO FLOOR SINK WITH APPROVED AIR GAP.
7. ROUTE INDIRECT WASTE FROM FOOD WARMER & REFRIGERATED SANDWICH MACHINE TO FLOOR SINK WITH APPROVED AIR GAP.
8. ROUTE INDIRECT WASTE FROM 3 COMP SINK DRAIN TO FLOOR SINK WITH APPROVED AIR GAP.
9. ROUTE INDIRECT WASTE FROM WALK IN COOLER TO MOP SINK WITH APPROVED AIR GAP.
10. ROUTE INDIRECT WASTE FROM ICE MAKER TO FLOOR SINK WITH APPROVED AIR GAP.
11. ROUTE INDIRECT WASTE FROM WATER HEATER (WH-1,2) TO MOP SINK.
12. ROUTE INDIRECT WASTE FROM DROP IN ICE BIN TO FLOOR DRAIN WITH APPROVED AIR GAP.
13. CONTRACTOR SHALL PROVIDE ALL NECESSARY PLUMBING FITTINGS FOR DISHWASHER INSTALLATION. CONTRACTOR TO COORDINATE WITH DISHWASHER MANUFACTURER FOR PLUMBING REQUIREMENTS. PROVIDE WATER SUPPLY PIPING & WATER TAMPERING VALVE IF & AS REQUIRED BY MANUFACTURER, BID BASE ACCORDINGLY.

02 06/04/2025 PERMIT SET
 01 05/06/2025 REVISED CHECK SET
 00 04/29/2025 CHECK SET
 NO. DATE ISSUE DESCRIPTION

NY ENGINEERS
 382 NE 191ST STREET
 SUITE 49674,
 MIAMI, FL 33179

PROJECT NAME		
PHYSICAL LOCATION		
DRAWING TITLE	PLUMBING SANITARY & VENT PLAN	
GRAPHIC SCALE		
SEAL	PROJECT NO.	
	SCALE	AS NOTED
	DRAWN BY	NYE
	CHECKED BY	NYE
	DATE	06/04/2025
	SHEET NUMBER	P1.1



WATER PIPING GENERAL NOTES

1. CW/HW PIPING TO BE PROVIDED WITH INSULATION AS PER 2009 INTERNATIONAL ENERGY CONSERVATION CODE (REFER SHEET P0.1)
2. PROVIDE BRANCH PRV IF PRESSURE EXCEEDS 80 PSI.
3. CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SLAB PENETRATION AS PER STRUCTURAL REQUIREMENT.
4. PROVIDE ACCESS PANELS FOR WATER HAMMER ARRESTOR, CLEANOUTS & SHUT-OFF VALVES AS REQUIRED.
5. REFER RISER DIAGRAMS FOR ALL PIPE SIZES.
6. ANY ROOF PENETRATION SHALL BE PERFORMED BY LANDLORD'S ROOFERS AT LANDLORD OPTION, A BONDED ROOFER APPROVED IN ADVANCE BY LANDLORD.
7. PROVIDE TRAP PRIMER/ SEAL ON FLOOR DRAIN AS PER LOCAL JURISDICTION.
8. ALL MATERIAL INDICATED AND IMPLIED ON THESE DRAWINGS SHALL BE NEW UNLESS OTHERWISE NOTED.
9. PROVIDE ASSE 1070 APPROVED LOCAL THERMOSTATIC MIXING VALVE FOR HAND SINK AND LAVATORIES.

PLUMBING WATER SUPPLY KEYED NOTES:

1. CONNECT NEW 2" CW PIPING TO THE EXISTING 2-1/2" WATER LINE IN SPACE. CONTRACTOR TO FIELD VERIFY ROUTING AND LOCATION OF EXISTING CW LINE. CONTRACTOR TO FIELD VERIFY LOCATION AND IF REQUIRED PROVIDE NEW APPROVED SECONDARY BACKFLOW PREVENTION DEVICE AND WATER METER ON DOMESTIC WATER SERVICE AS PER LOCAL CODE AND STATE AUTHORITIES. BID BASE ACCORDINGLY.
2. CONTRACTOR TO FIELD VERIFY INCOMING WATER PRESSURE IS GREATER THAN 65 PSI. PROVIDE WATER BOOSTER PUMP IF PRESSURE IS LESS THAN 65 PSI. BID BASE ACCORDINGLY.
3. PROVIDE ASSE 1070 OR SIMILAR THERMOSTATIC MIXING VALVE AT ALL HAND SINK AND LAVATORIES. SET AT 110F MAXIMUM.
4. PROPOSED NEW WALL MOUNTED WATER FILTRATION SYSTEM.
5. PROVIDE A PRESSURE REDUCING VALVE, BACK FLOW PREVENTER AND SHUT-OFF VALVE AT PLUMBING CONNECTIONS TO KITCHEN EQUIPMENTS.
6. NEW GAS FIRED TANK-LESS WATER HEATER (WH-1,2). REFER SCHEDULE FOR GAS FIRED WATER HEATER (WH-1,2).
7. NEW FUEL GAS METER WITH PRESSURE REGULATOR. COORDINATE EXACT LOCATION OF GAS METER WITH CIVIL UTILITY COMPANY AND MAKE NECESSARY CONNECTIONS AS REQUIRED. PLUMBING CONTRACTOR SHALL FIELD VERIFY PIPE ELEVATIONS AND PENETRATIONS PRIOR TO GAS LINE INSTALLATION. ARRANGE AND PAY FOR ANY REQUIRED UPGRADE TO GAS METER AND SERVICE REQUIRED TO MEET DESIGN GAS LOAD.
8. 2" GAS PIPE CONNECT TO WATER HEATER. PROVIDE SHUT-OFF VALVE, PRESSURE REGULATOR AND 6" DIRT LEG. GAS CONTRACTOR TO ENSURE THE EQUIPMENT RECEIVE SUFFICIENT GAS PRESSURE FOR EFFICIENT OPERATION.
9. CONTRACTOR TO FIELD VERIFY EXISTING AVAILABLE GAS PRESSURE AND MAKE SURE TO PROVIDE ADEQUATE INLET PRESSURE REQUIRED FOR ITEM-28, ITEM-31 AND ITEM-32 SHALL NOT EXCEED MAXIMUM GAS PRESSURE REQUIREMENT OF EQUIPMENT. REFER TO EQUIPMENT CUT SHEET FOR MAXIMUM AND MINIMUM ALLOWABLE NATURAL GAS PRESSURE AND PROVIDE REGULATOR IF REQUIRED. PROVIDED ANSUL FIRE PROTECTION SYSTEM AT HOOD.
10. NEW ELECTRIC TANK-LESS WATER HEATER (WH-3) FOR 3 COMP. SINK SANITIZATION BOWL. REFER SCHEDULE FOR ELECTRIC WATER HEATER (WH-3).

NY ENGINEERS

382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

JECT NAME


AI LOCATION

3. TITLE

1000

PROJECT NO.	
SCALE	AS
DRAWN BY	NY
CHECKED BY	NY
DATE	06/

SHEET NUMBER
P1.2



02 06/04/2025 PERMIT SET
01 05/06/2025 REVISED CHECK SET
00 04/29/2025 CHECK SET
NO. DATE ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

PROJECT NAME	
PHYSICAL LOCATION	
DRAWING TITLE	PLUMBING DETAILS (1 OF 2)
GRAPHIC SCALE	
SEAL	PROJECT NO. _____ SCALE AS NOTED DRAWN BY NYE CHECKED BY NYE DATE 06/04/2025 SHEET NUMBER

Property of NY Engineers

1 INSULATION OF PIPING, VALVES AND FITTINGS FOR EXPOSED AND CONCEALED LOCATIONS
N.T.S.

2 INDIRECT/CONDENSATE DRAIN
N.T.S.

3 GAS FIRED INSTANTANEOUS WATER HEATER DETAIL
N.T.S.

4 WALL CLEANOUT DETAIL
N.T.S.

5 VENT THROUGH ROOF (VTR) DETAILS
N.T.S.

6 FLOOR SINK DETAILS
N.T.S.

7 INLINE RECIRCULATING PUMP DETAIL
N.T.S.

8 WATER HAMMER ARRESTORS
N.T.S.

PDI SIZE	PIPE SIZE	Fixture Unit Load
A	1/2"	1-11
B	3/4"	12-32
C	1"	33-60
D	1-1/4"	61-113
E	1-1/2"	114-154
F	2"	154-330

PC TO PROVIDE WATER HAMMER ARRESTERS BY SIOUX CHIEF, PRECISION PLUMBING PRODUCTS, WATTS OR APPROVED EQUIVALENT WITH PISTON AND O-RING CONSTRUCTION, HAVING PDI #WH-201, ASSE #1010 AND ANSI #A112.26.1M CERTIFICATION. INSTALL IN HORIZONTAL OR VERTICAL POSITION, BUT NEVER UPSIDE DOWN. INSTALL IN LINE WITH WATER FLOW DIRECTION IF POSSIBLE. SIZE THE UNITS AS SHOWN ON THE DRAWINGS AND/OR PER THE TABLES SHOWN ABOVE.

WALL CLEANOUT DETAIL NOTES:


1. PROVIDE WCO WHERE SHOWN ON PLAN, AND ON SANITARY WASTE BRANCHES NOT SERVED WITH A FLOOR CLEANOUT.
2. LOCATE ABOVE FIXTURE FLOOR RIM WITHIN 4" OF FLOOR.
3. CONSULT LOCAL CODES FOR OTHER WCO REQUIREMENTS.
4. LONG SWEEP AT END OF LINE OR COMBINATION WYE AND EIGHT BEND IN RUN OF LINE.
5. CLEAN OUT FACE SHALL BE WITHIN 4" OF WALL SURFACE. PROVIDE A PIPE EXTENSION IF REQUIRED.

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

02 06/04/2025 PERMIT SET
01 05/06/2025 REVISED CHECK SET
00 04/29/2025 CHECK SET
NO. DATE ISSUE DESCRIPTION

PROJECT NAME
PHYSICAL LOCATION
DRAWING TITLE
GRAPHIC SCALE
SEAL PROJECT NO.
SCALE AS NOTED
DRAWN BY NYE
CHECKED BY NYE
DATE 06/04/2025
SHEET NUMBER
P4.2

<p style="text-align: center;">1 PLUMBING SANITARY RISER N.T.S.</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="10">DRAIN ACCESSORIES & SCHEDULE</th> </tr> <tr> <th colspan="2">DESIGNATION</th> <th colspan="2">REQUIRED</th> <th colspan="2">BODY</th> <th colspan="2">STRAINER</th> <th colspan="2">REMARKS</th> </tr> <tr> <th colspan="2"></th> <th colspan="2">SERIES NO.</th> <th colspan="2"></th> <th colspan="2"></th> <th colspan="2"></th> </tr> </thead> <tbody> <tr> <td colspan="2">FD-1</td> <td colspan="2">• ZURN-Z505</td> <td colspan="2">• CAST IRON GALVANIZED ALL BRONZE HIGH DENSITY POLYETHYLENE SECONDARY CLAMP CLAMPING DEVICE DECK CLAMP BACK WATER VALVE SUMP RECEIVER FLASHING COLLAR CAST IRON ALL BRONZE NICKEL BRONZE(ADJUSTABLE) CHROME PLATED SEDIMENT BUCKET SECONDARY STRAINER POLISHED FINISH SATIN FINISH TRACTOR GRATE ST. STEEL FUNNEL TOP FLAT TOP</td> <td colspan="2">• CAST IRON GALVANIZED ALL BRONZE HIGH DENSITY POLYETHYLENE SECONDARY CLAMP CLAMPING DEVICE DECK CLAMP BACK WATER VALVE SUMP RECEIVER FLASHING COLLAR CAST IRON ALL BRONZE NICKEL BRONZE(ADJUSTABLE) CHROME PLATED SEDIMENT BUCKET SECONDARY STRAINER POLISHED FINISH SATIN FINISH TRACTOR GRATE ST. STEEL FUNNEL TOP FLAT TOP</td> <td colspan="2">• DOME RAISED LIP EXTENSION(WHERE REQUIRED) LESS GRATE BRONZE TOP IRON GRATE POLYETHYLENE SOLID HINGED COVER</td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2">LOCATION REFER PLANS</td> </tr> </tbody> </table> <p>NOTES:</p> <ol style="list-style-type: none"> 1. ALL FLOOR DRAINS IN FINISHED AREAS AND ALL ROOF DRAINS SHALL BE LOCATED AS PER THE ARCHITECTURAL DRAWINGS. 2. ALL FLOOR DRAINS IN MECHANICAL EQUIPMENT ETC., SHALL BE LOCATED IN COORDINATION WITH THE MECHANICAL CONTRACTOR. 3. THE CONTRACTOR SHALL VERIFY THE COMPATIBILITY OF THE DRAINS WITH THE APPROVED ROOFING AND/OR WATER PROOFING SYSTEMS PRIOR TO SUBMITTING SHOP DRAWINGS. 4. THE TOP OF ALL FLOOR DRAINS SHALL BE FLUSH WITH THE ADJACENT FINISHED FLOOR. 5. PROVIDE ELECTRONIC TRAP PRIMER FOR MECHANICAL/TRASH ROOM FLOOR DRAINS & FUNNEL DRAIN. PROVIDE FLOW CONTROL TRAP PRIMER FOR ALL OTHER ROOM FLOOR DRAINS. <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="10">PLUMBING FIXTURE SCHEDULE</th> </tr> <tr> <th>ITEM NO</th> <th>QTY</th> <th>DESCRIPTION</th> <th>CW</th> <th>HW</th> <th>HWR</th> <th>DRAINAGE</th> <th></th> <th></th> <th></th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>DIRECT</th> <th>INDIRECT</th> <th>VENT</th> <th></th> </tr> </thead> <tbody> <tr> <td>WC-1</td> <td>2</td> <td>WATER CLOSET</td> <td>1"</td> <td>-</td> <td>-</td> <td>4"</td> <td>-</td> <td>2"</td> <td></td> </tr> <tr> <td>LAV-1</td> <td>2</td> <td>LAVATORY</td> <td>1/2"</td> <td>1/2"</td> <td>1/2"</td> <td>1/2"</td> <td>-</td> <td>1/2"</td> <td></td> </tr> <tr> <td>FD-1</td> <td>2</td> <td>FLOOR DRAIN</td> <td>-</td> <td>-</td> <td>-</td> <td>3"</td> <td>-</td> <td>2"</td> <td></td> </tr> <tr> <td>FS-1</td> <td>8</td> <td>FLOOR SINK</td> <td>-</td> <td>-</td> <td>-</td> <td>3"</td> <td>-</td> <td>2"</td> <td></td> </tr> <tr> <td></td> </tr> </tbody> </table> <p>NOTES:</p> <ol style="list-style-type: none"> 1. PROVIDE SHUT OFF VALVES FOR ALL WATER LINES AT PLUMBING FIXTURES AND EQUIPMENT CONNECTIONS. 2. MAXIMUM FLOW FROM A SINK FAUCET SHALL NOT EXCEED 2.2 GPM AT 60 PSI OF WATER/MIN. 3. MAXIMUM FLOW FROM A LAVATORY FAUCET SHALL NOT EXCEED 0.5 GPM AT 60 PSI OF WATER/MIN. 4. MAXIMUM FLOW FROM WATER CLOSET SHALL NOT EXCEED 1.6 GPM PER FLUSHING CYCLE. 5. INSTALL TRAP PRIMER FOR FLOOR DRAIN THAT SERVE THE RESTROOM. 6. PROVIDE ELECTRONIC TRAP PRIMER FOR HUB DRAIN. PROVIDE FLOW CONTROL TRAP PRIMER FOR ALL OTHER ROOM FLOOR DRAINS. 7. THE TOP OF ALL FLOOR DRAINS SHALL BE FLUSH WITH THE ADJACENT FINISHED FLOOR. 8. ALL FLOOR DRAINS IN FINISHED AREAS AND ALL ROOF DRAINS SHALL BE LOCATED AS PER THE ARCHITECTURAL DRAWINGS. <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="10">KITCHEN EQUIPMENT SCHEDULE</th> </tr> <tr> <th>ITEM NO</th> <th>QTY</th> <th>DESCRIPTION</th> <th>CW</th> <th>HW</th> <th>HWR</th> <th>FW</th> <th>DRAINAGE</th> <th></th> <th></th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>DIRECT</th> <th>INDIRECT</th> <th>VENT</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1</td> <td>MOP SINK</td> <td>3/4"</td> <td>3/4"</td> <td>-</td> <td>-</td> <td>3"</td> <td>-</td> <td>2"</td> </tr> <tr> <td>8</td> <td>1</td> <td>PREP SINK</td> <td>1/2"</td> <td>1/2"</td> <td>-</td> <td>-</td> <td>1/2"</td> <td>-</td> <td>1/2"</td> </tr> <tr> <td>12</td> <td>1</td> <td>ICE MAKER</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1/2"</td> <td>-</td> <td>-</td> </tr> <tr> <td>7</td> <td>2</td> <td>HAND SINK</td> <td>1/2"</td> <td>1/2"</td> <td>-</td> <td>-</td> <td>2"</td> <td>-</td> <td>1/2"</td> </tr> <tr> <td>21</td> <td>1</td> <td>SOILED DISHTABLE</td> <td>1/2"</td> <td>1/2"</td> <td>-</td> <td>-</td> <td>2"</td> <td>-</td> <td>2"</td> </tr> <tr> <td>19</td> <td>1</td> <td>DISHWASHER</td> <td>-</td> <td>1/2"</td> <td>-</td> <td>-</td> <td>2"</td> <td>-</td> <td>2"</td> </tr> <tr> <td>16</td> <td>1</td> <td>3 COMP. SINK</td> <td>3/4"</td> <td>3/4"</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>2"</td> </tr> <tr> <td>41</td> <td>2</td> <td>SALAD PREPARATION REFRIGERATOR</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1"</td> </tr> <tr> <td>43</td> <td>2</td> <td>FOOD PAN WARMER</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>2"</td> </tr> <tr> <td>60</td> <td>1</td> <td>COFFEE GRINDER</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1/2"</td> <td>-</td> <td>1"</td> </tr> <tr> <td>59</td> <td>1</td> <td>ESPRESSO MACHINE</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1/2"</td> <td>-</td> <td>1"</td> </tr> <tr> <td>46</td> <td>1</td> <td>BACK COUNTER W/SINK</td> <td>1/2"</td> <td>1/2"</td> <td>-</td> <td>-</td> <td>2"</td> <td>-</td> <td>1/2"</td> </tr> <tr> <td>44</td> <td>1</td> <td>ICE CREAM FREEZER</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1"</td> </tr> <tr> <td>47</td> <td>1</td> <td>DROP-IN ICE BIN</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1"</td> </tr> <tr> <td>56</td> <td>1</td> <td>DROP-IN REFRIGERATED WELL</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1"</td> </tr> <tr> <td>67</td> <td>1</td> <td>ICE DISPENSER</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1"</td> </tr> <tr> <td>69</td> <td>1</td> <td>BEVERAGE DISPENSER</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1/2"</td> <td>-</td> <td>1"</td> </tr> </tbody> </table> <p>KITCHEN EQUIPMENT NOTES:</p> <ol style="list-style-type: none"> 1. IT SHALL BE THE PLUMBING CONTRACTORS RESPONSIBILITY TO MAKE ALL FINAL CONNECTIONS FROM KITCHEN EQUIPMENT TO THE PLUMBING MAINS SHOWN ON PLAN/RISER. 2. THE PLUMBING CONNECTION SCHEDULE RELATES REQUIRED CONNECTIONS TO INDIVIDUAL EQUIPMENT ONLY. 3. PLUMBING CONTRACTOR SHALL REFER TO "KITCHEN EQUIPMENT COMPANY" CUT SHEETS FOR ALL ROUTINE OF FINAL CONNECTION TO EQUIPMENT AND EXACT ROUGH-IN LOCATION. 4. PLUMBING CONTRACTOR SHALL MOUNT ALL FLOOR SINKS FLUSH WITH FINISHED FLOOR ELEVATION AND A MINIMUM OF 16" OFF THE FINISH FACE OF THE WALL. 5. INSTALL SECONDARY BFP ASSE 1056 IF CHEMICAL DISPENSER USED WITH MOP SINK. <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="6">GREASE INTERCEPTOR SIZING CALCULATION</th> </tr> <tr> <th>ITEM NO.</th> <th>Fixture</th> <th>QTY.</th> <th colspan="2">GREASE</th> <th></th> </tr> <tr> <th></th> <th></th> <th></th> <th>DFU PER FIXTURE</th> <th>TOTAL DFU</th> <th></th> </tr> </thead> <tbody> <tr> <td>FS-1</td> <td>FLOOR SINK</td> <td>8</td> <td>5</td> <td>40</td> <td></td> </tr> <tr> <td>1</td> <td>MOP SINK</td> <td>1</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>8</td> <td>PREP SINK</td> <td>1</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>7</td> <td>HAND SINK</td> <td>2</td> <td>2</td> <td>4</td> <td></td> </tr> <tr> <td>21</td> <td>SOILED DISHTABLE</td> <td>1</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>19</td> <td>DISHWASHER</td> <td>1</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>46</td> <td>BACK COUNTER W/SINK</td> <td>1</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>TOTAL:</td> <td>54</td> </tr> <tr> <td colspan="6">REQUIRED GRAVITY GREASE INTERCEPTOR CAPACITY = 54X30 (RETENTION TIME) = 1620 GALLONS. (CALCULATION AS PER ARKANSAS PLUMBING CODE 2018, SECTION 1003.3.7)</td> </tr> <tr> <td colspan="6">EXISTING GRAVITY GREASE INTERCEPTOR CAPACITY = 3000 GALLONS.</td> </tr> </tbody> </table> <p>PROJECT NAME: _____</p> <p>PHYSICAL LOCATION: _____</p> <p>DRAWING TITLE: PLUMBING SANITARY RISER AND SCHEDULES</p> <p>GRAPHIC SCALE: _____</p> <p>SEAL: _____</p> <p>PROJECT NO.: _____</p> <p>SCALE: AS NOTED</p> <p>DRAWN BY: NYE</p> <p>CHECKED BY: NYE</p> <p>DATE: 06/04/2025</p> <p> SHEET NUMBER: P5.1</p>	DRAIN ACCESSORIES & SCHEDULE										DESIGNATION		REQUIRED		BODY		STRAINER		REMARKS				SERIES NO.								FD-1		• ZURN-Z505		• CAST IRON GALVANIZED ALL BRONZE HIGH DENSITY POLYETHYLENE SECONDARY CLAMP CLAMPING DEVICE DECK CLAMP BACK WATER VALVE SUMP RECEIVER FLASHING COLLAR CAST IRON ALL BRONZE NICKEL BRONZE(ADJUSTABLE) CHROME PLATED SEDIMENT BUCKET SECONDARY STRAINER POLISHED FINISH SATIN FINISH TRACTOR GRATE ST. STEEL FUNNEL TOP FLAT TOP		• CAST IRON GALVANIZED ALL BRONZE HIGH DENSITY POLYETHYLENE SECONDARY CLAMP CLAMPING DEVICE DECK CLAMP BACK WATER VALVE SUMP RECEIVER FLASHING COLLAR CAST IRON ALL BRONZE NICKEL BRONZE(ADJUSTABLE) CHROME PLATED SEDIMENT BUCKET SECONDARY STRAINER POLISHED FINISH SATIN FINISH TRACTOR GRATE ST. STEEL FUNNEL TOP FLAT TOP		• DOME RAISED LIP EXTENSION(WHERE REQUIRED) LESS GRATE BRONZE TOP IRON GRATE POLYETHYLENE SOLID HINGED COVER										LOCATION REFER PLANS		PLUMBING FIXTURE SCHEDULE										ITEM NO	QTY	DESCRIPTION	CW	HW	HWR	DRAINAGE										DIRECT	INDIRECT	VENT		WC-1	2	WATER CLOSET	1"	-	-	4"	-	2"		LAV-1	2	LAVATORY	1/2"	1/2"	1/2"	1/2"	-	1/2"		FD-1	2	FLOOR DRAIN	-	-	-	3"	-	2"		FS-1	8	FLOOR SINK	-	-	-	3"	-	2"												KITCHEN EQUIPMENT SCHEDULE										ITEM NO	QTY	DESCRIPTION	CW	HW	HWR	FW	DRAINAGE										DIRECT	INDIRECT	VENT	1	1	MOP SINK	3/4"	3/4"	-	-	3"	-	2"	8	1	PREP SINK	1/2"	1/2"	-	-	1/2"	-	1/2"	12	1	ICE MAKER	-	-	-	-	1/2"	-	-	7	2	HAND SINK	1/2"	1/2"	-	-	2"	-	1/2"	21	1	SOILED DISHTABLE	1/2"	1/2"	-	-	2"	-	2"	19	1	DISHWASHER	-	1/2"	-	-	2"	-	2"	16	1	3 COMP. SINK	3/4"	3/4"	-	-	-	-	2"	41	2	SALAD PREPARATION REFRIGERATOR	-	-	-	-	-	-	1"	43	2	FOOD PAN WARMER	-	-	-	-	-	-	2"	60	1	COFFEE GRINDER	-	-	-	-	1/2"	-	1"	59	1	ESPRESSO MACHINE	-	-	-	-	1/2"	-	1"	46	1	BACK COUNTER W/SINK	1/2"	1/2"	-	-	2"	-	1/2"	44	1	ICE CREAM FREEZER	-	-	-	-	-	-	1"	47	1	DROP-IN ICE BIN	-	-	-	-	-	-	1"	56	1	DROP-IN REFRIGERATED WELL	-	-	-	-	-	-	1"	67	1	ICE DISPENSER	-	-	-	-	-	-	1"	69	1	BEVERAGE DISPENSER	-	-	-	-	1/2"	-	1"	GREASE INTERCEPTOR SIZING CALCULATION						ITEM NO.	Fixture	QTY.	GREASE						DFU PER FIXTURE	TOTAL DFU		FS-1	FLOOR SINK	8	5	40		1	MOP SINK	1	2	2		8	PREP SINK	1	2	2		7	HAND SINK	2	2	4		21	SOILED DISHTABLE	1	2	2		19	DISHWASHER	1	2	2		46	BACK COUNTER W/SINK	1	2	2						TOTAL:	54	REQUIRED GRAVITY GREASE INTERCEPTOR CAPACITY = 54X30 (RETENTION TIME) = 1620 GALLONS. (CALCULATION AS PER ARKANSAS PLUMBING CODE 2018, SECTION 1003.3.7)						EXISTING GRAVITY GREASE INTERCEPTOR CAPACITY = 3000 GALLONS.					
DRAIN ACCESSORIES & SCHEDULE																																																																																																																																																																																																																																																																																																																																																																																																																									
DESIGNATION		REQUIRED		BODY		STRAINER		REMARKS																																																																																																																																																																																																																																																																																																																																																																																																																	
		SERIES NO.																																																																																																																																																																																																																																																																																																																																																																																																																							
FD-1		• ZURN-Z505		• CAST IRON GALVANIZED ALL BRONZE HIGH DENSITY POLYETHYLENE SECONDARY CLAMP CLAMPING DEVICE DECK CLAMP BACK WATER VALVE SUMP RECEIVER FLASHING COLLAR CAST IRON ALL BRONZE NICKEL BRONZE(ADJUSTABLE) CHROME PLATED SEDIMENT BUCKET SECONDARY STRAINER POLISHED FINISH SATIN FINISH TRACTOR GRATE ST. STEEL FUNNEL TOP FLAT TOP		• CAST IRON GALVANIZED ALL BRONZE HIGH DENSITY POLYETHYLENE SECONDARY CLAMP CLAMPING DEVICE DECK CLAMP BACK WATER VALVE SUMP RECEIVER FLASHING COLLAR CAST IRON ALL BRONZE NICKEL BRONZE(ADJUSTABLE) CHROME PLATED SEDIMENT BUCKET SECONDARY STRAINER POLISHED FINISH SATIN FINISH TRACTOR GRATE ST. STEEL FUNNEL TOP FLAT TOP		• DOME RAISED LIP EXTENSION(WHERE REQUIRED) LESS GRATE BRONZE TOP IRON GRATE POLYETHYLENE SOLID HINGED COVER																																																																																																																																																																																																																																																																																																																																																																																																																	
								LOCATION REFER PLANS																																																																																																																																																																																																																																																																																																																																																																																																																	
PLUMBING FIXTURE SCHEDULE																																																																																																																																																																																																																																																																																																																																																																																																																									
ITEM NO	QTY	DESCRIPTION	CW	HW	HWR	DRAINAGE																																																																																																																																																																																																																																																																																																																																																																																																																			
						DIRECT	INDIRECT	VENT																																																																																																																																																																																																																																																																																																																																																																																																																	
WC-1	2	WATER CLOSET	1"	-	-	4"	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																	
LAV-1	2	LAVATORY	1/2"	1/2"	1/2"	1/2"	-	1/2"																																																																																																																																																																																																																																																																																																																																																																																																																	
FD-1	2	FLOOR DRAIN	-	-	-	3"	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																	
FS-1	8	FLOOR SINK	-	-	-	3"	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																	
KITCHEN EQUIPMENT SCHEDULE																																																																																																																																																																																																																																																																																																																																																																																																																									
ITEM NO	QTY	DESCRIPTION	CW	HW	HWR	FW	DRAINAGE																																																																																																																																																																																																																																																																																																																																																																																																																		
							DIRECT	INDIRECT	VENT																																																																																																																																																																																																																																																																																																																																																																																																																
1	1	MOP SINK	3/4"	3/4"	-	-	3"	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																
8	1	PREP SINK	1/2"	1/2"	-	-	1/2"	-	1/2"																																																																																																																																																																																																																																																																																																																																																																																																																
12	1	ICE MAKER	-	-	-	-	1/2"	-	-																																																																																																																																																																																																																																																																																																																																																																																																																
7	2	HAND SINK	1/2"	1/2"	-	-	2"	-	1/2"																																																																																																																																																																																																																																																																																																																																																																																																																
21	1	SOILED DISHTABLE	1/2"	1/2"	-	-	2"	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																
19	1	DISHWASHER	-	1/2"	-	-	2"	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																
16	1	3 COMP. SINK	3/4"	3/4"	-	-	-	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																
41	2	SALAD PREPARATION REFRIGERATOR	-	-	-	-	-	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
43	2	FOOD PAN WARMER	-	-	-	-	-	-	2"																																																																																																																																																																																																																																																																																																																																																																																																																
60	1	COFFEE GRINDER	-	-	-	-	1/2"	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
59	1	ESPRESSO MACHINE	-	-	-	-	1/2"	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
46	1	BACK COUNTER W/SINK	1/2"	1/2"	-	-	2"	-	1/2"																																																																																																																																																																																																																																																																																																																																																																																																																
44	1	ICE CREAM FREEZER	-	-	-	-	-	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
47	1	DROP-IN ICE BIN	-	-	-	-	-	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
56	1	DROP-IN REFRIGERATED WELL	-	-	-	-	-	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
67	1	ICE DISPENSER	-	-	-	-	-	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
69	1	BEVERAGE DISPENSER	-	-	-	-	1/2"	-	1"																																																																																																																																																																																																																																																																																																																																																																																																																
GREASE INTERCEPTOR SIZING CALCULATION																																																																																																																																																																																																																																																																																																																																																																																																																									
ITEM NO.	Fixture	QTY.	GREASE																																																																																																																																																																																																																																																																																																																																																																																																																						
			DFU PER FIXTURE	TOTAL DFU																																																																																																																																																																																																																																																																																																																																																																																																																					
FS-1	FLOOR SINK	8	5	40																																																																																																																																																																																																																																																																																																																																																																																																																					
1	MOP SINK	1	2	2																																																																																																																																																																																																																																																																																																																																																																																																																					
8	PREP SINK	1	2	2																																																																																																																																																																																																																																																																																																																																																																																																																					
7	HAND SINK	2	2	4																																																																																																																																																																																																																																																																																																																																																																																																																					
21	SOILED DISHTABLE	1	2	2																																																																																																																																																																																																																																																																																																																																																																																																																					
19	DISHWASHER	1	2	2																																																																																																																																																																																																																																																																																																																																																																																																																					
46	BACK COUNTER W/SINK	1	2	2																																																																																																																																																																																																																																																																																																																																																																																																																					
				TOTAL:	54																																																																																																																																																																																																																																																																																																																																																																																																																				
REQUIRED GRAVITY GREASE INTERCEPTOR CAPACITY = 54X30 (RETENTION TIME) = 1620 GALLONS. (CALCULATION AS PER ARKANSAS PLUMBING CODE 2018, SECTION 1003.3.7)																																																																																																																																																																																																																																																																																																																																																																																																																									
EXISTING GRAVITY GREASE INTERCEPTOR CAPACITY = 3000 GALLONS.																																																																																																																																																																																																																																																																																																																																																																																																																									



ELECTRICAL SYMBOLS LIST

ELECTRICAL SYMBOLS LIST				GENERAL NOTES (APPLY TO ALL "E" DRAWINGS)																											
LIGHTING		POWER AND TELECOMMUNICATION		ELECTRICAL ABBREVIATIONS																											
	LIGHTING FIXTURE AND OUTLET BOX LUMINAIRE TYPE: INDICATE BY UPPERCASE LETTER SEE LIGHTING FIXTURE SCHEDULE. CIRCUIT NUMBER : INDICATED BY NUMBER SWITCHING INDICATED BY LOWER CASE LETTERS. A_O 2_a		JUNCTION BOX WITH BLANK COVER PLATE, FLUSH IN FLOOR/CEILING.	A	AMPERES	EA	EACH																								
	EXIT SIGN WITH EMERGENCY LIGHT & BATTERY UNIT		SIMPLEX RECEPTACLE, +18" AFF OR AS NOTED. SUFFIXE DENOTES FOLLOWING: A- NEMA 5-15R B- NEMA 6-15R C- NEMA 14-30R D- NEMA 14-50R	A/C, AC	AIR CONDITIONING UNIT	EC	ELECTRICAL CONTRACTOR																								
	EMERGENCY BATTERY UNIT WITH ATTACHED EMERGENCY FIXTURES AND OUTLET BOX.		DUPLEX GFI RECEPTACLE, +18" AFF OR AS NOTED.	AF	AMPERE FRAME/AMP FUSE	EM	EMERGENCY																								
	WALL BOX DIMMER SWITCH, LUTRON MAESTRO SERIES. "a" DENOTES LIGHTING FIXTURE CONTROLLED.		DUPLEX RECEPTACLE, +18" AFF OR AS NOTED.	AFF	ABOVE FINISHED FLOOR	EMT	ELECTRICAL METALLIC TUBING																								
	WALL OCCUPANCY SENSOR.		CEILING MOUNTED RECEPTACLE	AS	AMP SWITCH	EQUIP	EQUIPMENT																								
	20A SPST TOGGLE SWITCH U.O.N. "a" DENOTES LIGHTING FIXTURE CONTROLLED.		DUPLEX CONVENIENCE RECEPTACLE, CONTROLLED FROM WALL SWITCH. HALF SWITCHED, HALF CONSTANT HOT.	AIC	AMPS INTERRUPTING CAPACITY	ER	EXISTING TO BE RELOCATED																								
	20A 3-WAY TOGGLE SWITCH U.O.N. "a" DENOTES LIGHTING FIXTURE CONTROLLED		DOUBLE DUPLEX RECEPTACLE - 20A-1P, 125V, NEMA 5-20R.	AT	AMP TRIP	E	EXISTING																								
	MANUAL OVERRIDE SWITCH		DUPLEX DEDICATED RECEPTACLE	ATS	AUTOMATIC TRANSFER SWITCH	FA	FIRE ALARM																								
	WIRING SYSTEM 1#12 Ø, 1#12 N. & 1#12 G. IN 3/4" C, UNLESS OTHERWISE NOTED. NUMBER WHERE USED INDICATES CIRCUIT NUMBER, IT SHALL CONSISTS OF POWER OR LIGHTING CIRCUITRY HOMERUN WITH PANELBOARD DESIGNATION.		TELEPHONE/DATA OUTLET, 4" SQUARE OUTLET BOX WITH SINGLE GANG COLLAR AND BLANK PLATE. PROVIDE 3/4" E.C., U.O.N., UP TO HUNG CEILING AND TERMINATE WITH 90° ELBOW, BUSHING AND DRAG WIRE.	AUTO	AUTOMATIC	FIXT	Fixture																								
	CONDUIT AND WIRE TO BUILDING GROUND.		DATA OUTLET - (1) PORT UNO, +18" AFF, UNO TEL / DATA OUTLET TO BE PROVIDED WITH 1" CONDUIT U.O.N. TO H.C. AND TERMINATED WITH 90 DEGREE ELBOW AND BUSHING. TEL / DATA OUTLET PLATE SHALL BE PROVIDED WITH 1 1/4" DIAMETER GROMMETED OPENING.	AWG	AMERICAN WIRE GAUGE	FL	FLOOR																								
	EXISTING		MOTORS AND CONTROLS	C	CONDUIT	G	GROUND																								
	NEW		AC INDOOR UNIT MOTOR AS NOTED WITH LIQUID TIGHT FLEXIBLE CONNECTION WITH JUNCTION BOX AND MOTOR SWITCH.	C/B,CB	CIRCUIT BREAKER	GFI	GROUND FAULT INTERRUPTER																								
	POWER OR LIGHTING CIRCUITRY HOMERUN WITH PANELBOARD DESIGNATION. NUMBER WHERE USED INDICATES CIRCUIT NUMBER. IT SHALL CONSISTS OF 2#12 Ø, 2#12 N. & 2#12 G. IN 3/4" C, UNLESS OTHERWISE NOTED.		AC OUTDOOR UNIT MOTOR AS NOTED WITH CONTROLLER AND DISCONNECT SWITCH WITH WEATHER PROOF.	CKT	CIRCUIT	GP	GENERAL PURPOSE																								
	NUMBER WHERE USED INDICATES CIRCUIT NUMBER. IT SHALL CONSISTS OF POWER OR LIGHTING CIRCUITRY HOMERUN WITH PANELBOARD DESIGNATION, 3#12 Ø, 3#12 N. & 3#12 G. IN 3/4" C, UNLESS OTHERWISE NOTED.		FUSED DISCONNECT SWITCH AMPERAGE, AND NUMBER OF POLES AS NOTED.	CLG	CEILING	HP	HORSEPOWER																								
	CONDUIT AND WIRE TO BUILDING GROUND.		30A/240V NON FUSED DISCONNECT SWITCH	COMM	COMMUNICATION	HWH	HOW WATER HEATER																								
	EXISTING		60A/240V NON FUSED DISCONNECT SWITCH	CT	CURRENT TRANSFORMER	HZ	HERTZ																								
	NEW		100A/240V NON FUSED DISCONNECT SWITCH	CU	COPPER	IC	INTERRUPTING CAPACITY																								
	ELECTRICAL DRAWING LIST		COMBINATION MAGNETIC STARTER AND DISCONNECT SWITCH, FURNISHED BY HVAC/CONTRACTOR, INSTALLED AND WIRED BY ELECTRICAL CONTRACTOR.	DIA	DIAMETER	PP	POWER PANEL																								
	E0.1 ELECTRICAL NOTES, ABBREVIATIONS, SYMBOLS		ELECTRICAL HEATER, NUMBER DENOTES HEATER RATING	DISC	DISCONNECT	PVC	POLYVINYL CHLORIDE																								
	E0.2 ELECTRICAL SPECIFICATIONS SHEET 1 OF 2		INDICATES MOUNTING HEIGHT, CENTER LINE TO FINISHED FLOOR.	DN	DOWN	PWR	POWER																								
	E0.3 ELECTRICAL SPECIFICATIONS SHEET 2 OF 2		KEYED NOTE REFERENCE	DP	DISTRIBUTION PANEL	R	REMOVE																								
	E1.1 ELECTRICAL POWER PLAN		DETAIL REFERENCE: DETAIL NUMBER INDICATED ON TOP; DRAWING NUMBER INDICATED ON BOTTOM	DWG	DRAWING	RE	RELOCATED EXISTING																								
	E2.1 ELECTRICAL LIGHTING PLAN		POWER DISTRIBUTION	IG	ISOLATED GROUNDING	REC	RECEPTACLE																								
	E3.1 ELECTRICAL ROOF POWER PLAN		DISTRIBUTION PANELBOARD, 208Y/120V-SURFACE OR FLUSH MOUNTED.	JB	JUNCTION BOX	RGS	RIGID GALVANIZED STEEL																								
	E4.1 ELECTRICAL DETAILS		DISTRIBUTION PANELBOARD, 480Y/277V-SURFACE OR FLUSH MOUNTED	KCMIL	ONE THOUSAND CIRCULAR MILS	RR	REMOVE & RELOCATE																								
	E5.1 ELECTRICAL RISER DIAGRAM		MAJOR ELECTRICAL COMPONENT OR DEVICE. VOLTAGE AND AMPERAGE AS NOTED.	KV	KILOVOLT	SECT	SECTION																								
	E5.2 ELECTRICAL PANEL SCHEDULE			KVA	KILOVOLT-AMPERES	SPDT	SINGLE POLE DOUBLE THROW																								
	CODE COMPLIANCE			KW	KILOWATTS	SPST	SINGLE POLE SINGLE THROW																								
	ALL WORK AND MATERIAL SHALL BE PERFORMED AND INSTALLED IN COMPLIANCE WITH THE FOLLOWING CODES AS ADOPTED AND AMENDED BY THE INSPECTING AUTHORITY. NOTHING IN THESE DRAWINGS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THESE PROJECT:			LTC	LIGHTING	SPEC	SPECIFICATION																								
a.	ARKANSAS BUILDING CODE 2021			MAX	MAXIMUM	SW	SWITCH																								
b.	ARKANSAS MECHANICAL CODE 2021			MC	MOTOR CONTROLLER	SWBD	SWITCHBOARD																								
c.	ARKANSAS PLUMBING CODE 2018			MCB	MAIN CIRCUIT BREAKER	SYM	SYMMETRICAL																								
d.	ARKANSAS FUEL GAS CODE 2018			MLO	MAIN LUGS ONLY	SYS	SYSTEMS																								
e.	INTERNATIONAL ENERGY CONSERVATION CODE 2009			MTD	MOUNTED	TELE	TELEPHONE																								
f.	NATIONAL ELECTRICAL CODE 2020			MTS	MANUAL TRANSFER SWITCH	TEMP	TEMPERATURE																								
	ANNOTATION			N	NEUTRAL	TXF	TOILET EXHAUST FAN																								
	+24"			NE	NEW DEVICE TO REPLACE EXISTING	TYP	TYPICAL																								
	INDICATES MOUNTING HEIGHT, CENTER LINE TO FINISHED FLOOR.			NIC	NOT IN CONTRACT	UON	UNLESS OTHERWISE NOTED																								
	KEYED NOTE REFERENCE			NL	NIGHT LIGHT	V	VOLT/VOLTAGE																								
	DETAIL REFERENCE: DETAIL NUMBER INDICATED ON TOP; DRAWING NUMBER INDICATED ON BOTTOM			NTS	NOT TO SCALE	VA	VOLT AMPERE																								
	POWER DISTRIBUTION			OC	ON CENTER	VAV	VARIABLE AIR VOLUME																								
	DISTRIBUTION PANELBOARD, 208Y/120V-SURFACE OR FLUSH MOUNTED.			PC	PERSONAL COMPUTER	VP	VAPORPROOF																								
	DISTRIBUTION PANELBOARD, 480Y/277V-SURFACE OR FLUSH MOUNTED			Ø	PHASE	WP	WEATHER PROOF																								
	MAJOR ELECTRICAL COMPONENT OR DEVICE. VOLTAGE AND AMPERAGE AS NOTED.			PNL	PANEL	XFMR	TRANSFORMER																								
				W	WATT																										
				W	WIRE																										
				WH	WALL HEATER																										
				E	EXISTING																										
	NY ENGINEERS 382 NE 191ST STREET SUITE 49674, MIAMI, FL 33179		PROJECT NAME		PHYSICAL LOCATION		ELECTRICAL NOTES, ABBREVIATIONS, SYMBOLS		GRAPHIC SCALE		SEAL		PROJECT NO.		SCALE		DRAWN BY		CHECKED BY		DATE		06/04/2025		05/06/2025		04/29/2025		06/04/2025		E0.1

ELECTRICAL SPECIFICATIONS

1. GENERAL:
 A. THE "GENERAL CONDITIONS OF THE CONTRACT FOR CONSTRUCTION," AIA DOCUMENT A201, LATEST EDITION, AND THESE SPECIFICATIONS AS APPLICABLE ARE PART OF THIS CONTRACT.
 B. DRAWINGS ARE DIAGRAMMATIC AND INDICATE GENERAL ARRANGEMENT OF SYSTEMS AND WORK. CONDUIT ROUTING IS SHOWN DIAGRAMMATICALLY AND DOES NOT SHOW ALL OFFSETS, DROPS AND RESTRAints. THE CONTRACTOR SHALL ALLOW HIS PRICE FOR ROUTING OF CONDUIT TO AVOID OBSTRUCTIONS. COORDINATION WITH EXISTING SERVICES, INCLUDING THOSE OF OTHER TRADES, IS REQUIRED, MAINTAIN HEADROOM AND SPACE CONDITIONS.
 C. BIDDERS, BEFORE SUBMITTING PROPOSALS, SHALL VISIT AND CAREFULLY EXAMINE THE AREA AFFECTED BY THIS WORK TO FAMILIARIZE THEM WITH THE EXISTING CONDITIONS AND THE DIFFICULTIES THAT WILL ATTEND THE EXECUTION OF THIS WORK. SUBMISSION OF A PROPOSAL WILL BE CONSTRUED AS EVIDENCE THAT SUCH AN EXAMINATION HAS BEEN MADE, AND LATER CLAIMS WILL NOT BE RECOGNIZED FOR EXTRA LABOR, EQUIPMENT, OR MATERIALS, REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WHICH COULD HAVE BEEN FORESEEN HAD SUCH AN EXAMINATION BEEN MADE.
 D. INSTALL WORK SO AS TO BE READILY ACCESSIBLE. FOR OPERATION, MAINTENANCE AND REPAIR, MINOR DEVIATIONS FROM DRAWING MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST SHALL NOT BE MADE WITHOUT APPROVAL.
 E. REMOVAL AND RELOCATION OF CERTAIN EXISTING WORK MAY BE NECESSARY FOR THE PERFORMANCE OF THE GENERAL WORK. ALL EXISTING CONDITIONS CANNOT BE COMPLETELY DETAILED ON THE DRAWINGS. THE CONTRACTOR SHALL SURVEY THE SITE AND INCLUDE ALL CHANGES AND CHARGES IN MAKING UP THE WORK PROPOSAL.
 F. CONNECTIONS TO EXISTING WORK: INSTALL NEW WORK AND CONNECT TO EXISTING WORK. MINIMUM DIFFERENCES TO EXISTING FACILITIES, TEMPORARY SHUTDOWNS OF EXISTING SERVICES SHALL BE PERFORMED AT NO ADDITIONAL CHARGES. AT TIMES NOT TO INTERFERE WITH NORMAL OPERATION OF EXISTING FACILITIES AND ONLY WITH WRITTEN CONSENT OF OWNER. ALARM AND EMERGENCY SYSTEMS SHALL NOT BE INTERRUPTED. MAINTAIN CONTINUOUS OPERATION OF EXISTING FACILITIES AS REQUIRED WITH NECESSARY TEMPORARY CONNECTIONS BETWEEN NEW AND EXISTING WORK. CONNECT NEW WORK TO EXISTING WORK IN A SAFE AND ACCEPTABLE MANNER. RESTORE EXISTING DISTURBED WORK TO ORIGINAL CONDITION, INCLUDING MAINTENANCE OF WIRING CONTINUITY AS REQUIRED.
 G. DISCONNECT, REMOVE AND/OR RELOCATE EXISTING MATERIAL, EQUIPMENT AND OTHER WORK AS NOTED OR REQUIRED FOR PROPER INSTALLATION OF NEW WORK.
 H. THE CONTRACTOR SHALL KEEP ALL EQUIPMENT AND MATERIALS, AND ALL PARTS OF THE BUILDING EXTERIOR SPACES AND ADJACENT STREETS, SIDEWALKS AND PAVEMENTS, FREE FROM MATERIAL AND DEBRIS RESULTING FROM THE EXECUTION OF THIS WORK. EXCESS MATERIALS WILL NOT BE PERMITTED TO ACCUMULATE EITHER ON THE INTERIOR OR THE EXTERIOR.
 I. SEAL OPENINGS THROUGH PARTITIONS, WALLS AND FLOORS WITH MINERAL WOOL OR OTHER NONCOMBUSTIBLE MATERIAL, UNLESS OTHERWISE NOTED.
 J. PROVIDE ALL NECESSARY FLASHING AND COUNTER FLASHING TO MAINTAIN THE WATERPROOFING INTEGRITY OF THE BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF CONDUIT AND EQUIPMENT. PROVIDE EQUIPMENT CURBS AS REQUIRED.
 K. ALL EXISTING MATERIAL, EQUIPMENT AND CONSTRUCTION DEBRIS TO BE REMOVED UNDER THIS CONTRACT SHALL BECOME THE PROPERTY OF THE CONTRACTOR WITH THE EXCEPTION OF SPECIFIC EQUIPMENT AND APPARATUS REQUESTED BY THE BUILDING REPRESENTATIVE, ARCHITECT OR AS NOTED TO BE RELOCATED ON THE DRAWINGS. REMOVED EQUIPMENT SHALL BE PROPERLY DISPOSED OF BY THIS CONTRACTOR.
 L. THE CONTRACTOR'S PROPOSAL FOR ALL WORK SHALL BE PREDICATED ON THE PERFORMANCE OF THE WORK DURING REGULAR WORKING HOURS. WHEN SO DIRECTED, HOWEVER, THE CONTRACTOR SHALL INSTALL WORK DURING OVERTIME HOURS AND THE ADDITIONAL COST TO BE CHARGED THEREFOR SHALL BE ONLY THE "PREMIUM" PORTION OF THE WAGES PAID.
 M. UNLESS OTHERWISE SPECIFICALLY NOTED OR SPECIFIED, INCLUDE ALL CUTTING AND PATCHING OF EXISTING FLOORS, WALLS, PARTITIONS AND OTHER MATERIALS IN THE EXISTING BUILDING. THE CONTRACTOR SHALL RESTORE THESE AREAS TO ORIGINAL CONDITION.
 N. ALL MATERIAL AND EQUIPMENT SHALL BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
 O. INSURANCE: PROVIDE IN ACCORDANCE WITH OWNER/BUILDING REQUIREMENTS AND SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND INSURER.
 P. THE FINAL ACCEPTANCE SHALL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, TESTED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATE OF INSPECTION AND APPROVAL.

2. GENERAL PROVISIONS FOR ELECTRICAL WORK:
 A. DEFINITIONS:
 1) "PROVIDE": TO FURNISH, INSTALL AND CONNECT UP COMPLETE AND READY FOR SAFE AND REGULAR OPERATION THE PARTICULAR WORK REFERRED TO UNLESS SPECIFICALLY OTHERWISE NOTED.
 2) "INSTALL": TO ERECT, MOUNT AND CONNECT COMPLETE WITH RELATED ACCESSORIES.
 3) "FURNISH" OR "SUPPLY": TO PURCHASE, PROCURE, ACQUIRE, AND DELIVER COMPLETE WITH RELATED ACCESSORIES.
 4) "WORK": LABOR, MATERIALS, EQUIPMENT, APPARATUS, CONTROLS, ACCESSORIES AND OTHER ITEMS REQUIRED FOR PROPER AND COMPLETE INSTALLATION.
 5) "WIRING": RACEWAY, FITTINGS, WIRE, BOXES, AND RELATED ITEMS.
 6) "CONCEALED": EMBEDDED IN MASONRY OR OTHER CONSTRUCTION, INSTALLED IN FURRED SPACES, WITHIN DOUBLE PARTITIONS OR HUNG CEILINGS, IN TRENCHES, IN CRAWL SPACES, OR IN ENCLOSURES.
 7) "EXPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.
 8) "SIMILAR" OR "EQUAL": EQUAL IN MATERIALS, WEIGHT, SIZE, DESIGN AND EFFICIENCY OF SPECIFIED PRODUCT.
 B. TEMPORARY LIGHT AND POWER: PROVIDE TEMPORARY LIGHT AND POWER SYSTEMS, EASING POSSIBLE DATE WITHIN THE CONTRACT AREA FOR THE REQUIREMENTS OF ALL TRADES AS HEREIN DESCRIBED. EXTEND SYSTEMS TO NEW CONSTRUCTION AS SOON AS PHYSICALLY POSSIBLE. MAINTAIN SYSTEM DURING WORKING OWNER. PROVIDE ALL REQUIRED MAINTENANCE, INCLUDING LAMPS AND SOCKETS.

C. QUALITY ASSURANCE:
 1) QUALITY OF MATERIALS: ALL EQUIPMENT SHALL BE NEW SPECIFICATION GRADE, FREE FROM DEFECTS AND LISTED BY APPROVED TESTING AGENCY AND BEARING THEIR LABEL MATERIALS AND EQUIPMENT OF SIMILAR APPLICATION SHALL BE OF SAME MANUFACTURER, EXCEPT AS NOTED.
 2) GUARANTEE: ALL MATERIALS AND WORKMANSHIP SHALL BE GUARANTEED AS DEFINED IN PARAGRAPH 2.C.
 3) CURRENT CHARACTERISTICS:
 a. SERVICE: 120/208 VOLT, 3 PHASE, 4 WIRE, 60 HERTZ WITH GROUNDED NEUTRAL.
 b. DISTRIBUTION: 120/208 VOLT, 3 PHASE, 4 WIRE, 60 HERTZ WITH GROUNDED NEUTRAL.
 4) HEIGHTS OF OUTLETS:
 a. FROM FINISHED FLOOR TO CENTERLINE OF OUTLETS FOR:
 - RECEPTACLES AND TELEPHONES: 1 FT - 6 IN.
 - WALL SWITCHES: 4 FT - 0 IN.
 - WALL FIXTURES: 7 FT - 0 IN.
 - MOTOR CONTROLLERS: 5 FT - 0 IN.
 - CLOCKS: 7 FT - 6 IN
 b. EXCEPTIONS: AT JUNCTION OF DIFFERENT WALL FINISH MATERIALS, ON MOLDING OR BREAK IN WALL SURFACE, IN VIOLATION OF CODE, OR AS NOTED OR DIRECTED.
 D. PRODUCT DELIVERY, STORAGE AND HANDLING:
 1) MOVING OF EQUIPMENT: WHERE NECESSARY, SHIP IN CARTED SECTIONS OF SIZE TO PERMIT PASSING THROUGH AVAILABLE SPACES.
 2) ACCESSIBILITY: FOR OPERATION, MAINTENANCE AND REPAIR, MINOR DEVIATIONS SHALL BE PERMITTED, CHANGES OF MAGNITUDE OR INVOLVING EXTRA COST ARE NOT PERMISSIBLE WITHOUT REVIEW. GROUP CONCEALED ELECTRICAL EQUIPMENT REQUIRING ACCESS WITH EQUIPMENT FREELY ACCESSIBLE THROUGH ACCESS DOORS.
 E. MATERIALS:
 1) NAMEPLATES: PROVIDE BLACK LAMINOID SHEET WITH 3/4 IN. WHITE LETTERING, FASTENED WITH EPOXY CEMENT FOR EACH DISCONNECT SWITCH, CIRCUIT BREAKER, PANEL, CABINET, TRANSFORMER, ENCLOSURE, MOTOR CONTROLLER AND THE LIKE. NAMEPLATES SHALL DESCRIBE THE NAME AND NUMBER OF EACH COMPONENT.
 2) CABLE TAGS: TAG EACH CONDUCTOR PASSING THROUGH SPLICING OR PULL BOX WITH A WHITE LINEN TAG, INDICATING POINT OF ORIGIN AND TERMINATION OF THE CIRCUIT.
 3) INSERTS AND SUPPORTS:
 a. INSERTS: STEEL, SLOTTED TYPE, FACTORY PAINTED.
 - SINGLE ROD: SIMILAR TO GRINNELL FIG. 281.
 - MULTI-ROD: SIMILAR TO FEE AND MASON SERIES 9000 WITH END CAPS AND CLOSURE STRIPS.
 - CLIP FORM NAILS FLUSH WITH INSERTS.
 - MAXIMUM LOADING 75 PERCENT OF RATING.
 b. SUPPORTS FROM BUILDING CONSTRUCTION: INSERTS, BEAM CLAMPS, STEEL FISHPLATES (IN CONCRETE FILL ONLY), CANTILEVER BRACKETS OR OTHER MEANS. SUBMIT FOR REVIEW.
 c. GROUPED LINES AND SERVICES: TRAPEZE HANGERS OF BOLTED ANGLES OR CHANNELS.
 d. WHERE BUILDING CONSTRUCTION IS INADEQUATE: PROVIDE ADDITIONAL FRAMING. SUBMIT FOR REVIEW.
 F. PAINT SHALL BE THE BEST GRADE FOR ITS PURPOSE. DELIVER IN ORIGINAL SEALED CONTAINERS AND APPLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. COLOR SHOULD BE SELECTED BY ARCHITECT OR ENGINEER. UTILIZE GALVANIZED IRON PRIMER ON PANEL AND PULL BOXES. AFTER FABRICATION, UTILIZE HOT DIPPED GALVANIZED OR DIPPED IN ZINC BASED PRIMER FOR OUTLET BOXES, JUNCTION BOXES, CONDUIT HANGERS, RODS, INSERTS AND SUPPORTS. ZINC BASED PRIMER WITH FINISH TO MATCH SURROUNDINGS SHALL BE USED FOR MARRED SURFACES OF STEEL EQUIPMENT AND RACEWAYS. A FIELD-APPLIED ZINC BASED PRIMER COAT SHALL BE UTILIZED FOR STEEL OR IRONWORK.
 G. BRUSH AND CLEAN WORK PRIOR TO CONCEALING, PAINTING AND ACCEPTANCE. PAINTED EXPOSED WORK SOILED OR DAMAGED; CLEAN AND REPAIR TO MATCH ADJOINING WORK BEFORE FINAL ACCEPTANCE. REMOVE DEBRIS FROM INSIDE AND OUTSIDE OF MATERIAL AND EQUIPMENT.
 H. FINAL LOCATIONS AND MOUNTING ORIENTATIONS OF ALL SWITCHES, RECEPTACLES AND LIGHT FIXTURES SHALL BE VERIFIED WITH ARCHITECT.
 I. ALL ACCESS DOOR LOCATIONS SHALL BE REVIEWED BY ARCHITECT PRIOR TO INSTALLATION.
 3. SCOPE OF WORK:
 A. SCOPE OF WORK SHALL CONSIST OF PROVIDING LABOR, MATERIALS, EQUIPMENT, SERVICES AND FEES NECESSARY FOR COMPLETE AND SAFE INSTALLATION IN CONFORMING WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE INDUSTRY, NATIONAL AND LOCAL CODES AND AUTHORITIES HAVING JURISDICTION, AS INDICATED ON DRAWINGS AND HEREIN SPECIFIED.
 B. ALL DRAWINGS, PLANS, DETAILS, SPECIFICATIONS AND SPECIFICATION ADDENDA ARE MADE PART OF THIS CONTRACT AND SHALL APPLY TO ALL WORK UNDER THE CONTRACT UNLESS OTHERWISE AMENDED, MODIFIED, SUPPLIED OR SPECIFIED HEREIN.
 C. THE CONTRACTOR SHALL FURNISH A WRITTEN GUARANTEE TO REPLACE OR REPAIR, PROMPTLY AND ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED FOR ANY WORKMANSHIP AND EQUIPMENT IN WHICH DEFECTS DEVELOP WITHIN ONE YEAR FROM THE DATE OF FINAL CERTIFICATE FOR PAYMENT AND/OR FROM DATE OF ACTUAL USE OF EQUIPMENT OR OCCUPANCY OF SPACES BY OWNER INCLUDED UNDER THE VARIOUS PARTS OF THE WORK, WHICHEVER, DATE IS EARLIER. THIS WORK SHALL BE BONDED AND INSURED BY THE OWNER. THIS GUARANTEE SHALL ALSO PROVIDE THAT WHERE DEFECTS OCCUR, THE CONTRACTOR WILL ASSUME RESPONSIBILITY OF OTHER TRADES AFFECTED BY DEFECTS, REPAIRS OR REPLACEMENTS IN EQUIPMENT SUPPLIED BY THE CONTRACTOR.

7. FUSES:
 A. CIRCUITS 0 TO 600 AMPERES SHALL BE PROTECTED BY FUSES SIMILAR TO CURRENT LIMITING BUSSMANN LOW-PEAK DUAL-ELEMENT TIME-DELAY LPN-RK (AMP)SP (250V) /LPS-RK (AMP)SP (600V) OR LPJ (AMP)SP (250V) /LPS-RK (AMP)SP (600V) (UL CLASS RK1 OR CLASS J), AND BE LISTED BY UL WITH AN INTERRUPTING RATING OF 300,000 AMPERES RMS SYMMETRICAL.
 B. MOTOR CIRCUITS - ALL INDIVIDUAL MOTOR CIRCUITS WITH FULL LOAD AMPERE RATINGS (FLA) OF 480 AMPERES OR LESS SHALL BE PROTECTED BY FUSES SIMILAR TO CURRENT LIMITING BUSSMANN LOW-PEAK DUAL-ELEMENT TIME-DELAY LPN-RK (AMP)SP (250V) /LPS-RK (AMP)SP (600V) OR LPJ (AMP)SP (600V) (UL CLASS RK1 OR CLASS J), AND BE LISTED BY UL WITH AN INTERRUPTING RATING OF 300,000 AMPERES RMS SYMMETRICAL.
 C. ALL FUSES SHALL BE PROVIDED BY SAME MANUFACTURER.
 D. PROVIDE 1 SPACE MATCHING FUSE FOR EACH SET OF 3.
 E. CIRCUIT BREAKERS: MOLDED CASE BREAKERS SHALL BE THERMAL-MAGNETIC, QUICK-MAKE-QUICK-BREAK, BOLT-ON TYPE, MANUALLY OPERATED WITH INSULATED TRIP-FREE HANDLE. MULTI-POLE TYPE BREAKERS SHALL CONTAIN INTERNAL TRIP BAR TERMINALS SHALL BE LISTED BY UL FOR COPPER OR ALUMINUM CABLE. PROVIDED AUXILIARY DEVICES WHERE REQUIRED FOR SHUNT-TRIPPING, OPEN AND CLOSE MOTOR OPERATOR AND ALARM INDICATION. ENCLOSURES SHALL BE DEAD FRONT, NEMA TYPE 1, EXCEPT AS NOTED. FRAMES, IC AND INTERCHANGEABLE TRIPS SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED:
 1) 120 VOLTS, 100-AMP FRAME: 10,000 AMPS, 1 POLE.
 2) 120/240 VOLTS, 225-AMP FRAME: 22,000 AMPS MINIMUM.
 3) AIC RATING SHALL BE COORDINATED WITH THE UTILITY COMPANY. BASE BID ACCORDINGLY.

8. RACEWAYS:
 A. PROVIDE RACEWAYS COMPLETE WITH BOXES, FITTINGS AND ACCESSORIES. CONDUIT OR TUBING SIZES REFERRED TO IN SPECIFICATIONS AND ON DRAWINGS ARE NOMINAL DIAMETERS. MINIMUM DIAMETER SHALL BE 3/4 IN.
 B. MATERIALS:
 1) RACEWAYS:
 a. RIGID STEEL CONDUIT: FULL-WEIGHT PIPE, GALVANIZED, THREADED.
 b. ELECTROMETALLIC TUBING (EMT): THIN WALL PIPE, GALVANIZED, THREADED.
 c. FLEXIBLE STEEL CONDUIT: CONTINUOUS SINGLE STRIP, GALVANIZED.
 d. WIREWAYS: WIRE SHALL BE AS NOTED, MINIMUM NO. 16 GAUGE STEEL, WITH GROUND CONTINUITY. FINISH SHALL BE BAKED ENAMEL. COVERS SHALL BE SCREW-ON.
 e. SURFACE METAL RACEWAY: SIZE AS NOTED. BASE 0.04 IN., COVER 0.25 IN. MATERIAL SHALL BE STEEL. FINISH SHALL BE BAKED ENAMEL. COVERS SHALL BE SCREW-ON.
 2) FITTINGS AND ACCESSORIES:
 a. RIGID STEEL: NONSPLIT, THREADED, STEEL OR MALLEABLE IRON. ZINC DIE CAST NOT PERMITTED.
 b. ELECTROMETALLIC TUBING: COMPRESSION TYPE. GALVANIZED RIGID STEEL ELBOWS, 2 IN. OR LARGER.
 c. FLEXIBLE METALLIC CONDUIT: ANGLE WEDGE TYPE WITH INSULATED THROAT.
 3) BOXES:
 a. OUTLET BOXES: EXCEPT AS OTHERWISE REQUIRED BY CONSTRUCTION, DEVICES OR WIRING, BOXES SHALL BE STANDARD STEEL, 1 1/4 IN. OR OCTAGON FOR FIXTURES. BOXES ABOVE CEILING SHALL BE 1 1/2 IN. DEEP. BOXES IN CEILING OR SLAB SHALL BE 3 IN. DEEP. BOXES IN WALL FOR FIXTURES SHALL BE 2-3/4 IN. DEEP. BOXES IN WALL FOR RECEPTACLES AND SWITCHES SHALL BE 1-1/2 IN. DEEP, FURNISH WITH RAISED COVERS AND FIXTURE STUDS WHERE REQUIRED. WITHOUT FIXTURE OR DEVICE: FURNISH BLANK COVERS. OFFSET BACK-TO-BACK OUTLETS WITH MINIMUM 6 IN. SEPARATION.
 b. JUNCTION AND PULL BOXES: GALVANIZED SHEET STEEL WITH SCREW-ON COVERS, EXCEPT AS NOTED. FURNISH WITH INSULATED SUPPORTS FOR CABLES. LOCATIONS SHALL BE AS NOTED OR REQUIRED AND ACCESSIBLE. PROVIDE BARRIERS IN NEW AND RENOVATED BOXES BETWEEN 120/208 VOLT AND 265/460 VOLT WIRING AND BETWEEN EMERGENCY AND NORMAL WIRING. FLOOR BOXES SHALL BE SUITABLE FOR CONDUIT AND DEVIATION. RAISED OUTLETS SHALL BE HUBBELL #B2414 SERIES WITH FLUSH FLOOR FITTING FOR TELEPHONE AND FLUSH DUAL FLAP COVERS WITH DUPLEX RECEPTACLE FOR POWER AS NOTED. INCREASE SIZE TO SUIT AS NECESSARY.

6. LOW-VOLTAGE DISTRIBUTION EQUIPMENT:
 A. PROVIDE COMPLETE EQUIPMENT INCLUDING: SWITCHES, FUSES, CIRCUIT BREAKERS, PANELS AND TRANSFORMERS.
 B. ALL EQUIPMENT SHALL CONFORM TO NEMA, ANSI AND IEEE STANDARDS.
 C. DISCONNECT SWITCHES SHALL BE FUSED OR NONFUSED AS NOTED. VOLTAGE SHALL BE AS REQUIRED. SWITCHES SHALL BE HEAVY DUTY, EXCEPT AS NOTED, AND HORSEPOWER RATED FOR MOTOR LOADS. TWO-POLE SWITCHES SHALL BE PULL-TRIP. UL LISTED, MAXIMUM RATINGS OF 20 AMP AT 600 VOLTS AND 30 AMP AT 240 VOLTS. THREE-POLE SWITCHES SHALL BE SIMILAR TO HART AND HEGEMAN NO. 6808F. THREE-POLE SWITCHES SHALL BE SIMILAR TO HART AND HEGEMAN NO. 7810F. KNIFE-BLADE TYPE SWITCHES SHALL BE LOAD BREAK, QUICK-MAKE-QUICK-BREAK, UL CLASS R UP TO 600 AMP. MAXIMUM RATING EXCEPT AS NOTED SHALL BE 800 AMP. ALL OUTLETS SHALL BE PROVIDED WITH COVERS. COVERS SHALL BE SIMILAR TO GENERAL ELECTRIC QMR. ALL SWITCH ENCLOSURES SHALL BE DEAD FRONT, NEMA TYPE 1, EXCEPT AS NOTED.

NY ENGINEERS
 382 NE 191ST STREET
 SUITE 49674,
 MIAMI, FL 33179

02 06/04/2025 PERMIT SET
 01 05/06/2025 REVISED CHECK SET
 00 04/29/2025 CHECK SET
 NO. DATE ISSUE DESCRIPTION

PROJECT NAME
 PHYSICAL LOCATION
 DRAWING TITLE

ELECTRICAL
 SPECIFICATIONS
 SHEET 1 OF 2
 GRAPHIC SCALE

SEAL PROJECT NO. _____
 SCALE AS NOTED
 DRAWN BY NYE
 CHECKED BY NYE
 DATE 06/04/2025
 SHEET NUMBER E0.2

ELECTRICAL SPECIFICATIONS (CONT.)

C. PROVIDE RACEWAYS ONLY AS HEREIN SPECIFIED, EXCEPT AS NOTED. RACEWAYS SHALL BE RUN CONCEALED, EXCEPT AS NOTED.

PROVIDE RACEWAY SUPPORT UTILIZING CEILING TRAPEZE, STRAP HANGERS, OR WALL BRACKETS. PROVIDE U-BOLTS AT EACH FLOOR LEVEL OF RISER RACEWAYS AND REINFORCED U-BOLTS FOR THROUGH THE FLOOR SYSTEMS. UTILIZE AN ASSEMBLY SIMILAR TO HUBBELL FIRE-STOP POKER-THROUGH-FLOOR BOX SYSTEM. FOR ABOVE FLOOR FITTINGS, TELEPHONE SHALL BE BUSHED HOLE AND POWER SHALL BE DUPLEX RECEPTACLE OR OTHER AS NOTED. PROVIDE SEPARATION BARRIER BETWEEN POWER AND TELEPHONE COMPARTMENTS. PROVIDE JUNCTION BOX ON UNDERSIDE OF FLOOR. PACK FITTING TO RESTORE FIRE RATING OF FLOOR.

SECURE ALL RACEWAYS TO SUPPORTS WITH PIPE STRAPS, OR U-BOLTS. SPACING OF SUPPORTS SHALL BE A MINIMUM OF 10 FT ON CENTER FOR METALLIC RACEWAY AND AS REQUIRED FOR NONMETALLIC RACEWAY. SPACING SHALL BE 5 FT ON CENTER FOR RACEWAYS AS PER CODE AND AS NOTED FOR OTHERS. MOUNT SUPPORTS TO STRUCTURE, MASONRY WITH TOGGLE BOLTS, OR HOLLOW MASONRY EXPANSION SHIELDS OR INSERTS IN CONCRETE AND BRICK. MACHINE SCREWS ON METAL, BEAM CLAMPS ON FRAMEWORK, WOOD SCREWS ON WOOD, AND PAN THROUGH STRAPS IN METAL DECK, NAILS, RAWL PLUGS OR WOOD PLUGS SHALL NOT BE PERMITTED, WHERE REQUIRED BY STRUCTURE, FURNISH THROUGH BOLTS AND FISHPLATES.

EXPOSED RACEWAYS SHALL BE RUN PARALLEL WITH OR AT RIGHT ANGLES TO WALLS. PROVIDE CLEARANCE WITH WATER, STEAM OR OTHER PIPING (MINIMUM 3 IN. SEPARATION FROM STEAM AND HOT WATER PIPES, EXCEPT 1 IN. FROM PIPE COVER AT CROSSINGS AND 18 IN. FOR PARALLEL RUNS), FOR HUNG CEILING OUTLETS, RUN IN HUNG CEILING AND CONNECT TO CEILING SUPPORT CHANNELS. IN MASONRY AND Poured CONCRETE, RUN VERTICALLY ONLY.

MANTAIN GROUNDING CONTINUITY OF INTERRUPTED METALLIC RACEWAYS WITH GROUND CONDUCTOR, AND IN FLEXIBLE CONDUIT FOR FEEDERS AND MOTOR TERMINAL CONNECTIONS.

EMPTY RACEWAYS OVER 10 FT LONG: PROVIDE FISH OR PULL WIRE, GALVANIZED OR NYLON ROPE.

RIGID STEEL CONDUIT SHALL BE PERMITTED FOR FEEDERS AND BRANCH CIRCUITS. PAINT MALE THREADS OF FIELD-THREADED CONDUIT WITH GRAPHITE-BASE PIPE COMPOUND AND BUTT CONDUIT ENDS. TOUCH UP MARRED SURFACES AND FIELD-CUT THREADS. CRC-COLD GALVANIZED, EMT SHALL BE PERMITTED FOR BRANCH CIRCUITS ONLY IN DRY LOCATIONS, DRY WALLS, HUNG CEILINGS, HOLLOW BLOCK WALLS AND DRY SPACES. EMT SHALL NOT BE PERMITTED IN RAISED FLOORS. FLEXIBLE STEEL CONDUIT SHALL BE UTILIZED FOR SHORT CONNECTIONS WHERE RIGID CONDUIT IS IMPRACTICAL. FROM OUTLET BOX TO RECESSED LIGHTING FIXTURE: PROVIDE MINIMUM 4 FT AND MAXIMUM 6 FT LENGTHS. FOR FINAL CONNECTION TO MOTOR TERMINAL BOX, TRANSFORMER AND OTHER VIBRATING EQUIPMENT: PROVIDE WITH POLYVINYL SHEATHING AND GROUND CONDUCTOR. MINIMUM LENGTH: 18 IN. WITH SLACK. CONNECT GROUND CONDUCTOR TO ENCLOSURE OR RACEWAY AT EACH END. FOR EXPANSION JOINT CROSSINGS, CROSS AT RIGHT ANGLES AND ANCHOR ENDS.

CUT CONDUIT ENDS SQUARE, REAM SMOOTH, PAINT MALE THREADS OF FIELD-THREADED RACEWAYS WITH GRAPHITE BASE PIPE COMPOUND. DRAW UP TIGHT WITH RACEWAY COUPLING.

ALL COUPLINGS SHALL BE COMPRESSION TYPE. NO SET SCREW FITTINGS.

EXPANSION FITTINGS SHALL BE INSTALLED AT RIGHT ANGLES WITH CLIP JOINT CENTERED IN EXPANSION JOINT. PROVIDE A LENGTH OF RUN IN ACCORDANCE MANUFACTURER'S RECOMMENDATIONS. PRESET FITTINGS SHALL ALLOW FOR TEMPERATURE VARIATION.

RACEWAYS PASSING THROUGH FIRE-RATED CONSTRUCTION: SEAL OPENING WITH FIRE SEALANT.

D. PROVIDE CABLE SUPPORTS IN ACCORDANCE WITH NATIONAL ELECTRIC CODE ARTICLE 300.19. CABLE SUPPORTS SHALL UTILIZE A ONE-PIECE PLUG WITH POZI-GRIP WEDGING PLUG AS MANUFACTURED BY OZ-GEDNEY.

INSTALL CABLE SUPPORTS AT THE TOP OF A VERTICAL RISE AND PROVIDE INTERMEDIATE ADDITIONAL SUPPORTS AS REQUIRED TO LIMIT SUPPORTED CONDUCTOR LENGTHS TO NOT GREATER THAN THOSE SPECIFIED IN TABLE 300.19(A).

ERECT WALL AND SWITCH OUTLETS IN ADVANCE OF FUllING AND FIREPROOFING. OUTLET BOXES SHALL BE SET SQUARE AND TRUE WITH BUILDING FINISH. SECURE TO BUILDING STRUCTURE BY ADJUSTABLE STRAP IRON OR GROUT IN WITH MASONRY. VERIFY OUTLET LOCATIONS IN FINISHED SPACES WITH ARCHITECTURAL DRAWINGS OF INTERIOR DETAILS AND FINISHES. PROVIDE BARRIERS BETWEEN SWITCHES CONNECTED TO DIFFERENT PHASES FOR VOLTAGES EXCEEDING 150 VOLTS TO GROUND.

PANEL JUNCTION AND PULL BOXES SHALL BE LOCATED CLEAR OF OTHER TRADES. CONCEAL JUNCTION AND PULL BOXES IN FINISHED SPACES, WHERE NECESSARY, REROUTE RACEWAYS OR MAKE OTHER ARRANGEMENTS FOR CONCEALMENT. BOXES SHALL BE ACCESSIBLE. SUPPORT BOXES FROM BUILDING STRUCTURE, INDEPENDENT OF CONDUIT. PROVIDE FLOOR-TO-CEILING CHANNELS FOR MOUNTING ON DRYWALL AND LIGHTWEIGHT CONSTRUCTION. OUTLET BOXES FOR FIXTURES RECESSED IN HUNG CEILINGS SHALL BE ACCESSIBLE THROUGH OPENING CREATED BY REMOVAL OF FIXTURE. SECURE TO BLACK IRON SUPPORT. MOTOR TERMINAL BOXES: COORDINATE WITH MOTOR BRANCH CIRCUIT CONDUIT AND WIRING; ADD BOX VOLUME WHERE REQUIRED.

E. FIRE SEALANTS: PROVIDE FOR RACEWAYS AND WIRE PASSING THROUGH FLOOR SLOTS, SLEEVES OR OPENINGS IN FIRE-PARTITION ROOMS.

F. PERFORM CONTINUITY TESTS OF RESISTANCE OF FEEDER CONDUITS FROM SERVICE TO POINT OF FINAL DISTRIBUTION USING 1 CONDUCTOR RETURN. MAXIMUM RESISTANCE SHALL BE 25 OHMS.

10. WIRE AND CABLE:

A. PROVIDE WIRE AND CABLE COMPLETE WITH ACCESSORIES. SIZE REFERENCE SHALL BE AWG EXCEPT AS NOTED.

B. CONDUCTORS SHALL BE COPPER, ASTM STANDARD SOLID (NO. 10 AND SMALLER) OR STRANDED (NO. 8 AND LARGER). GENERAL USE CABLEING SHALL BE NO. 12 MINIMUM, AT 120 VOLTS AND OVER 100 FT CIRCUIT LENGTH. PROVIDE NO. 10 MINIMUM, AT 265 VOLTS AND OVER 200 FT CIRCUIT LENGTH. PROVIDE NO. 10 MINIMUM.

C. CONTROL AND ALARM CABLING, EXCEPT AS NOTED, SHALL BE NO. 14 MINIMUM, AT 120 VOLTS AND OVER 200 FT CIRCUIT LENGTH. PROVIDE NO. 12 MINIMUM. OTHER VOLTAGES AND PHASES: ADJUST CABLE SIZING AS REQUIRED TO MAINTAIN VOLTAGE DROP, INCREASE RACEWAY SIZES FOR LARGER WIRE AS REQUIRED.

D. INSULATION SHALL BE RUBBER AND THERMOPLASTIC MEETING ASTM AND IEC60068-2-20 AND IEC60068-2-21. EXCEPT AS NOTED, TYPE SHH SHALL BE UTILIZED FOR BRANCH CIRCUITS LOCATED IN WIRING CHANNELS OF CONTINUOUS FLUORESCENT FIXTURES AND IN AMBIENT TEMPERATURES OVER 90 DEG C. FOR UNGROUNDED ISOLATED BRANCH CIRCUITS, PROVIDE CROSS-LINKED POLYETHYLENE INSULATION (TYPE XHHW).

E. FLEXIBLE METAL CONDUIT SHALL BE UTILIZED FOR BRANCH CIRCUITS IN DRY HOLLOW LOCATIONS, HUNG CEILINGS, AND BLOCK WALLS. NO. ARMORED CABLE, BX MC CABLE AND ROMEX ARE PERMITTED TO USE. THESE SPECIFIED CABLES ARE TO BE AVOIDED AS THESE ARE NOT APPROVED TO USE.

F. COLOR CODING SHALL BE AS FOLLOWS:

120/208 VOLT SYSTEM:
BLACK FOR A PHASE
RED FOR B PHASE
BLUE FOR C PHASE

1) NEUTRAL WIRE SHALL UTILIZE WHITE OUTER COVERING THROUGHOUT. EQUIPMENT GROUND WIRE SHALL UTILIZE GREEN OUTER COVERING THROUGHOUT.

WHERE COLOR-CODED CABLE IS NOT AVAILABLE, CERTIFY IN WRITING AND REQUEST PERMISSION TO OVERLAP CONDUCTORS WITH 6 IN. OF COLOR TAPING IN ACCESSIBLE LOCATIONS.

G. PROVIDE FLAMEPROOF LINEN OR FIBER TAGS IN ACCESSIBLE LOCATIONS. FOR FEEDERS INDICATE FEEDER NUMBER, SIZE, PHASE AND POINTS OF ORIGIN AND TERMINATIONS. FOR CONTROL AND ALARM WIRING INDICATE TYPE (CONTROL OR ALARM), SIZE OF WIRE, AND POINTS OF ORIGIN AND TERMINATIONS.

H. TERMINATIONS, SPLICES AND TAPS UNDER 600 VOLTS: COPPER CONDUCTORS NO. 10 AND SMALLER SHALL UTILIZE COMPRESSION-TYPE OF TWIST-ON SPRING-LOADED CONNECTORS AND CLEAR NYLON-INSULATED COVERING. COPPER CONDUCTORS NO. 8 AND LARGER SHALL UTILIZE MECHANICAL BOLTED PRESSURE OR HYDRAULIC COMPRESSION TYPE USING MANUFACTURER'S RECOMMENDED TOOLING. CABLE LUGS AND CONNECTORS SHALL UTILIZE COMPRESSION TYPE OF SAME METAL AS CONDUCTOR. PROVIDE TO MATCH CABLE, WITH MARKING INDICATING SIZE AND TYPE. COPPER LUG CONNECTIONS TO BUS BARS: USE ANTISEIZE COMPOUND ON TANG.

I. NOT MORE THAN 3 LIGHTING OR CONVENIENCE OUTLET CIRCUITS SHALL BE INSTALLED IN ONE CONDUIT UNLESS OTHERWISE INDICATED. FOR NO THERMOPLASTIC CABLES AT TEMPERATURES LOWER THAN 32 DEG F, PROVIDE SEPARATE RACEWAYS FOR CONDUCTORS OF 120/208 AND 265/460 VOLT SYSTEMS. EXCEPT 460 VOLT, MOTOR BRANCH CIRCUIT WIRING AND RELATED 120 VOLT CONTROL WIRING, THERMOPLASTIC WIRES SHALL NOT BE INSTALLED IN COMPUTER AREA RAISED FLOORS.

J. LEAVE WIRES WITH SUFFICIENT SLACK TO PERMIT MAKING FINAL CONNECTIONS.

K. PERFORM CONTINUITY AND INSULATION TESTS. MEGGER TEST 100 PERCENT OF FEEDERS, 10 PERCENT OF BRANCH CIRCUITS AND ALL MOTOR CIRCUITS OVER 25 HP.

L. PERFORM TESTS PRIOR TO CONNECTING EQUIPMENT AND IN PRESENCE OF AUTHORIZED REPRESENTATIVES. SUBMIT WRITTEN REPORT OF RESULTS. CORRECT OR REPLACE CABLE TESTING BELOW MANUFACTURER'S STANDARDS.

11. WIRING DEVICES:

A. WIRING DEVICES SHALL BE SPECIFICATION GRADE UNLESS OTHERWISE SPECIFIED. ALL DEVICES SHALL BE FLUSH MOUNTED, UNLESS OTHERWISE NOTED. PROVIDE COMPLETE MATERIAL AND ACCESSORIES AS NOTED.

B. LOCAL WALL SWITCHES SHALL BE ROCKER TYPE, QUIET OPERATING, RATED 20 AMP, 120/277 VOLT, AC, SIMILAR TO LEVITON DECORA SERIES A5621 (SINGLE POLE), A5623 (3-WAY) AND A5624 (4-WAY).

C. DEVICE PLATES: SEE ARCHITECT FOR TYPE, FOR RECEPTACLES WITH OTHER THAN 120 VOLT, INSCRIBED VOLTAGE AVAILABLE.

D. COLORS: COORDINATE COLORS WITH ARCHITECT.

E. MOUNTING ORIENTATION OF RECEPTACLES (HORIZONTAL OR VERTICAL): COORDINATE WITH ARCHITECT.

12. LIGHTING FIXTURES:

A. FIXTURES TO BE AS SPECIFIED BY ARCHITECT AND SHALL BE COMPLETELY FACTORY ASSEMBLED, WIRED, AND EQUIPPED WITH ALL NECESSARY SOCKETS, BALLASTS, SUPPORTING HARDWARE AND ACCESSORIES. REFER TO DRAWINGS FOR INDIVIDUAL FIXTURE DESCRIPTIONS.

B. FIXTURE CATALOG NUMBERS USED TO ILLUSTRATE EQUIPMENT TYPE DO NOT NECESSARILY DENOTE REQUIRED MOUNTING EQUIPMENT OR ACCESSORIES. PROVIDE ACCESSORIES TO SUIT.

C. LED DRIVERS SHALL BE ELECTRONIC TYPE, LABELED AS COMPLIANT WITH RADIO FREQUENCY INTERFERENCE (RFI) REQUIREMENTS OF FCC TITLE 47, PART 15 AND COMPLY WITH NEMA SSL-1 "ELECTRONIC DRIVERS FOR LED DEVICES, ARRAYS, OR SYSTEMS". LED DRIVERS SHALL HAVE A SOUND RATING OF "A", HAVE A MINIMUM EFFICIENCY OF 65% AND BE RATED FOR A THD OF LESS THAN 20% AT ALL INPUT VOLTAGES.

D. DIMMABLE LED DRIVERS SHALL BE CAPABLE OF DIMMING WITHOUT LED STROBING OR FLICKER ACROSS THEIR FULL DIMMING RANGE. PROVIDE TYPE OF LED DRIVER AS PER LIGHTING FIXTURE SCHEDULE. DIMMABLE LED DRIVERS SHALL BE 0-10V WHERE NOT INDICATED. COORDINATE WITH LIGHTING VENDOR FOR TYPE OF DIMMER. BASE BID ACCORDINGLY.

E. CONTINUOUS ROW, TWO LAMP STRIP FIXTURES SHALL BE STAGGERED TYPE.

F. EXIT SIGNS SHALL BE PRECISION DIE-CAST ALUMINUM HOUSING WITH LASER-FORMED ACRYLIC LEGEND. EXIT SIGNS SHALL COMPLY WITH UL 924 AND APPROVED AS REQUIRED. AC POWERED WITH

PREMIUM LONG-LIFE NICKEL CADMIUM BATTERY WITH STANDARD UL LISTED 3-HOUR RUN TIME. PROVIDE WITH INTEGRAL AUTOMATIC CHARGER IN A SELF CONTAINED POWER PACK. LED INDICATOR WITH PUSH TO TEST SWITCH.

13. GROUNDING AND BONDING:

A. PROVIDE GROUNDING SYSTEM IN ACCORDANCE WITH (NATIONAL ELECTRICAL CODE AND THESE SPECIFICATIONS). THE WIRING SYSTEM SHALL BE INSTALLED AS REQUIRED TO PROVIDE A COMPLY GROUNDED SYSTEM. WHERE FLEXIBLE CONDUIT IS USED FOR PART OF THE CONDUIT RUN, EXCEPT LIGHTING BRANCH CIRCUITS, AN INSULATED GROUNDING CONDUCTOR SHALL BE PROVIDED IN THE CONDUIT AND CONNECTED TO GROUNDING BUSHINGS AT EACH END OF THE RUN.

B. USE EXOTHERMIC WELDING PROCESS FOR INACCESSIBLE CONNECTIONS.

C. EXTEND SYSTEM GROUND TO INCLUDE ALL THE ELECTRICAL EQUIPMENT IN THE SCOPE OF WORK.

D. WHERE FLEXIBLE METALLIC CONDUIT IS USED AN INTERNAL GROUND CONDUCTOR SHALL BE INSTALLED.

E. IN ADDITION, FURNISH A SEPARATE INSULATED GREEN EQUIPMENT GROUND CONDUCTOR WHERE INDICATED ON DRAWINGS AND FOR THE FOLLOWING BRANCH CIRCUITS:

1) CIRCUITS SERVING ANY WALL BOX DIMMER.

2) CIRCUITS SERVING ANY ISOLATED GROUND RECEPTACLES. TERMINATE GROUND DIRECTLY AT AN EQUIPMENT GROUNDING CONDUCTOR TERMINAL OF THE SOURCE AT THE SOURCE, OR AS OTHER WISE NOTED ON DRAWINGS.

3) CIRCUITS SERVING ANY DUPLEX OR SIMPLEX COMPUTER RECEPTACLES

4) ANY CIRCUIT SERVED VIA AN ISOLATION TRANSFORMER OR COMPUTER POWER DISTRIBUTION UNIT.

14. PANELBOARDS:

A. PANELBOARDS SHALL BE OF THE DEAD FRONT TYPE MANUFACTURED IN CODE GAUGE AND SIZE BOXES FOR MOUNTING AS INDICATED ON PLANS COMPLETE WITH TRIM, DOORS AND LOCKS. ALL LOCKS SHALL BE KEYED ALIKE.

B. CIRCUIT BREAKERS SHALL BE OF THE BOLT-ON THERMAL MAGNETIC MOLDED CASE TYPE, AND SHALL HAVE THE TRIP RATINGS AND NUMBER OF POLES SHOWN IN SCHEDULES ON THE CONTRACT DRAWINGS. FOR BLANK (SPACE) COMPARTMENTS, PROVIDE FULL RATED BUS. MINIMUM CUTTER SPACES SHALL BE 5-3/4", SIDES, TOP AND BOTTOM, INCREASE FOR THROUGH FEEDERS. PROVIDE 25% COPPER GROUND BUS AND 100% COPPER NEUTRAL BUS AND INCREASE NEUTRAL BUS INDICATED.

C. LOCKING TABS SHALL BE PROVIDED ON ALL CIRCUIT BREAKERS SERVING EMERGENCY LIGHTING, FIRE ALARM SYSTEM, SECURITY SYSTEMS AND OTHER EMERGENCY OR CRITICAL EQUIPMENT AND AS NOTED ON THE CONTRACT DRAWINGS. A TOTAL OF 5 SPARE LOCKING TABS SHALL BE FURNISHED TO THE OWNER.

D. BUSES SHALL BE HARD DRAWN COPPER OF 98 PERCENT CONDUCTIVITY AND SHALL HAVE CROSS SECTIONAL AREAS LARGE ENOUGH TO LIMIT THE TEMPERATURE RISE WHEN CARRYING FULL LOAD, TO 35 DEGREES C. ABOVE AN AMBIENT INSIDE THE ENCLOSURE OF 55 DEGREES C. AS DEFINED IN IEEE STANDARD RULES. MAIN BUS CAPACITY SHALL BE AS SHOWN ON THE CONTRACT DRAWINGS.

E. ENCLOSURES SHALL BE SURFACE OR FLUSH AS INDICATED. TRIMS SHALL BE SECURED TO PANEL WITH MACHINE SCREWS. COVERS SHALL BE HINGED DOOR-IN-DOOR CONSTRUCTION WITH CYLINDER LOCKS AND CATCHES. LOCKS MUST BE COMPATIBLE WITH BUILDING STANDARD KEY SYSTEM AND WHEN NONE EXISTS, THEY SHALL BE SIMILAR TO A YALE NO. 911 KEY.

F. DISTRIBUTION AND SUB-DISTRIBUTION PANELBOARD SHALL BE A MINIMUM OF 30" WIDE AND 10" DEEP.

G. ALL STANDARD PANELBOARDS SHALL BE A MINIMUM OF 20" WIDE AND 5 3/4" DEEP.

H. FURNISH ALL PANELBOARDS WITH FEED-THRU LUGS UNLESS OTHERWISE INDICATED ON THE DRAWINGS.

I. ALL NEW PANELBOARDS SHALL BE PROVIDED WITH AN ENGRAVED WHITE CORE LAMACOID NAMEPLATE, WITH 3/4 IN. WHITE LETTERING ON A BLACK BACKGROUND, WITH DESIGNATION LISTED (PANELBOARD NAME), FASTENED WITH EPOXY CEMENT OR OVAL HEAD CHROME PLATED MACHINE SCREWS.

J. THE CIRCUIT DIRECTORY SHALL BE TYPEWRITTEN AND PROVIDED INSIDE EACH PANEL DOOR TO INDICATE EQUIPMENT AND/OR AREA SERVED. DIRECTORY HOLDER SHALL BE METAL FRAME WITH CLEAR PLASTIC, TRANSPARENT COVER. THE TYPEWRITTEN LIST INDICATING CIRCUIT NUMBERS, OUTLETS SUPPLIED AND THEIR LOCATIONS SHALL BE PROVIDED.

K. TIE-BARS SHALL NOT BE USED TO CREATE MULTI-POLE CIRCUITS. MAXIMUM 42 CIRCUITS ALLOWED.

L. ONLY ONE WIRE SHALL BE INSTALLED UNDER EACH CIRCUIT BREAKER LUG.

M. SHORT CIRCUIT RATING OF PANELBOARDS SHALL NOT BE LESS THAN AS INDICATED ON THE CONTRACT DRAWINGS OR SPECIFIED HEREIN. WHERE NOT INDICATED OR SPECIFIED THE MINIMUM SHORT CIRCUIT RATING SHALL BE EQUAL TO THE INTERRUPTING CAPACITY OF THE LOWEST RATED CIRCUIT BREAKER IN THE PANELBOARD, BUT IN NO CASE LESS THAN 10,000 AMPERES R.M.S. SYMMETRICAL FOR 208Y/120 VOLT SYSTEM AND 14,000 AMPERES R.M.S. SYMMETRICAL FOR 480Y/277 VOLT SYSTEM. SERIES RATED PANELBOARDS SHALL BE USED TO ACHIEVE REQUIRED SHORT CIRCUIT RATINGS.

15. TELEPHONE/ DATA/ TELEVISION CABLING SYSTEM

A. PROVIDE COMPLETE SYSTEM CONSISTING OF CABLING/ WIRING, OUTLETS BOXES, SLEEVES AND FISHWIRES AS REQUIRED.

B. EQUIPMENT SHALL BE LATEST MODEL YEAR AVAILABLE IN ACCORDANCE WITH UTILITY COMPANY AND TV PROVIDE REQUIREMENTS.

C. OUTLETS SHALL BE:

1) WALL: 4 IN. SQUARE WITH REDUCING COVER

02 06/04/2025 PERMIT SET
01 05/06/2025 REVISED CHECK SET
00 04/29/2025 CHECK SET

NO. DATE ISSUE DESCRIPTION

PROJECT NAME

PHYSICAL LOCATION

DRAWING TITLE

ELECTRICAL SPECIFICATIONS SHEET 2 OF 2

GRAPHIC SCALE

SEAL PROJECT NO. -


SCALE AS NOTED

DRAWN BY NYE

CHECKED BY NYE

DATE 06/04/2025

SHEET NUMBER E0.3



ELECTRICAL POWER PLAN KEYED WORK NOTES

1. PROVIDE NEW 200A, 120/208V "PANEL A" AND 100A, 120/208V "PABEL B". E.C. SHALL COORDINATE THE EXACT LOCATION AND REQUIREMENT PRIOR TO ROUGH-IN.
2. E.C. SHALL VERIFY THAT THE PANEL AREA IS UNOBSRUCTED AND SHALL HAVE CLEARANCE AS PER 110.26(A)&(B).
3. PROVIDE SHOW WINDOW RECEPTACLE AS PER NEC 210.62. VERIFY EXACT LOCATION WITH ARCHITECT/OWNER.
4. J-BOX FOR WALK-IN COOLER HEATER. E.C. SHALL COORDINATE EXACT LOCATION AND ELECTRICAL REQUIREMENT WITH ELECTRICAL MANUFACTURER.
5. MOUNT RECEPTACLE UNDER COUNTER TOP. PROVIDE (2) POWER CIRCUIT AS SHOWN. E.C. SHALL PROVIDE TWO CAT 6 CABLING FOR DESK. PROVIDE AN ADDITIONAL 6 FEET OF CABLING AT EITHER END OF CONNECTION. E.C. SHALL COORDINATE WITH IT DRAWINGS/SPECIALIST FOR EXACT LOCATION, POWER REQUIREMENTS AND MAKE PROVISIONS ACCORDINGLY. BASE BID ACCORDINGLY.
6. ELECTRICAL SUPPLY PROVISION FOR THE WATER HEATER(WH-1), WATER FILTRATION SYSTEM (WFS) & RECIRCULATION PUMP(RCP-1). E.C. SHALL COORDINATE WITH THE PLUMBING CONTRACTOR FOR THE EXACT POWER REQUIREMENTS PRIOR TO ROUGH-IN. BASE BID ACCORDINGLY.
7. PROVIDE LOCK ON TYPE CIRCUIT BREAKER FOR HAND DRYER JB. IN ACCORDANCE WITH THE NEC 422.31. E.C. SHALL COORDINATE EXACT POWER CONNECTION REQUIREMENT FOR HAND DRYERS WITH EQUIPMENT MANUFACTURER AND LOCATION WITH ARCHITECT/ OWNER. BASE BID ACCORDINGLY.
8. 15/1P CIRCUIT FOR WALK-IN COOLER EVAPORATOR. E.C. SHALL COORDINATE EXACT LOCATION AND ELECTRICAL REQUIREMENT WITH ELECTRICAL MANUFACTURER.
9. E.C. SHALL PROVIDE POWER AND NECESSARY WIRING FOR THE HOOD CONTROL PANEL & FIRE SUPPRESSION SYSTEM. E.C. TO COORDINATE WIT MANUFACTURER FOR POWER AND CONTROL REQUIREMENTS AND PROVIDE AS REQUIRED. BASE BID ACCORDINGLY.
10. LOCATION OF TIME CLOCK AND LIGHTING CONTACTOR. REFER TO CONTROL DIAGRAM ON DETAIL SHEET.
11. E.C. SHALL COORDINATE DISCONNECT AND FUSE REQUIREMENT FOR MECHANICAL UNIT WITH MECHANICAL CONTRACTOR AND EQUIPMENT MANUFACTURER PRIOR TO ROUGH-IN AND PROVIDE AS REQUIRED. COORDINATE LOCATION OF DISCONNECT WITH MANUFACTURER AND MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN. LOCATE AS REQUIRED TO MAINTAIN NEC CLEARANCES.
12. E.C. SHALL COORDINATE WITH THE OWNER/VENDOR FOR THE DISHWASHER POWER REQUIREMENTS.
13. ELECTRICAL CONTRACTOR SHALL STUB ALL ELECTRICAL CABLES FROM THE NEAREST WALL UNDER THE CABINET THROUGH UNDERGROUND CONDUITS AND PULL TO THE REQUIRED LOCATIONS. BASE BID ACCORDINGLY.
14. EXHAUST FAN INTERLOCKED WITH THE LIGHTING. E.C. SHALL COORDINATE THE EXACT POWER AND CONTROL REQUIREMENT FOR THE EXHAUST FAN IN COORDINATION WITH THE MECHANICAL CONTRACTOR. BASE BID ACCORDINGLY. REFER SHEET M-5.1 FOR MORE DETAIL.
15. PROVIDE TAMPER RESISTANT RECEPTACLES IN ACCORDANCE WITH THE NEC 406.12. E.C. SHALL COORDINATE EXACT REQUIREMENT AND LOCATION. BASE BID ACCORDINGLY.
16. E.C. TO RELOCATE EXISTING 277/480V, 200A "RETAIL PANEL RB4" AS SHOWN. VERIFY THE OPERABLE CONDITION AT THE SITE AND PROVIDE NEW IF FOUND IN-OPERABLE. REPORT ENGINEER IF ANY DISCREPANCY FOUND RELATED TO EXISTING PANELS. BASE BID ACCORDINGLY. REFER RISER DIAGRAM ON E-5.1 SHEET FOR MORE INFORMATION.
17. E.C. TO VERIFY EXISTING 277/480V, WIREWAY EXACT LOCATION AND CONDITION AT THE SITE AND PROVIDE AS REQUIRED IF FOUND IN-OPERABLE. REPORT ENGINEER IF ANY DISCREPANCY FOUND RELATED TO EXISTING PANELS. BASE BID ACCORDINGLY.
18. E.C. SHALL PROVIDE NEW 75 KVA, PRIMARY 480V AND SECONDARY 120/208V, CEILING SUSPENDED TRANSFORMER AS PER 450.13(B) & 450.21(A). E.C. SHALL COORDINATE WITH THE ARCHITECT/OWNER AS PER SITE CONDITION. BASE BID ACCORDINGLY.
19. E.C. TO COORDINATE WITH FURNITURE VENDOR FOR THE CONDUIT ROUTING AND OUTLET INSTALLATION. BASE BID ACCORDINGLY.
20. E.C. TO COORDINATE THE EXACT LOCATION, POWER REQUIREMENT AND MOUNTING HEIGHT WITH THE ARCHITECT/EQUIPMENT VENDOR. BASE BID ACCORDINGLY.
21. INDOOR HVAC UNITS POWERED FROM THE OUTDOOR UNIT. E.C. SHALL COORDINATE WITH THE MECHANICAL CONTRACTOR FOR EXACT LOCATION AND WIRING REQUIREMENT. BASE BID ACCORDINGLY.
22. E.C. SHALL COORDINATE THE EXACT LOCATION OF CONDENSER WITH THE WALK-IN-COOLER VENDOR AND PROVIDE POWER AS REQUIRED. BASE BID ACCORDINGLY.
23. E.C. SHALL PROVIDE RECEPTACLE ON NEARBY WALL FOR BEVERAGE DISPENSER AND PROVIDE POWER TO THE EQUIPMENT. E.C. TO COORDINATE EXACT LOCATION AND MOUNTING OF RECEPTACLE WITH OWNER/ARCHITECT PRIOR TO COMMENCEMENT OF WORK. BASE BID ACCORDINGLY.

ELECTRICAL POWER PLAN GENERAL NOTES

1. E.C. SHALL COORDINATE WITH OTHER TRADE CONTRACTORS FOR EXACT LOCATION AND POWER REQUIREMENT OF THE EQUIPMENT FROM OTHER TRADES. PROVIDE WIRING AND CONTROLS AS REQUIRED (IF NOT PROVIDED BY THEM), PRIOR TO BID. BASE BID ACCORDINGLY.
2. THE CLEAR WORKING SPACE SHALL BE PROVIDED FOR THE METERS, PANEL BOARDS, AND OTHER ELECTRICAL EQUIPMENT AS PER SECTION 110.26 OF NEC.
3. E.C. SHALL COORDINATE WITH THE UTILITY/ARCHITECT/OWNER FOR EXACT LOCATION OF THE NEW SERVICE METER AND OTHER ELECTRICAL DEVICES. PRIOR TO BID. BASE BID ACCORDINGLY.
4. ALL 125-VOLT THROUGH 250-VOLT RECEPTACLES IN KITCHEN OR AREAS WITH SINK, BATHROOMS AND ROOFTOPS SUPPLIED BY SINGLE-PHASE BRANCH CIRCUITS RATED 150 VOLTS OR LESS TO GROUND, 50 AMPERES OR LESS, AND ALL RECEPTACLES SUPPLIED BY THREE-PHASE BRANCH CIRCUITS RATED 150 VOLTS OR LESS TO GROUND, 100 AMPERES OR LESS SHALL HAVE GROUND-FAULT CIRCUIT-INTERRUPTER PROTECTION FOR PERSONNEL PER NEC 210.8(B).
5. ALL THE CIRCUITS SUPPLYING KITCHEN EQUIPMENT AND SHOWN "GFI" ON POWER PLAN SHALL BE PROTECTED EITHER AT A PANEL WITH GFI RATED BREAKER OR RECEPTACLE WITH GFI AS PER NEC 210.8. IF GFI RECEPTACLES ARE USED, CONTRACTOR SHALL LOCATE THE GFI RECEPTACLES SUCH THAT THESE ARE READILY ACCESSIBLE PER CODE.
6. E.C. SHALL FOLLOW GROUNDING/BONDING AS PER NEC ARTICLE 250.
7. ALL THE RECEPTACLES SHALL BE RATED PER CIRCUIT. E.C. SHALL VERIFY AND MAKE FINAL CONNECTIONS ACCORDINGLY.
8. E.C. SHALL PROVIDE GFCI PROTECTION FOR ALL THE FLOOR OUTLETS AS PER NEC ARTICLE 406.4(D)(3).
9. E.C. SHALL PROVIDE TYPED PANEL DIRECTORY FOR ALL THE ELECTRICAL PANELS AS PER NEC 408.4(A).
10. ALL CONDUITS PENETRATING COOLER WALLS SHALL BE PROVIDED WITH CONDUIT SEALS.
11. E.C. SHALL COORDINATE THE POWER REQUIREMENTS WITH EQUIPMENT MANUFACTURER FOR ALL THE EQUIPMENTS SHOWN ON THE PLAN AND FINAL NEMA RATINGS OF THE RECEPTACLES SHALL BE BASED ON THE FINAL MODEL SELECTED. COORDINATE EQUIPMENT MODEL NUMBERS WITH ARCHITECT/OWNER. CONTRACTOR SHALL CONSIDER THIS ALLOWANCE IN THE BID.
12. E.C. SHALL PROVIDE POWER TO THE GAS SHUT OFF VALVE (SOLENOID) VIA FIRE SUPPRESSION SYSTEM CIRCUIT. BASE BID ACCORDINGLY.

02 06/04/2025 PERMIT SET
01 05/06/2025 REVISED CHECK SET
00 04/29/2025 CHECK SET
NO. DATE ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

PROJECT NAME

PHYSICAL LOCATION

DRAWING TITLE

ELECTRICAL POWER
PLAN

GRAPHIC SCALE

SEAL

PROJECT NO. -

SCALE AS NOTED


DRAWN BY NYE

CHECKED BY NYE

DATE 06/04/2025

SHEET NUMBER

E1.1



ELECTRICAL LIGHTING PLAN KEYED WORK NOTES


1. CONNECT ALL EMERGENCY EGRESS LIGHTING FIXTURES TO THE NEAREST LIGHTING BRANCH CIRCUIT AHEAD OF ALL SWITCHING AND CONTROLS PER STATE AND LOCAL CODES.
2. COORDINATE EXACT LOCATION OF DIMMER SWITCH BANK WITH OWNER/ARCHITECT. PROVIDE DIMMERS IN COORDINATION WITH LIGHTING VENDOR AS PER DIMMER TYPE BASE BID ACCORDINGLY.
3. E.C. TO COORDINATE THE BUILDING SIGNAGE CONNECTION REQUIREMENTS WITH SIGN VENDOR. BASE BID ACCORDINGLY.
4. E.C. SHALL PROVIDE POWER CONNECTIONS TO THE WALK-IN BOX LIGHT FIXTURES IN COORDINATION WITH WALKIN BOX MANUFACTURER. BASE BID ACCORDINGLY.
5. E.C. SHALL PROVIDE POWER CONNECTIONS TO THE HOOD LIGHTING IN COORDINATION WITH HOOD MANUFACTURER. BASE BID ACCORDINGLY.
6. E.C. SHALL PROVIDE LIGHTING CONTROLS FOR WALK-IN-COOLER IN COORDINATION WITH WALK-IN-COOLER VENDOR. BASE BIDE ACCORDINGLY.

ELECTRICAL LIGHTING PLAN GENERAL NOTES

1. VERIFY ALL LUMINARIE COLORS, TRIMS, LENGTHS, ETC. WITH THE ARCHITECT PRIOR TO PLACING FINAL PURCHASE ORDERS. SUBMISSION OF SHOP DRAWINGS WILL BE INTERPRETED AS HAVING BEEN COORDINATED WITH THE ARCHITECTURAL DRAWINGS.
2. PROVIDE ALL LENGTHS, FEEDS, ACCESSORIES, CONNECTORS, WIRING, POWER SUPPLIES, DRIVERS, ETC. FOR A COMPLETE INSTALLATION. THE E.C. SHALL VERIFY THE COMPLETE BILL OF MATERIAL WITH MANUFACTURER'S REPRESENTATIVE AND ENSURE ALL EQUIPMENT ARE INCLUDED IN BID PRICE. COORDINATE INSTALLATION WITH ARCHITECTURAL DETAILS.
3. VERIFY FINAL LUMINARIE LOCATIONS WITH OTHER CEILING MOUNTED EQUIPMENT SUCH AS DIFFUSER WITH ARCHITECTURAL REFLECTED CEILING PLANS.
4. VERIFY EXACT MOUNTING HEIGHT AND LOCATIONS OF ALL WALL MOUNTED LUMINAIRE WITH ARCHITECTURAL PLANS AND ELEVATIONS PRIOR TO ROUGH-IN.
5. E.C. TO COORDINATE EXACT LOCATION WITH ARCHITECT FOR LIGHTING DETAILS.
6. OCCUPANCY SENSORS SHALL BE PROVIDED AS SHOWN AND ALSO CONSIDER POWER PACKS AS REQUIRED IN COORDINATION WITH LIGHTING VENDOR.
7. E.C. SHALL PROVIDE THE AUTOMATIC LIGHTING CONTROLS AS PER IECC C405.2.


02	06/04/2025	PERMIT SET
01	05/06/2025	REVISED CHECK SET
00	04/29/2025	CHECK SET
NO.	DATE	ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179




2 TIME CLOCK CONTACTOR WIRING DIAGRAM
NTS

PROJECT NAME		
PHYSICAL LOCATION		
DRAWING TITLE	ELECTRICAL LIGHTING PLAN	
GRAPHIC SCALE		
SEAL	PROJECT NO.	
	SCALE	AS NOTED
	DRAWN BY	NYE
	CHECKED BY	NYE
	DATE	06/04/2025
	SHEET NUMBER	E2.1



1 ELECTRICAL ROOF POWER PLAN



ELECTRICAL ROOF POWER PLAN KEYED NOTES

1. ELECTRICAL CONTRACTOR SHALL COORDINATE DISCONNECT AND FUSE REQUIREMENT FOR MECHANICAL UNIT WITH MECHANICAL CONTRACTOR AND EQUIPMENT MANUFACTURER PRIOR TO ROUGH-IN AND PROVIDE AS REQUIRED. COORDINATE LOCATION OF DISCONNECT WITH MANUFACTURER AND MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN. LOCATE AS REQUIRED TO MAINTAIN NEC CLEARANCES.

ELECTRICAL ROOF POWER PLAN GENERAL NOTES

1. COORDINATE EXACT LOCATION OF HVAC EQUIPMENTS WITH MECHANICAL CONTRACTOR.
2. ELECTRICAL CONTRACTOR SHALL PROVIDE WEATHER PROOF GFI RECEPTACLE AS PER NEC 210.63.

02	06/04/2025	PERMIT SET
01	05/06/2025	REVISED CHECK SET
00	04/29/2025	CHECK SET
NO.	DATE	ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

PROJECT NAME		
PHYSICAL LOCATION		
DRAWING TITLE	ELECTRICAL ROOF POWER PLAN	
GRAPHIC SCALE		
SEAL	PROJECT NO.	
	SCALE	AS NOTED
	DRAWN BY	NYE
	CHECKED BY	NYE
	DATE	06/04/2025
	SHEET NUMBER	E3.1

Property of NY Engineers

MANUAL MODE OPERATION:

1. PUSHBUTTON PRESS IS REQUIRED TO TURN LOAD ON.
2. LOAD TURNS OFF WHEN SENSOR TIMES OUT OR BY PRESSING PUSH BUTTON.
3. IF DAYLIGHT SENSOR IS ENABLED AND LIGHT LEVEL IS ABOVE SETPOINT, LOAD WILL NOT TURN ON.



AUTOMATIC MODE OPERATION:

1. WHEN SENSOR ACTIVATES LOAD TURNS ON.
2. PUSHBUTTON CAN BE USED TO TURN LOAD ON OR OFF. IF PUSHBUTTON IS USED TO TURN LOAD OFF, SENSOR MUST TIME OUT FIRST, BEFORE LOAD CAN TURN BACK ON AUTOMATICALLY.
3. IF DAYLIGHT SENSOR IS ENABLED AND LIGHT LEVEL IS ABOVE SETPOINT, LOAD WILL NOT TURN ON.


SENSOR TYPES INCLUDE:

ONW-D-1001-MV-N

 PROVIDE SENSING CONDUCTOR TAPPED AHEAD OF ANY SWITCHES WHERE SWITCH SERVES EMERGENCY FIXTURES.




3
E4.1 N.T.S
CONNECTION) OCCUPANCY/VACANCY-SINGLE LEVEL
WIRING DIAGRAM-LOW VOLTAGE WALL SWITCH SENSOR(NEUTRAL)



2
E4.1 N.T.S
FIRE STOP DETAIL

NOTE:
THIS INFORMATION MAY NOT CONTAIN ALL DETAILS REQUIRED FOR CONSTRUCTION. APPROPRIATE MODIFICATION MAY BE REQUIRED TO ENSURE SUITABILITY OF THESE DRAWINGS FOR THE SPECIFIC APPLICATION. IT IS THE USER'S RESPONSIBILITY TO ENSURE INSTALLATION OF THE EQUIPMENT/SYSTEM IS IN ACCORDANCE WITH BUILDING/PROJECT SPECIFICATIONS, APPLICABLE CODES AND STANDARDS.



NOTES:

1. ALL CONDUIT MAY BE COMBINED ON SAME SUPPORT CHANNEL WHERE PRACTICAL.
2. SUPPORT CHANNEL LENGTH SHALL NOT BE DETERMINED UNTIL ALL PIPING, CONDUIT, ETC. TO BE SUPPORTED IS COORDINATED.
3. SUPPORT CHANNEL SPACING SHALL BE NO MORE THAN 10'-0".
4. UNISTRUT AND CONDUIT INSTALLATION MAY BE REVERSED.

1
E4.1 N.T.S
CONDUIT SUPPORT DETAIL

02 06/04/2025 PERMIT SET
01 05/06/2025 REVISED CHECK SET
00 04/29/2025 CHECK SET
NO. DATE ISSUE DESCRIPTION

NY ENGINEERS
382 NE 191ST STREET
SUITE 49674,
MIAMI, FL 33179

PROJECT NAME

PHYSICAL LOCATION

DRAWING TITLE
ELECTRICAL
DETAILS

GRAPHIC SCALE

SEAL	PROJECT NO.
	SCALE AS NOTED
	DRAWN BY NYE
	CHECKED BY NYE
	DATE 06/04/2025
	SHEET NUMBER E4.1


Property of NY Engineers

LIGHTING FIXTURE SCHEDULE								
TAG	QTY	REMARKS	MANUFACTURER	CATALOG NUMBER	DESCRIPTION	LAMPS	WATTAGE	SUPPLIED BY
A2	23	2x2 LIGHT FIXTURES	LITHONIA/EQUIVALENT	2GTL2-3300LM-LP835/EQUIVALENT	2x2 LED LAY-IN TROFFER	LED	28 W	EC
D1	13	LED RECESSED DOWNLIGHT	LITHONIA/EQUIVALENT	LDN6-3000LM-30K-L06-XX-XX-90CRI	ROUND LED LIGHT	LED	38 W	EC
D2	4	SPHERE MINI PENDANT	LIGHTOLOGY	ZAN776819	PEWTER FINISH- 1 X. EDISON GLOBE/MEDIUM (E26)/6W/120V LED WITH GREEN SUSPENSION WIRE	LED	6 W	EC
P	31	PENDANT FIXTURE	WARELIGHT	WL-CYL6-25W-SCT-0-10V-UNV-S-BK	6" SUSPENDED-CYLINDRICAL CAN LIGHTS	LED	25 W	EC
EM	6	EMERGENCY LIGHTING	LITHONIA	ELM2-LED-XX-XX	SURFACE MOUNTED BATTERY UNIT WITH SELF DIAGNOSTICS	LED	3 W	EC
X1	3	EXIT LIGHT WITH DUAL EMERGENCY HEADS	LITHONIA	LHOM-LED-XX-R-SD	LED EXIT LIGHT WITH DUAL EMERGENCY HEADS	LED	3 W	EC
R1	3	REMOTE EMERGENCY LIGHT	SIGNETIX	MUE-BBB-10-XX-XX-XX	REMOTE EMERGENCY LIGHT	LED	1.5 W	EC

KITCHEN EQUIPMENT POWER SCHEDULE					
REMARKS:					
1. PROVIDE SO CORD DROP WITH STRAIN RELIEF. REFER TO ELECTRICAL POWER PLAN.					
2. FURNISHED WITH CONTROL BOX. CONNECT ALL COMPONENTS.					
3. PROVIDE WP DISCONNECT SWITCH. VERIFY RATING WITH ACTUAL EQUIPMENT					
TAG	EQUIPMENT DESCRIPTION	VOLT	PH	LOAD	REMARKS
2	WALK-IN COOLER REF. SYSTEM	120 V	1	180 VA	
3	WALK-IN COOLER CONDENSER	208 V	3	1686 VA	
4	WALK-IN COOLER EVAPORATOR	120 V	1	98 VA	
12	ICE MAKER W/BIN	120 V	1	1416 VA	
13	REACH-IN FREEZER	120 V	1	1032 VA	
19	DISHWASHER	120 V	1	1920 VA	
24	EXHAUST HOOD CONTROL PANEL	120 V	1	180 VA	
27	FIRE SUPPRESSION SYSTEM	120 V	1	180 VA	
28	RANGE 36" OPEN BURNERS	120 V	1	708 VA	
29	EQUIP. STAND REFRIGERATED BASE	120 V	1	276 VA	
31	CHARBROILER	120 V	1	200 VA	
32	GRIDDLE	120 V	1	200 VA	
33	COUNTERTOP CONVECTION OVEN	208 V	1	4200 VA	1
34	RICE/GRAIN COOKER	120 V	1	1560 VA	
41	SANDWICH/SALAD PREP. TABLE	120 V	1	276 VA	
43	FOOD PAN WARMER/RETHEMALIZER	120 V	1	1440 VA	
44	ICE CREAM FREEZER	120 V	1	156 VA	
48	TRASH RECEPTACLE	120 V	1	180 VA	
49	JUICER	120 V	1	1296 VA	
51	UNDERCOUNTER FREEZER	120 V	1	216 VA	
52	SANDWICH/SALAD PREP. TABLE	120 V	1	276 VA	
56	DROP-IN REFRIGERATED WELL	120 V	1	300 VA	
57	POS SYSTEM	120 V	1	276 VA	
59	ESPRESSO MACHINE	208 V	1	6024 VA	
60	ESPRESSO GRINDER	120 V	1	276 VA	
61	BLENDOR BAR	120 V	1	1800 VA	
66	REACH-IN DISPLAY REFRIGERATOR	120 V	1	192 VA	
67	ICE DISPENSER	120 V	1	336 VA	
69	BEVERAGE DISPENSER	120 V	1	1020 VA	

RISER DIAGRAM KEYED NOTES:
1. EXISTING GEC, E.C. SHALL VERIFY AT SITE, REPORT IF ANY DISCREPANCIES OBSERVED PRIOR TO BID.
2. EXISTING 800A, 3 PHASE, 4 WIRE SERVICE FROM THE UTILITY COMPANY. E.C. TO VERIFY IN FIELD AND COORDINATE ALL SERVICE INSTALLATION REQUIREMENTS WITH UTILITY COMPANY PRIOR TO BID. SCOPE OF WORK TO BE COORDINATED WITH UTILITY COMPANY/OWNER/LAND LORD. PROVIDE NEW IF INOPERABLE. REPORT IF ANY DISCREPANCIES OBSERVED PRIOR TO BID.
3. RE-USE EXISTING ELECTRICAL 200A, 277/480V, 3-PHASE, 4-WIRE ELECTRICAL METER & DISCONNECT SWITCH FOR THE TENANT SPACE. E.C. SHALL VERIFY THE OPERABLE CONDITION AND REPLACE WITH NEW OR RECTIFY IF INOPERABLE. SCOPE OF WORK TO BE COORDINATED WITH UTILITY COMPANY/OWNER/LAND LORD. REPORT IF ANY DISCREPANCIES OBSERVED PRIOR TO BID.
4. NEW 200A MCB, 120/208V, 3-PHASE, 4-WIRE ELECTRICAL PANEL "A". E.C. SHALL COORDINATE WITH ARCHITECT/OWNER FOR EXACT LOCATION OF ELECTRICAL PANEL IN FIELD.
5. NEW 100A MLO, 120/208V, 3-PHASE, 4-WIRE ELECTRICAL PANEL "B". E.C. SHALL COORDINATE WITH ARCHITECT/OWNER FOR EXACT LOCATION OF ELECTRICAL PANEL IN FIELD.
6. E.C. SHALL PROVIDE THE CEILING SUSPENDED NEW 75KVA TRANSFORMER AS PER 450.13(B) & 450.21(A). E.C. SHALL COORDINATE WITH THE ARCHITECT/OWNER AS PER SITE CONDITIONS. BASE BID ACCORDINGLY.
7. E.C. SHALL VERIFY THE EXISTING FEEDER AND EXTEND WITH NEW FEEDER TO THE RELOCATED LOCATION OF THE PANEL. BASE BID ACCORDINGLY.
8. REUSE AND RELOCATE EXISTING 225A MLO, 277/480V, 3-PHASE, 4-WIRE ELECTRICAL RETAIL PANEL "RB4". E.C. SHALL COORDINATE WITH ARCHITECT/OWNER FOR EXACT LOCATION AND OPERATING CONDITION OF ELECTRICAL PANEL IN FIELD. PROVIDE AS REQUIRED. BASE BID ACCORDINGLY.

GENERAL PANEL NOTES
A. AIC RATING FOR PANEL AND ALL BRANCH CIRCUIT BREAKERS: CONTRACTOR SHALL OBTAIN THE AVAILABLE FAULT CURRENT AT THE SERVICE POINT FROM THE LOCAL UTILITY. PROVIDE THE AIC RATING OF THE PANEL AS NECESSARY.
B. ELECTRICAL SERVICE AND SYSTEM DETAILED IS DESIGNED BASED ON 208Y/120 VOLT THREE PHASE SERVICE. ELECTRICAL CONTRACTOR TO VERIFY AVAILABLE SERVICE PRIOR TO START OF CONSTRUCTION. COORDINATE ANY REQUIRED CHANGES WITH OWNER.
C. BALANCE PANELS WITHIN 10% PHASE TO PHASE.
D. E.C. SHALL VERIFY INCOMING SERVICE AMPERAGE, WIRE SIZING AND DISTRIBUTION IN FIELD COORDINATION WITH OWNER/LANDLORD/UTILITY COMPANY.
E. E.C. SHALL COORDINATE THE POWER REQUIREMENTS WITH EQUIPMENT MANUFACTURER FOR ALL THE EQUIPMENTS SHOWN ON THE PLAN AND FINAL NEMA RATINGS OF THE RECEPTACLES SHALL BE BASED ON THE FINAL MODEL SELECTED. COORDINATE EQUIPMENT MODEL NUMBERS WITH ARCHITECT/OWNER. CONTRACTOR SHALL CONSIDER THIS ALLOWANCE IN THE BID.



PANEL: RB4 (EXISTING)										NEMA ENCLOSURE EXISTING		
480Y/277 VOLTS,		3 PHASE		4 WIRE		MOUNTING RECESSED						
MAIN CB: MLO 225A		BUS: 225A		MIN,		LOC R.R. CORRIDOR						
NOTE: L : LIGHTING, H : HVAC LOAD, M : MOTOR LOAD, R : RECEPTACLES, O : OTHER/MISC, E : KITCHEN EQUIPMENT												
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	MINIMUM BRANCH CIRCUIT	PER PHASE (KVA)	MINIMUM BRANCH CIRCUIT	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.
1			O	17.86		25.56		7.70	H			2
3	100/3P*	PANEL A THRU XFMR	O	17.86	3#3, #8G, 1" C.		25.56	7.70	H	ACCU-3 (N)	45/3P*	4
5			O	17.86			25.56	7.70	H			6
7			H	1.01		8.71		7.70	H			8
9	15/3P*	MAF-1 (N)	H	1.01	3#12, #12G, 3/4" C		8.71	7.70	H	ACCU-4 (N)	45/3P*	10
11			H	1.01			8.71	7.70	H			12
13			H	0.37		8.40		2#10, #10G, 3/4" C	8.03	O	30*	14
15	15/3P*	OAF-1 (N)	H	0.37	3#12, #12G, 3/4" C		8.40	2#10, #10G, 3/4" C	8.03	O	30*	16
17			H	0.37			1.14	0.77	H	KEF-1 (N)	15/3P*	18
19	20	SPARE				0.77		0.77	H		20	20
21	20	SPARE					0.00			SPARE	20	24
23	20	SPARE					0.00			SPARE	20	26
25	20	SPARE					0.00			SPARE	20	28
27	20	SPARE					0.00			SPARE	20	30
31	20	SPARE					0.00			SPARE	20	32
33	20	SPARE					0.00			SPARE	20	34
35	20	SPARE					0.00			SPARE	20	36
37	20	SPARE					0.00			SPARE	20	38
39	20	SPARE					0.00			SPARE	20	40
41	20	SPARE					0.00			SPARE	20	42
TOTAL CONNECTED LOAD (KVA)										** INDICATES NEW BREAKER		

PANEL: A (NEW)										NEMA ENCLOSURE TYPE 1					
208Y/120 VOLTS,		3 PHASE		4 WIRE		MOUNTING SURFACE									
MAIN CB: 200A		MLO		BUS: 200A		MIN,					LOC BOH				
NOTE: L : LIGHTING, H : HVAC LOAD, M : MOTOR LOAD, R : RECEPTACLES, O : OTHER/MISC, E : KITCHEN EQUIPMENT															
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	MINIMUM BRANCH CIRCUIT	PER PHASE (KVA)	MINIMUM BRANCH CIRCUIT	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.			
1	20	12-ICE MAKER W/BIN	E	1.42	2#12, #12G, 3/4" C	2.30		2#12, #12G, 3/4" C	0.88	L	LIGHTING KITCHEN AREA	20	2		
3	40/2P	ACCU-2 (N)	H	3.22			3.88	2#12, #12G, 3/4" C	0.65	L	LIGHTING DINNING AREA	20	4		
5			H	3.22	2#8, #10G, 3/4" C			2#12, #12G, 1/2" C	0.36	R	57-POS SYSTEM	20	6		
7	20	19-DISHWASHER	E	1.84	2#12, #12G, 3/4" C	2.20		2#12, #12G, 1/2" C	0.36	R	57-POS SYSTEM	20	8		
9	20	27-FIRE SUPPRESSION SYSTEM	E	0.20	2#12, #12G, 3/4" C		0.92	2#12, #12G, 3/4" C	0.72	E	60-ESPRESSO GRINDER	20	10		
11	20	28-6 BURNER RANGE	E	0.71	2#12, #12G, 3/4" C		3.83	2#10, #10G, 3/4" C	3.12	E	59-ESPRESSO MACHINE	30/2P	12		
13		SHUNT TRIP BREAKER				3.12						14			
15	20	31-CHARBROILER, GAS, COUNTERTOP	E	0.20	2#12, #12G, 3/4" C		2.00	2#12, #12G, 3/4" C	1.80	E	61-BLENDOR BAR	20	16		
17		SHUNT TRIP BREAKER					1.80	2#12, #12G, 3/4" C	1.80	E	61-BLENDOR BAR	20	18		
19	20	41-SANDWICH / SALAD PREPARATION REFRIGERATOR	E	0.28	2#12, #12G, 3/4" C	0.48		2#12, #12G, 3/4" C	0.20	L	TIME CLOCK	20	20		
21	20	43-FOOD PAN WARMER/REHEATRALIZER, COUNTERTOP	E	1.44	2#12, #12G, 3/4" C		2.74	2#12, #12G, 3/4" C	1.30	E	49-JUICER	20	22		
23	20	43-FOOD PAN WARMER/REHEATRALIZER, COUNTERTOP	E	1.44	2#12, #12G, 3/4" C		3.14	2#12, #12G, 3/4" C	1.70	R	SHOW WINDOW RECEPTACLE	20	24		
25	20	41-SANDWICH / SALAD PREPARATION REFRIGERATOR	E	0.28	2#12, #12G, 3/4" C	1.54		2#12, #12G, 3/4" C	1.26	R	GENERAL RECEPTACLES	20	26		
27	20	34-RICE/GRAIN COOKER	E	1.55	2#12, #12G, 3/4" C		1.83	2#12, #12G, 3/4" C	0.28	E	29-REFRIGERATED EQUIPMENT STAND	20	28		
29	20	34-RICE/GRAIN COOKER	E	1.55	2#12, #12G, 3/4" C		1.55	2#12, #12G, 3/4" C			SHUNT TRIP BREAKER	30			
31	20/2P	33-COUNTERTOP CONVECTION OVEN	E	2.10	2#12, #12G, 3/4" C	3.12		2#12, #12G, 3/4" C	1.02	E	69-BEVERAGE DISPENSER	20	32		
33			E	2.10			5.32	2#8, #10G, 3/4" C			3.22 H ACCU-1 (N)	40/2P	34		
35	20	EXTERIOR SIGNAGE	L	1.00	2#12, #12G, 3/4" C			2#12, #12G, 3/4" C	4.22			3.22 H	36		
37			O	4.91			5.27			2#12, #12G, 3/4" C	0.36	R	GENERAL RESTROOM RECEPTACLES	20	38
39	100/3P	PANEL B	O	4.91	4#3, #8G, 1-1/4" C			5.11	2#12, #12G, 3/4" C	0.20	E	32-GRIDLE GAS, COUNTERTOP	20	40	
41			O	4.91			4.91					SHUNT TRIP BREAKER	42		
TOTAL CONNECTED LOAD (KVA)															

PANEL: B (NEW)										NEMA ENCLOSURE TYPE 1		
208Y/120 VOLTS,		3 PHASE		4 WIRE		MOUNTING SURFACE						
MAIN CB: MLO 100A		MLO		BUS: 125A		MIN,						