



EXTEND 3/4" CW TO HOSE REEL  
(CONTRACTOR TO FIELD VERIFY AND CONNECT TO EXISTING COLD WATER LINE)

3/4" CW FOR HOSE REEL

NEW HOSE REEL

NEW TROUGH FLOOR DRAIN  
(PROVIDE NEW P-TRAP AT EXISTING FD)  
(CONTRACTOR TO FIELD VERIFY AND REMOVE EXISTING P-TRAP LOCATED NEAR GREASE TRAP)

EXISTING AIR COMPRESSOR NOZZLES.  
PROVIDE ADDITIONAL NOZZLE.  
(CONTRACTOR TO COORDINATE WITH EQUIPMENT CONTRACTOR/OWNERSHIP FOR FLEXIBLE PIPE CONNECTION AND REQUIREMENTS)

GREASE INTERCEPTOR(GI-1)  
(CONTRACTOR TO FIELD VERIFY AND REPLACE EXISTING GREASE INTERCEPTOR AND RELATED ACCESSORIES WITH NEW GREASE INTERCEPTOR INSIDE EXISTING PIT) (REFER P-501 FOR ADDITIONAL INFORMATION).  
VERIFY LOCATION OF EXISTING VENT IN FIELD. PROVIDE NEW VENT IF REQUIRED.

EXISTING HWHT TO REMAIN. PROTECT PIPING AND ASSOCIATED VALVES DURING CONSTRUCTION. DISCONNECT AND RECONNECT AS REQUIRED.

OIL/WATER SEPARATER. FOLLOW MANUFACTURER'S GUIDELINES FOR INSTALLATION.

AIR COMPRESSOR  
68.5"LX30"WX67.2"H

GREASE INTERCEPTOR SCHEDULE					
ITEM	LOCATION	SERVICE	FLOW IN GPM	GREASE CAPACITY IN LBS	REMARKS
GREASE INTERCEPTOR GI-1	GROUND FLOOR	SECTION-3/ SECTION-6	70	175.6	-SCHIER, MODEL GB-3 INTERCEPTOR. SIZE-37"X28"X21"

NOTES:  
1. CONCRETE AROUND EXISTING GREASE TRAP SHALL BE CUT AS NECESSARY TO CONNECT PIPING TO NEW GREASE TRAP.  
2. PROVIDE THIRD OUTLET FOR CLEAN OUT AT SIDE OF GREASE TRAP FROM MANUFACTURER. PROVIDE CLEAN OUT FLUSH WITH FLOOR NEXT TO PIT.

AIR COMPRESSOR SCHEDULE						
ITEM	LOCATION	CAPACITY	MHP	RATED AIR DELIVERY	MODEL	REMARKS
AIR COMPRESSOR	GROUND FLOOR	80 GALLONS	7.5	27.5 CFM @ 115PSI	INGERSOLL RAND R5.5i-TAS	DIMENSIONS: 68.5"LX30"WX67.2"H

NOTES:  
1. CONNECT CONDENSATE DRAIN PIPE TO NEAREST SINK WITH FUNNEL DRAIN.